

ADDENDUM TO THE SAN PEDRO WATERFRONT PROJECT ENVIRONMENTAL IMPACT REPORT FOR THE SAN PEDRO PUBLIC MARKET PROJECT

PREPARED FOR:

Los Angeles Harbor Department
425 S. Palos Verdes Street
San Pedro, CA 90731
Contact: Laura Masterson
(310) 732-3679

PREPARED BY:

ICF International
1 Ada, Suite 100
Irvine, California 92618
Contact: Chad Beckstrom
(949) 333-6625

May 2016



ICF International. 2016. Addendum to the San Pedro Waterfront Project Environmental Impact Report for the San Pedro Public Market Project. May. (ICF 00177.16) Irvine, CA. Prepared for: Los Angeles Harbor Department, Los Angeles, CA.

Contents

List of Tables and Figures	iv
List of Acronyms and Abbreviations	v
Chapter 1 Introduction and Summary	1-1
1.1 Introduction and Overview	1-1
1.2 Purpose and Use of an Addendum to a Previously Certified EIR	1-2
1.3 Previous Environmental Documents Incorporated by Reference	1-3
1.4 Evaluation of Environmental Impacts	1-3
1.5 Summary of Findings	1-5
Chapter 2 Project Description	2-1
2.1 Project Location and Setting	2-1
2.2 Project Objectives	2-1
2.3 EIR Project Description Assumptions	2-2
2.4 Proposed Modifications	2-3
2.4.1 Landside Improvements	2-5
2.4.2 Waterside Improvements	2-7
2.4.3 Construction Phasing	2-7
Chapter 3 Environmental Setting	3-1
3.1 Aesthetics	3-1
3.1.1 U.S.S. Iowa	3-1
3.1.2 AltaSea Marine Research Center	3-1
3.1.3 Downtown Harbor	3-2
3.1.4 Crafted Marketplace & Brouwerij West	3-2
3.1.5 Redesign of Sampson Way/7th Street Intersection	3-2
3.2 Air Quality and Meteorology	3-3
3.2.1 Air Quality	3-3
3.2.2 Greenhouse Gas Emissions	3-4
3.3 Biological Resources	3-4
3.4 Cultural Resources	3-5
3.5 Geology and Soils	3-5
3.6 Groundwater and Soils	3-7
3.6.1 February 2013: Soil-Gas Investigation Report	3-7
3.6.2 April 2013: Phase I ESA	3-8
3.6.3 November 2013: Phase II ESA	3-9

3.6.4	July 2014: HHRA	3-10
3.6.5	Feb 2016: Soil Management Plan for Ports O’Call	3-11
3.7	Hazards and Hazardous Materials.....	3-12
3.8	Land Use and Planning	3-13
3.9	Noise.....	3-14
3.10	Recreation	3-14
3.11	Transportation and Circulation (Ground).....	3-14
3.12	Transportation and Navigation (Marine)	3-15
3.13	Utilities and Public Services.....	3-16
3.14	Water Quality, Sediment, and Oceanography	3-16
3.15	Environmental Justice	3-17
3.16	Socioeconomics and Environmental Quality.....	3-17
Chapter 4 Environmental Impact Analysis		4-1
4.1	Aesthetics	4-1
4.2	Air Quality and Meteorology.....	4-5
4.3	Biological Resources	4-11
4.4	Cultural Resources.....	4-15
4.5	Geology and Soils	4-17
4.6	Groundwater and Soils.....	4-18
4.7	Hazards and Hazardous Materials.....	4-22
4.8	Land Use and Planning	4-24
4.9	Noise.....	4-25
4.10	Recreation	4-26
4.11	Transportation and Circulation (Ground).....	4-28
4.12	Transportation and Navigation (Marine)	4-43
4.13	Utilities and Public Services.....	4-44
4.14	Water Quality, Sediment and Oceanography	4-48
4.15	Environmental Justice	4-49
4.16	Socioeconomics and Environmental Quality.....	4-50
4.17	Growth Inducement	4-51
4.18	Cumulative Analysis.....	4-52
4.18.1	Introduction.....	4-52
4.18.2	Summary of SPW EIS/EIR Findings	4-52
4.18.3	Impacts of the SPPM Project.....	4-52
Chapter 5 References		5-1

Appendix A Level of Service Worksheets

**Appendix B Summary of Mitigation Measures for San Pedro Waterfront Addendum –
San Pedro Public Market Project**

Tables and Figures

Table	On Page
2-1 Ports O’Call Development Comparison: SPW Project EIS/EIR vs. SPPM Project	2-4
3.2-1 Maximum Pollutant Concentrations Measured at the North Long Beach Monitoring Station	3-3
3.2-3 2013 12-Month Average Pollutant Concentrations Measured for the Port of Los Angeles Air Quality Monitoring Program	3-4
4-1 Summary of Over-Water and In-Water Project Elements under the SPW Project at Ports O’Call	4-12
4-2 Significant Impacts at Intersections without Mitigation—SPW Project.....	4-30
4-3 Significant Residual Impacts at Intersections—SPW Project.....	4-31
4-4 Comparison of SPW Project EIS/EIR Ports O’Call Component and SPPM Project Trip Generation	4-34
4-5 Comparison of SPW Project EIS/EIR and 2016 Update Trip Generation	4-36
4-6 Intersection Level of Service Summary	4-39
4-7 Code-Required Auto Parking Spaces – SPPM Project (Phase I).....	4-41

Figure	Follows Page
2-1 San Pedro Waterfront Project Area.....	2-2
2-2 Project Location.....	2-2
2-3 Proposed Site Plan Phase 1.....	2-6
2-4 Proposed Parking Plan Phase 1	2-6
2-5 Phase 1 Construction	2-8
2-6 Phase 2 Construction	2-8
3-1 Project Areas.....	3-8
3-2 Sites of Potential Concern Based on Historical Reviews and Site Interviews	3-8

Acronyms and Abbreviations

AB	Assembly Bill
BACT	best available control technology
BMP	best management practice
Board	Los Angeles Board of Harbor Commissioners
CalEPA	California Environmental Protection Agency
CARB	California Air Resources Board
CEQA	California Environmental Quality Act
CHHSL	California Human Health Screening Level
City	City of Los Angeles
CO	carbon monoxide
CO ₂ e	carbon dioxide equivalent
dB	decibel
dBA	A-weighted decibels
EIR	Environmental Impact Report
EIS	Environmental Impact Statement
ENA	Exclusive Negotiating Agreement
EPA	U.S. Environmental Protection Agency
ERM	ERM-West, Inc.
ESA	Environmental Site Assessment
ESL	environmental screening level
GHG	greenhouse gas
HAZWOPER	Hazardous Waste Operations and Emergency Response
HHRA	Human Health Risk Assessment
HI	hazard index
I-110	Harbor Freeway
LADOT	Los Angeles Department of Transportation
LAHD	Los Angeles Harbor Department
LAWA	LA Waterfront Alliance
LOI	Letter of Intent
LOS	level of service
MCL	Maximum Contaminant Level
mg/kg	milligrams per kilogram
mg/L	milligrams per liter
Mike's	Mike's Main Channel Marine
MRZ	Mineral Resource Zone
NAHC	Native American Heritage Commission
NO ₂	nitrous oxide
NO _x	nitrogen oxides
OCP	organochlorine pesticide
PAH	polycyclic aromatic hydrocarbon
Paleo Plan	Paleontological Monitoring and Mitigation Plan San Pedro Waterfront Project
PCB	polychlorinated biphenyl

PCE	tetrachloroethene
PM10	particulate matter 10 microns or less in diameter
PM2.5	particulate matter 2.5 microns or less in diameter
PMP	Port Master Plan
Port	Port of Los Angeles
REC	recognized environmental condition
RMP	Risk Management Plan
RSL	regional screening level
S.P.	Southern Pacific
SCAQMD	South Coast Air Quality Management District
SGI	Source Group, Inc.
SMP	Soil Management Plan
SO _x	sulfur oxides
SPPM Project	San Pedro Public Market Project
SPW	San Pedro Waterfront
SR	State Route
STLC	Soluble Threshold Limit Concentration
SWPPP	Stormwater Pollution Prevention Plan
TAC	toxic air contaminant
TCLP	toxicity characteristic leaching procedure
TEU	twenty-foot equivalent unit
TPH	total petroleum hydrocarbons
V/C	volume to capacity
VOC	volatile organic compound
WB	westbound

1
2

3
4
5
6
7
8

9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27

28
29
30
31
32
33
34
35
36
37

Chapter 1

Introduction and Summary

1.1 Introduction and Overview

Pursuant to the California Environmental Quality Act (CEQA) Public Resources Code section 21000 et. seq., this Addendum to the San Pedro Waterfront (SPW) Project Final Environmental Impact Report (EIR) has been prepared to address proposed changes to the redevelopment of Ports O’Call located between the Main Channel and Sampson Way from Berths 73-Z to 83 within the Port of Los Angeles (Port).

In the SPW Project Environmental Impact Statement (EIS)/EIR, the Los Angeles Harbor Department (LAHD) identified the redevelopment of Ports O’Call as one of the objectives of the SPW Project. Specifically, the objective called for enhanced visitor-serving commercial opportunities within Ports O’Call, complementary to those found in downtown San Pedro, as well as a potential conference center. The SPW Project EIS/EIR acknowledged that to successfully redevelop Ports O’Call, LAHD plans to work with a master developer in order to redevelop the entire area homogeneously. Since the certification of the SPW Project EIS/EIR on September 29, 2009, the Los Angeles Board of Harbor Commissioners (Board) selected LA Waterfront Alliance (LAWA), a joint venture consisting of The Ratkovich Company and Jerico Development, Inc., as the master developer for the redevelopment of Ports O’Call pursuant to a competitive, public request for qualifications process conducted by the Board in late 2012. LAWA entered into an Exclusive Negotiating Agreement (ENA) with the Port and the City of Los Angeles (City), effective March 2013. The ENA was extended through March 2015 and was replaced by a Letter of Intent (LOI), effective March 2015 and originally expiring in July 2015. During the initial term of the LOI, the Port and the City negotiated a term sheet describing the business terms of a proposed Ground Lease between the Port and LAWA. The term sheet was approved by the Board in July 2015, at which time the term of the LOI was extended through December 2015.

In December 2015, the master developer initially proposed modifications to the previous project design and uses that were analyzed for Ports O’Call in the SPW Project EIS/EIR. The proposed modifications constitute the “proposed Project” or SPPM Project for the purpose of this Addendum, and include the development of similar building area; a slightly larger development envelope, which now includes a portion of the Town Square originally evaluated in the SPW Project EIS/EIR; reconfiguration of the waterfront promenade; extension of the term of the proposed lease between LAHD and the developer of the proposed Project from 30 years to 50 years; and possible modification to the U.S. Army Corps of Engineers permits issued related to construction of the waterfront promenade and other over- and in-water features. The development of a 75,000-square-

1 foot conference center, as originally proposed in the SPW Project EIS/EIR, is currently
2 not anticipated to occur.

3 **1.2 Purpose and Use of an Addendum to a** 4 **Previously Certified EIR**

5 State CEQA Guidelines Section 15164 states: “The lead agency or responsible agency
6 shall prepare an addendum to a previously certified EIR if some changes or additions are
7 necessary but none of the conditions described in Section 15162 calling for the
8 preparation of a subsequent EIR have occurred.” An addendum need not be circulated for
9 public review but can be included in or attached to the EIR. The decision-making body
10 must consider the addendum with the EIR prior to making a decision on the project.

11 Pursuant to Section 15162 of the State CEQA Guidelines, no subsequent EIR may be
12 required for a project unless the City determines, on the basis of substantial evidence, one
13 or more of the following conditions are met.

14 (a) When an EIR has been certified or a negative declaration adopted for a project, no
15 subsequent EIR shall be prepared for that project unless the lead agency determines,
16 on the basis of substantial evidence in the light of the whole record, one or more of
17 the following:

18 (1) Substantial changes are proposed in the project which will require major
19 revisions of the previous EIR or negative declaration due to the involvement of
20 new significant environmental effects or a substantial increase in the severity of
21 previously identified significant effects;

22 (2) Substantial changes occur with respect to the circumstances under which the
23 project is undertaken which will require major revisions of the previous EIR or
24 negative declaration due to the involvement of new significant environmental
25 effects or a substantial increase in the severity of previously identified significant
26 effects; or

27 (3) New information of substantial importance, which was not known and could not
28 have been known with the exercise of reasonable diligence at the time the
29 previous EIR was certified as complete or the negative declaration was adopted,
30 shows any of the following:

31 (A) The project will have one or more significant effects not discussed in the
32 previous EIR or negative declaration;

33 (B) Significant effects previously examined will be substantially more severe
34 than shown in the previous EIR;

35 (C) Mitigation measures or alternatives previously found not to be feasible would
36 in fact be feasible, and would substantially reduce one or more significant
37 effects of the project, but the project proponents decline to adopt the
38 mitigation measure or alternative; or

1 (D) Mitigation measures or alternatives which are considerably different from
2 those analyzed in the previous EIR would substantially reduce one or more
3 significant effects on the environment, but the project proponents decline to
4 adopt the mitigation measure or alternative.

5 None of the conditions requiring preparation of a Subsequent EIR exist for the proposed
6 Project and, as such, the preparation of an Addendum to the previously certified EIR is
7 appropriate.

8 **1.3 Previous Environmental Documents** 9 **Incorporated by Reference**

10 Consistent with Section 15150 of the State CEQA Guidelines, the following documents
11 were used in preparation of this Addendum and are incorporated herein by reference.

- 12 ▪ Port of Los Angeles. 2008, September. San Pedro Waterfront Project Draft
13 EIS/EIR (SCH No. 2005061041).
- 14 ▪ Port of Los Angeles. 2009, September. San Pedro Waterfront Project Findings of
15 Fact and Statement of Overriding Considerations.
- 16 ▪ Port of Los Angeles. 2009, September. San Pedro Waterfront Project Mitigation
17 Monitoring Report and Program.
- 18 ▪ Port of Los Angeles. 2009, September. San Pedro Waterfront Project Final
19 EIS/EIR (SCH No. 2005061041).
- 20 ▪ Port of Los Angeles. 2011, November. Addendum to the San Pedro Waterfront
21 Project Final EIR/EIS Warehouse Nos. 9 and 10, Crafted at the Port of Los
22 Angeles.
- 23 ▪ Port of Los Angeles. 2015, June. EIR Addendum San Pedro Waterfront Project,
24 Harbor Boulevard/7th Street/Sampson Way Intersection Improvements (SCH No.
25 2005061041, APP No. 041122-208).

26 **1.4 Evaluation of Environmental Impacts**

27 This document, prepared pursuant to CEQA, constitutes an Addendum to the SPW
28 Project EIR. These documents, together with the other documents incorporated by
29 reference herein, serve as the environmental review of the SPPM Project, as required
30 pursuant to the provisions of CEQA, the State CEQA Guidelines, and the City of Los
31 Angeles procedures for CEQA implementation.

32 The SPW Project EIS/EIR described the affected resources and evaluated the potential
33 impacts on those resources as a result of building and operating the SPW Project,
34 including redevelopment of Ports O'Call. Impacts on Cultural Resources, Groundwater
35 and Soils, Hazards and Hazardous Materials, Land Use and Planning, Transportation and
36 Navigation (Marine), and Utilities and Public Services were determined to be less than
37 significant or were reduced to a level that is considered less than significant through the
38 adoption of mitigation measures. Impacts on Aesthetics, Air Quality, Biological

1 Resources, Geology, Noise, Recreation, Ground Transportation, and Water Quality,
2 Sediments, and Oceanography, however, were identified as significant and unavoidable.
3 For those impact areas, the Board adopted a Statement of Overriding Considerations.

4 The First EIR Addendum for Warehouse Nos. 9 and 10, Crafted at the Port of Los
5 Angeles, analyzed the development of a marketplace for handmade goods with a higher
6 number of visitors and workers than for the originally proposed low-intensity uses and
7 did not find any new significant impacts or increase in severity of previously identified
8 impacts as previously disclosed in the SPW Project EIS/EIR. Because the First
9 Addendum did not change the findings and conclusions of the SPW Project EIS/EIR, the
10 impact analysis below primarily compares the SPPM Project to the conclusions of the
11 SPW Project EIS/EIR.

12 Additionally, the Second EIR Addendum that analyzed design changes to the Harbor
13 Boulevard/7th Street/Sampson Way Intersection did not find any new significant impacts
14 or increase in severity of previously identified impacts as previously disclosed in the
15 SPW Project EIS/EIR. Because the Second Addendum did not change the findings and
16 conclusions of the SPW Project EIS/EIR, the impact analysis below primarily compares
17 the SPPM Project to the conclusions of the SPW Project EIS/EIR.

18 This Addendum addresses whether the conditions set forth in Section 15162 of the State
19 CEQA Guidelines that would require a subsequent or supplemental EIR are met, and
20 whether there are new significant impacts or a substantial increase in the severity of
21 previously identified impacts resulting from the proposed Project. For purposes of
22 determining whether new or substantially more severe “significant effects” would occur
23 under State CEQA Guidelines Section 15162, the criteria for determining whether
24 environmental effects would be significant in this Addendum analysis are the same as the
25 significance thresholds contained within the certified SPW Project EIS/EIR.

26 The potential environmental effects of the SPPM Project are evaluated for each of the
27 following areas that were previously evaluated in the SPW Project EIS/EIR.

- 28 ▪ Aesthetics
- 29 ▪ Air Quality
- 30 ▪ Biological Resources
- 31 ▪ Cultural Resources
- 32 ▪ Geology and Soils
- 33 ▪ Greenhouse Gas Emissions
- 34 ▪ Groundwater and Soils
- 35 ▪ Hazards and Hazardous Materials
- 36 ▪ Hydrology and Water Quality
- 37 ▪ Land Use and Planning
- 38 ▪ Noise
- 39 ▪ Recreation
- 40 ▪ Transportation and Circulation (Ground)

- 1 ▪ Transportation and Circulation (Marine)
- 2 ▪ Utilities and Public Services
- 3 ▪ Water Quality, Sediments, and Oceanography
- 4 ▪ Environmental Justice
- 5 ▪ Socioeconomics and Environmental Quality
- 6 ▪ Growth Inducement
- 7 ▪ Cumulative Impacts

8 **1.5 Summary of Findings**

9 Based on the findings of this Addendum, the SPPM Project would not result in any new
10 significant impacts or a substantial increase in the severity of previously identified
11 impacts that were analyzed in the SPW Project EIS/EIR, and none of the conditions set
12 forth in Section 15162 of the State CEQA Guidelines that would otherwise require
13 preparation of a subsequent EIR are met in this instance.

14

3 **2.1 Project Location and Setting**

4 The SPPM Project would involve redevelopment of Ports O’Call in the Port of Los
5 Angeles (Port) as part of the San Pedro Waterfront (SPW) Project. The SPW Project
6 comprises approximately 400 acres along the western boundary of the Port, adjacent to
7 the community of San Pedro, generally encompassing the land and water areas between
8 Los Angeles Harbor’s Main Channel to the east and Harbor Boulevard to the west, from
9 the Vincent Thomas Bridge to the north, and southward toward Inner Cabrillo Beach (see
10 Figure 2-1).

11 The SPPM Project site is contained within the boundaries of the study areas for Ports
12 O’Call redevelopment and a small portion of the town square development that were
13 analyzed in the SPW Project EIS/EIR and comprises a total of approximately 45 acres
14 within the San Pedro Waterfront area between the Los Angeles Harbor’s Main Channel
15 and Sampson Way from Berths 73-Z to 83 (Figure 2-2). The existing uses within the
16 Project area, which is still currently known as Ports O’Call Village, include a faux New
17 England fishing village that was developed in 1963 with a total of approximately 150,000
18 square feet of restaurant and retail space and a staging area for various festivals,
19 including the Lobster Festival and the Tall Ship Festival. The Project area also includes
20 sport fishing at Berth 79, harbor cruise and whale watching at Berths 79 and 77, a marina
21 with 126 boat slips, approximately 0.9 acre of open space near the western end of the
22 Project site, and parking lots totaling 1,848 parking spaces (Desman Associates 2014).

23 At the southern end of Ports O’Call is the Jankovich fueling station at Berth 74. This
24 facility currently contains six aboveground storage tanks, including a 100,000-gallon
25 fixed-roof tank within an approximately 2,500-square-foot diked area that is used to store
26 diesel fuel. The other five tanks are located within a separate diked area, and include four
27 25,000-gallon fixed-roof tanks that are used to store diesel fuel and one 15,000-gallon
28 tank used to store gasoline.

29 **2.2 Project Objectives**

30 The California Environmental Quality Act (CEQA) project objectives identified in the
31 SPW Project EIS/EIR that are relevant to the SPPM Project are described below.

- 1) Enhance and revitalize the existing San Pedro Waterfront area, improve existing pedestrian corridors along the waterfront, increase waterfront access from upland areas, and create more open space, through:
- providing public access to the San Pedro Waterfront and new open spaces, including parks and other landscape amenities linked to the promenade;
 - creating a continuous waterfront promenade throughout the project area allowing the public access to the water's edge;
 - enhancing key linkages between downtown San Pedro and the waterfront, including the creation of a downtown harbor and promenade that will become the focal point for vessel activity and draw visitors to downtown San Pedro;
 - creating and expanding the waterfront promenade as part of the California Coastal Trail to connect the community and region to the waterfront;
 - providing for a variety of waterfront uses, including berthing for visiting vessels, harbor service craft and tugboats, as well as other recreational, commercial, and port-related waterfront uses;
 - providing for enhanced visitor-serving commercial opportunities within Ports O'Call, complementary to those found in downtown San Pedro, as well as a potential conference center; and
- 2) Demonstrate the Los Angeles Harbor Department's commitment to sustainability by reflecting the Port's Sustainability Program policies and goals in the project design, construction, and implementation.

2.3 EIR Project Description Assumptions

As described above, among the CEQA Project Objectives identified in the SPW Project EIS/EIR was "providing for enhanced visitor-serving commercial opportunities within Ports O'Call, complementary to those found in downtown San Pedro, as well as a potential conference center." As one component of the SPW Project, Ports O'Call redevelopment was identified at a conceptual level, allowing for a total of 375,000 square feet of development that would include redevelopment of approximately 150,000 square feet of existing uses and 150,000 square feet of new development (the SPW Project EIS/EIR assumed that approximately 125,000 square feet of this area would be developed for restaurant uses, and approximately 175,000 square feet would be developed for commercial uses), and a new conference center measuring up to 75,000 square feet, of which approximately 37,500 square feet would be available for congregation or meeting space.

Other elements of the SPW Project at Ports O'Call included extension of the waterfront promenade along the entire Ports O'Call site and around the Southern Pacific (S.P.) Slip; removal of existing waterside structures and piles and installation of new piles, bulkheads, and floating docks; removal of marina slips in the Ports O'Call area for which replacement slips have already been made available in the Cabrillo Way Marina; and incorporation of "Fishermen's Park," an approximately 4.3-acre park within Ports O'Call that would be designed as an integral feature of the commercial development to accommodate Ports O'Call visitors, encourage harbor viewing, allow for picnicking, and

K:\In\me\GIS\Projects\POL\A\00000_16\mapdoc\Fig02_2_Proj_Loc.mxd Date: 4/22/2016 24991



Legend

- Proposed Project Boundary
- EIS/EIR Project Boundary



Figure 2-2
Project Location
Addendum to the San Pedro Waterfront Project EIR for the San Pedro Public Market Project

1 host special events. It was envisioned to incorporate landscaping, hardscape, outdoor
2 furniture, lighting, a water feature, and an outdoor amphitheater with seating for 500
3 people. The precise location of the park within Ports O'Call was unspecified, as it was to
4 be integrated into a larger development plan for the redevelopment of the entire Ports
5 O'Call area.

6 Several parking areas that would total 2,638 parking spaces for Ports O'Call patrons were
7 also identified, including the following.

- 8 • approximately 400 surface spaces at Berths 78–83
- 9 • approximately 1,652 spaces in four 4-level structures that would be constructed
10 at the bluff site located at the existing S.P. Railyard
- 11 • approximately 330 existing surface spaces at Berths 73–77
- 12 • approximately 256 spaces at a new surface parking lot proposed at 22nd Street
13 and Sampson Way

14 The SPW Project EIS/EIR assumed that redevelopment of Ports O'Call would occur in
15 two phases over a 5- to 10-year period. For the purposes of the analyses in the SPW
16 Project EIS/EIR, Phase 1 of construction was assumed to occur between June 2009 and
17 June 2010, and Phase 2 of construction was assumed to occur between December 2010
18 and June 2012. Additionally, the lease was assumed to be for a period of 30 years out to
19 2037.

20 **2.4 Proposed Modifications**

21 The SPPM Project is consistent with the development scenario for Ports O'Call analyzed
22 in the SPW Project EIS/EIR and summarized above. The SPPM Project would introduce
23 a similar mix of land uses and would include most of the other SPW Project components,
24 such as extension of the promenade and provision of other recreational elements, a
25 trolley, parking areas, and waterside improvements. Under the SPPM Project, overall
26 development intensity would be similar; however, the development of a 75,000-square-
27 foot conference center, which was a possibility discussed in the SPW Project EIS/EIR, is
28 not currently anticipated to be developed. Also, the SPPM Project would reconfigure the
29 promenade to avoid the coverage and shading of the mudflat at Berth 78 that would have
30 occurred under the development scenario for Ports O'Call analyzed in the SPW Project
31 EIS/EIR, eliminating the need to mitigate for this impact at the Salinas de San Pedro Salt
32 Marsh (see Section 4.4, Biological Resources). Additionally, the proposed lease would be
33 for 50 years, which extends beyond the planning horizon of 2037, which was assumed in
34 the SPW Project EIS/EIR. Lastly, adjustments to the SPPM Project from that which was
35 analyzed in the SPW Project EIS/EIR will require review by the U.S. Army Corps of
36 Engineers for all in-water development. All modifications are being developed and
37 designed in coordination with the respective resource agencies (U.S. Army Corps of
38 Engineers and California Department of Fish and Wildlife). A detailed description of the
39 SPPM Project features is provided below and a comparison between the project analyzed
40 in the SPW Project EIS/EIR and the SPPM Project analyzed in this Addendum is
41 provided in Table 2-1 below.

1 **Table 2-1. Ports O'Call Development Comparison: SPW Project EIS/EIR vs. SPPM Project**

Project Feature	SPW Project EIS/EIR	SPPM Project
Total development square footage	375,000 total sf: <ul style="list-style-type: none"> • 125,000 sf restaurant space • 175,000 sf commercial • 75,000 sf conference center 	300,000 total sf: <ul style="list-style-type: none"> • 100,000 sf restaurant • 38,600 sf retail • 30,000 sf maritime-related office uses • 131,400 sf retail, restaurant, or commercial uses (based on market conditions) in Phase 2
Conference space	75,000 sf, assumed to accommodate a maximum 1,000 people, with an average of 300 people attending 5 daytime events/month, and an average of 100 people attending 15 weekend/evening events per month	None
Fishermen's Park	3 acres with amphitheater for 500 people	Now called City Park. 4.3-acre multi-purpose plaza with landscaping, hardscape, outdoor furniture and lighting; separate 500-seat amphitheater included in Discovery Sea Amusement area of the Project site
Discovery Sea Amusement Area	Not included	During Phase 1, 6.4-acre amusement area with playground facilities, entertainment attractions, and garden uses. During Phase 2, some of these uses in this area may be removed to allow construction of remaining square footage.
Waterfront Promenade	A continuous water's edge Promenade (with over-water sections ranging from 12 to 70 feet-wide). The mudflat at Berth 78 was proposed to be fully covered.	The Promenade will be constructed mostly landside, with an over-water component surrounding and not affecting the mudflat.
Waterfront Red Car Line	Rail, with stops at 7th and 13th Streets	Rail right-of-way within the SPPM Project footprint to be provided along Sampson Way alignment for future potential reinstatement of Red Car rail line. A rubber-tired trolley or rail trolley is anticipated to be included to move visitors within the Project site as well as provide connections to SPW attractions and the downtown San Pedro commercial district.
Red Car Maintenance Facility	To be located in the bluff area, near 13th Street	If a rail trolley is implemented, a maintenance facility will be constructed on site.
Over-Water Wharf/Floating Dock Structures	Removal of 89,900 sf of existing wharf/floating dock area; replace with 83,700 sf of wharf/floating dock	Removal and/or restoration of 89,900 sf of existing wharf/floating dock area; replace and/or renovation with 73,200 sf of wharf/floating dock area and floating restaurants.
No. of new piles	451 piles	Detailed design is not yet available, but would be fewer than 451.
Bulkhead installation (linear feet)	150	No replacement of bulkhead, only minor repairs to existing bulkhead

Project Feature	SPW Project EIS/EIR	SPPM Project
Berth 78 mudflat	750 sf of coverage	No coverage of mudflat. Impact avoided. No mitigation required at Salinas de San Pedro Salt Marsh.
Parking	2,638 spaces dedicated to Ports O’Call patrons in the following locations: <ul style="list-style-type: none"> • approximately 400 surface spaces at Berths 78–83 • approximately 1,652 spaces in four 4-level structures that would be constructed at the bluff site located at the existing S.P. Railyard • approximately 330 existing surface spaces at Berths 73–77 • approximately 256 spaces at a new surface parking lot proposed at 22nd Street and Sampson Way 	1,909 surface spaces in Phase 1: <ul style="list-style-type: none"> • Approximately 915 spaces at main parking lot • Approximately 220 spaces at secondary/valet parking lot • Approximately 100 spaces at north parking lot • Approximately 670 spaces at west parking lot Structured parking spaces will be developed in Phase 2 with total spaces to be determined based on land use mix. The surface parking lot at 22nd Street and Sampson Way with 256 spaces was completed in 2009.
Construction Schedule	Phase 1: June 2009 – June 2010 Phase 2: December 2010 – June 2012	Phase 1: late 2018 – late 2020 Phase 2: to be determined; for the purposes of the addendum, assumed to begin within 5 to 10 years of Phase 1 completion, and last approximately 2 to 3 years.
Visitor Trip Generation (Build Out)	Weekday Daily: 8,632 trips Weekend Daily: 8,517 trips	Weekday Daily: 5,798 trips Weekend Daily: 6,285 trips
Terms of Lease	30 years, through 2037	50 years, through 2066

1

2 2.4.1 Landside Improvements

3 The SPPM Project would include a combination of redevelopment of the existing uses
 4 and new development, all of which would total approximately 300,000 square feet of
 5 restaurants, retail, office, open space, and entertainment uses (see Figure 2-3). New
 6 restaurant uses are anticipated to include full service restaurants, food halls, fish markets,
 7 farmers’ markets, quick-serve dining, and an assortment of various food and beverage
 8 establishments that would include alcohol sales for both on-site and off-site consumption.
 9 Retail uses would include visitor-serving shops targeting visitors to the Project area, and
 10 office uses would include maritime-related office uses. In addition, the SPPM Project
 11 would include entertainment uses such as attractions and arcade-style games, a Ferris
 12 wheel, a merry-go-round, playground facilities, a 500-seat outdoor amphitheater, and
 13 other general entertainment uses. The outdoor amphitheater may be used for both public
 14 and private ticketed events. The SPPM Project would also include installation of a
 15 waterside promenade and a trolley system. At full buildout, the SPPM Project would
 16 operate 7 days a week during normal business hours with special events and other
 17 activities as scheduled.

18 The SPPM Project would be divided into three main planning areas: the City Park, the
 19 Marketplace, and the Discovery Sea Amusement Area (see Figure 2-3).

- 1 • **City Park (formerly “Fisherman’s Park”):** The City Park planning area would
 2 occupy the northern portion of the Project site—an extension of San Pedro’s
 3 downtown off 6th and 7th streets. This area of the Project site would include
 4 approximately 23,800 square feet of restaurants as well as a 4.3-acre park—a
 5 multi-purpose plaza with landscape, hardscape, outdoor furniture, and lighting
 6 that could be used for public events, such as a Farmer’s Market and art shows.
 7 Buildings are anticipated to be no taller than 40 feet in height.
- 8 • **Marketplace:** The Marketplace area would occupy the central portion of the
 9 Project site and would include the highest concentration of development, with
 10 approximately 142,200 square feet of restaurants, visitor-serving retail, fish and
 11 farmers’ markets, and maritime-related office space in buildings ranging from 40
 12 to 50 feet in height as well as a 60-foot-tall centrally located tower.
- 13 • **Discovery Sea Amusement Area:** The Discovery Sea Amusement Area would
 14 occupy the southern portion of the Project site and would include a 6.4-acre
 15 privately operated amusement component. This area would be generally open to
 16 the public, but may occasionally have restricted access for private functions, such
 17 as weddings or private concerts. This space would include playground facilities,
 18 entertainment attractions, and garden uses. Entertainment attractions within this
 19 area could include various temporary and permanent rides and attractions, such
 20 as an approximately 100-foot-high Ferris wheel, a carousel, and arcade-style
 21 games. It would also include a 500-seat amphitheater, which was previously
 22 evaluated in the SPW Project EIS/EIR. Garden uses could include art, public and
 23 private dining spaces, wedding facilities, water features, and informational and
 24 educational displays.


25 In addition, the SPPM Project may include a trolley route through the Project site that
 26 would act as a private transportation amenity paying homage to the historic San Pedro
 27 Red Car Line. This trolley may be fixed-rail or rubber tire or both. In the event a fixed-
 28 rail trolley is included, a maintenance facility comparable with the facility evaluated in
 29 the SPW Project EIS/EIR would be constructed on the site. Also as evaluated in the SPW
 30 Project EIS/EIR, the existing railroad tracks within the “bluff” area (west of Sampson
 31 Way) would be removed as part of the SPPM Project. The Port would retain a right-of-
 32 way for rail tracks along the newly aligned Sampson Way for possible Waterfront Red
 33 Car or other light rail system operation should they be constructed in the future.

34 The initial phase of the SPPM Project would include up to approximately 1,909 surface
 35 parking spaces at parking ratios consistent with or in excess of those in the SPW Project
 36 EIS/EIR. Phase 1 of construction (described in more detail below) would include the
 37 development of all surface lots depicted in Figure 2-4 comprising:

- 38 ▪ Approximately 1,235 spaces at the parking lots east of the realigned Sampson
 39 way, and
- 40 ▪ Approximately 670 spaces at the west parking lot to be constructed in the bluff
 41 area west of the realigned Sampson Way.

42 In Phase 2, the number of spaces to be developed in the parking structures would be
 43 determined according to the specific land use mix determined by market demand, and
 44 consistent with the parking ratios in the SPW Project EIS/EIR. In addition to a paid

K:\Irvine\GIS\Projects\POI\A\00000_16\mapdoc\Fig2_3_Proposed_Site_Plan_Phase1.mxd Date: 4/22/2016 2:49:51



DISCOVERY SEA AMUSEMENT SECTION



MARKETPLACE SECTION




CITY PARK SECTION



Figure 2-3
Proposed Site Plan Phase 1
Addendum to the San Pedro Waterfront Project EIR for the San Pedro Public Market Project

Improvements Overview



Parking Overview

Phase 1A - Main Parking lot: approx 915 spaces
 Phase 1B - Secondary / Valet Parking Lot: approx 220 spaces
 Phase 1C - North Parking lot : approx 100 spaces + valet drop off areas
 Phase 1D - West Parking lot on grade approx 670 spaces
 Total Surface Parking (non-structured) approx 1909 Spaces
 Current POC Parking: approx 1800

Development Overview

Ground Floor 123,000 SF
 Second Floor 43,000 SF
 Total 166,000 SF
 Open Space Improvements + Buildings
 Occupy Approximately 16 Acres
 Total Site Land 36 Acres

K:\Irvine\GIS\Projects\POLA\00000_16\mapdoc\Fig02_4_Proposed Parking Phase 1.mxd Date: 4/22/2016 2:49:51



Figure 2-4
Proposed Parking Plan Phase 1
Addendum to the San Pedro Waterfront Project EIR for the San Pedro Public Market Project

1 parking system, a variety of standard and compact spaces may be used along with
2 operational systems such as valet to meet parking requirements.

3 The Jankovich fueling station will be removed and the site remediated consistent with the
4 SPW Project EIS/EIR prior to development of the Discovery Sea portion of the SPPM
5 Project. Relocation of the Jankovich fueling station is not part of the SPPM Project and
6 would be conducted under a separate project approval process. While the details of the
7 relocation are in the process of being finalized, the fueling station may move to Mike's
8 Marine Fueling Station south of the Project site at Berth 72 off the Main Channel.

9 **2.4.2 Waterside Improvements**

10 The SPPM Project would reconfigure the existing waterside amenities, including the
11 boardwalks and docks, into visitor-serving courtesy docks and docks for commercial
12 sport fishing, whale watching, harbor cruise, water taxis, and related water-side tenants
13 and up to 25,000 square feet of restaurant, retail, or maritime-related office space.
14 Consistent with the SPW Project EIS/EIR, the SPPM Project would replace and/or
15 restore the existing 89,900 square feet of over-the-water wharf structures and floating
16 docks in the Project site, including the existing marina and all its associated in-water
17 structures, with no more than 73,200 square feet of new and/or restored over-the-water
18 wharf structures and floating docks. No dredging activities would be conducted as part of
19 the SPPM Project. Existing tenants of the marina are in the process of vacating, which
20 should be completed before the end of 2016.

21 Reconstruction of the floating dock (which was previously analyzed in the SPW Project
22 EIS/EIR as part of the 7th Street Harbor and 7th Street Pier) would include approximately
23 600 linear feet of dock. New floating transient vessel docks, as contemplated in the SPW
24 Project EIS/EIR, would be constructed as well. The SPPM Project includes waterside
25 attractions consisting of floating restaurants which may be semi-permanently moored at
26 the dock, while others would offer harbor and dinner cruises. Whereas in the SPW
27 Project EIS/EIR the proposed waterfront promenade would have been built with half of
28 the structure hanging over the water, the majority of the proposed promenade would now
29 be built completely on land adjacent to the water's edge with the exception of a small
30 portion that would extend over the water around the mudflat at Berth 78. This portion of
31 the promenade would be raised above the surface of the water and elevated on piers. The
32 mudflat (0.175 acre) is essentially a low, flat area landward of shoreline protection rock
33 that is tidally inundated and has been the site of fine sediment deposition. All over-water
34 improvements, including the floating restaurants and promenade around the mudflat,
35 would not exceed the square footage of over-water structures or total number of piles
36 evaluated in the SPW Project EIS/EIR.

37 **2.4.3 Construction Phasing**


38 The SPPM Project would be developed in two phases. Phase 1 would involve
39 development of 100,000 square feet of restaurant space, 38,600 square feet of retail, and
40 30,000 square feet of Port-related office uses (see Figure 2-5), for a total of 168,600
41 square feet in the City Park and Marketplace planning areas. In addition, the 4.3-acre
42 Fishermen's Park would be developed in the City Park area and 6.4 acres of
43 amusement/playground space would be developed in the Discovery Sea Amusement
44 Area. Overall, Phase 1 is envisioned to include a series of waterfront buildings,
45 Fishermen's Park (City Park) and associated attractions, over-water uses, and parking all

1 linked by a promenade. Ancillary restaurants, retail, and entertainment uses may be
2 incorporated within the proposed Fishermen’s Park (City Park). Construction of Phase 1
3 is anticipated to begin in late 2018 and would be completed by late-2020.

4 Phase 2 would involve development of the remaining 131,400 square feet of retail,
5 restaurant, and/or commercial uses within the Discovery Sea Amusement Area and would
6 shift the amusement/playground space west and decrease the size of the amusement area,
7 partially taking some surface parking (see Figure 2-6). The displaced surface parking
8 would be accommodated in the bluff site parking structure also planned to be developed
9 in Phase 2. The development of the remaining 131,400 square feet of retail, restaurant,
10 and/or commercial uses would be programmed based on market conditions. In addition,
11 as mentioned above, the number of spaces in the parking garage would be determined
12 according to the specific land use mix, and consistent with the parking ratios in the SPW
13 Project EIS/EIR. Timing for construction of Phase 2 is yet to be determined and would be
14 driven by market demand, but for the purposes of this Addendum, it is anticipated that
15 construction would begin within 5 to 10 years of Phase 1 completion, and last
16 approximately 2 to 3 years.

17


K:\Irvine\GIS\Projects\POLA\000000_16\mapdoc\Fig02_5_Phase_1.mxd Date: 3/31/2016 2:49:51



**DEVELOPER CONSTRUCTION
PHASE 1**
COMMENCEMENT EARLY 2018
COMPLETION MID 2020



Figure 2-5
Phase I Construction
Addendum to the San Pedro Waterfront Project EIR for the San Pedro Public Market Project



K:\livine\GIS\Projects\POLA\00000_16\mapdoc\Fig02_6_Phase_2.mxd Date: 3/31/2016 2:49:11

1
2

Chapter 3 Environmental Setting

3 This chapter presents the environmental setting for the SPPM Project site and
4 surrounding areas. The setting is described as it relates to potential environmental effects
5 associated with the SPPM Project. A discussion of the potential environmental impacts is
6 provided in Chapter 4, *Environmental Impact Analysis*.

7 **3.1 Aesthetics**

8 The overall visual character of the project area has remained relatively the same since the
9 certification of the San Pedro Waterfront (SPW) Project EIS/EIR.

10 The Port’s visual setting is varied due to the diverging intensity of development,
11 topographic characteristics, landscape features, and the quality of views of the harbor and
12 open sea that are afforded from specific locations.

13 The view from Sampson Way looking west toward Beacon Street and Harbor Boulevard
14 is of the residences that flank Beacon Street and their approximate 60-foot elevation
15 above the waterfront at Ports O’Call. The sloped hillside separates Harbor Boulevard
16 from Beacon Street and locates the residents back from the viewing edge so that sight
17 lines extend over this area and the red rooftops at Ports O’Call frame the lower edge of
18 the view. The bluff in this location is stabilized by a vertical, unadorned concrete wall
19 with an average height of 30 feet. Palm trees of varying heights line the bluff and Beacon
20 Street and define the view as a well-established, Southern California coastal community.

21 There are also some new visual elements in the area, and a few of the SPW Project
22 components have been either completed or modified. These features are described below.

23 **3.1.1 U.S.S. Iowa**

24 Located at First Street and Harbor Boulevard at Berth 87, the U.S.S. Iowa is a new
25 feature to the San Pedro Waterfront area. The ship is an historic vessel commissioned in
26 1943 and is now a museum operated by the Pacific Battleship Center. The battleship is a
27 45,000-ton Iowa class battleship and iconic because of its history of active military
28 service, big guns, heavy armor, and design for speed.

29 **3.1.2 AltaSea Marine Research Center**

30 In 2012 the City Dock No. 1 Marine Search Center Project EIR was certified and
31 included 28 acres of marine research facilities and marine business space at Berths 56

1 through 60 and Berths 70 and 71. At the time of preparation of the SPW Project EIS/EIR,
2 no specific development plans had been identified for this site; however, the EIS/EIR did
3 evaluate the future uses of the site as institutional/research and development use at a
4 programmatic level. The project is now called the AltaSea Marine Research Center.
5 Planning and design of the AltaSea facility is ongoing and will be assessed in a separate
6 environmental analysis. At final buildout the AltaSea Marine Research Center is expected
7 to include a new building with classrooms, a lecture hall/auditorium, and interpretive
8 center open to the public at Berth 56; establishment of a marine science business
9 park/incubator space with offices and research laboratory space within the Berths 58–60
10 transit sheds; and construction of a new marine research facility at Berth 57.

11 **3.1.3 Downtown Harbor**

12 Several design elements for the Downtown Harbor have changed since the approval of
13 the SPW Project EIS/EIR and include more open space, widening of the promenades, and
14 improvement of the physical and visual connectivity with downtown San Pedro. The
15 Downtown Harbor project was completed in 2014 and included development of the area
16 along Harbor Boulevard between 5th and 6th Streets with modifications to Berths 84–86
17 (between the LA Maritime Museum and Fire Station 112). Overall, the project cut 1.2
18 acres of existing waterfront land to create a new harbor inlet for vessels and
19 approximately 700 linear feet of promenade. Surrounding the inlet is a public plaza and
20 pedestrian promenade that features trees and landscaping, decorative lighting, a picnic
21 area, and an overlook pier.

22 **3.1.4 Crafted Marketplace & Brouwerij West**

23 Reuse of Warehouses Nos. 9 and 10 was envisioned in the SPW Project EIS/EIR to be
24 adapted for low-intensity, visitor-serving commercial or educational uses. Warehouse No.
25 9 has been adaptively reused and is now the location of Brouwerij West, a 15,000-barrel
26 craft brewing operation with tours and tastings. Food is currently available from food
27 trucks that visit the site but a restaurant is part of future development plans. Warehouse
28 No. 10 has been restored and is the location of Crafted, a new large-scale permanent craft
29 marketplace hosting more than 100 shop spaces for artists, crafters, and food vendors.

30 **3.1.5 Redesign of Sampson Way/7th Street 31 Intersection**

32 Redesign of the Sampson Way and 7th Street intersection was previously analyzed in the
33 SPW Project EIS/EIR and included an enhanced four-way intersection with a
34 modification of the 6th Street connection to Sampson Way, eliminating access to
35 Sampson Way from Harbor Boulevard via 6th Street. The modification would have
36 resulted in two through lanes in each direction on Sampson Way and two through lanes in
37 each direction on Harbor Boulevard.

38 In June 2015, the Port prepared an addendum to the SPW Project EIS/EIR that would
39 shift the intersection farther south of 7th Street, improve vehicular access to and along the
40 waterfront, and provide additional pedestrian access. The project would also improve
41 safety for pedestrians and vehicles by providing signalized intersections, shorter-distance
42 striped crosswalks, designated bike lanes, and continuous pedestrian pathways. The
43 redesign also proposed an extension of Plaza Park to an open space area west of Harbor

Boulevard including a plaza area, lighting, trees, and irrigation. Construction is expected to start in late August 2016 and be completed by the end of March 2018.

3.2 Air Quality and Meteorology

3.2.1 Air Quality

The setting for air quality and meteorology has remained relatively the same since the certification of the SPW Project EIS/EIR. The most recent available air quality data for the project area are presented in Tables 3.2-1 and 3.2-2. As shown, maximum pollutant concentrations of criteria pollutants have decreased slightly for the most part in the immediate project area since preparation of the SPW Project EIS/EIR.

Table 3.2-1. Maximum Pollutant Concentrations Measured at the North Long Beach Monitoring Station

Pollutant	Averaging Period	National Standard	State Standard	Highest Monitored Concentration	
				2007 (from the SPW Project EIS/EIR)	2013
Ozone (ppm)	1 hour	NA	0.09	0.099	0.092
	8 hours	0.08	0.07	0.073	0.070
Carbon monoxide (CO) (ppm)	1 hour	35	20	3.3	Not available
	8 hours	9	9	2.59	2.0
Nitrogen dioxide (NO ₂) (ppm)	1 hour	NA	0.18	0.107	0.066
	Annual	0.053	0.030	0.020	0.014
Sulfur dioxide (SO ₂) (ppm)	1 hour	NA	0.25	0.037	0.022
	24 hours	0.14	0.04	0.010	0.010
	Annual	0.03	NA	0.003	NA
Coarse particulate matter (PM ₁₀) (µg/m ³)	24 hours	150	50	232.0	37
	Annual	NA	20	33.5	23.2
Fine particulate matter (PM _{2.5}) (µg/m ³)	24 hours	35	NA	82.8	47.2
	Annual	12	12	14.6	11.34
Lead (µg/m ³)	30 days	1.5	1.5	Not available	0.006
	Calendar quarter	1.5	NA	0.01	0.006
Sulfates (µg/m ³)	24 hours	NA	25	Not available	4.5

Note:
 Exceedances of the standards are bolded. Although the National Ambient Air Quality Standards were not exceeded at the North Long Beach Station for CO and PM₁₀, the U.S. Environmental Protection Agency has classified the South Coast Air Basin as being in as nonattainment for these pollutants because violations have occurred at other monitoring stations in the South Coast Air Basin.
 µg/m³ micrograms per cubic meter
 ppm: parts per million
 NA: Not applicable
 The state 1-hour ozone standard was exceeded on 1 day in 2007 and on 0 days in 2013.
 The national 8-hour ozone standard was not exceeded.
 The state 24-hour PM₁₀ standard was exceeded 6 days in 2007 and 0 days in 2013. The national PM₁₀ standard was exceeded once in 2007 and for 0 days in 2013.
 The national 24-hour PM_{2.5} standard was exceeded on 1 day in 2007 and 2 days in 2013.
 Source: SCAQMD 2013

1 **Table 3.2-3. 2013 12-Month Average Pollutant Concentrations Measured for the Port of**
 2 **Los Angeles Air Quality Monitoring Program**

Pollutant	Port of Los Angeles Monitoring Stations					SCAQMD Monitoring Station
		Wilmington Community Station	Coastal Boundary Station	San Pedro Station	Source-Dominated Station	North Long Beach Station
PM10 ($\mu\text{g}/\text{m}^3$)	2007	27.8	--	--	--	30.9
	2013	26.0	24.4	--	--	23.2
PM2.5 ($\mu\text{g}/\text{m}^3$)	2007	12.4	9.8	10.7	13.5	14.1
	2013	8.9	5.9	9.3	8.3	11.3
Elemental carbon PM2.5 ($\mu\text{g}/\text{m}^3$)	2007	1.5	1.1	1.5	2.5	--
	2013	0.74	0.41	0.74	0.83	--

Notes:
 For PM10, the South Coast Air Quality Management District (SCAQMD) North Long Beach Station measures a 24-hour sample every 6 days, compared to every 3 days for the Port monitoring stations. Therefore, only one-half of the Port monitoring station samples (every other sample) have a corresponding sample from the North Long Beach Station. For PM2.5, all monitoring sites measure a 24-hour sample every 3 days.
 PM10 is not measured at the Coastal Boundary, San Pedro, or Source-Dominated Stations.
 Elemental carbon PM2.5 is not measured at the SCAQMD North Long Beach Station.
 Source: Port of Los Angeles 2015.

3

4 **3.2.2 Greenhouse Gas Emissions**

5 Sources of greenhouse gas (GHG) emissions present within the project area have
 6 remained relatively the same since the certification of the SPW Project EIS/EIR.
 7 Calculations conducted for the annual operational GHG emissions assumed sources
 8 typical of operations within the Port, including vessel transit and maneuvering, vessel
 9 hoteling, harbor craft, motor vehicles, terminal equipment, alternative marine power
 10 electricity usage, on-terminal electricity usage, and electricity associated with
 11 commercial uses and the Waterfront Red Car Line. With the exception of the Waterfront
 12 Red Car Line, operation of which has been suspended for the Sampson Way Realignment
 13 Project, these uses are still the primary sources of GHG emissions in the project area and
 14 no new major sources of GHG emissions have been constructed in the Port in the
 15 intervening years that would substantially affect GHG emissions.

16 **3.3 Biological Resources**

17 The biological resources present within the project area have remained relatively the
 18 same since the certification of the SPW Project EIS/EIR. The environmental setting
 19 contains terrestrial habitat consisting of vacant lots and developed land. Many of the trees
 20 along the waterfront provide valuable nesting and roosting habitat for both native and
 21 nonnative birds. There are also a variety of marine habitats, including mudflat, soft- and
 22 hard-bottomed benthic habitats, pier and pilings, eelgrass, riprap, and kelp forests, which

1 promote a diversity in marine species, as well as additional foraging opportunities for
2 many bird species.

3 The mudflat at Berth 78–Ports O’Call is essentially a low, flat area landward of shoreline
4 protection rock that is intermittently submerged (from tidal action) and supports intertidal
5 benthic species. The mudflat was created at the time of development of the adjacent fish
6 retail market deck that extends over the intertidal area. This area is protected from wave
7 action and as a result is a depositional area for fine sediment. The mudflat is considered a
8 depleted natural community with respect to number and extent, as well as value for
9 habitat. In addition, mudflats are regulated under the Clean Water Act as special aquatic
10 sites pursuant to the Section 404(b)(1) Guidelines (40 CFR 230). Small polychaete and
11 oligochaete worms, peracarid crustaceans, and insects are common within unvegetated
12 mudflat habitat. These invertebrate species serve as prey for shorebirds that forage at the
13 mudflats within the proposed project area.

14 **3.4 Cultural Resources**

15 The setting for cultural resources has remained relatively the same since the certification
16 of the SPW Project EIS/EIR. No specific listed archaeological or paleontological
17 resources were identified in the Ports O’Call area, but the Ports O’Call area overlies land
18 that includes both artificial fill and original bedrock areas that could contain unknown
19 fossilized remains and historic archaeological features.

20 According to the record search performed during the preparation of the SPW Project
21 EIS/EIR, two prehistoric archaeological sites (CA-LAN-145 and CA-LAN-146) were
22 previously identified within 0.3 mile of the SPPM Project area. Nearby site CA-LAN-145
23 was recorded by N.C. “Nels” Nelson in 1912, who described the site as traces of a
24 campsite. Because of the lack of artifacts, Nelson questioned the authenticity of this
25 deposit as an actual archaeological site. In addition, the site is described in Nelson’s notes
26 as being located on top of a 50-foot bluff. Development and redevelopment have resulted
27 in the grading of 40 to 50 feet of the original Palos Verdes Sand and San Pedro Sand in
28 this area. Site CA-LAN-146 was also recorded in 1912 by N.C. Nelson. He described the
29 site as a refuse heap consisting of pecten, abalone, oyster, and clamshells. CA-LAN-146
30 measured 75 feet by 150 feet with an estimated depth of 3 feet. A note in the Information
31 Center’s files dating to 1977 stated that CA-LAN-146 appeared to be completely
32 destroyed by grading activities associated with the construction of the cruise terminal
33 parking lot that currently covers the area.

34 **3.5 Geology and Soils**

35 Because geologic conditions do not generally change significantly over a short span of
36 time, the setting for geology and soils remains the same since the certification of the SPW
37 Project EIS/EIR.

38 The project site is near sea level in the coastal area of the Los Angeles Basin, a low-lying
39 plain that rises inland to the Santa Monica Mountains to the north, the Repetto and Puente
40 Hills to the northeast, the Santa Ana Mountains to the east, and the San Joaquin Hills to
41 the southeast. The basin is bordered on the west by the Pacific Ocean and the Palos

1 Verdes Hills. The major faults in the region that contribute to the seismic hazard at the
2 project site include the Palos Verdes Fault zone, north of the project site in the vicinity of
3 the Vincent Thomas Bridge, and the more distant Newport-Inglewood Fault zone,
4 approximately 7 miles northeast of the project site. The Cabrillo Fault, just south of the
5 federal breakwater, may be a branch of the Palos Verdes Fault zone, but not much is
6 known about its seismic activity. However, even a small earthquake on this fault could
7 cause damage due to its proximity to the SPPM Project site.

8 Surficial geology of the Los Angeles Harbor is characterized by Holocene-age, near-
9 shore, marine and non-marine deposits, including beach, estuary, tidal flat, lagoon,
10 shallow-water bay sediments, and shoreline terrace deposits. Dredging and filling
11 operations have modified these native sediments to create extensive land masses of
12 dredged fill material that support numerous harbor facilities. Consequently, most of the
13 harbor facilities in the project area have been constructed on dredged fill material.

14 Natural drainages at Port berths have been backfilled with undocumented fill materials.
15 In addition, the natural alluvial deposits below the site generally are unconsolidated, soft,
16 and saturated. Groundwater is present at shallow depths beneath the site. These
17 conditions are conducive to liquefaction.

18 Tsunamis are gravity waves of long wavelength generated by a sudden disturbance in a
19 body of water. Typically, oceanic tsunamis are the result of sudden vertical movement
20 along a fault rupture in the ocean floor, submarine landslides or subsidence, or volcanic
21 eruption, where the sudden displacement of water may set off transoceanic waves with
22 wavelengths of up to 125 miles and with periods generally lasting from 5 to 60 minutes.
23 Offshore faults present a local tsunami hazard and landslide-derived tsunamis are now
24 perceived as a viable local tsunami hazard.

25 Seiches are seismically induced water waves that surge back and forth in an enclosed
26 basin and may be expected in the harbor as a result of earthquakes. Any significant wave
27 front could cause damage to seawalls and docks, and could breach sea walls at the project
28 site. However, modern shoreline protection techniques are designed to resist seiche
29 damage.

30 Subsidence is the phenomenon where the soils and other earth materials underlying the
31 site settle or compress, resulting in a lower ground surface elevation. Fill and native
32 materials on site can be water saturated, and a net decrease in the pore pressure and
33 contained water will allow the soil grains to pack closer together. This closer grain
34 packing results in less volume and the lowering of the ground surface. Subsidence near
35 the project site, due to previous oil extraction in the Port area, has been mitigated and is not
36 anticipated to affect adversely the SPPM Project.

37 Generally, a landslide is defined as the downward and outward movement of loosened
38 rock or earth down a hillside or slope. Slope stabilization efforts have been completed for
39 the Ports O'Call bluff area. The remaining area within the project site is relatively flat
40 and paved, and no known or probable bedrock landslide areas have been identified.

41 Expansive soils generally result from specific clay minerals that expand when saturated
42 and shrink in volume when dry. These expansive clay minerals are common in the
43 geologic units in the adjacent Palos Verdes Peninsula. Clay minerals in geologic units in

1 the project area could be expansive, and previously imported fill soils could be expansive
2 as well.

3 The project site is in a Mineral Resource Zone (MRZ) area classified as MRZ-1, which is
4 defined as an area where adequate information indicates that no significant mineral
5 deposits (i.e., aggregate deposits) are present or where it is judged that little likelihood
6 exists for their presence (California Department of Conservation 1994).

7 **3.6 Groundwater and Soils**

8 As described in the SPW Project EIS/EIR, the Ports O'Call redevelopment area was
9 defined as "Area C" for the purposes of the groundwater and soils analysis. See Figure 3-
10 1 (Figure 3.6-1 of the SPW Project EIS/EIR) for the location of the project areas
11 evaluated in the SPW Project EIS/EIR. Area C included restaurants and shops within the
12 Ports O'Call Village, docks and facilities for commercial fishing, Jankovich & Son
13 fueling station in the SP Slip area, and a portion of the Red Car Line. Historic maps
14 indicated the area included warehousing as well as oil and gas tank facilities and
15 operations dating back to the 1960s. The following properties of concern were identified
16 within Area C of the Ports O'Call area as having a moderate likelihood of being
17 contaminated by hazardous materials from prior or ongoing operations: Jankovich & Son
18 fueling station in the SP Slip area, SP Railyard, and the former Standard/Union Oil gas
19 and oil tanks/northern. Additionally, varied historical industrial and retail uses, including
20 gas and oil companies, lumber yards, railroad rights-of way, machine shops, and repair
21 shops, were identified as non-specific areas of concern in Area C. See Figure 3-2 (Figure
22 3.6-3 of the SPW Project EIS/EIR) for the location of sites of potential concern identified
23 in the SPW Project EIS/EIR.

24 As reported in the SPW Project EIS/EIR, soil and groundwater in limited areas of the
25 Ports O'Call redevelopment area have been affected by hazardous substances and
26 petroleum products as a result of spills during historic industrial land uses. These areas
27 have been and continue to be in various stages of contaminant site characterization and
28 remediation. Mitigation Measure MM GW-1 of the SPW Project EIS/EIR required
29 LAHD to remediate all contaminated soils within the SPW Project boundaries prior to or
30 during demolition and grading activities.

31 Below is a summary of the site investigation reports and management plans that have
32 been conducted on the project site since the preparation of the SPW Project EIS/EIR.
33 Any new conditions of concern identified in these reports would be remediated or
34 resolved through compliance with Mitigation Measure MM GW-1 as well as completion
35 of any specific recommendations.

36 **3.6.1 February 2013: Soil-Gas Investigation Report**

37 The Source Group, Inc. (SGI) conducted a Soil-Gas Survey Investigation for the Ports
38 O'Call area, dated February 26, 2013. The goal of the investigation was to provide a
39 preliminary environmental screening for Berths 75 through 79 (Ports O'Call area) and to
40 evaluate site conditions, spatial variability of contaminants, and potential associated risks
41 associated with the identified compounds. The soil-gas survey was conducted to evaluate
42 the presence of volatile organic compounds (VOCs) fuel oxygenates, and total petroleum

1 hydrocarbons (TPH) in soil gas throughout the site. A total of 150 passive soil gas
2 samplers were deployed during the investigation.

3 A number of samples contained chemical levels that exceeded commercial environmental
4 screening levels (ESLs) developed by the San Francisco Regional Water Quality Control
5 Board,¹ and California Human Health Screening Levels (CHHSLs) developed by the
6 California Environmental Protection Agency (CalEPA):

- 7 ▪ TPH exceeded commercial ESLs at three locations and residential ESLs at four
8 locations.
- 9 ▪ Benzene exceeded the commercial/industrial CHHSL at four sample locations
10 and exceeded the residential CHHSL at 26 locations.
- 11 ▪ Tetrachloroethene (PCE) exceeded the commercial/industrial CHHSL at seven
12 locations and the residential CHHSL at 18 locations.

13 The highest TPH and benzene values were detected in the parking area located in the
14 central portion of the site, in the grass-covered area along the northwestern border, along
15 the southern border, and in the northern area of the site. The highest PCE and
16 trichloroethene (TCE) values were reported in the southwestern portion of the site, as
17 well as in the north-central portion of the site. SGI states the comparison of the results to
18 the CHHSLs and ESLs should not be used to draw conclusions with respect to potential
19 risk; rather, the comparison is provided as a general basis for evaluating the passive soil-
20 gas results. The data collected during this investigation were used to prepare a Phase II
21 site investigation of soil and groundwater conditions at the site discussed below.

22 **3.6.2 April 2013: Phase I ESA**

23 In April 2013, Partner Engineering and Science, Inc. was retained to prepare a Phase I
24 Environmental Site Assessment (ESA) to provide the Port with an assessment of the
25 environmental conditions at Berths 73 and 75 through 83. The following recognized
26 environmental conditions (RECs) were identified and are also consistent with what was
27 evaluated in the SPW Project EIS/EIR.

- 28 ▪ Former Unocal Marine Station No. 0692: In 2012, the Regional Water Quality
29 Control Board reopened this case for soil and groundwater contamination after
30 additional sampling of soil and groundwater conducted in 2009 detected the
31 presence of petroleum-impacted soils and groundwater. On February 14, 2012,
32 the Port submitted a Soil Management Plan (SMP) for the site and the facility
33 continues to be an open remediation site, which is planned for remediation during
34 the demolition of the buildings prior to development of the SPPM Project.
- 35 ▪ Former lumber handling and planning operations: This operation included
36 hydraulic material handling equipment, a steam-fired power plant, and heavy
37 industrial wood planning equipment. No documentation was available for review
38 regarding any clean-up operations or investigations; therefore, it is likely that oils
39 and chlorinated solvents could still be present.

¹ CalEPA has developed CHHSLs to evaluate contaminants in soil gas; however, CHHSLs were not developed for TPH and the Los Angeles Regional Water Quality Control Board does not have ESL standards. Therefore, the Soil-Gas Survey Investigation (SGI 2013) utilized the San Francisco Regional Water Quality Control Board ESLs for TPH.



Figure 3-1
Project Areas
Addendum to the San Pedro Waterfront Project EIR
for the San Pedro Public Market Project




Figure 3-2
Sites of Potential Concern Based on Historical Reviews and Site Interviews
Addendum to the San Pedro Waterfront Project EIR
for the San Pedro Public Market Project

- 1 ▪ Former rail yard and tanker storage areas: This area was investigated by CH2M
2 HILL in 2004 and the previously identified soil and groundwater contamination
3 still remain.
- 4 ▪ Jankovich: This facility is within the project site and was previously identified in
5 the SPW Project EIS/EIR. It still remains a recognized environmental condition
6 due to petroleum-impacted soil and groundwater.

7 One new REC and one new environmental issue were identified that were not previously
8 evaluated nor discussed in the SPW Project EIS/EIR.

- 9 ▪ VOCs: The findings of the 2013 Soil-Gas Investigation Report (SGI 2013),
10 described above in Section 3.6.1, were also reviewed as part of this Phase I ESA
11 and the presence of elevated levels of VOCs above ESLs and CHHSLs were
12 identified as a REC that would require further investigation and potentially
13 remediation.
- 14 ▪ Active and previously abandoned oil lines: Partner Engineering and Science, Inc.
15 reviewed a map depicting the locations of several active and previously
16 abandoned oil lines that may cross the project site. The actual locations and
17 presence of the pipelines have not been field checked, and the age and condition
18 of these pipelines require further evaluation.

19 **3.6.3 November 2013: Phase II ESA**

20 In June 2013, the Port retained ERM-West, Inc. (ERM) to prepare a Phase II ESA for the
21 area containing Berths 75–83 in the Ports O’Call redevelopment area. The goal of the
22 Phase II ESA was to provide a broad characterization of the possible impacts on soil and
23 groundwater at the site from historical operations. Fifty-five borings were advanced on
24 the site; 150 soil samples, 15 duplicate samples, and 6 groundwater samples were
25 collected. A total of 110 soil samples were analyzed for the following results:

- 26 ▪ Soil at the site does not appear to be affected by either organochlorine pesticides
27 (OCPs) or polychlorinated biphenyls (PCBs).
- 28 ▪ TPH in soil concentrations above the Regional Water Quality Control Board
29 screening criteria were only detected at two sample locations, both within the
30 southwestern portion of the site.
- 31 ▪ Black-stained soil was observed in one soil boring at a depth of 5.5 feet to 8 feet
32 below ground surface, in the western portion of the site.
- 33 ▪ VOCs were not detected in soils above industrial regional screening levels
34 (RSLs) in any of the soil samples.
- 35 ▪ Metals were detected in all soil samples. Arsenic and lead were detected at
36 concentrations above either the industrial RSLs or commercial/industrial
37 CHHSLs. Only one soil sample exceeded the commonly accepted California
38 background concentration for arsenic. Only one soil sample exceeded the
39 industrial RSLs for lead, and four soil samples exceeded the
40 commercial/industrial CHHSL for lead. Laboratory test results indicate that the
41 lead detected in soils at the site exceeded the Soluble Threshold Limit
42 Concentration (STLC)-Citric Acid Extraction for lead for use in waste
43 characterization purposes in four samples analyzed, with total lead exceeding 50
44 milligrams per kilogram (mg/kg). Further analyses of the four soil samples

1 exceeding the STLC-Citric Acid Extraction indicated that only one of the
2 samples analyzed exceeds the toxicity characteristic leaching procedure (TCLP).
3 The STLC of 5 milligrams per liter (mg/L) and the TCLP of 5 mg/L soluble lead
4 are the regulatory thresholds for the characterization as a California hazardous
5 waste and federal Resource Conservation and Recovery Act hazardous waste,
6 respectively.

- 7 ▪ Polycyclic aromatic hydrocarbons (PAHs) were detected in six soil samples,
8 primarily within the southwestern portion of the site, at concentrations above
9 industrial RSLs.

10 A total of seven groundwater samples were taken from six sample locations on the site.
11 Laboratory analysis identified the following results:

- 12 ▪ There were no detections of OCPs or PCBs in the groundwater samples.
- 13 ▪ TPH was detected in all seven groundwater samples. Only one of the samples, in
14 the southeastern portion of the site, exceeded the Regional Water Quality Control
15 Board screening level.
- 16 ▪ VOCs were detected in three groundwater samples. Only vinyl chloride was
17 detected in two groundwater samples with concentrations exceeding the
18 California Maximum Contaminant Level (MCL). These samples were located in
19 the central portion of the site.
- 20 ▪ California Title 22 Metals were detected in all seven groundwater samples.
21 Arsenic, barium, cadmium, chromium, lead, and nickel were detected above the
22 MCLs.
- 23 ▪ PAHs were detected in one of the seven groundwater samples.

24 The ERM Phase II ESA included a number of site-specific recommendations. Relatively
25 isolated soil removal or additional characterization may be warranted at the location of
26 the black-stained soil dependent upon redevelopment plans. If soils at the site are
27 disturbed by grading or excavation, they should be properly managed in accordance with
28 their waste characteristic as determined by additional laboratory confirmation testing
29 during excavation and grading. Site concentrations that exceed the groundwater screening
30 levels do not automatically indicate unacceptable human health risks; rather, an
31 exceedance may indicate that a site-specific Human Health Risk Assessment (HHRA)
32 may also be warranted (see Section 3.6.4 for discussion of HHRA conducted). In
33 addition, evaluation of the potential for vapor intrusion may be warranted once
34 development plans are finalized. Section 3.6.5 below discusses the soil management plan
35 for the Ports O'Call site that was developed in response to these issues, which will be
36 implemented during construction of the SPPM Project.

37 **3.6.4 July 2014: HHRA**

38 In August 2013, the Port retained ERM to prepare an HHRA for the Ports O'Call area
39 (Berths 75–83). ERM utilized the data collected during the Phase II ESA, discussed
40 above. As no specific redevelopment design details were available at the time the HHRA
41 was prepared, the HHRA examined generic commercial/industrial land use scenarios for
42 the potential redevelopment of the Ports O'Call area, and presented a Conceptual Site
43 Model. The HHRA did not evaluate a residential (i.e., unrestricted) use scenario for the
44 subject site. Furthermore, the HHRA specifically did not include data from the areas

1 occupied by the current tenants, the former Unocal marine fueling station at Berth 78 or
2 the Jankovich and Son property at Berth 74, as these sites are known to be contaminated
3 and/or regulated and contamination was expected to be mitigated or removed prior to
4 development. Once the final design for the SPPM Project is approved, the HHRA may be
5 re-evaluated at the discretion of the Port and the applicant.

6 The Conceptual Site Model (1) included identification of chemical sources and exposure
7 pathways that may result in human exposures and health risks; (2) aids in developing a
8 sampling plan to address significant chemical releases and migration pathways; and
9 (3) aids in identification of effective remediation alternatives, if necessary, targeted at
10 significant contaminant sources and exposure pathways. The HHRA assessed the
11 potential risk to human health of chemicals of potential concern in soil and groundwater
12 known to underlie the Ports O'Call site. The potential receptors evaluated in the HHRA
13 were future hypothetical construction workers, maintenance workers, indoor adult
14 commercial workers, shoppers, and amusement park visitors. A series of conservative
15 exposure assumptions were developed for assessing the exposure of these receptors.

16 Estimated hazards and risks associated with calculated exposures of future workers in the
17 Ports O'Call area are less than 10^{-5} and consistent with the most conservative end of the
18 acceptable risk range (10^{-6}). Hazard indexes (HIs) for estimated indoor adult workers
19 were below acceptable non-cancer hazard levels (HI=1) for all locations within the Ports
20 O'Call except sample location POC-1, which was located along the southeast property
21 line, and only slightly above the target of 1.0 at this location. At the Jankovich property,
22 estimated HIs were greater than 1.0 at several locations, indicating potentially significant
23 vapor intrusion potential associated with petroleum hydrocarbons in groundwater.

24 **3.6.5 Feb 2016: Soil Management Plan for Ports O'Call**

25 In February 2016, the Port retained Leighton Consulting Inc. to prepare an SMP for the
26 development of the Ports O'Call area (Berths 25–83). The contaminants of potential
27 concern (based on the Phase II ESA) included the following.

- 28 ▪ TPH as gasoline, diesel, and oil-range hydrocarbons
- 29 ▪ VOCs
- 30 ▪ PAHs
- 31 ▪ Title 22 metals

32 The SMP also provides protocols to prevent and minimize impacts related to
33 groundwater, soils, and hazardous materials.

34 When implemented, the SMP would provide protection and coverage for the following:

- 35 ▪ Provide protocols and approaches to be utilized during redevelopment of the
36 Ports O'Call area as they relate to the management of previously identified
37 contaminated soil material as well as unforeseen conditions, if encountered.
- 38 ▪ Identify proper handling and management practices to minimize waste creation
39 and the disposal of waste generated during construction activities, as construction
40 activities shall not contribute to the generation of hazardous waste except the
41 excavation of soils that are known to be chemically impacted, if encountered.

- 1 ▪ Prevent on-site worker and public exposure to potentially hazardous conditions
- 2 and materials.
- 3 ▪ Protect the environment through efficient resource allocation and recycling to the
- 4 greatest extent practical.

5 The findings in these reports are consistent with what was evaluated and assumed in the
6 SPW Project EIS/EIR and no new conditions of concern have been identified, with the
7 exception of the presence of elevated levels of VOCs as identified in the Passive Soil Gas
8 Survey and the active and previously abandoned oil lines.

9 **3.7 Hazards and Hazardous Materials**

10 The setting for hazards and hazardous materials has remained relatively the same since
11 the certification of the SPW Project EIS/EIR.

12 The SP Railyard was identified in the SPW Project EIS/EIR as an existing hazard
13 because it stored rail containers from the Westway Terminal, which handled and stored
14 hazardous materials and was also identified as a hazard in the SPW Project EIS/EIR. The
15 SPW Project EIS/EIR described the SP Railyard as having similar characteristics as a
16 hazardous materials storage facility, but with a reduced hazard footprint due to the
17 number of rail cars that can be stored at this site. Since the certification of the SPW
18 Project EIS/EIR, the Westway Terminal has been decommissioned and the SP Railyard
19 no longer transports or stores hazardous rail cars.

20 The Jankovich & Son fueling station is located at Berth 74 at the southern end of Ports
21 O'Call, where it meets with the mouth of the SP Slip. According to the SPW Project
22 EIS/EIR, it generally handles two commodities (gasoline and diesel) and services
23 tugboats, cruise ships, Port Police, U.S. Coast Guard, California Department of Fish and
24 Wildlife, and Los Angeles Fire Department vessels, and other shipping operations within
25 the harbor. Gasoline is considered a flammable liquid, and diesel is considered a
26 combustible liquid. Flammable materials have a flash point below 100 degrees
27 Fahrenheit, while combustible products have a flash point between 100 degrees
28 Fahrenheit and 200 degrees Fahrenheit. *Flash point* is defined as the lowest temperature
29 at which a liquid can form an ignitable mixture in air near the surface of the liquid. The
30 lower the flash point, the easier it is to ignite the material. Therefore, gasoline is slightly
31 easier to ignite at the surface of the liquid than diesel. Based on this information, the
32 Jankovich fueling station has an existing hazardous footprint per the Port's Risk
33 Management Plan that overlaps with the Ports O'Call development and the open space
34 next to the fueling station. This overlap constitutes an existing risk to vulnerable
35 populations that use the Ports O'Call area should the Jankovich fueling station have an
36 accidental release, spill, or explosion of the hazardous materials it regularly handles and
37 stores. As described in the SPW Project EIS/EIR, the operations at the fueling station
38 were planned to cease on or about June 2012, and the site was to be decommissioned,
39 including removal of the tanks and other facilities. Remediation of the site would occur,
40 if necessary, under the oversight of the Regional Water Quality Control Board. At the
41 time of preparation of this Addendum, the Jankovich fueling station is still slated to be
42 moved, but may be relocated to the current location of Mike's Main Channel Marine
43 (Mike's) fueling station at Berth 72; however, further details were not available. Mike's
44 has similar operations to the Jankovich fueling station and primarily sells fuel and
45 alternative fuels to commercial fishing boats and commercial trucks that service adjacent

1 facilities. Mike's was contemplated for continuing operations at its current location in the
2 SPW Project EIS/EIR, with restrictions identified in Mitigation Measure MM RISK-1,
3 which involved removal of all hazardous materials with flashpoints below 140 degrees to
4 remove the hazard associated with its proximity to the waterfront promenade that was
5 planned to be built adjacent to the facility at Berth 72.

6 In addition, the SPW Project EIS/EIR addressed the probability of the risk of a terrorist
7 action. There are limited data available to indicate how likely or unlikely a terrorist action
8 aimed at the Port would be; therefore, the probability of a risk of a terrorist action cannot
9 be evaluated accurately without a considerable amount of uncertainty. Nonetheless, this
10 fact does not invalidate the analysis contained herein. A terrorist action could be the cause
11 of events such as hazardous materials release and/or explosion. The potential impact of a
12 hazardous materials release, explosion, or spill due to a terrorist action would remain the
13 same as evaluated in the SPW Project EIS/EIR.

14 As discussed in the SPW Project EIS/EIR, there is also the potential for a large tsunami to
15 affect the Port, and the project area could be exposed to tsunami-induced flooding.
16 However, the Main Channel, where the Ports O'Call redevelopment would occur, was not
17 identified as an area that would experience overtopping of the existing deck elevations.

18 3.8 Land Use and Planning

19 Some land uses in the project area have changed since the certification of the SPW
20 Project EIS/EIR. New elements have been introduced into the area, including the U.S.S.
21 Iowa, the Downtown Harbor, and the Crafted Marketplace & Brouwerij West (see
22 Section 3.1, *Aesthetics*, above). While the San Pedro Community Plan was updated in
23 2013 (City of Los Angeles 2013), no major changes have occurred to the City of Los
24 Angeles General Plan or the San Pedro Community Plan. However, a comprehensive
25 amendment to the Port Master Plan (PMP) was adopted in February 2014 (Port of Los
26 Angeles 2014a).

27 The PMP establishes policies and guidelines to direct the future development of the Port
28 of Los Angeles. Goal 4 of the PMP, Increase Public Access to the Waterfront, provides
29 for enhanced public access to the waterfront and visitor-serving facilities including retail,
30 restaurants, museums, and parks. The Ports O'Call area is located in Planning Area 1 –
31 San Pedro, which encompasses the San Pedro Waterfront from the breakwater to the
32 Vincent Thomas Bridge along the western boundary of the Port. Planning Area 1
33 primarily includes land uses focused on public access to the waterfront, but also has
34 limited cargo operations and commercial fishing activities. Planning Area 1 emphasizes
35 waterfront access through a waterfront promenade, parks, museums, academic uses, and
36 visitor-serving commercial uses and attractions. The PMP reflects the SPW Project,
37 which is focused on increased public access to the waterfront, additional visitor-serving
38 commercial development within the Port, and expanded cruise activities.

39 The entire Ports O'Call Site is identified for Visitor-Serving Commercial uses on the
40 Planning Area 1 land use map. Ports O'Call Redevelopment was also specifically
41 identified as one of the proposed projects, which would redevelop Ports O'Call Village
42 into a vibrant, world-class urban waterfront destination, entitled for up to 300,000 square
43 feet of visitor-serving commercial uses and up to 75,000 square feet for a conference
44 center, a waterfront promenade, and 3 acres of open space.

1 **3.9 Noise**

2 Nothing within the Ports O'Call project area has changed substantially since certification
3 of the SPW Project EIS/EIR that would cause the noise environment to change
4 significantly. The environmental setting includes sources of noise typical of an
5 industrialized port environment with commercial and visitor-serving uses.

6 **3.10 Recreation**

7 The setting for recreational resources has remained relatively the same since certification
8 of the SPW Project EIS/EIR. All recreational resources still exist and some new
9 recreational resources have opened in the project area, including the Downtown Harbor
10 (see discussion of these resources under Section 3.1, *Aesthetics*, above). Service for the
11 existing Waterfront Red Car Line has been suspended; however, there are no other
12 disruptions to other recreational resources that were not analyzed in the SPW Project
13 EIS/EIR.

14 **3.11 Transportation and Circulation (Ground)**

15 Primary regional access to the study area is provided by the Harbor Freeway (I-110)
16 northwest of the SPPM Project site and by the Vincent Thomas Bridge and Seaside
17 Avenue (State Route [SR] (SR-47) northeast of the SPPM Project site. Access to the
18 Project area from I-110 is provided via the freeway terminus at Gaffey Street or ramps at
19 Harbor Boulevard. From SR-47, the SMMP Project site can be accessed via ramps on
20 Harbor Boulevard. Local access to the SMMP Project site is provided by a well-defined
21 grid of arterial and collector roads. The primary roadway facilities in the proposed Project
22 study area are as follows.

- 23 ▪ **Gaffey Street** is classified by the City of Los Angeles as a Major Class II
24 Highway that runs north-south in the study area. This arterial provides a
25 connection for local and regional travel from San Pedro to other parts of Los
26 Angeles and the South Bay region. Gaffey Street is a major commercial corridor
27 within San Pedro.
- 28 ▪ **Pacific Avenue** is classified as a Secondary Highway that provides north-south
29 access within San Pedro. It is a major commercial corridor within San Pedro
30 consisting of strip commercial, auto repair, and restaurants. The roadway's
31 northern terminus is at Channel Street, where the roadway continues as John S.
32 Gibson Boulevard. Its southern terminus is at the Pacific Ocean where it
33 intersects with Shepard Street and Bluff Place.
- 34 ▪ **Harbor Boulevard** is classified as a Major Class II Highway and provides north-
35 south access along the eastern side of the community of San Pedro. Harbor
36 Boulevard forms the western edge of the SMMP Project site. It continues as
37 Front Street north of Regan Street, as John S. Gibson Boulevard north of Pacific
38 Avenue, and as Miner Street south of Crescent Avenue.
- 39 ▪ **7th Street** is classified as a Secondary Highway between Weymouth Avenue and
40 Harbor Boulevard, providing east-west access through the central portion of the

1 community of San Pedro. This roadway starts just east of Western Avenue and
2 terminates at Harbor Boulevard.

- 3 ■ **9th Street** is classified as a Major Class II Highway between Western Avenue
4 and Pacific Avenue, providing east-west access through the central portion of the
5 community of San Pedro. Between Pacific Avenue and Beacon Street it is
6 classified as a Local Street. This roadway starts west of Western Avenue and
7 terminates at Beacon Street, one block west of Harbor Boulevard.

8 Freight rail activity related to the former Westways Terminal at Berth 71 no longer
9 occurs in the vicinity of the SPPM Project site, and the S.P. Railyard that was located
10 along the east side of Harbor Boulevard and west of Sampson Way is no longer
11 operational. This track was previously shared by the Waterfront Red Car Line, which is
12 also not currently operational.

13 Pedestrian and bicycle facilities compose the existing nonmotorized traffic features.
14 Pedestrian facilities include sidewalks, crosswalks, and pedestrian signals. Sidewalks are
15 provided along existing major roadway facilities in the study area, with the exception of
16 Sampson Way. Additionally, an existing pedestrian promenade extends south from the
17 Harbor Freeway along the east side of the existing rail lines to Ports O'Call. Pedestrian
18 crossings and signals are located at most major roadway intersections. Class II bike lanes
19 (lanes on roadways designated for use by bicycles through striping, pavement legends,
20 and signs) are provided on Harbor Boulevard from Front Street to 22nd Street.

21 There are a total of 13,159 parking spaces within the SPW Project area, including 11,002
22 public and 2,157 private spaces. The Ports O'Call site (including the Maritime Museum)
23 provides 1,848 existing surface parking spaces, with an additional 313 spaces in the
24 public lot adjacent to the bluff area. Additionally, the Jankovich facility provides 15
25 existing private spaces for its employees and visitors (Desman Associates 2014).

26 Changes to the development along the San Pedro Waterfront that have occurred since the
27 completion of the traffic analysis for the SPW Project EIS/EIR and that are accounted for
28 in the traffic analysis performed for this Addendum include the following:

- 29 • Replacing the original "Mercado" land use in Warehouses 9 and 10 as assessed
30 in the SPW Project EIS/EIR with the existing Crafted at the Port of Los Angeles
31 marketplace (opened June 2012) and Brewery West restaurant/micro-brewery
32 (opened February 2016)
- 33 • Revised design for the Harbor Boulevard/7th Street/Sampson Way Intersection
34 compared to what was assessed in the SPW Project EIS/EIR (construction to start
35 September 2016 and be completed March 2018)
- 36 • Adding the USS Iowa Museum project (opened July 2012)
- 37 • Replacing the original 13 acres of research & development park as assessed in
38 the SPW Project EIS/EIR with the approved City Dock #1 project

39 **3.12 Transportation and Navigation (Marine)**

40 The setting for transportation and navigation (marine) has not changed substantially since
41 certification of the SPW Project EIS/EIR. Overall, vessel traffic has decreased in recent

1 years (2,820 vessel calls in 2006 versus 2,088 vessel calls in 2015) (Port of Los Angeles
2 2016a). Similarly, cargo movement is still down from 2006 levels from 8.5 million
3 twenty-foot equivalent units (TEUs)² in 2006 to 8.2 million TEUs in 2015 (Port of Los
4 Angeles 2016b, 2016c). Cruise traffic has also decreased in recent years, with 578,668
5 cruise passengers and 122 ship calls passing through the Port in 2014 (Port of Los
6 Angeles 2016d), compared to 798,886 passengers and 162 ship calls in 2009.
7 Occurrences of vessel accidents have changed; in 2012, there were six reported allisions,
8 which involves the collision of a moving ship with one that is stationary, and one
9 grounding (Los Angeles/Long Beach Harbor Safety Committee 2015) compared to two
10 reported allisions and no groundings in 2006.

11 **3.13 Utilities and Public Services**

12 The setting for utilities and public services has remained relatively the same since
13 certification of the SPW Project EIS/EIR. Police and fire protection services continue to
14 be provided by the Los Angeles Police Department, the Port Police, and the Los Angeles
15 Fire Department. Station 36 of the Los Angeles Fire Department, which was under
16 construction at the time of preparation of the EIS/EIR, is now open and operational.
17 Water supply sources and forecasts have remained the same, and the Terminal Island
18 Treatment Plant is still within its wastewater treatment capacity and currently processes
19 approximately 15 million gallons per day (LA Sanitation 2016). This is a slight decrease
20 from the amount of wastewater treatment of 16 to 17 million gallons per day that was
21 reported in the SPW Project EIS/EIR. In addition, a bulletin dated March 2015 and
22 published by the Los Angeles County Sanitation Districts estimated that the Puente Hills
23 Intermodal Facility, which would transport waste generated in the project area to the
24 Mesquite Regional Landfill in Imperial County, would be operational within the first
25 quarter of 2016 (Sanitation Districts of Los Angeles 2015).

26 **3.14 Water Quality, Sediment, and** 27 **Oceanography**

28 The water quality, sediment, and oceanography conditions present within the Ports
29 O'Call area have remained relatively the same since the certification of the SPW Project
30 EIS/EIR. There have been no new uses or substantial changes in the project vicinity that
31 would affect the water quality in the project area and it is assumed that the setting
32 information provided in the SPW Project EIS/EIR provides appropriate characterization
33 of the water quality, sediment, and oceanography environment. Construction of the
34 Downtown Harbor, located on Harbor Boulevard, between 5th and 6th Streets, north of
35 Ports O'Call, which provides 1.2 acres of open water, was completed in June 2014.
36 Previously a parking lot, the space has been transformed with a new harbor inlet for
37 recreational vessels to dock free of charge for up to 4 hours.

² A TEU is a measure of container cargo capacity based on the volume of a 20-foot-long by 8-foot-wide by 8-foot, 6-inch-tall container. When the measure was first developed, shipping containers were generally 20 feet long or 1 TEU. Currently, most containers are 40 feet long or 2 TEUs.

3.15 Environmental Justice

The demographic and population data presented in the SPW Project EIS/EIR determined that the project area includes concentrations of minority and low-income populations based on information provided in the 2000 census data. While the demographics of the area have changed during the intervening years (for example, the California Department of Finance reported a slight decrease in the population of Los Angeles County from 10,331,939 in 2007 to 10,136,559 in 2015), it is assumed for the purposes of the environmental justice analysis in this Addendum that the demographic make-up of the project area still constitutes a minority population concentration and a low-income population concentration, as identified in the SPW Project EIS/EIR.

3.16 Socioeconomics and Environmental Quality

The SPW Project EIS/EIR provided a detailed characterization of the socioeconomic environment within the Southern California Association of Governments area as well as within Los Angeles County and the project area. For the purposes of comparison between the data presented in the SPW Project EIS/EIR to the current socioeconomic environment, updates to the broader socioeconomic categories of Los Angeles County are provided here. As noted above under Section 3.16, the population for Los Angeles County has decreased slightly since certification of the SPW Project EIS/EIR. However, employment has increased since the 2006 figure of 4,100,200 jobs reported in the SPW Project EIS/EIR to 4,674,800 jobs in 2015 (California Employment Development Department 2016). The 2015 unemployment rate in Los Angeles County was 6.7 percent in 2015, which is up from 4.7 percent in 2006. Median household income increased from \$42,000 in Los Angeles in 2006 to \$55,870 in 2014 (U.S. Census Bureau 2014a). Los Angeles County experienced a slight decrease in owner-occupied housing units since the 2000 census data presented in the SPW Project EIS/EIR, with owner-occupied housing units composing 48 percent of the housing units versus 46.4 percent in 2014 (U.S. Census Bureau 2014b). In addition, median housing prices for Los Angeles decreased, going from \$515,063 in 2006 to \$425,100 in 2014 (U.S. Census Bureau 2014b). Housing vacancy rates increased from 4.4 percent in 2000 to 6.3 percent in 2014 (U.S. Census Bureau 2014b).

The environmental quality conditions present within the project area have remained relatively the same since the certification of the SPW Project EIS/EIR.

Chapter 4

Environmental Impact Analysis

This chapter presents information and analysis of the potential environmental impacts, if any, of the proposed modifications to the previous project design analyzed in the SPW Project EIS/EIR for the Ports O'Call area with implementation of the SPPM Project. The SPPM Project's effects were largely covered and analyzed in the SPW Project EIS/EIR, which identified redevelopment of Ports O'Call as a project element. The analysis contained within this chapter addresses the changes to impacts identified in the SPW Project EIS/EIR that could potentially occur as a result of the SPPM Project.

A summary of the SPW Project EIS/EIR findings is provided, followed by a discussion of the impacts associated with the SPPM Project modifications and significance of the impacts. Mitigation measures from the SPW Project EIS/EIR are incorporated into the SPPM Project where applicable.

4.1 Aesthetics

4.1.1.1 Summary of San Pedro Waterfront EIS/EIR Findings

The SPW Project EIS/EIR did not identify any significant aesthetic impacts related to development of the Ports O'Call and bluff site parking. No impacts were determined to occur related to development of the Ports O'Call and bluff site parking on a scenic vista from a designated scenic resource and damage to scenic resources within a state scenic highway. The less-than-significant aesthetic impacts related to development of the Ports O'Call are discussed below.

Ports O'Call

Views of Ports O'Call are limited to land uses elevated along Beacon Street and motorists and pedestrians along Harbor Boulevard. The project features identified in the SPW Project EIS/EIR that had the potential to affect the visual landscape in the area included the waterfront promenade and Ports O'Call redevelopment (including Fishermen's Park). At the time, these project features were not specified, but were envisioned to incorporate landscaping; hardscape; outdoor furniture, lighting, and signage; a water feature; and an amphitheater with lawn seating for 500 people. Additionally, the San Pedro Waterfront and Promenade Design Guidelines¹ were developed as part of the project to provide the framework for quality and appropriate design to ensure that SPW Project features would not adversely affect visual quality by introducing highly contrasting, inharmonious, or

¹ Updated in February 2014 (Port of Los Angeles 2014b)

1 unsuitably scaled architecture. LA Waterfront Design Guidelines (Port of Los Angeles
2 2014b) related to maintaining views and building heights include the following:

- 3 ▪ Buildings should protect upland views to the water and adhere to the existing
4 scale of development in Wilmington and San Pedro.
- 5 ▪ The maximum building height for development should comply with the City of
6 Los Angeles Zoning Ordinance. Where deemed appropriate by the Port,
7 however, buildings can exceed this height through a variance.
- 8 ▪ Roof elements such as poles and masts and other structures that occupy no more
9 than 10% of the roof area are exempt from building height limits.
- 10 ▪ Buildings should generally decrease in height as they approach the waterfront,
11 with taller buildings away from the water and shorter buildings nearer the
12 promenade.
- 13 ▪ Tower elements or those portions of a building over 60 feet should be designed
14 as slender structures to minimize view obstructions from inland areas and
15 maintain upland views and east-west view corridors from existing streets.

16 LA Waterfront Design Guidelines (Port of Los Angeles 2014b) related to signage include
17 the following:

- 18 ▪ Signs should be scaled based on their environment and intended user. For
19 example, larger signs should be used for drivers moving at faster speeds while
20 smaller signs should be used for pedestrians.
- 21 ▪ Signs should be located where most effective in terms of decision points and
22 information needs. They should be located for prominence and readability.
- 23 ▪ Signs should be illuminated uniformly and use appropriate contrasting
24 backgrounds to ensure visibility and legibility, even during night hours. Glare
25 and reflection should be minimized.

26 These design standards, combined with unified planning that would be provided in a
27 comprehensive master plan, were determined to result in visual improvements to the
28 current facilities at Ports O'Call. Development of Ports O'Call as a unified district would
29 provide visual structure through a master-designed approach to this area, while adding to
30 the quality of vividness by providing a distinctive element in the visual tapestry of the
31 Port.

32 The SPW Project was also found to have little effect on shade sensitive viewers because
33 sensitive viewers would not be present in the specific settings where shadows cast by
34 limited multiple-story development would occur. The potential shadow area could
35 occupy the promenade during morning hours; however, this area is designed for
36 pedestrian circulation and users would not be considered shadow sensitive because of
37 their limited length of stay.

38 The SPW Project also included removal of tall light standards and floodlights, and
39 development of new nighttime lighting and streetscape lighting consistent with
40 commercial development and public spaces, including decorative lighting, thematic light
41 poles, and walkway lighting. Overall, the SPW Project lighting features were found to
42 have negligible impacts within the context of the function lighting of the Port. Proposed
43 lighting along the waterfront promenade and at Ports O'Call were determined to not be

1 significant enough to provide a substantial adverse change in ambient Port lighting.
2 Light-sensitive residents would be located over 40 feet above and approximately 500 feet
3 or more away from Ports O'Call and would not be exposed to spill light. Furthermore,
4 ambient lighting and special event lighting would be provided, but because this area is
5 adjacent to downtown commercial and office buildings, night lighting would not affect
6 light-sensitive areas. Lighting associated with the SPW Project would comply with the
7 San Pedro Waterfront and Promenade Design Guidelines, which include lighting
8 recommendations to minimize light pollution, spill light, and glare while promoting goals
9 to create an attractive and safe daytime and nighttime waterfront that supports local
10 economic growth. Design consistency with these guidelines and regulations would ensure
11 that views of the area would not be adversely affected. New lighting would be both
12 functional and decorative to enhance visual quality. Impacts would be less than
13 significant.

14 **Bluff Site Parking**

15 The bluff site parking area was originally analyzed to comprise an approximately 1,652-
16 space parking structure facility with four 3-level structures. The height of the structures
17 was to be at or near the top of the bluffs so as to not block views and to minimize visual
18 disruption toward the waterfront from Harbor Boulevard. The structures were also
19 planned to have green rooftops designed for pedestrian access and to accommodate solar
20 panels, viewing areas, and walkways to entice pedestrians to venture down staircases to
21 the waterfront and Ports O'Call.

22 Beacon Street is raised approximately 50 feet above the Southern Pacific Railroad tracks,
23 and the bluff blocks views of much of the area between Beacon Street and the waterfront.
24 The rooftops of the current Ports O'Call buildings frame the lower edges of the view
25 from this location, and the proposed parking structures were determined to not be within
26 sightlines from Beacon Street nor from the ground floor of the buildings that front the
27 street. The structures were proposed to be integrated into the existing topography and
28 hidden from view from these sensitive residential areas. However, the structures were
29 determined to be within views from San Pedro Plaza Park and the upper floors of the
30 buildings across from the park, including the U.S. Post Office and adjacent rehabilitation
31 center.

32 Representative foreground views shown in the SPW Project EIS/EIR from San Pedro
33 Plaza Park (Draft EIS/EIS Figure 3.1-6) show a continuous stretch of transportation
34 infrastructure including streets, rail lines, and parking lots. Additionally, adjacent to the
35 proposed bluff site parking area across Sampson Way is a large surface parking lot
36 servicing the existing Ports O'Call area. Ultimately, these surface parking areas were
37 planned to be replaced by the bluff site parking, which would open up areas for public
38 space by consolidating parking in a vertical structure. Some vantage points from Harbor
39 Boulevard, San Pedro Plaza Park, and higher elevations to the west were determined to
40 also have views of the top level of the proposed bluff site parking, but would not
41 introduce inharmonious elements that would change the visual character of the area from
42 these viewpoints. The bluff site parking was planned to be sited and scaled within the
43 continuous approximately 30-foot grade separation that extends from 7th to 14th Streets.
44 Integration of the design into the hillside was intended to minimize visual impact due to
45 height, bulk, and contrast of the building. Furthermore, the parking structures would be
46 designed according to design standards framed in the San Pedro Waterfront and

1 Promenade Design Guidelines (Appendix C.2 of the SPW Project EIS/EIR). Therefore,
2 impacts from the bluff site parking were determined be less than significant.

3 As mentioned above, the SPW Project was also found to have little effect on shade-
4 sensitive viewers because sensitive viewers would not be present in the specific settings
5 where shadows cast by limited multiple-story development would occur. The four 3-level
6 parking structures proposed in the to-be-vacated SP Railyard abutting Harbor Boulevard
7 would be sited and scaled to take advantage of the continuous, approximately 30-foot
8 grade separation that extends from 7th to 14th Streets to hide the presence of the garages
9 from views (such as from vantage points along Harbor Boulevard, Beacon Street, other
10 from higher elevations to the west). Because the height of the structures would be at or
11 near the top of the bluffs with vehicular access to the top parking levels from Harbor
12 Boulevard, there would be no shadow effect to the west. East-directed shadows would
13 primarily extend over Sampson Way and would not occupy buildings or open space, or
14 use areas where sensitive groups might be present.

15 The SPW Project EIS/EIR also found that proposed lighting for the parking structures
16 would be shielded and directed downward to prevent spillover light and glare and would
17 not adversely affect adjacent areas. There would be no substantial change over existing
18 ambient illumination levels. Night lighting of Port operations would have remained a
19 brightly lit backdrop for the SPW Project.

20 **4.1.1.2 Impacts of the SPPM Project**

21 The SPPM Project would generally be consistent with the redevelopment scenario that
22 was analyzed in the SPW Project EIS/EIR. The SPPM Project would be contained within
23 mostly the same development boundaries for Ports O'Call that were analyzed in the SPW
24 Project EIS/EIR with the exception of a small portion of the Town Square area, which is
25 now within the SPPM Project boundaries. Also, the SPPM Project would introduce a
26 similar mix of land uses and would include most of the other project components, such as
27 an extension of the promenade and provision of other recreational elements, a trolley,
28 parking areas, and waterside improvements. In addition, the SPPM Project would include
29 marquee signage, entertainment uses such as attractions and arcade-style games, a Ferris
30 wheel, merry-go-round, playground facilities, and other general entertainment uses in the
31 Discovery Sea Amusement Area.

32 Under the SPPM Project, overall development intensity would similar to the SPW
33 Project, and the development of a 75,000-square-foot conference center is currently not
34 anticipated to occur. The Ferris wheel and marquee signage would be new elements in
35 the visual landscape. The Ferris wheel would not exceed 100 feet in height and marquee
36 signage would be located on top of various buildings. Both the Ferris wheel and marquee
37 signage would be designed in coordination with LAHD and would minimize view
38 obstructions from inland areas per the San Pedro Waterfront and Promenade Design
39 Guidelines (Port of Los Angeles 2014b), which specify that tower elements or those
40 portions of a building over 60 feet should be designed as slender structures to minimize
41 view obstructions from inland areas and maintain upland views and east-west view
42 corridors from existing streets. These new visual elements do not represent a substantial
43 change in the visual landscape from what was evaluated in the SPW Project EIS/EIR.
44 They would be consistent with the uses and theme for both the SWP Project and SPPM
45 Project and would not result in highly contrasting, inharmonious, or unsuitably scaled
46 architecture.

1 Furthermore, nighttime lighting would include decorative lighting, thematic light poles,
2 walkway lighting, and lighting for the Ferris wheel and marquee signage. Impacts related
3 to nighttime lighting would be similar to those evaluated in the SPW Project EIS/EIR as
4 night lighting of Port operations would still remain a brightly lit backdrop for the SPPM
5 Project. As described above for the SPW Project, light-sensitive residents would be
6 located over 40 feet above and approximately 500 feet or more away from Ports O'Call
7 and would not be exposed to spill light. Ambient lighting and special event lighting
8 would be provided, but because this area is adjacent to downtown commercial and office
9 buildings, night lighting would not affect light-sensitive areas. The lighting proposed for
10 the Ferris wheel and marquee signage does not represent a substantial change from what
11 was evaluated in the SPW Project EIS/EIR, as it too would blend in with the night
12 lighting of Port operations and would not adversely affect light-sensitive areas.

13 As mentioned above, the SPW Project EIS/EIR did not identify any significant aesthetic
14 impacts related to development of the Ports O'Call and bluff site parking. The SPPM
15 Project would not result in new significant impacts, substantially increase the severity of
16 a previously analyzed impact, or require new mitigation measures that have not already
17 been evaluated in the SPW Project EIS/EIR. Therefore, impacts resulting from the SPPM
18 Project would be less than significant, and there is no substantial change from the
19 findings in the SPW Project EIS/EIR.

20 **4.1.1.3 Mitigation Measures Applicable to the SPPM Project**

21 No mitigation measures are required.

22 **4.2 Air Quality and Meteorology**

23 **4.2.1.1 Summary of San Pedro Waterfront EIS/EIR Findings**

24 **Air Quality**

25 The SPW Project EIS/EIR identified significant air quality impacts related to both the
26 construction and operation phases. For construction activities, the air quality analysis for
27 the SPW Project assumed that construction activities would occur during a 54-month
28 period beginning in 2009 and concluding in 2014. Emission forecasts conducted for the
29 SPW Project EIS/EIR assumed that a relatively large amount of construction would occur
30 in a relatively intensive manner, and due to this conservative approach, actual emissions
31 could be lower than forecasted. Significant air quality impacts identified for construction
32 of the SPW Project include exceedance of emission thresholds for volatile organic
33 compounds (VOC), carbon monoxide (CO), nitrogen oxides (NO_x), particulate matter 10
34 microns or less in diameter (PM₁₀), and particulate matter 2.5 microns or less in diameter
35 (PM_{2.5}). With implementation of mitigation measures, these impacts would remain
36 significant and unavoidable.

37 Operation of the SPW Project would exceed NEPA and CEQA thresholds for all
38 pollutants (VOC, NO_x, sulfur oxides [SO_x], PM₁₀, and PM_{2.5}), except for CO, and even
39 with the implementation of mitigation measures, these impacts would remain significant
40 and unavoidable. In addition, operational emissions would be significant for nitrous oxide
41 (NO₂) and 24-hour PM₁₀ and PM_{2.5} as well as annual PM₁₀; however, these operational
42 impacts would result largely from operation of the cruise ship terminals. Operational

1 impacts associated with increased motor vehicle trips would be less than significant. In
2 addition, the SPW Project would result in a significant impact related to cancer risk and
3 acute hazard index at occupational, residential, and recreational receptors.

4 Greenhouse Gas Emissions

5 Total carbon dioxide equivalent (CO₂e) emissions during construction of the SPW
6 Project would be greater than the baseline (which is zero for construction), and for each
7 future project year, annual operational CO₂e emissions would increase relative to the
8 baseline. Thus, the SPW Project would result in significant greenhouse gas (GHG)
9 emission impacts. Measures that reduce electricity consumption or fossil fuel usage from
10 project emission sources would also reduce GHG emissions; however, impacts would
11 remain significant and unavoidable even with implementation of mitigation measures.

12 4.2.1.2 Impacts of SPPM Project

13 Air Quality

14 As noted in Section 3.2, *Air Quality and Meteorology*, concentrations of criteria
15 pollutants have decreased in the project area over the last few years; therefore, the air
16 quality analysis within the SPW Project EIS/EIR likely represents a more conservative
17 scenario than actual emissions that have occurred, or are expected to occur, from
18 implementation of the SPW Project. The SPPM Project would be similar to the
19 previously analyzed elements for the Ports O'Call site both for construction and
20 operations. Additionally, the following assumptions can be made related to the air quality
21 impacts associated with the SPPM Project.

- 22 • The SPPM Project would be constructed and operated later than the previously
23 analyzed SPW Project. Because source emissions tend to decrease in future years
24 due to more stringent regulatory requirements and equipment turnover, the
25 original analysis would likely remain more conservative.
- 26 • The elements of the SPPM Project are geographically similar to those of the
27 Ports O'Call redevelopment analyzed in the SPW Project EIS/EIR and new
28 receptors would not be affected; therefore, localized impacts would not change
29 from the previous analysis.
- 30 • Previously analyzed Ports O'Call elements contributed little to the cancer risk in
31 the SPW Project EIR/EIS. The previously analyzed, mitigated residential cancer
32 risk was less than 1 in a million, for the whole SPW Project, of which the SPPM
33 Project is just one component.
- 34 • Emission estimation models do not project emissions past 2040; emission factors
35 in the model projections past 2040 are assumed to flat line or remain constant.
36 Assuming that emission factors past 2040 would not change is conservative,
37 because it is expected that technology will get cleaner and emission factors will
38 continue to decline. Therefore, a longer lease would not change air quality
39 impacts.

40 It is anticipated that project construction emissions for the SPPM Project would be
41 similar to those analyzed in the SPW Project EIS/EIR for the Ports O'Call site because
42 the area of impact and the square footage of development would be similar to that

1 anticipated in the SPW Project EIS/EIR. Therefore, the SPPM Project would require
2 implementation of Mitigation Measures MM AQ-1 and MM AQ-3 through MM AQ-8.
3 Mitigation Measure MM AQ-2 applies to dredging activities, and the SPPM Project
4 would not require dredging; therefore, MM AQ-2 does not apply to the SPPM Project. As
5 discussed above, operational air quality impacts associated with the SPW Project would
6 result largely from the cruise ship terminal. As discussed in Section 4.11, *Transportation*
7 *and Circulation (Ground)*, the SPPM Project would result in fewer daily vehicle trips to
8 the Ports O'Call site than identified in the SPW Project EIS/EIR (the SPW Project
9 EIS/EIR assumed up to 8,632 daily trips and the SPPM Project is estimated to generate
10 up to 6,285 daily trips). Therefore, motor vehicles would not result in significant impacts
11 on air quality. Overall, air quality impacts associated with the SPPM Project would not
12 result in new significant impacts, substantially increase the severity of a previously
13 analyzed impact, or require new mitigation measures that have not already been
14 evaluated in the SPW Project EIS/EIR. Therefore, there is no substantial change from the
15 findings in the SPW Project EIS/EIR.

16 Greenhouse Gas Emissions

17 Similar to the air quality analysis above, the GHG emissions analysis assumes that
18 because the SPPM Project would be constructed and operated later than the previously
19 analyzed SPW Project, source emissions would decrease in future years due to more
20 stringent regulatory requirements and equipment turnover. Thus, the original analysis
21 would likely be more conservative. In addition, emission estimation models do not
22 project emissions past 2040; emission projections past 2040 are assumed to flat line.
23 Therefore, a longer lease would not change GHG emissions impacts. The SPPM Project
24 would be similar to the Ports O'Call redevelopment component that was analyzed in the
25 SPW Project EIS/EIR in terms of general land uses and square feet of development.
26 Thus, the SPPM Project would result in similar GHG emissions impacts related to
27 construction and operational activities as identified in the SPW Project EIS/EIR.
28 Therefore, implementation of Mitigation Measures MM AQ-25 and MM AQ-27 are
29 required. With implementation of mitigation measures, GHG impacts of the SPPM
30 Project would not result in new significant impacts, substantially increase the severity of
31 a previously analyzed impact, or require new mitigation measures that have not already
32 been evaluated in the SPW Project EIS/EIR. Therefore, there is no substantial change
33 from the findings in the SPW Project EIS/EIR.

34 4.2.1.3 Mitigation Measures Applicable to the SPPM Project

35 **MM AQ-1. Harbor Craft Used During Construction.** All harbor craft used during the
36 construction phase of the proposed project shall, at a minimum, be repowered to meet the
37 cleanest existing marine engine emission standards or U.S. Environmental Protection
38 Agency (EPA) Tier 2. Additionally, where available, harbor craft shall meet the proposed
39 EPA Tier 3 (which are proposed to be phased in beginning 2009) or cleaner marine
40 engine emission standards.

41 The above harbor craft measure shall be met unless one of the following circumstances
42 exists and the contractor is able to provide proof that any of these circumstances exists.

- 43 ■ A piece of specialized equipment is unavailable in a controlled form within the
44 state of California, including through a leasing agreement;

- 1 ■ A contractor has applied for necessary incentive funds to put controls on a piece
2 of uncontrolled equipment planned for use on the proposed project, but the
3 application process is not yet approved, or the application has been approved, but
4 funds are not yet available; or
- 5 ■ A contractor has ordered a control device for a piece of equipment planned for
6 use on the proposed project, or the contractor has ordered a new piece of
7 controlled equipment to replace the uncontrolled equipment, but that order has
8 not been completed by the manufacturer or dealer. In addition, for this exemption
9 to apply, the contractor must attempt to lease controlled equipment to avoid using
10 uncontrolled equipment, but no dealer within 200 miles of the proposed project
11 has the controlled equipment available for lease.

12 **MM AQ-3. Fleet Modernization for Onroad Trucks.**

- 13 1. Trucks hauling materials such as debris or fill shall be fully covered while operating
14 off Port property.
- 15 2. Idling shall be restricted to a maximum of 5 minutes when not in use.
- 16 3. Tier Specifications:
- 17 ■ All onroad heavy-duty diesel trucks with a gross vehicle weight rating of 19,500
18 pounds or greater used on site or to transport materials to and from the site shall
19 comply with 2010 emission standards, where available.

20 A copy of each unit's certified EPA rating, best available control technology
21 (BACT) documentation, and California Air Resources Board (CARB) or South
22 Coast Air Quality Management District (SCAQMD) operating permit shall be
23 provided at the time of mobilization of each applicable unit of equipment.

24 The above standards/specifications shall be met unless one of the following
25 circumstances exists and the contractor is able to provide proof that any of these
26 circumstances exists.

- 27 ■ A piece of specialized equipment is unavailable in a controlled form within the
28 state of California, including through a leasing agreement;
- 29 ■ A contractor has applied for necessary incentive funds to put controls on a piece
30 of uncontrolled equipment planned for use on the proposed project, but the
31 application process is not yet approved, or the application has been approved, but
32 funds are not yet available; or
- 33 ■ A contractor has ordered a control device for a piece of equipment planned for
34 use on the proposed project, or the contractor has ordered a new piece of
35 controlled equipment to replace the uncontrolled equipment, but that order has
36 not been completed by the manufacturer or dealer. In addition, for this exemption
37 to apply, the contractor must attempt to lease controlled equipment to avoid using
38 uncontrolled equipment, but no dealer within 200 miles of the proposed project
39 has the controlled equipment available for lease.

MM AQ-4. Fleet Modernization for Construction Equipment.

1. Construction equipment shall incorporate, where feasible, emissions savings technology such as hybrid drives and specific fuel economy standards.
 2. Idling shall be restricted to a maximum of 5 minutes when not in use.
 3. Tier Specifications:
 - All offroad diesel-powered construction equipment greater than 50 horsepower shall meet the Tier 4 emission standards, where available. In addition, all construction equipment shall be outfitted with BACT devices certified by CARB. Any emissions control device used by the contractor shall achieve emissions reductions that are no less than what could be achieved by a Level 3 diesel emissions control strategy for a similarly sized engine as defined by CARB regulations.
- A copy of each unit's certified tier specification, BACT documentation, and CARB or SCAQMD operating permit shall be provided at the time of mobilization of each applicable unit of equipment.

The above standards/specifications shall be met unless one of the following circumstances exists and the contractor is able to provide proof that any of these circumstances exists:

- A piece of specialized equipment is unavailable in a controlled form within the state of California, including through a leasing agreement;
- A contractor has applied for necessary incentive funds to put controls on a piece of uncontrolled equipment planned for use on the proposed project, but the application process is not yet approved, or the application has been approved, but funds are not yet available; or
- A contractor has ordered a control device for a piece of equipment planned for use on the proposed project, or the contractor has ordered a new piece of controlled equipment to replace the uncontrolled equipment, but that order has not been completed by the manufacturer or dealer. In addition, for this exemption to apply, the contractor must attempt to lease controlled equipment to avoid using uncontrolled equipment, but no dealer within 200 miles of the proposed project has the controlled equipment available for lease.

MM AQ-5. Additional Fugitive Dust Controls. The calculation of fugitive dust (PM10) from unmitigated proposed project earth-moving activities assumes a 75% reduction from uncontrolled levels to simulate rigorous watering of the site and use of other measures (listed below) to ensure proposed project compliance with SCAQMD Rule 403.

The construction contractor shall apply for a SCAQMD Rule 403 Dust Control Permit.

The construction contractor shall further reduce fugitive dust emissions to 90% from uncontrolled levels. The construction contractor shall designate personnel to monitor the dust control program and to order increased watering or other dust control measures, as

1 necessary, to ensure a 90% control level. Their duties shall include holiday and weekend
2 periods when work may not be in progress.

3 The following measures, at minimum, must be part of the contractor Rule 403 dust
4 control plan.

- 5 ▪ Active grading sites shall be watered one additional time per day beyond that
6 required by Rule 403.
- 7 ▪ Contractors shall apply approved nontoxic chemical soil stabilizers to all inactive
8 construction areas or replace groundcover in disturbed areas.
- 9 ▪ Construction contractors shall provide temporary wind fencing around sites being
10 graded or cleared.
- 11 ▪ Trucks hauling dirt, sand, or gravel shall be covered or shall maintain at least
12 2 feet of freeboard in accordance with Section 23114 of the California Vehicle
13 Code.
- 14 ▪ Construction contractors shall install wheel washers where vehicles enter and exit
15 unpaved roads onto paved roads or wash off tires of vehicles and any equipment
16 leaving the construction site.
- 17 ▪ The grading contractor shall suspend all soil disturbance activities when winds
18 exceed 25 mph or when visible dust plumes emanate from a site; disturbed areas
19 shall be stabilized if construction is delayed.
- 20 ▪ Trucks hauling materials such as debris or fill shall be fully covered while
21 operating off LAHD property.
- 22 ▪ A construction relations officer shall be appointed to act as a community liaison
23 concerning on-site construction activity including resolution of issues related to
24 PM10 generation.
- 25 ▪ All streets shall be swept at least once a day using SCAQMD Rule 1186, 1186.1
26 certified street sweepers or roadway washing trucks if visible soil materials are
27 carried to adjacent streets.
- 28 ▪ Water or non-toxic soil stabilizer shall be applied three times daily to all unpaved
29 parking or staging areas or unpaved road surfaces.
- 30 ▪ Roads and shoulders shall be paved.
- 31 ▪ Water shall be applied three times daily or as needed to areas where soil is
32 disturbed.

33 **MM AQ-6. Best Management Practices.** The following types of measures are required
34 on construction equipment (including onroad trucks).

- 35 1. Use diesel oxidation catalysts and catalyzed diesel particulate traps.
- 36 2. Maintain equipment according to manufacturers' specifications.
- 37 3. Restrict idling of construction equipment to a maximum of 5 minutes when not in
38 use.
- 39 4. Install high-pressure fuel injectors on construction equipment vehicles.

1 LAHD shall implement a process by which to select additional best management
2 practices (BMPs) to further reduce air emissions during construction. LAHD shall
3 determine the BMPs once the contractor identifies and secures a final equipment list.

4 Because the effectiveness of the above measure has not been established, it is not
5 quantified in this study.

6 **MM AQ-7. General Mitigation Measure.** For any of the above mitigation measures
7 (MM AQ-1 through AQ-6), if a CARB-certified technology becomes available and is
8 shown to be as good as or better in terms of emissions performance than the existing
9 measure, the technology could replace the existing measure pending approval by LAHD.

10 Because the effectiveness of the above measure has not been established, it is not
11 quantified in this study.

12 **MM AQ-8. Special Precautions near Sensitive Sites.** When construction activities are
13 planned within 1,000 feet of sensitive receptors (defined as schools, playgrounds, day
14 care centers, and hospitals), the construction contractor shall notify each of these sites in
15 writing at least 30 days before construction activities begin.

16 4.3 Biological Resources

17 4.3.1.1 Summary of San Pedro Waterfront EIS/EIR Findings

18 The SPW Project EIS/EIR identified impacts on biological resources associated with
19 redevelopment of Ports O'Call. Most construction impacts were considered temporary
20 and less than significant because the majority of potentially affected terrestrial and
21 marine organisms are motile and would be able to avoid construction disturbances. Many
22 trees within the project provide valuable foraging, roosting, and nesting habitat for both
23 native and nonnative bird species. Tree removal activities could have a significant impact
24 if birds are roosting or nesting in the area. Performing nesting bird surveys prior to
25 ground-disturbing activities will minimize this impact to a less-than-significant level.
26 Some benthic and sessile marine invertebrates were identified to be potentially displaced
27 from pile replacement; however, this too was considered a temporary and less-than-
28 significant impact because there would be an overall net gain in the number of piles.
29 Noise and vibration generated from pile driving activities can also have a negative impact
30 on marine mammals. Although marine mammals are motile and able to avoid areas that
31 cause them distress, additional measures to minimize impacts on marine mammals
32 include sound abatement practices for pile driving and creating a safety zone with
33 additional operational procedures in place if marine mammals enter this area. To address
34 and reduce these impacts to less-than-significant levels, the SPW Project EIS/EIR
35 included the following construction-related mitigation measures.

- 36 • MM BIO -2: Conduct Nesting Bird Surveys
- 37 • MM BIO-3: Avoid Marine Mammals

38 The threat of introducing invasive species through vessel hull fouling, equipment, or
39 ballast water discharges from any vessel was the only potentially significant and
40 unavoidable operational impact associated with the SPW Project. At this time, there is no

1 proven technology to completely eliminate this threat, and there were no mitigation
 2 measures proposed for the introduction of invasive species. All other operational impacts
 3 associated with the SPW Project were considered to be temporary and less than
 4 significant.

5 The originally proposed promenade design for the Ports O'Call site analyzed in the SPW
 6 Project EIS/EIR would have created a significant unavoidable impact on the 0.175-acre
 7 mudflat at Berth 78 by shading the mudflat, reducing its ecological functionality and
 8 value. As stated in the SPW Project EIR/EIS, under Section 404(b)(1) Guidelines,
 9 mudflats are considered special aquatic sites. To compensate for the loss of functional
 10 mudflat habitat, a new mudflat would have been created at a mitigation ratio of 1:1 as
 11 part of the Salinas de San Pedro Salt Marsh habitat enhancement and expansion (SPW
 12 Project EIS/EIR Mitigation Measure MM BIO-4). In addition to creating new salt marsh
 13 habitat, a Habitat and Mitigation Monitoring Plan (SPW Project EIS/EIR Mitigation
 14 Measure MM BIO-5) would need to be developed and implemented to ensure that any
 15 new habitat created would become self-sustaining within 5 years. Because these impacts
 16 are associated with an overall enhancement and net gain in saltmarsh habitat, the project
 17 impacts would be self-mitigating, and no further mitigation measures would be needed to
 18 address these impacts.

19 The SPW Project EIS/EIR found operation of the SPW Project would not cause a
 20 substantial disruption of biological communities from shading as a result of changes to
 21 existing structures and construction of new over-water structures including wharves,
 22 piers, bulkheads, floating docks, and the promenade. Shade reduces energy available for
 23 photosynthesis and, therefore, reduces growth of algae or submerged vegetation;
 24 however, overhead structures also attract some fish species that shade and cover in the
 25 vicinity of the structure. The effect of shade on biological communities depends on local
 26 site conditions that also affect habitat variables. The area of over-water and in-water work
 27 proposed under the SPW Project at the Ports O'Call is summarized in Table 4-1.

28 **Table 4-1. Summary of Over-Water and In-Water Project Elements under the SPW Project**
 29 **at Ports O'Call**

Activity	Location	Quantity
Bulkhead Removal	Promenade, Berth 78	150 Linear Feet
Over-Water Structure Removal	Ports O'Call Promenade	89,900 Square feet
Piling Placement	Ports O'Call Promenade	451 Piles
Bulkhead Installation	Ports O'Call Promenade	150 Linear Feet
Over-Water Structure Installation	Ports O'Call Promenade (new wharf structures/floating docks/mudflat deck)	83,700 Square feet

30 These over-water and in-water structures could affect local biological communities by
 31 shading aquatic habitat and by providing cover and vertical (piling and rock) structure.
 32 However, the SPW Project EIS/EIR found that the SPW Project would create the
 33 majority of the open-water marine habitat that would contain these over-water and in-
 34 water structures. Furthermore, although there would be a short-term disruption to
 35 biological communities as a result of removal of existing over-water and in-water
 36 structures, and recolonization of these areas would take 1 to 3 years, there would be no
 37 net loss of open-water marine habitat or long-term biological community disruption
 38 overall. Therefore, with the exception of the above-mentioned shade impacts created at

1 the mudflat, shade created by the SPW Project's proposed over-water and in-water
2 features was found to be less than significant.

3 **4.3.1.2 Impacts of SPPM Project**

4 The SPPM Project would generally be consistent with the redevelopment scenario that
5 was analyzed in the SPW Project EIS/EIR. The SPPM Project would be contained mostly
6 within the same development boundaries that were analyzed in the SPW Project EIS/EIR
7 with the exception of a small portion of the Town Square area, which is now within the
8 SPPM Project boundaries.

9 Consistent with the SPW Project EIS/EIR, the SPPM Project would replace and/or
10 restore the existing 89,900 square feet of over-the-water wharf structures and floating
11 docks within the SPPM Project site, including the existing marina and all its associated
12 in-water structures, with no more than 73,200 square feet of new and/or restored over-
13 the-water wharf structures and floating docks. As with the SPW Project, the SPPM
14 Project would also place up to 451 new piles. The promenade would be redesigned and
15 constructed mostly landside, with limited over-water components consisting of over-
16 water wharf decks and new over-water commercial structures located outside the limits of
17 the mudflat.

18 To avoid the impact on the mudflat, the promenade design would be modified at Berth 78
19 so it no longer crosses or produces shade over the mudflat. Instead, this portion of the
20 promenade would be raised above the surface of the water and elevated on piers, and
21 would be constructed around the mudflat. This portion of the promenade would also be
22 designed in consultation with the resource agencies to ensure that the design would avoid
23 any impacts on the mudflat area. This, in turn, would eliminate the need for mitigation at
24 the Salinas de San Pedro Salt Marsh. These proposed modifications to the SPW Project
25 would result in an overall reduction of impacts on biological resources, eliminating the
26 need for Mitigation Measures MM BIO-4, Enhance and expand Salinas de San Pedro Salt
27 Marsh, and MM BIO-5, Prepare a habitat mitigation and monitoring plan.

28 Additionally, and included as part of the 73,200 square feet of new and/or restored over-
29 the-water wharf structures and floating docks mentioned above, the SPPM Project would
30 include waterside attractions consisting of floating restaurants that may be semi-
31 permanently moored at the dock, while others would offer harbor and dinner cruises.
32 There would be no additional shading impacts as a result of these semi-permanently
33 moored attractions because they would be included within the total proposed 73,200
34 square feet of new and/or restored over-water structures, which is less than what was
35 evaluated in the SPW Project EIS/EIR. Therefore shading impacts associated with this
36 new project feature would remain less than significant.

37 Construction impacts on terrestrial and marine organisms are expected to be generally the
38 same as those evaluated in the SPW Project EIS/EIR and Mitigation Measures MM BIO-
39 2 and BIO-3 would be required for the SPPM Project. Furthermore, no barriers to wildlife
40 passage would result from operation of the SPPM Project and impacts would remain less
41 than significant.

42 Overall, the SPPM Project would not result in any new significant impacts, substantially
43 increase the severity of a previously analyzed impact, or require new mitigation measures
44 that have not already been addressed in the SPW Project EIS/EIR. Therefore, biological

1 resource impacts would be similar to or less than those evaluated in the SPW Project
2 EIS/EIR, and there is no substantial change from the findings in the SPW Project
3 EIS/EIR.

4 **4.3.1.3 Mitigation Measures Applicable to the SPPM Project**

5 Implementation of Mitigation Measures MM BIO-2 and MM BIO-3 would apply to the
6 SPPM Project to minimize impacts related to biological resources.

7 **MM BIO-2. Conduct nesting bird surveys.** This measure applies if construction is to
8 occur between February 15 and September 1. Prior to ground-disturbing activities, a
9 qualified biologist will conduct surveys for the presence of black-crowned night herons,
10 blue herons, and other nesting birds within Berth 78-Ports O'Call or other appropriate
11 and known locations within the study area that contain potential nesting bird habitat.
12 Surveys will be conducted 24 hours prior to the clearing, removal, or grubbing of any
13 vegetation or ground disturbance. If active nests of species protected under the Migratory
14 Bird Treaty Act and/or similar provisions of the California Fish and Game Code (i.e.,
15 native birds including but not limited to the black-crowned night heron) are located, then
16 a barrier installed at a 50- to 100-foot radius from the nest(s) will be established and the
17 tree/location containing the nest will be marked and will remain in place and undisturbed
18 until a qualified biologist performs a survey to determine that the young have fledged or
19 the nest is no longer active.

20 **MM BIO-3. Avoid marine mammals.** The contractor will be required to use sound
21 abatement techniques to reduce both noise and vibrations from pile driving activities.
22 Sound abatement techniques will include, but are not limited to, vibration or hydraulic
23 insertion techniques, drilled or augured holes for cast-in-place piles, bubble curtain
24 technology, and sound aprons where feasible. At the initiation of each pile driving event,
25 and after breaks of more than 15 minutes, the pile driving will also employ a "soft-start"
26 in which the hammer is operated at less than full capacity (i.e., approximately 40–60%
27 energy levels) with no less than a 1-minute interval between each strike for a 5-minute
28 period.

29 Although it is expected that marine mammals will voluntarily move away from the area
30 at the commencement of the vibratory or "soft start" of pile driving activities, as a
31 precautionary measure, pile driving activities occurring within the Outer Harbor will
32 include establishment of a safety zone, and the area surrounding the operations will be
33 monitored by a qualified marine biologist for pinnipeds. As the disturbance threshold
34 level sound is expected to extend at least 1,000 feet from the steel pile driving operations,
35 a safety zone will be established around the steel pile driving site and monitored for
36 pinnipeds within a 1,200-foot-radius safety zone around the pile. As the steel pile driving
37 site will move with each new pile, the 1,200-foot safety zone will move accordingly.
38 Observers on shore or by boat will survey the safety zone to ensure that no marine
39 mammals are seen within the zone before pile driving of a steel pile segment begins. If
40 marine mammals are found within the safety zone, pile driving of the segment will be
41 delayed until they move out of the area. If a marine mammal is seen above water and then
42 dives below, the contractor will wait at least 15 minutes, and if no marine mammals are
43 seen, it may be assumed that the animal has moved beyond the safety zone. This 15-
44 minute criterion is based on a study indicating that pinnipeds dive for a mean time of
45 0.50 minute to 3.33 minutes; the 15-minute delay will allow a more than sufficient period
46 of observation to be reasonably sure the animal has left the project vicinity.

1 If pinnipeds enter the safety zone after pile driving of a segment has begun, pile driving
2 will continue. The biologist will monitor and record the species and number of
3 individuals observed, and make note of their behavior patterns. If the animal appears
4 distressed, and if it is operationally safe to do so, pile driving will cease until the animal
5 leaves the area. Pile driving cannot be terminated safely and without severe operational
6 difficulties until reaching a designated depth. Therefore, if it is deemed operationally
7 unsafe by the project engineer to discontinue pile driving activities, and a pinniped is
8 observed in the safety zone, pile driving activities will continue until the critical depth is
9 reached (at which time pile driving will cease) or until the pinniped leaves the safety
10 zone. Prior to the initiation of each new pile driving episode, the area will again be
11 thoroughly surveyed by the biologist.

12 4.4 Cultural Resources

13 4.4.1.1 Summary of San Pedro Waterfront EIS/EIR Findings

14 The SPW Project EIS/EIR did not identify any significant and unavoidable impacts
15 related to cultural resources. Impacts on historical resources were determined to be less
16 than significant, and impacts on archaeological and paleontological resources would be
17 less than significant with mitigation.

18 As mentioned in Chapter 3, *Environmental Setting*, no specifically listed archaeological
19 or paleontological resources were identified in the Ports O'Call area, but the Ports O'Call
20 area overlies land that includes both artificial fill and original bedrock areas that could
21 contain unknown fossilized remains and historic archaeological features. The records
22 search performed for the SPW Project EIS/EIR identified two prehistoric archaeological
23 sites, CA-LAN 145 and CA-LAN 146, within 0.3 mile of the proposed project area. The
24 results of the study indicated a low potential to encounter subsurface evidence of either
25 archaeological site. Development in the Ports O'Call area would require implementation
26 of Mitigation Measures MM CR-3 and MM CR-4 during construction to minimize the
27 potential impacts on these resources. In addition, the S.P. Slip No. 1, which serves as the
28 southern border to Ports O'Call, has been identified by LAHD as a significant historical
29 resource, and appears eligible for the National Register of Historic Places under Criterion
30 A and California Register of Historical Resources under Criterion 1, events, as the first
31 large mooring facility for Pacific Coast lumber schooners in the early history of the Port
32 of Los Angeles. The S.P. Slip now serves as the last remaining harbor anchorage for
33 small-scale fishing boats. The SPW Project EIS/EIR determined that the project would
34 have an indirect impact on S.P. Slip No. 1 due to the proposed land-side promenades that
35 were planned to be constructed adjacent to the resource, but the effect would be less than
36 significant because the fishing operations that form the basis for significance of the
37 historic resource would not be affected.

38 4.4.1.2 Impacts of SPPM Project

39 The SPPM Project would generally be consistent with the redevelopment scenario for the
40 Ports O'Call site analyzed in the SPW Project EIS/EIR. The SPPM Project would be
41 contained within mostly the same development boundaries for Ports O'Call that were
42 analyzed in the SPW Project EIS/EIR with the exception of a small portion of the Town
43 Square area, which is now within the SPPM Project boundaries. Also, implementation of
44 the SPPM Project would not include any development around the S.P. Slip except Berth

1 73-Z. The proposed modifications to the SPW Project and the extension of the lease
2 through 2066 do not change or alter any of the findings of the SPW Project EIS/EIR's
3 cultural resources impact assessment. The SPPM Project would not result in new
4 significant impacts, substantially increase the severity of a previously analyzed impact, or
5 require new mitigation measures that have not already been addressed in the SPW Project
6 EIS/EIR. Therefore, cultural resource impacts resulting from the SPPM Project would be
7 similar to those evaluated in the SPW Project EIS/EIR, and there is no substantial change
8 from the findings in the SPW Project EIS/EIR.

9 It should be noted that since adoption of the SPW Project EIS/EIR, LAHD has developed
10 a program to mitigate impacts on nonrenewable paleontologic resources called the
11 Paleontological Monitoring and Mitigation Plan San Pedro Waterfront Project (Paleo
12 Plan, ICF 2015) in accordance with Mitigation Measure MM CR-4 as required by the
13 SPW Project EIS/EIR. The Applicant would be required to comply with this program
14 during excavation and construction activities for the SPPM Project. Per the Paleo Plan, a
15 paleontological monitor must be present during construction of the parking structure,
16 which is part of Phase 2 of the development. A monitor is not required for construction of
17 the other elements of the SPPM Project.

18 4.4.1.3 Mitigation Measures Applicable to the SPPM Project

19 Implementation of Mitigation Measure MM CR-3 as well as adherence to the Paleo Plan
20 developed by LAHD under MM CR-4 would minimize impacts on archaeological and
21 paleontological resources.

22 **MM CR-3: Stop work if unanticipated cultural resources are identified during**
23 **ground-disturbing activities.** In the event that any artifact or an unusual amount of
24 bone, shell, or nonnative stone is encountered during construction, work will be
25 immediately stopped and relocated from that area. The contractor will stop construction
26 within 100 feet of the exposure of these finds until a qualified archaeologist, retained by
27 LAHD in advance of construction, can be contacted to evaluate the find (see 36 CFR
28 800.11.1 and pertinent CEQA regulations). Examples of such cultural materials might
29 include concentrations of ground stone tools such as mortars, bowls, pestles, and manos;
30 chipped stone tools such as projectile points or choppers; flakes of stone not consistent
31 with the immediate geology such as obsidian or fused shale; trash pits containing bottles
32 and/or ceramics; or structural remains. If the resources are found to be significant, they
33 will be avoided or will be mitigated consistent with State Historic Preservation Office
34 guidelines as appropriate. All construction equipment operators will attend a pre-
35 construction meeting presented by a professional archaeologist retained by LAHD to
36 review types of cultural resources and artifacts that would be considered potentially
37 significant to ensure operator recognition of these materials during construction.

38 If human remains are encountered, there will be no further excavation or disturbance of
39 the site or any nearby area reasonably suspected to overlie adjacent human remains. The
40 Los Angeles County Coroner will be contacted to determine the age and cause of death.
41 If the remains are not of Native American heritage, construction in the area may
42 recommence. If the remains are of Native American origin, the most likely descendants
43 of the deceased will be identified by the Native American Heritage Commission
44 (NAHC). LAHD and USACE will consult with the Native American most likely
45 descendant(s) to identify a mutually acceptable strategy for treating and disposing of,
46 with appropriate dignity, the human remains and any associated grave goods as provided

1 in Public Resources Code Section 5097.98. If NAHC is unable to identify a most likely
2 descendant; if the descendant fails to make a recommendation within 24 hours of being
3 notified by NAHC, LAHD, or USACE; and if the descendant is not capable of reaching a
4 mutually acceptable strategy through mediation by NAHC, the Native American human
5 remains and associated grave goods will be reburied with appropriate dignity on the
6 proposed project site in a location not subject to further subsurface disturbance.

7 **4.5 Geology and Soils**

8 **4.5.1.1 Summary of San Pedro Waterfront EIS/EIR Findings**

9 The SPW Project EIS/EIR determined construction and operational impacts related to
10 seismic hazards and risks involving tsunamis or seiches would be significant and
11 unavoidable. The project area lies near the Palos Verdes Fault Zone and activity along
12 this fault zone, or other regional faults, would potentially produce fault rupture, seismic
13 ground shaking, liquefaction, or other seismically induced ground failure. Seismic
14 hazards are common to the Los Angeles region and are not increased by the SPW Project.
15 However, because the SPW Project area is potentially underlain by strands of the active
16 Palos Verdes Fault and liquefaction-prone hydraulic fill, there is a substantial risk of
17 seismic impacts. Design and construction in accordance with applicable laws and
18 regulations pertaining to seismically induced ground movement would minimize
19 structural damage in the event of an earthquake. However, increased exposure of people
20 and property during construction and operation to seismic hazards from a major or great
21 earthquake cannot be precluded even with incorporation of modern construction
22 engineering and safety standards. Therefore, impacts due to seismically induced ground
23 failure were found to be significant and unavoidable.

24 In addition, designing new facilities based on existing building codes may not prevent
25 substantial damage to structures from coastal flooding. Impacts due to tsunamis and
26 seiches are typical for the entire California coastline and would not be increased by
27 construction and operation of the SPW Project. Emergency planning and coordination
28 between the existing and future Port tenants and LAHD, as outlined in Mitigation
29 Measure MM GEO-1, would contribute to reducing on-site injuries during a tsunami.
30 However, even with incorporation of emergency planning and construction in accordance
31 with current City and State regulations, substantial damage and/or injury would occur in
32 the event of a tsunami or seiche. As a result, impacts during construction and operation of
33 the SPW Project were found to be significant and unavoidable.

34 Other geologic impacts were determined to be less than significant and include land
35 subsidence/settlement, expansive soils, unstable soil conditions, and mineral resources.
36 No impacts were determined to occur for landslides and damaging or destroying
37 prominent geologic or topographic features.

38 **4.5.1.2 Impacts of SPPM Project**

39 The SPPM Project would generally be consistent with the redevelopment scenario that
40 was analyzed in the SPW Project EIS/EIR. The SPPM Project would be contained mostly
41 within the same development boundaries for the Ports O'Call site and a small portion of
42 the Town Square that were analyzed in the SPW Project EIS/EIR. The SPPM Project
43 does not change or alter any of the findings of the SPW Project EIS/EIR's geology and

1 soils impact assessment. As with the SPW Project, all structures would be designed in
2 accordance with the applicable seismic building codes. The SPPM Project would not
3 result in new significant impacts, substantially increase the severity of a previously
4 analyzed impact, or require new mitigation measures that have not already been
5 addressed in the SPW Project EIS/EIR. Therefore, geology and soils impacts resulting
6 from the SPPM Project would be similar to those evaluated in the SPW Project EIS/EIR,
7 and there is no substantial change from the findings in the SPW Project EIS/EIR.

8 **4.5.1.3 Mitigation Measures Applicable to the SPPM Project**

9 Implementation of Mitigation Measure MM GEO-1 would apply to the SPPM Project to
10 reduce on-site injuries during a tsunami.

11 **MM GEO-1. Emergency response planning.** The tenants within the proposed project
12 area will work with Port engineers and LAHD police to develop tsunami response
13 training and procedures to ensure that construction and operations personnel will be
14 prepared to act in the event of a large seismic event. Such procedures will include
15 immediate evacuation requirements in the event that a large seismic event is felt at the
16 proposed project site, as part of overall emergency response planning for this proposed
17 project.

18 Such procedures will be included in any bid specifications for construction or operations
19 personnel, with a copy of such bid specifications to be provided to LAHD, including a
20 completed copy of its operations emergency response plan prior to commencement of
21 construction activities and/or operations.

22 **4.6 Groundwater and Soils**

23 **4.6.1.1 Summary of San Pedro Waterfront EIS/EIR Findings**

24 The SPW Project EIS/EIR did not identify any groundwater and soils impacts as
25 significant and unavoidable. Impacts related to encountering toxic substances and
26 expanding the area affected by contaminants were determined to be less than significant
27 with mitigation, and impacts on groundwater recharge would be less than significant.
28 There were no impacts related to potable water levels and water quality standards.

29 Construction and operation of the SPW Project was determined to pose a potential threat
30 to exposing personnel to contaminated soil and expanding the area affected by
31 contaminants. LAHD (or other Responsible Parties in the case of the Former Unocal
32 Station at Berth 78) would mitigate contaminated soil and groundwater where necessary
33 prior to construction as required by Mitigation Measure MM GW-1 for previously
34 identified contaminated sites. In addition, LAHD would implement Mitigation Measure
35 MM GW-2 to address the potential to encounter unanticipated contaminated soil and
36 groundwater during construction in areas outside currently identified contaminated sites.

37 Most of the proposed project area is currently paved and impermeable to groundwater
38 recharge. Construction activities at the proposed project site would result in removal of
39 pavement in select areas prior to repaving, thus resulting in a temporary increase in
40 groundwater recharge at the site. The proposed project area is underlain by highly saline,
41 non-potable groundwater, and it is not a designated recharge area for potable

1 groundwater. As such, any temporary increase in recharge would be inconsequential.
2 Because the water is non-potable, the amount of recharge is irrelevant with respect to
3 potential utilization of the perched aquifer as a drinking water source. During project
4 operations, the project site would be subsequently paved, resulting in continued denied
5 recharge at the majority of the site. Construction of new open space areas within the
6 project area could result in fewer impermeable surfaces. However, as described above,
7 the groundwater basin in the vicinity of the site does not contribute to recharge into
8 potable groundwater. Therefore, the overall impact was found to be less than significant.

9 Because drinking water is provided to the project area by the Los Angeles Department of
10 Water and Power and no existing production wells are located in the vicinity of the
11 project site, no impacts were found to occur with respect to changes in potable water
12 levels beneath the site or a violation of regulatory water quality standards at an existing
13 production well.

14 **4.6.1.2 Impacts of SPPM Project**

15 The SPPM Project would generally be consistent with the redevelopment scenario that
16 was analyzed in the SPW Project EIS/EIR. The SPPM Project would be contained mostly
17 within the same development boundaries for Ports O'Call and a small portion of the
18 Town Square that were analyzed in the SPW Project EIS/EIR. Although two new
19 recognized environmental conditions (RECs) have been identified, due to the long history
20 of industrial activity at the project site, it was always the assumption of the SPW Project
21 EIS/EIR that project activities could encounter historical soil or groundwater
22 contamination that had not been previously reported to regulatory agencies.

23 Specific to the SPPM Project site, and to implement Mitigation Measure MM GW-1 from
24 the SPW Project EIS/EIR, the recommendations presented in the Phase II ESA (ERM
25 2013) would be required prior to development of the site. These include the following.

- 26 ▪ Soil removal or additional characterization at the location of the black-stained
27 soil dependent upon redevelopment plans.
- 28 ▪ If soils at the site are disturbed by grading or excavation, they should be properly
29 managed in accordance with their waste characteristic as determined by
30 additional laboratory confirmation testing during excavation and grading.
- 31 ▪ Evaluation of the potential for vapor intrusion once development plans are
32 finalized.

33 In addition, implementation of the recommendations presented in the Soil Management
34 Plan (SMP) for Ports O'Call (Leighton Consulting Inc. 2016) would be required prior to
35 development of the site. The SMP provides protocols to prevent and minimize impacts
36 related to groundwater, soils, and hazardous materials. When implemented, the SMP
37 would provide protection and coverage for the following.

- 38 ▪ Provide protocols and approaches to be utilized during redevelopment of the
39 Ports O'Call area as they relate to the management of previously identified
40 contaminated soil material as well as unforeseen conditions, if encountered.
- 41 ▪ Identify proper handling and management practices to minimize waste creation
42 and the disposal of waste generated during construction activities, as construction

1 operations shall not contribute to the generation of hazardous waste except the
2 excavation of soils that are known to be chemically impacted, if encountered.

- 3 ■ Prevent on-site worker and public exposure to potentially hazardous conditions
4 and materials.
- 5 ■ Protect the environment through efficient resource allocation and recycling to the
6 greatest extent practical.

7 Furthermore, the Human Health Risk Assessment (HHRA) may be re-evaluated once the
8 final design for the SPPM Project is approved. Should any recommendations result from
9 the re-evaluation, they would be identified in the revised HHRA and implemented either
10 prior to or concurrent with development of the SPPM Project.

11 These measures do not represent a substantial change in what was previously evaluated in
12 the SPW Project EIS/EIR and Mitigation Measures MM GW-1 and MM GW-2 would
13 address the newly discovered conditions. In addition, the extension of the lease through
14 2066 would not change or alter any of the findings of the SPW Project EIS/EIR's
15 groundwater and soils impact assessment. The SPPM Project would not result in new
16 significant impacts, substantially increase the severity of a previously analyzed impact, or
17 require new mitigation measures that have not already been addressed in the SPW Project
18 EIS/EIR. Therefore, groundwater and soils impacts resulting from the SPPM Project
19 would be similar to those evaluated in the SPW Project EIS/EIR, and there is no
20 substantial change from the findings in the SPW Project EIS/EIR.

21 **4.6.1.3 Mitigation Measures Applicable to the SPPM Project**

22 Implementation of Mitigation Measures MM GW-1 and MM GW-2 would apply to the
23 SPPM Project to minimize impacts related to encountering toxic substances and altering
24 contaminant transport pathways.

25 **MM GW-1. Complete site remediation.** Unless otherwise authorized by the lead
26 regulatory agency for any given site, LAHD will remediate all contaminated soils within
27 proposed project boundaries prior to or during demolition and grading activities.
28 Remediation will occur in compliance with local, state, and federal regulations as
29 described in Section 3.6.3 of the SPW Project EIS/EIR and as directed by the Los
30 Angeles County Fire Department, Department of Toxic Substances Control, and/or
31 Regional Water Quality Control Board.

32 Soil remediation will be completed such that contamination levels are below health
33 screening levels established by the California Office of Environmental Health Hazard
34 Assessment and/or applicable action levels established by the lead regulatory agency with
35 jurisdiction over the site. Use of localized soil capping/paving, combined with agency-
36 approved deed restrictions, may be an acceptable remediation measure in upland areas
37 and/or risk-based soil assessments, but would be subject to the discretion of the lead
38 regulatory agency.

39 Existing groundwater contamination throughout the proposed project boundary will
40 continue to be monitored and remediated, simultaneous and/or subsequent to site
41 redevelopment, in accordance with direction provided by the Regional Water Quality
42 Control Board.

1 Unless otherwise authorized by the lead regulatory agency for any given site, areas of soil
2 contamination that will be remediated prior to or in conjunction with project demolition,
3 grading, and construction would include, but not be limited to, the properties within and
4 adjacent to the proposed project as listed in Table 3.6-3 and 3.6-4 of the SPW Project
5 EIS/EIR.

6 **MM GW-2. LAHD will prepare a contamination contingency plan for non-specific**
7 **facilities.** The project site has a long history of industrial activity, so it is possible that
8 future construction activity could encounter historical soil or groundwater contamination
9 that had not been previously reported to regulatory agencies. The following contingency
10 plan will be implemented to address previously unknown contamination during
11 demolition, grading, and construction.

- 12 a) All trench excavation and fill operations will be observed for the presence of
13 chemicals of potential concern and petroleum products. Soils that are suspected to be
14 impacted with chemicals of potential concern and/or petroleum products will be
15 segregated from clean soil. Indications of contaminated/impacted soil may include
16 but are not limited to: discolored soil, petroleum or organic odors, and/or visible
17 sheen. In the event unexpected suspected chemically impacted material (soil or
18 water) is encountered during construction, the contractor will notify LAHD's Chief
19 Harbor Engineer, Director of Environmental Management, and Risk Management's
20 Industrial Hygienist. LAHD will confirm the presence of the suspect material; direct
21 the contractor to remove, stockpile, or contain the material; and characterize the
22 suspect material identified within the boundaries of the construction area. Continued
23 work at a contaminated site will require the approval of the Chief Harbor Engineer.
- 24 b) As warranted, appropriate air monitoring equipment (e.g., photoionization detector,
25 combustible gas indicator, organic vapor analyzer) will be present during grading
26 and/or excavation activities in soils that are suspected to be impacted with chemicals
27 of concern and/or petroleum products.
- 28 c) Excavation of volatile organic compound-impacted soil will require obtaining and
29 complying with a South Coast Air Quality Management District Rule 1166 permit.
- 30 d) The remedial option(s) selected will be dependent upon a number of criteria
31 (including but not limited to types of chemical constituents, concentration of the
32 chemicals, health and safety issues, time constraints, cost, etc.) and will be
33 determined on a site-specific basis. Both off-site and on-site remedial options will be
34 evaluated.
- 35 e) The extent of removal actions will be determined on a site-specific basis. At a
36 minimum, the chemically impacted area(s) within the boundaries of the construction
37 area will be remediated to the satisfaction of the lead regulatory agency for the site.
38 The LAHD Project Manager overseeing removal actions will inform the contractor
39 when the removal action is complete.
- 40 f) Copies of hazardous waste manifests or other documents indicating the amount,
41 nature, and disposition of such materials will be submitted to the Chief Harbor
42 Engineer within 30 days of project completion.
- 43 g) In the event that suspected contaminated soil is encountered, all on-site personnel
44 handling the suspected contaminated material must be trained in accordance with the
45 federal Hazardous Waste Operations and Emergency Response (HAZWOPER)
46 standard. This training provides precautions and protective measures for workers

1 remediating contaminated sites. Workers not certified with HAZWOPER training
2 will not be allowed to resume work in suspected contaminated areas until appropriate
3 site characterization confirms that contaminated soil, groundwater, or soil vapor are
4 not present.

5 h) As warranted, real-time perimeter and ambient air monitoring stations will be
6 established during all grading, excavation, trenching, and/or soil handling activities
7 associated with contaminated soil.

8 i) All excavations will be filled with structurally suitable fill material that is free from
9 contamination.

10 4.7 Hazards and Hazardous Materials

11 4.7.1.1 Summary of San Pedro Waterfront EIS/EIR Findings

12 The SPW Project EIS/EIR did not identify any hazards and hazardous materials impacts
13 as significant and unavoidable. Impacts related to compliance with applicable regulations
14 and policies and accidental spill, release, or explosions as a result of construction and
15 operation of the Ports O'Call redevelopment were determined to be less than significant.
16 Additionally, impacts related to emergency response or evacuation plans and accidental
17 spill, release, or explosions as a result of a tsunami or terrorist action were found to be
18 less than significant.

19 General construction and demolition activities for the SPW Project would not involve the
20 handling of significant amounts of hazardous materials. Furthermore, implementation of
21 construction and demolition standards, including best management practices, and
22 compliance with the state and federal requirements for the transport, handling, and
23 storage of any hazardous materials during construction and demolition phases would
24 minimize the potential for an accidental release of petroleum products and/or hazardous
25 materials and/or explosion during construction/demolition activities. The
26 decommissioning of the S.P. Railyard would require compliance with the Emergency
27 Planning and Community Right-to-Know Act, Los Angeles Fire Department regulations,
28 and other state and federal regulations and guidelines governing the decommissioning
29 and remediation of hazardous materials and providing oversight and prevention
30 techniques for the decommissioning. Additionally, the decommissioning would include
31 remediation efforts as part of the SPW Project to remove the known or suspected
32 hazardous groundwater and soil contamination at the site. Therefore, construction of the
33 SPW Project was found to comply with applicable security and safety regulations and/or
34 LAHD policies guiding Port development, and there would be no increased risk of an
35 accidental spill, release, or explosion at the project site during construction.

36 Furthermore, the proposed expansion of the square footage in the Ports O'Call area,
37 including the addition of a conference center, was found to not substantially increase the
38 likelihood of an accidental hazardous material spill, release, or explosion involving
39 people or property. Any new tenant of the expanded Ports O'Call was assumed to
40 continue to comply with existing state and federal regulations regarding the use, storage,
41 and handling of hazardous materials. These regulations are in place to minimize spills,
42 releases, and explosions of hazardous materials and would serve to reduce the risk

1 associated with any slight increase in use of these materials within the expanded Ports
2 O'Call area.

3 Due to its existing operations handling gasoline and diesel fuels, the Jankovich fueling
4 station has an existing hazardous footprint per the Port's Risk Management Plan (RMP)
5 that overlaps with the southernmost portions of Ports O'Call in the open space next to the
6 fueling station. This overlap constitutes an existing risk to vulnerable populations that use
7 the Ports O'Call area should the Jankovich fueling station have an accidental release,
8 spill, or explosion of the hazardous materials it regularly handles and stores. The
9 Jankovich fueling station was to be decommissioned as part of the SPW Project.

10 SPW Project contractors and tenants would be required to adhere to all Homeland
11 Security, Port Police, and Los Angeles Fire Department emergency response and
12 evacuation regulations, ensuring compliance with existing emergency response plans.
13 Therefore, implementation of the SPW Project would not substantially interfere with an
14 existing emergency response or evacuation plan or increase the risk of injury or death,
15 and impacts were found to be less than significant.

16 In addition, the volume of spilled hazardous materials during a tsunami is expected to be
17 relatively low and of a manageable amount to clean up that would not result in significant
18 environmental impacts. Furthermore, the SPW Project would remove a number of
19 industrial uses that could potentially cause a release, spill, or explosion of a hazardous
20 material in the event of a tsunami; operation of the SPW Project would generally reduce
21 the potential for a release, spill, or explosion of hazardous materials. Therefore,
22 implementation of the SPW Project would not result in a substantially increased public
23 health and safety concern as a result of the accidental release, spill, or explosion of
24 hazardous materials due to a tsunami, and impacts were found to be less than significant.

25 Furthermore, because the amount of hazardous material released during construction or
26 demolition activities is generally small, and redevelopment of the Ports O'Call would
27 ultimately not substantially increase the vulnerability of these facilities or the seriousness
28 of the consequences over the existing conditions, implementation of the SPW Project
29 would not result in a substantial increase in the likelihood of a spill, release, or explosion
30 of hazardous material(s) due to a terrorist action, and impacts were found to be less than
31 significant.

32 **4.7.1.2 Impacts of SPPM Project**

33 The SPPM Project would generally be consistent with the redevelopment scenario for the
34 Ports O'Call site that was analyzed in the SPW Project EIS/EIR. The SPPM Project
35 would introduce a similar mix of land uses and is not expected to involve the handling of
36 significant amounts of hazardous materials. The SPPM Project would be contained mostly
37 within the same development boundaries for Ports O'Call and a small portion of the
38 Town Square that were analyzed in the SPW Project EIS/EIR. Furthermore, the proposed
39 modifications to the SPW Project and the extension of the lease through 2066 do not
40 change or alter any of the findings of the SPW Project EIS/EIR's hazards and hazardous
41 materials impact assessment. As described in Chapter 2, *Project Description*, the
42 Jankovich fueling station located at Berth 74 was originally proposed to be
43 decommissioned under the SPW Project. While the details of this project are in the
44 process of being finalized, the fueling station may now be moved to Mike's Marine
45 Fueling Station south of the project site at Berth 72 off the Main Channel. Relocation

1 would still be completed prior to the redevelopment of Ports O'Call. The SPPM Project
2 would not result in new significant impacts, substantially increase the severity of a
3 previously analyzed impact, or require new mitigation measures that have not already
4 been addressed in the SPW Project EIS/EIR. Therefore, hazards and hazardous materials
5 impacts resulting from the SPPM Project would be less than significant, and there is no
6 substantial change from the findings in the SPW Project EIS/EIR.

7 **4.7.1.3 Mitigation Measures Applicable to the SPPM Project**

8 No mitigation measures are required.

9 **4.8 Land Use and Planning**

10 **4.8.1.1 Summary of San Pedro Waterfront EIS/EIR Findings**

11 The SPW Project EIS/EIR identified a less-than-significant land use impact related to the
12 physical disruption, division, or isolation of existing neighborhoods, communities, or
13 land uses. The SPW Project EIS/EIR determined that the project would generally be
14 consistent with the adopted land use/density designation in the Community Plan,
15 redevelopment plan, or specific plan for the site with the exception of the location of the
16 promenade adjacent to a fueling station, which would be inconsistent with the objective
17 of the Port Master Plan to locate vulnerable populations away from hazardous facilities.

18 **4.8.1.2 Impacts of SPPM Project**

19 The SPPM Project would generally be consistent with the redevelopment scenario that
20 was analyzed in the SPW Project EIS/EIR with the exception that the overall building
21 square footage would be reduced by 75,000 square feet, and additional new features
22 associated with the Discover Sea Amusement Area have been added to the SPPM Project.
23 This space would include playground facilities, entertainment attractions such as various
24 temporary and permanent rides (i.e., a Ferris wheel, a carousel, and arcade-style games),
25 and garden uses that could include art, public and private dining spaces, wedding
26 facilities, water features, and informational and educational displays.

27 The commercial restaurant and retail uses that would be developed under the SPPM
28 Project are consistent with those analyzed in the SPW Project EIS/EIR, and other project
29 components (i.e., waterfront promenade and the trolley) would be included, as well. The
30 SPPM Project is consistent with the updated 2014 Port Master Plan (PMP). As mentioned
31 in Section 3.8, the PMP includes a goal to provide enhanced public access to the
32 waterfront and visitor-serving facilities including retail, restaurants, museums, and parks.
33 Specifically, the Ports O'Call area located in Planning Area 1 emphasizes waterfront
34 access through a waterfront promenade, parks, museums, academic uses, and visitor-
35 serving commercial uses and attractions. Thus, the proposed commercial retail and
36 restaurant uses, as well as the visitor-serving entertainment attractions, are consistent
37 with the PMP, and the SPPM Project would not result in new significant impacts,
38 substantially increase the severity of a previously analyzed impact, or require new
39 mitigation measures that have not already been addressed in the SPW Project EIS/EIR.
40 Therefore, impacts resulting from the SPPM Project would be less than significant, and
41 there is no substantial change from the findings in the SPW Project EIS/EIR.

1 **4.8.1.3 Mitigation Measures Applicable to the SPPM Project**

2 No mitigation measures are required.

3 **4.9 Noise**

4 **4.9.1.1 Summary of San Pedro Waterfront EIS/EIR Findings**

5 The SPW Project EIS/EIR determined that construction noise, primarily associated with
6 pile driving for the waterfront promenade, would be significant and unavoidable even
7 with implementation of noise mitigation. In addition, heavy equipment required to
8 construct the parking areas of the Ports O'Call development would exceed the 5 decibel
9 (dB) significance threshold. Other construction activities associated with redevelopment
10 of the Ports O'Call site were determined to result in less-than-significant impacts. The
11 only significant impact related to operational traffic noise was identified along Miner
12 Street, south of 22nd Street, and there was no feasible mitigation that would reduce this
13 impact to less-than-significant levels. However, this traffic would be generated by cruise
14 terminal operations and was not associated with the Ports O'Call development.

15 **4.9.1.2 Impacts of SPPM Project**

16 The SPPM Project would result in similar construction activities that would result in
17 similar previously identified impacts. While the SPPM Project would require the same or
18 fewer piles than analyzed in the SPW Project EIS/EIR and, thus, would result in a similar
19 or shorter duration of pile driving activities, pile driving would still exceed the 5 dB
20 threshold at the nearest sensitive receptors. Furthermore, construction of the parking
21 areas within the project site would require the use of heavy construction equipment and
22 would also exceed 5 dB at the nearest sensitive receptors. Therefore, consistent with the
23 findings of the SPW Project EIS/EIR, impacts associated with construction of the SPPM
24 Project would remain significant even with implementation of mitigation measures
25 (Mitigation Measures MM NOI-1 and MM NOI-2). The SPPM Project would not result
26 in new significant impacts, substantially increase the severity of a previously analyzed
27 impact, or require new mitigation measures that have not already been evaluated in the
28 SPW Project EIS/EIR. Therefore, there is no substantial change from the findings in the
29 SPW Project EIS/EIR.

30 **4.9.1.3 Mitigation Measures Applicable to the SPPM Project**

31 **MM NOI-1.** Construct temporary noise barriers, muffle and maintain construction
32 equipment, prohibit idling, locate equipment, use quiet construction equipment, and
33 notify residents. The following will reduce the impact of noise from construction
34 activities.

- 35 a) **Temporary Noise Barriers.** When construction is occurring within 500 feet of a
36 residence or park, temporary noise barriers (solid fences or curtains) will be located
37 between noise-generating construction activities and sensitive receivers.
- 38 b) **Construction Equipment.** All construction equipment powered by internal
39 combustion engines will be properly muffled and maintained.

- 1 c) **Idling Prohibitions.** Unnecessary idling of internal combustion engines near noise-
2 sensitive areas will be prohibited.
- 3 d) **Equipment Location.** All stationary noise-generating construction equipment, such
4 as air compressors and portable power generators, will be located as far as practical
5 from existing noise-sensitive land uses.
- 6 e) **Quiet Equipment Selection.** Select quiet construction equipment whenever possible.
7 Comply where feasible with noise limits established in the City of Los Angeles Noise
8 Ordinance.
- 9 f) **Notification.** Notify residents within 500 feet of the proposed project site of the
10 construction schedule in writing.

11 **MM NOI-2.** Construction activities for the proposed project would not exceed the
12 ambient noise level by 5 A-weighted decibels (dBA) at a noise-sensitive use between the
13 hours of 6:00 p.m. and 7:00 a.m. Monday through Friday, before 8:00 a.m. or after 6:00
14 p.m. on Saturday, or at any time on Sunday. If extended construction hours are needed
15 during weekdays under special circumstances, LAHD and the contractor will provide at
16 least 72 hours' notice to sensitive receptors within 0.5 mile of the construction area.
17 Under no circumstances will construction hours exceed the range prescribed by the City
18 of Los Angeles Municipal Code.

19 4.10 Recreation

20 4.10.1.1 Summary of San Pedro Waterfront EIS/EIR Findings

21 Construction activities, including construction noise and construction staging, resulting
22 from development of the Ports O'Call project analyzed in the SPW Project EIS/EIR
23 would result in significant impacts on nearby recreational resources due to temporary loss
24 or diminished quality of the resource. Recreational resources that would be affected by
25 construction of the Ports O'Call project include the following.

- 26 ▪ Bike lanes (obstruction of bike lanes by construction activities, construction
27 noise)
- 28 ▪ California Coastal Trail (construction noise)
- 29 ▪ Bloch Field (construction noise)
- 30 ▪ Waterfront Red Car Line (construction noise)
- 31 ▪ Recreational Fishing (removal of existing docks and slips, and harbor access)
- 32 ▪ Recreational boating and special boating events (removal of existing docks,
33 harbor access, disruption of harbor cruise services)

34 Even with the implementation of mitigation measures, these temporary construction-
35 related impacts would remain significant and unavoidable.

36 Operation of the SPW Project, including the Ports O'Call area, would enhance many of
37 the recreational opportunities within the project area through the construction of new

1 open space and transient slips for personal watercraft, and impacts on recreational
2 resources related to operation of the SPW Project would be less than significant.

3 **4.10.1.2 Impacts of SPPM Project**

4 Operation of the SPPM Project would result in similarly beneficial operational impacts
5 on recreational resources as those identified in the SPW Project EIS/EIR. Additionally,
6 the SPPM Project would result in similar levels of construction and demolition activities
7 as those analyzed in the SPW Project EIS/EIR. No new recreational resources have been
8 developed in the vicinity of the Ports O'Call area since certification of the SPW Project
9 EIS/EIR, and construction of the SPPM Project would result in the same temporary
10 significant and unavoidable impacts on the recreational resources listed above. Mitigation
11 Measures MM REC-1 through REC-4 and MM REC-6 through REC-7 as well as MM
12 NOI-1 and MM NOI-2, which were identified in the SPW Project EIS/EIR, would apply
13 to the SPPM Project. The SPPM Project would not result in new significant impacts,
14 substantially increase the severity of a previously analyzed impact, or require new
15 mitigation measures that have not already been evaluated in the SPW Project EIS/EIR.
16 Therefore, there is no substantial change from the findings in the SPW Project EIS/EIR.

17 **4.10.1.3 Mitigation Measures Applicable to the SPPM Project**

18 **MM REC-1. Maintain pedestrian access during construction.** LAHD and
19 construction contractors will follow standard safety procedures to protect pedestrian
20 traffic from construction hazards, including providing brightly colored fencing and
21 signage indicating closures and safely directing pedestrian traffic around construction
22 areas. This will also require coordinated construction activities such that pedestrian
23 access can be routed around construction with a minimum increase in distance.

24 **MM REC-2. Maintain bicycle access during construction.** LAHD and construction
25 contractors will provide signage notifying users of bike lanes of closure as well as
26 signage directing users to alternative bike routes. Alternative bike lanes in the proposed
27 project vicinity include a north-south Class II bike path along the entire length of South
28 Gaffey Street, and an east-west Class III bike path on 9th from North Harbor Boulevard
29 west to State Route 213. LAHD will be required to inform the public prior to
30 commencement of construction resulting in closures or possible disruptions to bike paths.
31 Public sources to notify will, at minimum, include the City of Los Angeles Department of
32 Transportation Bicycle Program and Los Angeles area bicycling groups.

33 **MM REC-3. Maintain parking during construction.** LAHD and construction
34 contractors will minimize parking obstructions during construction periods by placing
35 construction areas out of roadways and parking lots, where possible. In areas where
36 construction staging areas and construction activities must impede access to parking
37 areas, detour signs and lane striping will direct traffic to additional off-site parking areas.
38 LAHD will provide shuttle service to remote parking areas in the event that off-site
39 parking areas are farther than 1 mile from existing waterfront areas and the Waterfront
40 Red Car Line does not adequately service the off-site parking areas.

41 **MM REC-4. Maintain vehicle access during construction.** LAHD and construction
42 contractors will minimize obstructions to vehicle access during construction periods by
43 placing construction areas out of roadways and parking lots, where possible. In areas
44 where construction staging areas and construction activities must impede access to

1 roadways, detour signs and lane striping will safely direct traffic around construction
2 areas. See Section 3.11, *Transportation and Circulation (Ground)*, of the SPW EIS/EIR
3 for further details on mitigation measures related to vehicle access to the proposed project
4 site.

5 **MM REC-6. Maintain access to open waters of the harbor during construction.**

6 LAHD and construction contractors will minimize obstructions to open waters of the
7 harbor during construction periods by placing construction staging areas out of high-
8 traffic waterways, parking lots leading to boat ramps, and boat docks, where possible.
9 LAHD will embark on a public awareness campaign, providing information about
10 construction periods, construction areas, closures, and suggestions of alternative boating
11 areas. LAHD will inform the public prior to commencement of construction that will
12 result in closures or possible disruptions to open waters of the harbor. Public notifications
13 will, at minimum, include notifying local boating groups and posting flyers at boat ramps
14 in the proposed project vicinity. LAHD will offer boater safety training for the public,
15 specifically with respect to safe navigation around construction activities.

16 **MM REC-7. Maintain docking space and dock access during construction.**

17 LAHD and construction contractors will minimize obstructions to docking space and dock access
18 during construction periods by placing construction staging areas away from boat docks
19 where possible. LAHD will embark on a public awareness campaign, providing
20 information about construction periods, construction areas, closures, and suggestions of
21 alternative boating areas and docking locations. In cases where docking space will be
22 closed or removed and existing tenants need alternative docking space, LAHD will
23 provide temporary docking space in the near vicinity of the proposed project. LAHD will
24 provide notification and signage to direct users to these temporary alternative docking
25 areas. LAHD will inform the public prior to commencement of construction that will
26 result in closures or possible disruptions to dock access. Public notifications will, at
27 minimum, include notifying local boating groups and posting flyers at boat ramps in the
28 proposed project vicinity. LAHD will offer boater safety training for the public,
29 specifically with respect to safe navigation around construction activities.

30 See Mitigation Measures MM NOI-1 and MM NOI-2 (Section 4.9, *Noise*) for measures
31 to mitigate noise impacts.

32 4.11 Transportation and Circulation (Ground)

33 4.11.1.1 Summary of San Pedro Waterfront EIS/EIR Findings

34 Demolition and landside construction associated with various elements under the SPW
35 Project were found to generate truck and other vehicular traffic associated with
36 construction worker commutes, transport and staging of construction equipment,
37 transport of construction materials to the construction site, and hauling excavated and
38 demolished materials away from the site. Potential construction effects on roadway
39 operations identified included the following:

- 40 ■ A temporary increase in traffic associated with construction worker commutes,
41 delivery of construction materials, hauling of demolished and/or excavated
42 materials, and general deliveries would increase travel demand on roadways.

- 1 ■ Temporary roadway lanes closures or narrowings in areas directly abutting
2 construction activities would reduce capacity of roadways.
- 3 ■ Temporary roadway closures associated with the construction of transportation
4 infrastructure would reduce the capacity of the roadway system, and/or require
5 detours that increase travel times.
- 6 ■ Temporary lane or road closures could require route detours or reduced service
7 for transit routes that run adjacent to proposed project elements that are under
8 construction; namely, Metro lines 445 and 446/447, Los Angeles Department of
9 Transportation (LADOT) Commuter Express Line 142, the San Pedro Electric
10 Trolley, and the Waterfront Red Car Line.
- 11 ■ During proposed project construction, parking demand would increase from
12 construction workers and from construction equipment that is not in use. In
13 addition, parking spaces located adjacent to construction activities could be
14 temporarily closed.
- 15 ■ Temporary sidewalk, lane, or road closures could occur adjacent to proposed
16 project elements that are under construction, which could interfere with bicycle
17 or pedestrian circulation within the proposed project vicinity.
- 18 ■ Travel disruptions could occur along the Class I bike path located at the southern
19 end of the proposed project area parallel to Crescent Avenue and the Class II
20 bicycle lanes along Harbor Boulevard north of 22nd Street.
- 21 ■ Heavy and slow-moving construction vehicles would mix with general-purpose
22 vehicular and nonmotorized traffic in the area.

23 Once operational, the SPW Project would result in increased traffic volumes on the
24 surrounding roadways and would degrade intersection operations. The SPW Project was
25 determined to result in significant traffic impacts² at 10 intersections by 2015 and at 16
26 intersections by 2037 during one or more peak hours as shown in Table 4-2 below.

² A project is determined to result in a significant impact if an intersection would increase in volume to capacity (V/C) ratio equal to or greater than 0.04 for intersections operating at level of service (LOS) C; equal to or greater than 0.02 for intersections operating at LOS D; and equal to or greater than 0.01 for intersections operating at LOS E or F.

1 **Table 4-2. Significant Impacts at Intersections without Mitigation—SPW Project**

Intersection	LOS (V/C) ¹					
	2015			2037		
	AM	PM	Wkend	AM	PM	Wkend
5. Gaffey Street/9th Street			C (0.731)	E (0.909)	E (0.923)	D (0.833)
6. Gaffey Street/7th Street						D (0.804)
7. Gaffey Street/6th Street	E (0.918)		D (0.831)	F (1.040)		E (0.942)
8. Gaffey Street/5th Street	E (0.955)			F (1.089)		D (0.842)
9. Gaffey Street/1st Street	F (1.211)		E (0.943)	F (1.414)	F (1.080)	F (1.077)
20. Miner Street/22nd Street				C (0.723)		
21. Harbor Boulevard/Miner Street/Crescent Avenue				C (0.729)		
22. Harbor Boulevard/7th Street			D (0.859)	C (0.800)		E (0.972)
23. Harbor Boulevard/6th Street						C (0.721)
24. Harbor Boulevard/5th Street		D (0.806)			E (0.906)	D (0.806)
25. Harbor Boulevard/1st Street	D (0.806)		D (0.817)	F (1.002)	C (0.787)	E (0.975)
26. Harbor Boulevard/Swinford Street/SR-47 eastbound ramps	E (0.935)		E (0.939)	F (1.198)	C (0.726)	F (1.208)
27. Harbor Boulevard/SR-47 westbound on-ramp				D (0.876)		C (0.771)
29. Harbor Boulevard/O'Farrell Street	C (0.712)	E (0.931)	D (0.864)	D (0.830)	F (1.046)	F (1.006)
30. Harbor Boulevard/3rd Street	C (0.793)	D (0.865)	E (0.981)	E (0.928)	E (0.948)	F (1.108)
34. Gaffey Street /13th Street				E (0.969)		
Note: 1. Only analysis intersections at which significant impacts have been identified are listed in this table. LOS (V/C) information is provided only in the years/analysis periods in which a significant impact has been identified						

2

3 Several mitigation measures were identified to attempt to reduce intersection impacts
4 identified through 2015 and 2037, which were found to mitigate impacts identified at
5 seven of the 10 intersections in 2015 and six of the 16 intersections in 2037 to less-than-
6 significant levels. For the remaining locations, no feasible measures were identified that
7 would mitigate impacts to less-than-significant levels for all analysis periods due to
8 existing physical constraints at those locations caused by unavailable right-of-way to

1 improve capacity or reduce volume. Impacts at those locations would be significant and
 2 unavoidable. Table 4-3 summarizes the locations and scenarios at which residual
 3 significant and unavoidable impacts are expected to remain after implementation of all
 4 recommended mitigation measures.

5 **Table 4-3. Significant Residual Impacts at Intersections—SPW Project**

Intersection	LOS (V/C) ¹					
	2015			2037		
	AM	PM	Wkend	AM	PM	Wkend
5. Gaffey Street/9th Street			C (0.731)	E (0.909)		D (0.833)
6. Gaffey Street/7th Street						D (0.804)
8. Gaffey Street/5th Street						D (0.842)
9. Gaffey Street/1st Street	F (1.211)		E (0.943)	F (1.414)	F (1.080)	F (1.077)
21. Harbor Boulevard/Miner Street/Crescent Avenue				C (0.729)		
22. Harbor Boulevard/7th Street			C (0.787)	C (0.703)		D (0.891)
24. Harbor Boulevard/5th Street						C (0.710)
25. Harbor Boulevard/1st Street				C (0.742)		
27. Harbor Boulevard/SR-47 westbound on-ramp				D (0.876)		C (0.771)
Notes: ¹ LOS (V/C) information is provided only in the years/analysis periods in which a significant and unavoidable residual impact has been identified						

6
 7 The SPW Project also found that increased traffic volumes would occur on the
 8 surrounding neighborhood roadways. Specifically, impacts on West 17th Street between
 9 Centre and Palos Verdes were found to be significant under 2015 and 2037 conditions.
 10 Short of the permanent closure of the affected street segment, which would not be
 11 acceptable because it serves adjacent land uses and carries substantial traffic volumes, no
 12 mitigation measures exist that would fully eliminate the addition of significant or adverse
 13 traffic volumes to this segment of 17th Street. Impacts at this neighborhood roadway
 14 would be significant and unavoidable.

15 The SPW Project was found to increase parking demand at the waterfront facilities.
 16 When comparing the proposed parking supply to the proposed project demand and to the
 17 requirements set forth in the City of Los Angeles Municipal Code, sufficient parking was
 18 provided throughout the SPW Project area (9,076 spaces provided versus 8,997 spaces
 19 required by anticipated demand in 2037). Impacts were less than significant.

1 The realignment and extension of the Waterfront Red Car through the Ports O'Call area
2 was found to result in potential safety hazards at pedestrian and vehicle crossings, and
3 cross-overs within streets. Several mitigation measures were identified to minimize
4 potential conflicts to ensure the maximum safety and convenience, which reduced
5 impacts to less-than-significant levels.

6 **4.11.1.2 Impacts of SPPM Project**

7 The traffic assessment conducted for this Addendum is based upon the following three
8 modifications:

- 9 ▪ Modified project description for the Ports O'Call development area of the SPW
10 Project (SPPM Project)
- 11 ▪ Updated information, including projected or actual trip generation of the other
12 SPW Project elements
- 13 ▪ Modified proposed lease length of the SPPM Project from the year 2037 to the
14 year 2066

15 The SPPM Project would result in similar demolition and landside construction at the
16 Ports O'Call site and a small portion of the Town Square, as analyzed in the SPW Project
17 EIS/EIR. These activities would generate truck and other vehicular traffic associated with
18 construction worker commutes, transport and staging of construction equipment,
19 transport of construction materials to the construction site, and hauling of excavated and
20 demolished materials away from the site. Potential construction effects on roadway
21 operations would require implementation of Mitigation Measure MM TC-1, as required
22 under the SPW Project EIS/EIR, which requires preparation of a Traffic Control Plan to
23 minimize impacts from construction traffic.

24 The operational traffic assessment does not include a quantitative assessment of year
25 2066 traffic conditions using the revised trip generation of the SPPM Project and other
26 SPW Project components as described below because it is not viable or appropriate to
27 quantify traffic projections for conditions so many years in the future. First, the region's
28 official population and employment projections as contained in the federally required
29 long-range transportation plan prepared by the Southern California Association of
30 Governments only extends to the year 2040. Also, the Port's latest cargo forecasts,
31 released in February 2016, also only extend to the year 2040. Hence, it would be highly
32 speculative to project beyond the year 2040. Moreover, it is important to note that the
33 SPW Project as a whole (including the SPPM Project, USS Iowa, and Cruise Center), and
34 both the Ports of Long Beach and Los Angeles cargo facilities, are all projected to be
35 built out and at capacity by about the year 2037. Hence, a year 2040 traffic analysis is
36 used as the basis for assessing the impacts of the extended lease to the year 2066. It
37 should be noted that LAHD will monitor traffic volumes and operating conditions over
38 time and collaborate with the City of Los Angeles on necessary improvements to
39 maintain acceptable level of service (LOS) D or better conditions.

40 New analyses were conducted at 27 of the 36 intersections analyzed in the SPW Project
41 EIS/EIR. The remaining study intersections, which were projected to operate at LOS A or
42 B in the SPW Project EIS/EIR, were not re-analyzed as they are not expected to degrade
43 to LOS C or worse with 3 more years of ambient growth from the year 2037 to the year
44 2040.

1 In addition to the SPPM Project changes, other land use changes along the Waterfront
2 assumed in the new analysis include:

- 3 ▪ Replacing the original “Mercado” land use in Warehouses 9 and 10 with the
4 existing Crafted at the Port of Los Angeles marketplace, and Brewery West
5 restaurant/micro-brewery (opened February 27, 2016) as analyzed in and
6 approved with the Addendum to the SPW Project EIS/EIR (LAHD 2011) –
7 Crafted at Port of Los Angeles (traffic counts conducted in January 2016 and
8 used for trip generation);
- 9 ▪ Replacing the original 13 acres of research and development park with the
10 approved City Dock #1 project; and
- 11 ▪ Adding the USS Iowa Museum project (estimates as contained in the EIR for the
12 USS Iowa Project, March 2012); it should be noted that these are considered to
13 be conservative based upon observed use of the facility and visitor data.

14 Tables 4-4 and 4-5 compare the SPW Project EIS/EIR and updated trip generation
15 estimates. As can be seen, the updated overall SPW Project 24-hour trip generation is
16 projected to be less by about 3.5% and 5.8% on a weekday and weekend, respectively,
17 under buildout conditions compared to the analysis in the SPW Project EIS/EIR.

18 Long-term traffic volume forecasts were prepared in a manner similar to that employed in
19 the SPW Project EIS/EIR. An ambient growth factor of 0.65% per year was applied to
20 the existing baseline (2007) volumes for 3 additional years, for a total of 21.45%, as part
21 of the updated Cumulative (No Project) 2040 scenario. Trip distribution was refined to
22 better reflect local access. For two of the study intersections (Intersection #26, Harbor
23 Boulevard/Swinford Street/SR-47 ramps, and Intersection #27, Harbor Boulevard & SR-
24 47 westbound on-ramp), preliminary traffic projections from a more recent traffic study
25 have been incorporated into the analysis. The study is part of the Harbor Boulevard/SR-
26 47 Eastbound Ramps and Front Street & SR-47 Westbound Ramp project, which is
27 described in greater detail below.

1 **Table 4-4. Comparison of SPW Project EIS/EIR Ports O’Call Component and SPPM Project Trip Generation**

					WEEKDAY							WEEKEND				
					Weekday Daily	AM Peak Hour			PM Peak Hour			Weekend Daily	Midday Peak Hour			
						Inbound	Outbound	Total	Inbound	Outbound	Total		Inbound	Outbound	Total	
Original SPW Project EIS/EIR	Ports O’ Call Commercial	931 - Quality Restaurant	125	Ksf	11,244	51	51	101	627	309	936	11,795	798	555	1,353	
		814 - Specialty Retail	175	Ksf	7,756	113	72	186	209	266	474	7,357	380	351	732	
		Total Ports O’Call Commercial less 15% Internal Capture			16,150	139	105	244	711	488	1,199	16,279	1,002	770	1,771	
	Conference Facilities		300	Attendees	780	112	23	135	23	112	135	390	23	112	135	
	Public Open Space		6	Acres	120	8	8	16	5	5	11	120	8	8	16	
	Subtotal					17,050	259	135	394	739	606	1,345	16,789	1,032	890	1,922
	Less Existing Use Credit					8,418	122	78	200	343	234	577	8,272	534	419	953
Total SPW EIS/EIR Trips					8,632	137	57	194	396	372	768	8,517	498	471	969	
San Pedro Public Market Phase 1 Commercial	Phase 1 Restaurant Development	931 - Quality Restaurant	100	Ksf	8,995	41	41	81	502	247	749	9,436	638	444	1,082	
	- less Quality Restaurant pass-by trips		10%		(900)	(4)	(4)	(8)	(50)	(25)	(75)	(944)	(64)	(44)	(108)	
	Phase 1 Retail Development	814 - Specialty Retail	38.6	Ksf	1,711	25	16	41	46	59	105	1,623	84	77	161	
	- less Specialty Retail pass-by trips		10%		(171)	(2)	(2)	(4)	(5)	(6)	(10)	(162)	(8)	(8)	(16)	
	Single Tenant Office Development	715 - Single Tenant Office Bldg	30	Ksf	350	48	6	54	8	44	52	0	0	0	0	
	Total Phase 1 Commercial less 15% Internal Capture			15%	Internal Capture	8,487	91	48	139	426	272	697	8,460	553	399	951
San Pedro Public Market Phase 1 Open Space	Fishermen’s Park (including outdoor amphitheater)	Open Space	3	Acres	60	4	4	8	3	3	5	60	4	4	8	
	Fantasy Park	480 - Amusement Park	9	Acres	682	2	0	2	22	14	36	1,622	98	71	170	
	- less internal capture with restaurant/retail	Internal Capture Rate	50%	Internal Capture	(341)	(1)	(0)	(1)	(11)	(7)	(18)	(811)	(49)	(36)	(85)	
	Total Phase 1					401	5	4	9	14	10	23	871	53	40	93

					WEEKDAY							WEEKEND			
					Weekday Daily	AM Peak Hour			PM Peak Hour			Weekend Daily	Midday Peak Hour		
						Inbound	Outbound	Total	Inbound	Outbound	Total		Inbound	Outbound	Total
San Pedro Public Market Phase 2 Commercial	Open Space														
	Phase 2 Restaurant Development	931 - Quality Restaurant	25	Ksf	2,249	10	10	20	125	62	187	2,359	160	111	271
	- less Quality Restaurant pass-by trips		10%		(225)	(1)	(1)	(2)	(13)	(6)	(19)	(236)	(16)	(11)	(27)
	Phase 2 Retail Development	814 - Specialty Retail	106.4	Ksf	4,716	69	44	113	127	161	288	4,473	231	213	445
	- less Specialty Retail pass-by trips		10%		(472)	(7)	(4)	(11)	(13)	(16)	(29)	(447)	(23)	(21)	(44)
Total Phase 2 Commercial less 15% Internal Capture		15%	Internal Capture	5,328	60	41	102	193	171	364	5,227	299	248	547	
San Pedro Public Market Subtotal					14,216	156	94	250	632	452	1,084	14,557	905	686	1,591
Less Existing Use Credit					8,418	122	78	200	343	234	577	8,272	535	419	954
Total San Pedro Public Market Trips					5,798	34	16	50	289	218	507	6,285	370	267	637

1

2


1 **Table 4-5. Comparison of SPW Project EIS/EIR and 2016 Update Trip Generation**

		WEEKDAY							WEEKEND			
		Weekday Daily	AM Peak Hour		Total	PM Peak Hour		Total	Weekend Daily	Midday Peak Hour		Total
			Inbound	Outbound		Inbound	Outbound			Inbound	Outbound	
SPW EIR	Cruise Center	11,882	452	634	1,087	175	201	376	11,906	789	527	1,316
	Ports O'Call	8,632	137	57	194	396	372	768	8,517	498	471	969
	Warehouses No. 9&10	481	13	4	17	13	24	37	395	20	20	40
	Westways	1,004	180	34	214	22	174	196	284	20	18	38
	Other	680	27	11	38	17	41	58	1,088	23	20	43
	Total:	22,679	809	740	1,550	623	812	1,435	22,190	1,350	1,056	2,406
2016 Updates	Cruise Center	11,882	452	634	1,087	175	201	377	11,906	789	527	1,316
	SPPM	5,798	34	16	50	289	218	507	6,285	370	267	637
	Crafted and Brewery West	586	31	0	31	49	48	97	632	58	45	103
	CityDock	2,935	318	66	384	60	283	343	997	77	35	112
	Other	680	27	11	38	16	41	58	1,088	23	21	44
	Total:	21,880	863	727	1,590	590	792	1,382	20,908	1,317	895	2,212

2

This updated traffic analysis also accounts for the Harbor Boulevard/SR-47 Eastbound Ramps and Front Street & SR-47 Westbound Ramp project currently being developed by the Port. Although not a mitigation measure, this project will offset some of the impacts of the SPW Project, and accommodate other growth in traffic. The project is illustrated below, and entails the following:

- Removal of the existing westbound (WB) SR-47/Vincent Thomas Bridge off-ramp (south of the Vincent Thomas Bridge) with Harbor Boulevard;
- Construction of new WB SR-47/Vincent Thomas Bridge off-ramp (north of the Vincent Thomas Bridge) with Front Street, including a new signal with Front Street (directly opposite West Basin Container Terminal Entrance); and
- Realignment of Knoll Drive (south) at the intersection with Front Street, and reversal of the one-way direction of Knoll Drive (inbound at southerly driveway and outbound at northerly driveway).



This project is presently in the preliminary engineering phase, with an environmental document expected to be approved by December 2017. Completion of the project is expected in the year 2022.

Table 4-6 summarizes the revised LOS results for the year 2040 (detailed Level of Service worksheets are included in Appendix A). As can be seen, the revised project description of the overall SPW Project results in fewer impacts, even under year 2040 conditions (as compared to the year 2037 conditions analyzed in the SPW Project EIS/EIR).

Mitigation measures required in 2015 under the SPW EIS/EIR were associated with the traffic impacts of the overall SPW Project, which was assumed to be completely built out in 2015 under the SPW Project EIS/EIR analysis. Because overall impacts of the SPW Project, including the modified SPPM Project, are less than disclosed in the SPW

1 EIS/EIR and because the majority of the SPW Project elements have not yet been
2 constructed, no operational traffic mitigation measures are required for operation of the
3 SPPM Project. LAHD will continue to monitor traffic conditions and mitigation
4 requirements at the intersections assessed in the SPW EIS/EIR as development of the
5 overall SPW Project progresses; however, that analysis is outside the scope of this
6 Addendum, which is solely focused on the SPPM Project. The SPPM Project would not
7 result in new significant impacts, substantially increase the severity of a previously
8 analyzed impact, or require new mitigation measures that have not already been
9 evaluated in the SPW Project EIS/EIR. Therefore, there is no substantial change from the
10 findings in the SPW Project EIS/EIR.

11

1 **Table 4-6. Intersection Level of Service Summary**

INT #	INTERSECTION	PEAK HOUR	FUTURE (NO PROJECT)		PROPOSED PROJECT				PROPOSED PROJECT WITH MITIGATION			
			(YEAR 2040)		(YEAR 2040)		V/C		(YEAR 2040)		V/C	
			V/C	LOS	V/C	LOS	Change	Impact	V/C	LOS	Change	Impact
5	Gaffey St & 9th St	AM	0.893	D	0.902	E	0.009	NO	0.902	E	0.009	NO
		PM	0.924	E	0.940	E	0.016	YES	0.891	D	-0.033	NO
		WKND	0.804	D	0.841	D	0.037	YES	0.841	D	0.037	YES
6	Gaffey St & 7th St	AM	0.876	D	0.885	D	0.009	NO	0.694	B	-0.182	NO
		PM	0.861	D	0.867	D	0.006	NO	0.662	B	-0.199	NO
		WKND	0.778	C	0.795	C	0.017	NO	0.795	C	0.017	NO
7	Gaffey St & 6th St ^[a]	AM	0.901	E	0.913	E	0.012	YES	0.475	A	-0.426	NO
		PM	0.818	D	0.823	D	0.005	NO	0.425	A	-0.394	NO
		WKND	0.765	C	0.783	C	0.018	NO	0.606	B	-0.159	NO
8	Gaffey St & 5th St	AM	1.081	F	1.092	F	0.011	YES	0.859	D	-0.222	NO
		PM	1.020	F	1.025	F	0.005	NO	0.835	D	-0.185	NO
		WKND	0.820	D	0.840	D	0.020	YES	0.840	D	0.020	YES
9	Gaffey St & 1st St	AM	1.294	F	1.301	F	0.007	NO				
		PM	1.092	F	1.099	F	0.007	NO				
		WKND	1.072	F	1.092	F	0.020	YES				
11	Gaffey St & Summerland Ave	AM	0.932	E	0.935	E	0.004	NO				
		PM	1.005	F	1.008	F	0.004	NO				
		WKND	0.654	B	0.667	B	0.013	NO				
12	Pacific Ave & 22nd St	AM	0.617	B	0.666	B	0.049	NO				
		PM	0.517	A	0.570	A	0.053	NO				
		WKND	0.448	A	0.507	A	0.059	NO				
13	Pacific Ave & 9th St	AM	0.882	D	0.883	D	0.001	NO				
		PM	0.876	D	0.879	D	0.003	NO				
		WKND	0.668	B	0.685	B	0.017	NO				
14	Pacific Ave & 7th St	AM	0.859	D	0.861	D	0.002	NO				
		PM	0.844	D	0.853	D	0.009	NO				
		WKND	0.677	B	0.694	B	0.017	NO				
15	Pacific Ave & 6th St	AM	0.943	E	0.945	E	0.002	NO				
		PM	0.808	D	0.811	D	0.003	NO				
		WKND	0.707	C	0.716	C	0.009	NO				
16	Pacific Ave & 5th St	AM	0.959	E	0.960	E	0.001	NO				
		PM	0.745	C	0.747	C	0.001	NO				
		WKND	0.637	B	0.639	B	0.003	NO				
17	Pacific Ave & 1st St	AM	0.838	D	0.839	D	0.001	NO				
		PM	0.727	C	0.732	C	0.005	NO				
		WKND	0.617	B	0.626	B	0.009	NO				
20	Miner St & 22nd St	AM	0.401	A	0.693	B	0.292	NO				
		PM	0.411	A	0.490	A	0.079	NO				
		WKND	0.314	A	0.541	A	0.228	NO				
21	Miner St & Crescent Ave ^[a]	AM	0.440	A	0.658	B	0.218	NO				
		PM	0.435	A	0.528	A	0.093	NO				
		WKND	0.262	A	0.534	A	0.273	NO				

INT #	INTERSECTION	PEAK HOUR	FUTURE (NO PROJECT)		PROPOSED PROJECT				PROPOSED PROJECT WITH MITIGATION			
			(YEAR 2040)		(YEAR 2040)		V/C		(YEAR 2040)		V/C	
			V/C	LOS	V/C	LOS	Change	Impact	V/C	LOS	Change	Impact
22	Harbor Bl & 7th St	AM	0.372	A	0.595	A	0.223	NO	0.454	A	0.082	NO
		PM	0.427	A	0.687	B	0.260	NO	0.687	B	0.260	NO
		WKND	0.262	A	0.882	D	0.620	YES	0.882	D	0.620	YES
23	Harbor Bl & 6th St	AM	0.463	A	0.637	B	0.174	NO	0.406	A	-0.057	NO
		PM	0.498	A	0.677	B	0.179	NO	0.433	A	-0.065	NO
		WKND	0.772	C	1.012	F	0.240	YES	0.730	C	-0.042	NO
24	Harbor Bl & 5th St	AM	0.532	A	0.745	C	0.213	YES	0.515	A	-0.017	NO
		PM	0.807	D	0.968	E	0.161	YES	0.706	C	-0.101	NO
		WKND	0.515	A	0.843	D	0.328	YES	0.560	A	0.045	NO
25	Harbor Bl & 1st St	AM	0.799	C	1.041	F	0.242	YES	0.770	C	-0.029	NO
		PM	0.667	B	0.845	D	0.179	YES	0.575	A	-0.092	NO
		WKND	0.581	A	0.922	E	0.341	YES	0.618	B	0.037	NO
26	Harbor Bl & Swinford St / SR-47 EB Ramps	AM	0.434	A	0.659	B	0.225	NO	0.659	B	0.225	NO
		PM	0.506	A	0.617	B	0.111	NO	0.617	B	0.111	NO
		WKND	0.455	A	0.680	B	0.225	NO	0.680	B	0.225	NO
27	Harbor Bl & SR-47 WB On Ramp	AM	0.610	B	0.797	C	0.187	YES	0.797	C	0.187	YES
		PM	0.464	A	0.608	B	0.144	NO	0.608	B	0.144	NO
		WKND	0.357	A	0.538	A	0.181	NO	0.538	A	0.181	NO
29	Harbor Bl & O'Farrell St	AM	0.618	B	0.841	D	0.223	YES	0.558	A	-0.060	NO
		PM	0.903	E	1.057	F	0.155	YES	0.705	C	-0.198	NO
		WKND	0.637	B	0.997	E	0.361	YES	0.658	B	0.021	NO
30	Harbor Bl & 3rd St ^[a]	AM	0.581	A	0.842	D	0.261	YES	0.566	A	-0.015	NO
		PM	0.674	B	0.882	D	0.208	YES	0.583	A	-0.091	NO
		WKND	0.562	A	1.034	F	0.473	YES	0.690	B	0.128	NO
31	Pacific Av & 13th St	AM	0.776	C	0.789	C	0.013	NO				
		PM	0.655	B	0.667	B	0.012	NO				
		WKND	0.556	A	0.571	A	0.015	NO				
32	Pacific Av & 17th St	AM	0.609	B	0.614	B	0.005	NO				
		PM	0.548	A	0.559	A	0.011	NO				
		WKND	0.449	A	0.460	A	0.011	NO				
33	Pacific Av & 19th St	AM	0.395	A	0.400	A	0.005	NO				
		PM	0.515	A	0.525	A	0.009	NO				
		WKND	0.373	A	0.384	A	0.011	NO				
34	Gaffey St & 13th St	AM	0.975	E	0.986	E	0.011	YES	0.946	E	-0.029	NO
		PM	0.721	C	0.728	C	0.007	NO	0.705	C	-0.016	NO
		WKND	0.656	B	0.669	B	0.013	NO	0.628	B	-0.028	NO

Notes:

All signalized intersections assumed to operate under Automated Traffic Surveillance and Control (ATSAC)/Adaptive Traffic Control System (ATCS) system in the future.

^[a] Intersection is two-way stop-controlled.

City of Los Angeles Significant Project Impact Criteria:

If LOS C, must be ≥ 0.04

If LOS D, must be ≥ 0.02

If LOS E or F, must be ≥ 0.01

1 The initial phase of the SPPM Project would include up to 1,909 surface parking spaces
 2 at parking ratios consistent with or in excess of those in the SPW Project EIS/EIR. Phase
 3 1 would include the development of 1,239 parking spaces east of the realigned Sampson
 4 Way, and the remaining 670 surface parking spaces would be constructed in the bluff
 5 area west of the realigned Sampson Way. The number of spaces in the parking structure
 6 during Phase 2 would be determined according to the specific land use mix determined
 7 by market demand, and consistent with the parking ratios in the SPW Project EIS/EIR.
 8 Table 4-7 summarizes the parking provided relative to the requirements of the Los
 9 Angeles Municipal Code. As shown in the table, ample parking spaces in excess of code
 10 requirements are being provided onsite to accommodate parking demand for the SPPM
 11 Project. The SPPM Project would not result in new significant impacts, substantially
 12 increase the severity of a previously analyzed impact, or require new mitigation measures
 13 that have not already been evaluated in the SPW Project EIS/EIR. Therefore, there is no
 14 substantial change from the findings in the SPW Project EIS/EIR.

15 **Table 4-7. Code-Required Auto Parking Spaces – SPPM Project (Phase I)**

Project Component	Size	Code Requirement ^[a]		Provided ^[c]
		Ratio	Spaces	
Restaurants	125,000 sq. ft.	1/500 ^[a]	250	
Retail	145,000 sq. ft.	1/500 ^[a]	290	
Port offices	30,000 sq. ft.	1/500 ^[a]	60	
Discovery Park	500 seats	at 1/5 seats ^[b]	100	
Discovery Park	6 acres	none ^[a]	0	
<i>San Pedro Public Market Total</i>			700	
LA Maritime Museum	27,734 sq. ft.	1/500	55	
Ralph J. Scott Fireboat Museum	10,000 sq. ft.	1/500	20	
Subtotal Museums			75	
<i>San Pedro Public Market Total plus Museums</i>			775	
Notes:				
^[a] Los Angeles Municipal Code Section 12.21.A.4.x.3 requires 1 space per 500 square feet of development for this use, as the project site lies within a designated State Enterprise Zone (ZI-2130 Harbor Gateway State Enterprise Zone, confirmed through ZIMAS on 4/14/16).				
^[b] Los Angeles Municipal Code Section 12.21.A.4.				
^[c] The intent of the SPPM Project is that the 1,905 parking spaces adjacent to Ports O'Call will serve these uses. Proposed parking supply includes 1,235 spaces east of Sampson Way and approximately 670 spaces west of Sampson Way as part of Phase 1. The number of spaces in the parking structure during Phase 2 would be determined according to the specific land use mix determined by market demand, and consistent with the parking ratios in the SPW Project EIS/EIR.				

16

17 **4.11.1.3 Mitigation Measures Applicable to the SPPM Project**

18 **MM TC-1: Develop and implement a Traffic Control Plan throughout proposed**
 19 **project construction.** In accordance with the City's policy on street closures and traffic
 20 diversion for arterial and collector roadways, the construction contractor will prepare a
 21 traffic control plan (to be approved by the city and county engineers) before construction.
 22 The traffic control plan will include:

- 23 ■ a street layout showing the location of construction activity and surrounding
- 24 streets to be used as detour routes, including special signage;
- 25 ■ a tentative start date and construction duration period for each phase of
- 26 construction;

- 1 ▪ the name, address, and emergency contact number for those responsible for
2 maintaining the traffic control devices during the course of construction; and
3 ▪ written approval to implement traffic control from other agencies, as needed.

4 Additionally, the traffic control plan will include the following stipulations.

- 5 ▪ Provide access for emergency vehicles at all times.
6 ▪ Avoid creating additional delay at intersections currently operating at congested
7 conditions, either by choosing routes that avoid these locations, or constructing
8 during nonpeak times of day.
9 ▪ Maintain access for driveways and private roads, except for brief periods of
10 construction, in which case property owners will be notified.
11 ▪ Provide adequate off-street parking areas at designated staging areas for
12 construction-related vehicles.
13 ▪ Maintain pedestrian and bicycle access and circulation during proposed project
14 construction where safe to do so. If construction encroaches on a sidewalk, a safe
15 detour will be provided for pedestrians at the nearest crosswalk. If construction
16 encroaches on a bike lane, warning signs will be posted that indicate bicycles and
17 vehicles are sharing the roadway.
18 ▪ Traffic controls may include flag persons wearing Occupational Safety and
19 Health Administration–approved vests and using a “Stop/Slow” paddle to warn
20 motorists of construction activity.
21 ▪ Maintain access to Metro, LADOT, MAX, PVPTA, and LAHD transit services
22 and ensure that public transit vehicles are detoured.
23 ▪ Post standard construction warning signs in advance of the construction area and
24 at any intersection that provides access to the construction area.
25 ▪ Construction warning signs will be posted, in accordance with local standards or
26 those set forth in the Manual on Uniform Traffic Control Devices (Federal
27 Highway Administration 2001) in advance of the construction area and at any
28 intersection that provides access to the construction area.
29 ▪ During lane closures, notify LAFD and LAPD, as well as the Los Angeles
30 County Sheriff’s and Fire Departments, of construction locations to ensure that
31 alternative evacuation and emergency routes are designed to maintain response
32 times during construction periods, if necessary.
33 ▪ Provide written notification to contractors regarding appropriate routes to and
34 from construction sites, and weight and speed limits for local roads used to
35 access construction sites. Submit a copy of all such written notifications to the
36 City of Los Angeles Planning Department.
37 ▪ Repair or restore the road right-of-way to its original condition or better upon
38 completion of the work.

39 Mitigation measures are not expected to be required for the first or second phases of the
40 SPPM Project given the following:

- 41 ▪ The amount of traffic estimated to be generated by the first phase of the SPPM

- 1 ▪ Previously projected year 2015 good (LOC C or better) traffic conditions without
- 2 the proposed SPW Project, as contained in the SPW Project EIS/EIR
- 3 ▪ Updated year 2015 and future year 2040 LOS at the SR-47 interchange
- 4 intersections
- 5 ▪ Updated year 2014 LOS at the intersections of Harbor Boulevard with 6th and
- 6 7th Streets
- 7 ▪ The amount of activity and corresponding traffic growth as projected in the first
- 8 phase of the overall SPW Project program by 2015 has not come to fruition:
- 9
 - The outer harbor cruise facility/calls has not occurred.
 - 10 ▪ The City Dock EIR determined that no mitigation measures would be needed
 - 11 under year 2016, 2024, and year 2042 conditions.
 - 12 ▪ The City Dock EIR determined that no mitigation measures would be needed
 - 13 under year 2024 conditions.- 14 ▪ The incremental amount of traffic expected to be generated with the proposed
- 15 second phase (see Table 4-4); about 62.5% of the SPPM Project trips are
- 16 projected to be generated in the first phase.

17 **4.12 Transportation and Navigation (Marine)**

18 **4.12.1.1 Summary of San Pedro Waterfront EIS/EIR Findings**

19 The SPW Project EIS/EIR identified a potential increase in marine navigation hazards
20 during construction of the waterfront promenade along the Ports O'Call site.
21 Approximately 25 vessels were proposed to remove existing wharf decks and floating
22 docks, install new piles, and construct new wharf structures and floating docks.
23 Additionally, replacement of the existing wood bulkhead with a new sheet pile bulkhead
24 (approximately 150 linear feet) at Berth 78 would require marine-side construction
25 vessels. Several of the SPW Project elements would provide new facilities to
26 accommodate vessel traffic. Relocation of some facilities associated with the SPW
27 Project would not be expected to generate additional vessel demand but would change the
28 travel patterns of vessels that utilize them. Relocation of the existing recreational boat
29 slips at Ports O'Call would also result in some changes to vessel transportation patterns.
30 Additional marine vessels may be required for the removal of tanks and other facilities,
31 as well as site remediation, at the Jankovich fueling station. With adherence to standard
32 safety precautions, impacts would be less than significant and no mitigation was required.

33 **4.12.1.2 Impacts of SPPM Project**

34 Construction activities associated with the SPPM Project would be substantially similar
35 to those analyzed in the SPW Project EIS/EIR related to removal/replacement and/or
36 renovation of existing wharf decks and floating dock, and installation of new piles.
37 However, overall impacts may be reduced because construction of the waterfront
38 promenade would now be primarily on land rather than partially over water.
39 Operationally, the SPPM Project would include vessel activity associated with harbor
40 cruises and dinner cruises, charter fishing boats, water taxis, and transient harbor craft
41 visiting the site. This would be similar to existing operations at the Ports O'Call area and

1 would not result in new vessel transportation impacts. Relocation of the existing
2 recreational boat slips is occurring separately from the SPPM Project. The SPPM Project
3 would not result in new significant impacts, substantially increase the severity of a
4 previously analyzed impact, or require new mitigation measures that have not already
5 been evaluated in the SPW Project EIS/EIR. Therefore, there is no substantial change
6 from the findings in the SPW Project EIS/EIR.

7 **4.12.1.3 Mitigation Measures Applicable to the SPPM Project**

8 No mitigation measures are required.

9 **4.13 Utilities and Public Services**

10 **4.13.1.1 Summary of San Pedro Waterfront EIS/EIR Findings**

11 The SPW Project EIS/EIR did not identify any significant and unavoidable impacts
12 related to utilities or public services. Existing public services and utility infrastructure
13 and supplies were determined to be adequate to serve the entire project. Buildout of the
14 SPW Project would not increase the demand for additional law enforcement officers
15 and/or facilities such that the United States Coast Guard, Los Angeles Police Department,
16 or Port Police would not be able to maintain an adequate level of service without
17 additional facilities, nor would the SPW Project result in an increased demand for
18 personnel or equipment for the Los Angeles Fire Department in order to maintain
19 adequate fire protection services. However, project construction could have temporary
20 impacts on emergency access to portions of the proposed project area, which would be a
21 significant impact that would be mitigated to less-than-significant levels.

22 No major utility improvements or installations would be required to accommodate the
23 SPW Project. The SPW Project would not generate significant increases in water or
24 wastewater demand. While some utility upgrades or relocations may be required as part
25 of the Ports O'Call development, these improvements would occur within the existing
26 rights-of-way and would comply with the City's municipal code, and would be
27 performed under permit by the City Bureau of Engineering and/or LADWP.

28 Construction of the SPW Project may generate a substantial contribution to the solid
29 waste stream, possibly contributing to the exceedance of solid waste facility capacities,
30 which would result in a significant impact. In addition, construction and operation of the
31 SPW Project would increase demands for energy consumption, which could result in
32 significant impacts. Mitigation measures would reduce all impacts related to public
33 services and utilities to less-than-significant levels.

34 **4.13.1.2 Impacts of SPPM Project**

35 Demolition and construction activities under the SPPM Project would be substantially the
36 same as those identified in the SPW Project EIS/EIR and a similar amount of
37 construction waste would be generated. In addition, construction and operation of the
38 SPPM Project would result in similar demands on utilities and public services as those
39 identified in the SPW Project EIS/EIR. Therefore, no changes to the determinations of
40 the SPW Project EIS/EIR would occur and impacts would be less than significant with
41 implementation of mitigation measures that would require coordination with law

1 enforcement agencies during construction activities, recycling of construction materials,
2 and water/wastewater and energy conservation. The SPPM Project would not result in
3 new significant impacts, substantially increase the severity of a previously analyzed
4 impact, or require new mitigation measures that have not already been evaluated in the
5 SPW Project EIS/EIR. Therefore, there is no substantial change from the findings in the
6 SPW Project EIS/EIR.

7 **4.13.1.3 Mitigation Measures Applicable to the SPPM Project**

8 **MM PS-1. Coordinate with law enforcement agencies.** LAHD will be required,
9 pursuant to the Watch Manual, to coordinate with law enforcement agencies, during
10 construction of all roadway improvements, to establish emergency vehicular access and
11 ensure continuous law enforcement access to surrounding areas.

12 **MM PS-2: Recycle construction materials.** Demolition and/or excess construction
13 materials will be separated on site for reuse/recycling or proper disposal. During grading
14 and construction, separate bins for recycling of construction materials will be provided on
15 site.

16 **MM PS-3: Use materials with recycled content.** Materials with recycled content, such
17 as recycled steel from framing and recycled concrete and asphalt from roadway
18 construction, will be used in project construction. Wood chippers registered through
19 CARB's Portable Equipment Registration Program will be used on site during
20 construction. Wood from tree removal, not from demolished structures, will be reused as
21 landscape cover, further reducing the quantity of wood that would otherwise be disposed
22 of at solid waste facilities.

23 **MM PS-4: Comply with Assembly Bill (AB) 939.** LAHD and Port tenants will
24 implement a Solid Waste Management Program including the following measures to
25 achieve a 50% reduction of current waste generation percentages by 2037 and ensure
26 compliance with the California Solid Waste Management Act (AB 939).

- 27 a. Provide space and/or bins for storage of recyclable materials on the project site. All
28 garbage and recycle bin storage space will be enclosed and plans will show equal
29 area availability for both garbage and recycle bins in storage spaces.
- 30 b. Establish a recyclable material pick-up area for commercial buildings.
- 31 c. Participate in a curbside recycling program to serve the new development.
- 32 d. Develop a plan for accessible collection of materials on a regular basis.
- 33 e. Develop source reduction measures that indicate the method and amount of expected
34 reduction.
- 35 f. Implement a program to purchase materials that have recycled content for project
36 construction and operation (e.g., lumber, plastic, office supplies).
- 37 g. Provide a resident-tenant/employee education pamphlet to be used in conjunction
38 with available Los Angeles County and federal source reduction educational
39 materials. The pamphlet will be provided to all commercial tenants by the
40 leasing/property management agency.

- 1 h. Include lease language requiring tenant participation in recycling/waste reduction
2 programs, including specification that janitorial contracts support recycling.

3 **MM PS-5: Water Conservation and Wastewater Reduction.** LAHD and Port tenants
4 will implement the following water conservation and wastewater reduction measures to
5 further reduce impacts on water demand and wastewater flows.

- 6 a. The landscape irrigation system will be designed, installed, and tested to provide
7 uniform irrigation coverage for each zone. Sprinkler head patterns will be adjusted to
8 minimize overspray onto walkways and streets. Each zone (sprinkler valve) will
9 water plants having similar watering needs (i.e., shrubs, flowers, and turf will not be
10 in the same watering zone). Automatic irrigation timers will be set to water
11 landscaping during early morning or late evening hours to reduce water losses from
12 evaporation. Irrigation run times will be adjusted for all zones seasonally, reducing
13 length and frequency of waterings in the cooler months (i.e., fall, winter, spring).
14 Adjust sprinkler timer run time to avoid water runoff, especially when irrigating
15 sloped property. Sprinkler times will be reduced once drought-tolerant plants have
16 been established.
- 17 b. Drought-tolerant, low-water consuming plant varieties will be used to reduce
18 irrigation water consumption.
- 19 c. Recycled water will be used for irrigation and toilet flushing (dual-flushing).
- 20 d. Ultra-low-flush toilets, ultra-low-flush urinals, and water-saving showerheads must
21 be installed in both new construction and when remodeling. Low-flow faucet aerators
22 will be installed on all sink faucets.
- 23 e. Significant opportunities for water savings exist in air conditioning systems that
24 utilize evaporative cooling (i.e., employ cooling towers). LADWP will be contacted
25 for specific information of appropriate measures.
- 26 f. Recirculating or point-of-use hot water systems will be installed to reduce water
27 waste in long piping systems where water must be run for a considerable period
28 before heated water reaches the outlet.

29 **MM PS-6: Employ energy conservation measures.** During the design process, LAHD
30 will consult with LADWP's Efficiency Solutions Business Group regarding possible
31 energy efficiency measures. LAHD and its tenants will incorporate measures to meet or,
32 if possible, exceed minimum efficiency standards for Title XXIV of the California Code
33 of Regulations, such as:

- 34 a. Built-in appliances, refrigerators, and space-conditioning equipment will exceed the
35 minimum efficiency levels mandated in the California Code of Regulations.
- 36 b. High-efficiency air conditioning will be installed that is controlled by a computerized
37 energy-management system in office and retail spaces and provides the following:
- 38 ▪ a variable air-volume system that results in minimum energy consumption and
39 avoids hot water energy consumption for terminal reheat,

- 1 ▪ a 100% outdoor air-economizer cycle to obtain free cooling in appropriate
2 climate zones during dry climatic periods,
- 3 ▪ sequentially staged operation of air-conditioning equipment in accordance with
4 building demands,
- 5 ▪ the isolation of air conditioning to any selected floor or floors, and
- 6 ▪ considers the applicability of the use of thermal energy storage to handle cooling
7 loads.
- 8 c. Ventilation air will be cascaded from high-priority areas before being exhausted,
9 thereby decreasing the volume of ventilation air required. For example, air could be
10 cascaded from occupied space to corridors and then to mechanical spaces before
11 being exhausted.
- 12 d. Lighting system heat will be recycled for space heating during cool weather, while
13 exhaust lighting-system heat will be recycled from the buildings, via ceiling plenums,
14 to reduce cooling loads in warm weather.
- 15 e. Low and medium static-pressure terminal units will be installed, as well as ductwork
16 to reduce energy consumption by air-distribution systems.
- 17 f. Buildings must be well sealed to prevent outside air from infiltrating and increasing
18 interior space-conditioning loads. Where applicable, design building entrances with
19 vestibules to restrict infiltration of unconditioned air and exhausting of conditioned
20 air.
- 21 g. A performance check of the installed space-conditioning system will be completed by
22 the developer/installer prior to issuance of the certificate of occupancy to ensure that
23 energy-efficiency measures incorporated into the proposed project operate as
24 designed.
- 25 h. Exterior walls will be finished with light-colored materials and high-emissivity
26 characteristics to reduce cooling loads. Interior walls will be finished with light-
27 colored materials to reflect more light, and thus increase light efficiency.
- 28 i. White reflective material will be used for roofing meeting California standards for
29 reflectivity and emissivity to reject heat.
- 30 j. Thermal insulation that exceeds requirements established by the California Code of
31 Regulations will be installed in walls and ceilings.
- 32 k. Window systems will be designed to reduce thermal gain and loss, thus reducing
33 cooling loads during warm weather and heating loads during cool weather.
- 34 l. Heat-rejecting window treatments will be installed, such as films, blinds, draperies,
35 or others on appropriate exposures.
- 36 m. Fluorescent and high-intensity discharge lamps that give the highest light output per
37 watt of electricity consumed will be installed wherever possible, including all street
38 and parking lot lighting, to reduce electricity consumption. Reflectors will be used to
39 direct maximum levels of light to work surfaces.

- 1 n. Photosensitive controls and dimmable electronic ballasts will be installed to
2 maximize the use of natural daylight available and reduce artificial lighting load.
- 3 o. Occupant-controlled light switches and thermostats to permit individual adjustment
4 of lighting, heating, and cooling will be installed to avoid unnecessary energy
5 consumption.
- 6 p. Time-controlled interior and exterior public area light will be installed, limited to that
7 which is necessary for safety and security.
- 8 q. Mechanical systems (HVAC and lighting) in the building will be controlled with
9 timing systems to prevent accidental or inappropriate conditioning or lighting of
10 unoccupied space.
- 11 r. Windowless walls or passive solar inset of windows will be incorporated, where
12 feasible, in building design.
- 13 s. Project will focus pedestrian activity within sheltered outdoor areas.

14 **4.14 Water Quality, Sediment and** 15 **Oceanography**

16 **4.14.1.1 Summary of San Pedro Waterfront EIS/EIR Findings**

17 The SPW Project EIS/EIR determined there would be no significant and unavoidable
18 impacts on water quality, sediment, and oceanography related to redevelopment of the
19 Ports O'Call area. The impacts associated with removal of existing water-side structures
20 and piles and installation of new piles, bulkheads, and floating docks would disturb
21 sediments and result in localized impacts on water quality, such as turbidity. However,
22 sediment testing results (presented in Section 3.14.2.1.3 of the SPW Project EIS/EIR)
23 indicate that such disturbance of sediments in the project area would not cause significant
24 toxicity, contaminant bioaccumulation, or releases of contaminants to surface waters. In
25 addition, in compliance with LAHD's BMPs for in-water work, implementation of
26 minimization measures would minimize turbidity and sediment resuspension during
27 construction. Examples of such measures include using silt curtains to confine turbidity
28 within the work area and working at slack tide to minimize the potential for sediment
29 transport away from the work area.

30 Construction activities associated with upland improvements for the SPW Project have
31 the potential to adversely affect the quality of stormwater runoff. However, compliance
32 with the statewide General Permit for Storm Water Discharges Associated with
33 Construction and Land Disturbance Activities would be required. This would include
34 implementation of a Stormwater Pollution Prevention Plan (SWPPP) and incorporation of
35 BMPs, such as sediment basins or traps and fabric filter fences or straw bale barriers, to
36 control runoff of eroded soils and pollutants. The SWPPP would also incorporate
37 monitoring requirements intended to minimize potential impacts and verify BMP
38 effectiveness. These measures, combined with the low potential for erosion and the
39 remediation of sites prior to construction, would limit the soil and contaminant loading to
40 Los Angeles Harbor. Other construction impacts would be minimized through

1 implementation of BMPs. While accidental spills from vessels are possible, spill
2 prevention and cleanup procedures for the SPW Project would be addressed in a SWPPP
3 that would be implemented by the construction contractor. The plan would define actions
4 to minimize the potential for spills and provide efficient responses to spill events to
5 minimize the magnitude of the spill and extent of impacts. Therefore, accidental spills of
6 pollutants would cause less-than-significant impacts under CEQA.

7 Based on the analysis in the SPW Project EIS/EIR, compliance with existing regulations,
8 including implementation of a SWPPP and LAHD BMPs, the SPW Project would result
9 in less-than-significant impacts on water quality, sediment, and oceanography, and no
10 mitigation measures were required.

11 **4.14.1.2 Impacts of SPPM Project**

12 The SPPM Project would involve the removal and/or renovation and reuse of existing
13 water-side structures and piles, and the installation of new piles, wharfs, and floating
14 docks as analyzed in the SPW Project EIS/EIR. The SPPM Project would install or
15 rehabilitate and reuse up to 73,200 square feet of wharf and floating dock area—less than
16 the 83,700 square feet of wharf and floating dock. The SPPM Project would also include
17 451 piles or fewer, as analyzed in the SPW Project EIS/EIR. While impacts of the SPPM
18 Project would likely be reduced compared to those analyzed in the SPW Project EIS/EIR,
19 the SPPM Project would still result in localized impacts on water quality from temporary
20 turbidity and sediment suspension. The SPPM Project would be required to conduct
21 sediment testing in areas where jetting is used to drive new piles and implement
22 additional BMPs, including use of silt curtains around the pile driving operation if jetting
23 is used to ensure that the impacts would be less than significant. Applicable testing, and
24 permits, would need to be obtained prior to the start of in-water construction activities.
25 The project would be subject to existing regulations requiring the implementation of a
26 SWPPP and LAHD BMPs for in-water work, which would ensure that impacts related to
27 the SPPM Project would remain less than significant, consistent with the findings of the
28 SPW Project EIS/EIR. The SPPM Project would not result in new significant impacts,
29 substantially increase the severity of a previously analyzed impact, or require new
30 mitigation measures that have not already been evaluated in the SPW Project EIS/EIR.
31 Therefore, there is no substantial change from the findings in the SPW Project EIS/EIR.

32 **4.14.1.3 Mitigation Measures Applicable to the SPPM Project**

33 No mitigation measures are required.

34 **4.15 Environmental Justice**

35 **4.15.1.1 Summary of San Pedro Waterfront EIS/EIR Findings**

36 The SPW Project EIS/EIR determined the SPW Project would result in
37 disproportionately high and adverse effects on minority and low-income populations
38 from:

- 39 ▪ exceedance of significance thresholds of air pollutant emissions during
40 construction and operation of the SPW Project;
- 41 ▪ exposure to toxic air contaminants (TACs);

- 1 ▪ exceedance of noise standards during construction;
- 2 ▪ a permanent increase in ambient noise levels due to vehicular traffic;
- 3 ▪ the temporary diminished quality of recreational resources; and
- 4 ▪ increased traffic volumes that would degrade levels of service along roadway
- 5 segments and at intersections within the project vicinity.

6 **4.15.1.2 Impacts of SPPM Project**

7 The SPPM Project would result in similar contribution to the overall SPW Project
8 construction-related air quality impacts, construction and operational (due to increased
9 vehicular traffic) noise impacts, temporary diminished quality of recreational resources
10 (due to construction noise and temporary obstruction of resources), and degradation of
11 levels of service along roadway segments in the project vicinity as analyzed for the Ports
12 O’Call site in the SPW Project EIS/EIR. Exposure of sensitive receptors to TACs is
13 largely associated with operation of the cruise terminals and, therefore, the SPPM Project
14 would not result in a substantial contribution to impacts related to TACs. However, the
15 SPPM Project would contribute to other impacts identified above and, therefore,
16 implementation of the SPPM Project would result in disproportionately high and adverse
17 impacts on minority and low-income populations. The SPPM Project would not result in
18 new significant impacts, substantially increase the severity of a previously analyzed
19 impact, or require new mitigation measures that have not already been evaluated in the
20 SPW Project EIS/EIR. Therefore, there is no substantial change from the findings in the
21 SPW Project EIS/EIR.

22 **4.15.1.3 Mitigation Measures Applicable to the SPPM Project**

23 The following mitigation measures are required to reduce environmental justice impacts.

- 24 ▪ MM AQ-1 and MM AQ-3 through MM AQ-8
- 25 ▪ MM NOI-1 and MM NOI-2
- 26 ▪ MM REC-1 through MM REC-4, and MM REC-6 through MM REC-7

27 **4.16 Socioeconomics and Environmental**

28 **Quality**

29 **4.16.1.1 Summary of San Pedro Waterfront EIS/EIR Findings**

30 The SPW Project EIS/EIR determined there would be no significant and unavoidable
31 impacts on socioeconomics related to implementation of the SPW Project, including
32 redevelopment of the Ports O’Call project area. The SPW Project would not displace
33 substantial numbers of people or existing housing and would not require the construction
34 of new housing elsewhere, nor would the SPW Project adversely affect local property
35 values. Redevelopment of the Ports O’Call site was determined to result in the expiration
36 of existing leaseholds and, thus, the displacement of existing businesses, but this impact
37 would be less than significant. Furthermore, the SPW Project would result in a beneficial
38 impact related to local business revenue and would increase employment in the project
39 area from construction and operational activities.

4.16.1.2 Impacts of SPPM Project

Implementation of the SPPM Project would result in similar socioeconomic impacts identified in the SPW Project EIS/EIR, including no displacement of existing people or housing. As noted above, the SPPM Project would result in the retention of some of the existing leaseholds as well as the expiration of some of the existing leaseholds and, therefore, would result in the displacement of some existing businesses. The SPPM Project is expected to result in beneficial impacts on local business revenue and employment. Overall, socioeconomic impacts related to development of the SPPM Project would be less than significant. The SPPM Project would not result in new significant impacts, substantially increase the severity of a previously analyzed impact, or require new mitigation measures that have not already been evaluated in the SPW Project EIS/EIR. Therefore, there is no substantial change from the findings in the SPW Project EIS/EIR.

4.16.1.3 Mitigation Measures Applicable to the SPPM Project

No mitigation measures are required.

4.17 Growth Inducement

4.17.1.1 Summary of San Pedro Waterfront EIS/EIR Findings

The SPW Project EIS/EIR determined while the project would not introduce new housing, it could have direct and indirect growth-inducing effects through transportation system improvements and new investment in surrounding communities based on the new amenities the SPW Project would bring to the area. In addition, while the SPW Project would introduce new employment opportunities, it was determined that the majority of new employees would come from the diverse worker population already residing within Southern California and would not require a substantial influx of new residents into the area to fill new jobs. As such, the SPW Project would not adversely affect the existing housing stock in the surrounding area. The other impacts of growth, such as those related to air quality, traffic congestion, increases in noise, and increased public services and utility consumption, were addressed throughout the SPW Project EIS/EIR.

4.17.1.2 Impacts of SPPM Project

The SPPM Project would not contribute to the direct or indirect population growth that would occur under the overall SPW Project because it would not involve the development of transportation system improvements. While the SPPM project would result in new jobs, it is anticipated that new employees at the project site would come from the existing worker population in Southern California, and the SPPM Project would not require a large influx of new employees moving into the region.

4.17.1.3 Mitigation Measures Applicable to the SPPM Project

Mitigation measures for significant impacts associated with growth-inducement are identified under the appropriate resource discussions of this Addendum where growth-related impacts would occur.

4.18 Cumulative Analysis

4.18.1 Introduction

This section presents information and analysis of the potential cumulative environmental impacts, if any, of the proposed modifications to the previous project design analyzed in the SPW Project EIS/EIR for the Ports O'Call area with the SPPM Project. The SPPM Project's cumulative effects were largely covered and analyzed in the SPW Project EIS/EIR, which identified redevelopment of Ports O'Call as a project element. The analysis contained within this section addresses the changes to cumulative impacts identified in the SPW Project EIS/EIR that could potentially occur as a result of the SPPM Project.

4.18.2 Summary of SPW EIS/EIR Findings

The SPW Project EIS/EIR includes a comprehensive list of related and cumulative projects (Table 4-1 and Figure 4-1 of the SPW Project EIS/EIR), in which the cumulative contribution of the SPW Project was considered. Resource areas where the SPW Project was determined to contribute to a cumulatively considerable adverse effect included:

- aesthetics (nighttime lighting),
- air quality (construction emissions),
- biological resources (pile driving and mudflat habitat),
- cultural resources (archaeological resources),
- geology (fault rupture, ground-shaking, liquefaction, or other seismically induced ground failure, and tsunami risks),
- noise (construction noise),
- recreation (construction),
- transportation and circulation (ground), and
- water quality, sediments, and oceanography (stormwater runoff).

4.18.3 Impacts of the SPPM Project

The modifications proposed by the SPPM Project are minor. The project would be in the same general location, with the exception of a small portion of the Town Square area, which is now within the SPPM Project boundaries, and would develop similar uses. In addition, the construction equipment and duration of the proposed SPPM Project would be equal to or less than the original project analyzed in the SPW Project EIS/EIR. The following changes have occurred within or in the vicinity of the SPW Project area since approval of the SPW Project EIS/EIR, which include components of the SPW Project, as well as additional elements not previously considered. These have been noted and addressed throughout this Addendum where appropriate.

- U.S.S. Iowa: Located at First Street and Harbor Boulevard at Berth 87, the U.S.S. Iowa is a new museum feature to the San Pedro Waterfront area.

- 1 ▪ AltaSea Marine Research Center: In 2012, the City Dock No. 1 Marine Search
2 Center Project EIR was certified. The project has not been constructed, and
3 planning and design of the AltaSea facility is ongoing and will be assessed in a
4 separate environmental analysis.
- 5 ▪ Downtown Harbor: Located along Harbor Boulevard and 5th and 6th Streets, this
6 1.2-acre water cut feature of the SPW Project was completed in 2014 and
7 includes more open space, widening of the promenades, and improvement of the
8 physical and visual connectivity with downtown San Pedro.
- 9 ▪ Crafted Marketplace & Brouwerij West: Reuse of Warehouses Nos. 9 and 10 was
10 envisioned in the SPW Project EIS/EIR to be adapted for low-intensity, visitor-
11 serving commercial or educational uses. Warehouse No. 9 has been adaptively
12 reused and is now the location of Brouwerij West, and Warehouse No. 10 has
13 been restored and is the location of Crafted, a new large-scale permanent craft
14 marketplace hosting more than 100 shop spaces for artists, crafters, and food
15 vendors.
- 16 ▪ Redesign of Sampson Way/7th Street Intersection: Redesign of the Sampson
17 Way and 7th Street intersection was previously analyzed in the SPW Project
18 EIS/EIR and included an enhanced four-way intersection with a modification of
19 the 6th Street connection to Sampson Way, eliminating access to Sampson Way
20 from Harbor Boulevard via 6th Street. The modification would have resulted in
21 two through lanes in each direction on Sampson Way and two through lanes in
22 each direction on Harbor Boulevard. In June 2015, the Port prepared an
23 addendum to the SPW Project EIS/EIR that would shift the intersection farther
24 south of 7th Street, improve vehicular access to and along the waterfront, and
25 provide additional pedestrian access. The project would also improve safety for
26 pedestrians and vehicles by providing signalized intersections, shorter-distance
27 striped crosswalks, designated bike lanes, and continuous pedestrian pathways.
28 The redesign also proposed an extension of Plaza Park to an open space area west
29 of Harbor Boulevard including a plaza area, lighting, trees, and irrigation.
30 Construction is expected to start in late August 2016 and be completed by the end
31 of March 2018.
- 32 ▪ Los Angeles Waterfront Red Car Line: Operations along the 1.5-mile route have
33 been suspended along the waterfront between Swinford Street and 22nd Street.

34 In addition, cumulative projects from Table 4-1 and Figure 4-1 of the SPW Project
35 EIS/EIR that could potentially contribute to a cumulative traffic effect have been
36 considered in the analysis of the proposed SPPM Project as changes to baseline
37 conditions and have been considered within the updated traffic analysis. These include:

- 38 ▪ Cabrillo Way Marina Phase II at 22nd Street/Miner Street: constructed and
39 operational since 2011.
- 40 ▪ Port of Los Angeles Charter School and Port Police Headquarters at 330 S.
41 Centre Street in San Pedro: constructed and operational since 2011.
- 42 ▪ Westway Decommissioning at Berths 70–71: storage tanks removed in 2012.
- 43 ▪ San Pedro Waterfront Enhancements Project: portions of the project were
44 completed, including development of 22nd Street Park and parking lot at 22nd
45 Street and Sampson Way.

1 As concluded throughout this chapter, the proposed SPPM Project would not result in
2 new significant impacts, substantially increase the severity of a previously analyzed
3 impact, or require new mitigation measures that have not already been evaluated in the
4 SPW Project EIS/EIR. Mitigation measures relating to development of the project site for
5 air quality, biological resources, cultural resources, geology, groundwater and soils,
6 noise, recreation, ground transportation, utilities and public services, and environmental
7 justice would be adhered to during construction of the SPPM Project. The analysis shows
8 that the modifications would not affect any of the Project-specific impact determinations
9 made in the SPW Project EIS/EIR. As such, the modified SPPM Project would also not
10 affect most of the cumulative impact determinations made in the SPW Project EIS/EIR.
11 The only exception would be the SPW Project's contribution to cumulative impacts on
12 mudflat habitat, which would not occur under the proposed SPPM Project; as noted in
13 Section 4.3.1.2, implementation of MM BIO-4, Enhance and expand Salinas de San
14 Pedro Salt Marsh, and MM BIO-5, Prepare a habitat mitigation and monitoring plan,
15 would no longer be required.

16

17

5.1 Printed References

California Department of Conservation. 1994. Generalized Mineral Land Classification Map of Los Angeles County – South Half.

California Department of Finance. 2015. Population. Available at: <http://www.dof.ca.gov/research/demographic/reports/estimates/e-1/view.php>. Accessed March 30, 2016.

California Employment Development Department. 2016. Los Angeles Labor Market Information, Los Angeles County. March 18.

Desman Associates. 2014. *San Pedro Waterfront at the Port of Los Angeles Comprehensive Parking Strategy*. Chicago, Illinois. December.

ERM-West, Inc. 2013. Phase II Environmental Site Assessment Ports O’Call Village. Prepared for Port of Los Angeles, San Pedro, CA. November 2013.

ERM-West, Inc. 2014. Human Health Risk Assessment – Ports O’Call Village. Prepared for Port of Los Angeles, San Pedro, CA. July 2014.

Federal Highway Administration. 2001. *Manual on Uniform Traffic Control Devices*. Millennium Edition, Including Errata No. 1 dated June 14, 2001. Available: http://mutcd.fhwa.dot.gov/kno-millennium_06.14.01.htm.

ICF International. 2015. Paleontological Monitoring and Mitigation Plan—San Pedro Waterfront Project. August. Irvine, CA. Prepared for the Los Angeles Harbor Department, San Pedro, CA.

LA Sanitation (City of Los Angeles). 2016. Terminal Island Water Reclamation Plant. Available at: https://www.lacitysan.org/san/faces/home/portal/s-lsh-wwd/s-lsh-wwd-cw/s-lsh-wwd-cw-p/s-lsh-wwd-cw-p-tiwrp?_afzLoop=21797930903767685&_afzWindowMode=0&_afzWindowId=6uj1k3g8z_213#!%40%40%3F_afzWindowId%3D6uj1k3g8z_213%26_afzLoop%3D21797930903767685%26_afzWindowMode%3D0%26_adf.ctrl-state%3D6uj1k3g8z_278. Accessed April 2, 2016.

Leighton Consulting, Inc. 2016. Soil Management Plan Redevelopment of the Ports O’Call Village Port of Los Angeles, San Pedro, California. Project No. 603127.016.

- 1 Prepared for City of Los Angeles Harbor Department, San Pedro, CA. February 19,
2 2016.
- 3 Los Angeles, City of. 2013. San Pedro Community Plan. March 14. Los Angeles, CA.
- 4 Los Angeles Harbor Department. 2011. Addendum to the San Pedro Waterfront Project
5 Final EIR/EIS Warehouse Nos. 9 and 10, Crafted at the Port of Los Angeles.
6 November. San Pedro, CA.
- 7 Los Angeles Harbor Department. 2015. EIR Addendum San Pedro Waterfront Project,
8 Harbor Boulevard/7th Street/Sampson Way Intersection Improvements. June 22. San
9 Pedro, CA.
- 10 Los Angeles/Long Beach Harbor Safety Committee. 2015. Harbor Safety Plan for the
11 Ports of Los Angeles and Long Beach. June 30.
- 12 Partner Engineering and Science, Inc. 2013. Phase I Environmental Site Assessment
13 Report Ports of Call Village Berths 73W, 73X, 73Y, and 75-83 San Pedro, California
14 90731. Project No. 12-97575.1. Prepared for The Ports of Los Angeles, San Pedro,
15 CA. April 12, 2013.
- 16 Port of Los Angeles. 2014a. Port Master Plan. San Pedro, CA. February.
- 17 Port of Los Angeles. 2014b. LA Waterfront Design Guidelines. Version 2. February
18 2014. Available:
19 [http://www.lawaterfront.org/pdf/LA_Waterfront_Design_Guidelines_2014.pdf?k=En](http://www.lawaterfront.org/pdf/LA_Waterfront_Design_Guidelines_2014.pdf?k=EngineeringDesignguidelines)
20 [gineeringDesignguidelines](http://www.lawaterfront.org/pdf/LA_Waterfront_Design_Guidelines_2014.pdf?k=EngineeringDesignguidelines). Accessed: April 26, 2016.
- 21 Port of Los Angeles. 2015. Monthly Average Concentrations Measured in the Port of Los
22 Angeles Monitoring Network, February 2005 – November 2015 for PM2.5, PM 10,
23 and Elemental Carbon PM2.5.
- 24 Port of Los Angeles. 2016a. Facts & Figures. Available at:
25 <https://www.portoflosangeles.org/about/facts.asp>. Accessed April 2, 2016.
- 26 Port of Los Angeles, 2016b. Historical TEU Statistics. Available at:
27 <https://www.portoflosangeles.org/maritime/stats.asp>. Accessed April 19, 2016.
- 28 Port of Los Angeles 2016c. 100 Years of Growth. Available at:
29 <https://www.portoflosangeles.org/maritime/growth.asp>. Accessed April 19, 2016.
- 30 Port of Los Angeles. 2016d. Cruise Passenger and Ferry Terminals. Available at:
31 <https://www.portoflosangeles.org/facilities/passenger.asp>. Accessed April 2, 2016.
- 32 Sanitation Districts of Los Angeles. 2015. Puente Hills Intermodal Facility. March.
33 Available at: www.lacsd.org. Accessed April 2, 2016.
- 34 Scott, E. and K. Springer. 2003. CEQA and fossil preservation in southern California.
35 The Environmental Monitor, Fall 2003, p. 4-10, 17.
- 36 South Coast Air Quality Management District. 2013. 2013 Air Quality Report.

- 1 The Source Group, Inc. 2013. Report of Soil-Gas Investigation Ports O'Call Village
2 Berths 75-79, San Pedro, California 90731. Prepared for The Port of Los Angeles,
3 San Pedro, CA. February 26, 2013.
- 4 U.S. Census Bureau. 2014a. Income in the Past 12 Months, American Community
5 Survey 5-Year Estimates. Available at:
6 <http://factfinder.census.gov/faces/tableservices/jsf/pages/productview.xhtml?src=CF>.
7 Accessed April 3, 2016.
- 8 U.S. Census Bureau. 2014b. Selected Housing Characteristics, American Community
9 Survey 5-Year Estimates. Available at:
10 <http://factfinder.census.gov/faces/tableservices/jsf/pages/productview.xhtml?src=CF>.
11 Accessed April 3, 2016.

Appendix A
Level of Service Worksheets



Level of Service Worksheet (Circular 212 Method)



I/S #:
5

PROJECT TITLE: SPW, POC Addendum
North-South Street: Gaffey St
Scenario: Future No Project
Count Date: 1/0/1900

East-West Street: 9th St

Analyst: <Fehr & Peers> **Date:** <date>

		AM			PM		
		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
No. of Phases				2			2
Opposed Ø'ing: N/S-1, E/W-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		NB-- 0	SB-- 0	0	NB-- 0	SB-- 0	0
ATSAC-1 or ATSAC+ATCS-2?		EB-- 0	WB-- 0	0	EB-- 0	WB-- 0	0
Override Capacity				2			2
Override Capacity				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	↵ Left	68	1	68	56	1	56
	↵↔ Left-Through		0			0	
	→ Through	1503	2	752	1132	2	566
	↘ Through-Right		0			0	
	↘ Right	28	1	0	42	1	0
	↘↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
SOUTHBOUND	↵ Left	46	1	46	151	1	151
	↵↔ Left-Through		0			0	
	→ Through	1108	1	613	1620	1	881
	↘ Through-Right		1			1	
	↘ Right	118	0	118	141	0	141
	↘↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
EASTBOUND	↵ Left	287	1	287	195	1	195
	↵↔ Left-Through		0			0	
	→ Through	504	1	504	275	1	275
	↘ Through-Right		0			0	
	↘ Right	58	1	24	47	1	19
	↘↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
WESTBOUND	↵ Left	77	1	77	98	1	98
	↵↔ Left-Through		0			0	
	→ Through	325	0	404	283	0	404
	↘ Through-Right		1			1	
	↘ Right	79	0	0	121	0	0
	↘↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
CRITICAL VOLUMES				<i>North-South:</i> 798			<i>North-South:</i> 937
				<i>East-West:</i> 691			<i>East-West:</i> 599
				SUM: 1489			SUM: 1536
VOLUME/CAPACITY (V/C) RATIO:				0.993			1.024
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.893			0.924
LEVEL OF SERVICE (LOS):				D			E



Level of Service Worksheet (Circular 212 Method)



I/S #:
6

PROJECT TITLE: SPW, POC Addendum
North-South Street: Gaffey St
Scenario: Future No Project
Count Date: 1/0/1900

East-West Street: 7th St

Analyst: <Fehr & Peers> **Date:** <date>

		AM			PM		
		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
No. of Phases				2			2
Opposed Ø'ing: N/S-1, E/W-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		NB-- 0	SB-- 0	0	NB-- 0	SB-- 0	0
ATSAC-1 or ATSAC+ATCS-2?		EB-- 0	WB-- 0	0	EB-- 0	WB-- 0	0
Override Capacity				2			2
Override Capacity				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	↵ Left	22	1	22	53	1	53
	↵↔ Left-Through		0			0	
	→ Through	1797	2	899	1346	2	673
	↘ Through-Right		0			0	
	↘ Right	53	1	0	42	1	0
	↘↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
SOUTHBOUND	↵ Left	71	1	71	106	1	106
	↵↔ Left-Through		0			0	
	→ Through	1202	1	686	1739	1	918
	↘ Through-Right		1			1	
	↘ Right	170	0	170	97	0	97
	↘↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
EASTBOUND	↵ Left	302	1	302	163	1	163
	↵↔ Left-Through		0			0	
	→ Through	185	0	220	181	0	234
	↘ Through-Right		1			1	
	↘ Right	35	0	0	53	0	0
	↘↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
WESTBOUND	↵ Left	114	1	114	105	1	105
	↵↔ Left-Through		0			0	
	→ Through	113	0	192	197	0	308
	↘ Through-Right		1			1	
	↘ Right	79	0	0	111	0	0
	↘↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
CRITICAL VOLUMES				<i>North-South:</i> 970			<i>North-South:</i> 971
				<i>East-West:</i> 494			<i>East-West:</i> 471
				SUM: 1464			SUM: 1442
VOLUME/CAPACITY (V/C) RATIO:				0.976			0.961
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.876			0.861
LEVEL OF SERVICE (LOS):				D			D



Level of Service Worksheet (Circular 212 Method)



I/S #:
7

PROJECT TITLE: SPW, POC Addendum
North-South Street: Gaffey St
Scenario: Future No Project
Count Date: 1/0/1900

East-West Street: 6th St

Analyst: <Fehr & Peers> **Date:** <date>

		AM			PM		
		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
No. of Phases Opposed Ø'ing: N/S-1, E/W-2 or Both-3? Right Turns: FREE-1, NRTOR-2 or OLA-3? ATSAC-1 or ATSAC+ATCS-2? Override Capacity				0			0
				0			0
		NB-- 0		SB-- 0	NB-- 0		SB-- 0
		EB-- 0		WB-- 0	EB-- 0		WB-- 0
				2			2
				1200			1200
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	Left	61	1	61	64	1	64
	Left-Through		0			0	
	Through	2020	1	1042	1537	1	798
	Through-Right		1			1	
	Right	64	0	64	58	0	58
	Left-Through-Right		0			0	
	Left-Right		0			0	
SOUTHBOUND	Left	114	1	114	70	1	70
	Left-Through		0			0	
	Through	1487	1	794	1807	1	956
	Through-Right		1			1	
	Right	101	0	101	104	0	104
	Left-Through-Right		0			0	
	Left-Right		0			0	
EASTBOUND	Left	13	0	13	15	0	15
	Left-Through		1			1	
	Through	11	0	24	9	0	24
	Through-Right		0			0	
	Right	38	1	8	93	1	61
	Left-Through-Right		0			0	
	Left-Right		0			0	
WESTBOUND	Left	2	0	2	10	0	10
	Left-Through		1			1	
	Through	30	0	32	11	0	21
	Through-Right		0			0	
	Right	44	1	0	102	1	67
	Left-Through-Right		0			0	
	Left-Right		0			0	
CRITICAL VOLUMES				North-South: 1156 East-West: 45 SUM: 1201			North-South: 1020 East-West: 82 SUM: 1102
VOLUME/CAPACITY (V/C) RATIO:				1.001			0.918
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.901			0.818
LEVEL OF SERVICE (LOS):				E			D



Level of Service Worksheet (Circular 212 Method)



I/S #:
8

PROJECT TITLE: SPW, POC Addendum
North-South Street: Gaffey St
Scenario: Future No Project
Count Date: 1/0/1900

East-West Street: 5th St

Analyst: <Fehr & Peers> **Date:** <date>

		AM			PM		
		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
No. of Phases				3			3
Opposed Ø'ing: N/S-1, EW-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		NB-- 0	SB-- 0	0	NB-- 0	SB-- 0	0
ATSAC-1 or ATSAC+ATCS-2?		EB-- 0	WB-- 0	0	EB-- 0	WB-- 0	0
Override Capacity				2			2
Override Capacity				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	↵ Left	17	1	17	46	1	46
	↵↔ Left-Through		0			0	
	→ Through	2012	2	1006	1617	2	809
	↘ Through-Right		0			0	
	↘ Right	28	1	0	34	1	0
	↘↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
SOUTHBOUND	↵ Left	125	1	125	131	1	131
	↵↔ Left-Through		0			0	
	→ Through	1525	2	763	1881	2	941
	↘ Through-Right		0			0	
	↘ Right	141	1	0	137	1	69
	↘↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
EASTBOUND	↵ Left	299	1	299	137	1	137
	↵↔ Left-Through		0			0	
	→ Through	184	0	217	93	0	117
	↘ Through-Right		1			1	
	↘ Right	33	0	0	24	0	0
	↘↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
WESTBOUND	↵ Left	102	1	102	103	1	103
	↵↔ Left-Through		0			0	
	→ Through	116	0	253	339	0	472
	↘ Through-Right		1			1	
	↘ Right	137	0	0	133	0	0
	↘↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
CRITICAL VOLUMES				<i>North-South:</i> 1131			<i>North-South:</i> 987
				<i>East-West:</i> 552			<i>East-West:</i> 609
				SUM: 1683			SUM: 1596
VOLUME/CAPACITY (V/C) RATIO:				1.181			1.120
V/C LESS ATSAC/ATCS ADJUSTMENT:				1.081			1.020
LEVEL OF SERVICE (LOS):				F			F



Level of Service Worksheet (Circular 212 Method)



I/S #:
9

PROJECT TITLE: SPW, POC Addendum
North-South Street: Gaffey St
Scenario: Future No Project
Count Date: 1/0/1900

East-West Street: 1st St

Analyst: <Fehr & Peers> **Date:** <date>

		AM			PM		
		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
No. of Phases				4			4
Opposed Ø'ing: N/S-1, E/W-2 or Both-3?				2			2
Right Turns: FREE-1, NRTOR-2 or OLA-3?		NB-- 0	SB-- 0	0	NB-- 0	SB-- 0	0
ATSAC-1 or ATSAC+ATCS-2?		EB-- 0	WB-- 0	0	EB-- 0	WB-- 0	0
Override Capacity				2			2
0				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	↵ Left	19	1	19	38	1	38
	↵↔ Left-Through		0			0	
	→ Through	2560	2	857	1875	2	630
	↗ Through-Right		1			1	
	↘ Right	11	0	11	16	0	16
	↗↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
SOUTHBOUND	↵ Left	127	1	127	139	1	139
	↵↔ Left-Through		0			0	
	→ Through	1847	2	729	2184	2	901
	↗ Through-Right		1			1	
	↘ Right	341	0	341	519	0	519
	↗↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
EASTBOUND	↵ Left	1302	2	716	945	2	520
	↵↔ Left-Through		0			0	
	→ Through	77	0	95	143	0	202
	↗ Through-Right		1			1	
	↘ Right	18	0	0	59	0	0
	↗↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
WESTBOUND	↵ Left	55	1	55	88	1	88
	↵↔ Left-Through		0			0	
	→ Through	201	1	201	180	1	180
	↗ Through-Right		0			0	
	↘ Right	280	1	217	209	1	140
	↗↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
CRITICAL VOLUMES		<i>North-South:</i>		984	<i>North-South:</i>		939
		<i>East-West:</i>		933	<i>East-West:</i>		700
		SUM:		1917	SUM:		1639
VOLUME/CAPACITY (V/C) RATIO:				1.394			1.192
V/C LESS ATSAC/ATCS ADJUSTMENT:				1.294			1.092
LEVEL OF SERVICE (LOS):				F			F



Level of Service Worksheet (Circular 212 Method)



I/S #:
11

PROJECT TITLE: SPW, POC Addendum
North-South Street: Summerland Ave
Scenario: Future No Project
Count Date: 1/0/1900

East-West Street: Gaffey St
Analyst: <Fehr & Peers> **Date:** <date>

		AM			PM		
		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
No. of Phases				3			3
Opposed Ø'ing: N/S-1, E/W-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		NB-- 0	SB-- 0	0	NB-- 0	SB-- 0	0
ATSAC-1 or ATSAC+ATCS-2?		EB-- 0	WB-- 0	0	EB-- 0	WB-- 0	0
Override Capacity				2			2
Override Capacity				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	↵ Left	146	1	146	182	1	182
	↵↔ Left-Through		0			0	
	→ Through	589	1	307	567	1	310
	↘ Through-Right		1			1	
	↘ Right	25	0	25	53	0	53
	↘↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
SOUTHBOUND	↵ Left	13	1	13	23	1	23
	↵↔ Left-Through		0			0	
	→ Through	551	2	276	807	2	404
	↘ Through-Right		0			0	
	↘ Right	210	1	0	381	1	262
	↘↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
EASTBOUND	↵ Left	570	1	570	238	1	238
	↵↔ Left-Through		0			0	
	→ Through	5	0	74	4	0	73
	↘ Through-Right		1			1	
	↘ Right	69	0	0	69	0	0
	↘↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
WESTBOUND	↵ Left	399	2	219	676	2	372
	↵↔ Left-Through		0			0	
	→ Through	171	0	478	362	0	750
	↘ Through-Right		1			1	
	↘ Right	307	0	0	388	0	0
	↘↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
CRITICAL VOLUMES				<i>North-South:</i> 422			<i>North-South:</i> 586
				<i>East-West:</i> 1048			<i>East-West:</i> 988
				<i>SUM:</i> 1470			<i>SUM:</i> 1574
VOLUME/CAPACITY (V/C) RATIO:				1.032			1.105
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.932			1.005
LEVEL OF SERVICE (LOS):				E			F



Level of Service Worksheet (Circular 212 Method)



I/S #:
12

PROJECT TITLE: SPW, POC Addendum
North-South Street: Pacific Ave
Scenario: Future No Project
Count Date: 1/0/1900

East-West Street: 22nd St

Analyst: <Fehr & Peers> **Date:** <date>

		AM			PM		
		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
No. of Phases				2			2
Opposed Ø'ing: N/S-1, E/W-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		NB-- 0	SB-- 0	0	NB-- 0	SB-- 0	0
ATSAC-1 or ATSAC+ATCS-2?		EB-- 0	WB-- 0	0	EB-- 0	WB-- 0	0
Override Capacity				2			2
Override Capacity				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	↵ Left	24	1	24	34	1	34
	↵↵ Left-Through		0			0	
	→ Through	561	1	561	439	1	439
	↵↵↵ Through-Right		0			0	
	↵ Right	352	1	352	127	1	127
	↵↵↵ Left-Through-Right		0			0	
	↵↵ Left-Right		0			0	
SOUTHBOUND	↵↵ Left	40	1	40	24	1	24
	↵↵ Left-Through		0			0	
	→ Through	194	1	194	387	1	387
	↵↵↵ Through-Right		0			0	
	↵ Right	34	1	34	87	1	87
	↵↵↵ Left-Through-Right		0			0	
	↵↵ Left-Right		0			0	
EASTBOUND	↵ Left	47	0	47	34	0	34
	↵↵ Left-Through		0			0	
	→ Through	320	0	403	133	0	222
	↵↵↵ Through-Right		0			0	
	↵ Right	36	0	0	55	0	0
	↵↵↵ Left-Through-Right		1			1	
	↵↵ Left-Right		0			0	
WESTBOUND	↵ Left	72	0	72	218	0	218
	↵↵ Left-Through		0			0	
	→ Through	107	0	201	175	0	429
	↵↵↵ Through-Right		0			0	
	↵ Right	22	0	0	36	0	0
	↵↵↵ Left-Through-Right		1			1	
	↵↵ Left-Right		0			0	
CRITICAL VOLUMES		<i>North-South:</i>		601	<i>North-South:</i>		463
		<i>East-West:</i>		475	<i>East-West:</i>		463
		SUM:		1076	SUM:		926
VOLUME/CAPACITY (V/C) RATIO:				0.717			0.617
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.617			0.517
LEVEL OF SERVICE (LOS):				B			A



Level of Service Worksheet (Circular 212 Method)



I/S #:
13

PROJECT TITLE: SPW, POC Addendum
North-South Street: Pacific Ave
Scenario: Future No Project
Count Date: 1/0/1900

East-West Street: 9th St

Analyst: <Fehr & Peers> **Date:** <date>

		AM			PM		
		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
No. of Phases				2			2
Opposed Ø'ing: N/S-1, E/W-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		NB-- 0	SB-- 0	0	NB-- 0	SB-- 0	0
ATSAC-1 or ATSAC+ATCS-2?		EB-- 0	WB-- 0	0	EB-- 0	WB-- 0	0
Override Capacity				2			2
Override Capacity				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	↵ Left	97	1	97	62	1	62
	↵↔ Left-Through		0			0	
	→ Through	1053	1	1053	764	1	764
	↘ Through-Right		0			0	
	↘ Right	38	1	33	41	1	16
	↘↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
SOUTHBOUND	↵ Left	16	1	16	41	1	41
	↵↔ Left-Through		0			0	
	→ Through	591	1	591	1010	1	1010
	↘ Through-Right		0			0	
	↘ Right	132	1	49	130	1	67
	↘↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
EASTBOUND	↵ Left	166	1	166	127	1	127
	↵↔ Left-Through		0			0	
	→ Through	162	0	213	191	0	296
	↘ Through-Right		1			1	
	↘ Right	51	0	0	105	0	0
	↘↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
WESTBOUND	↵ Left	11	1	11	50	1	50
	↵↔ Left-Through		0			0	
	→ Through	186	0	238	202	0	265
	↘ Through-Right		1			1	
	↘ Right	52	0	0	63	0	0
	↘↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
CRITICAL VOLUMES				<i>North-South:</i> 1069			<i>North-South:</i> 1072
				<i>East-West:</i> 404			<i>East-West:</i> 392
				SUM: 1473			SUM: 1464
VOLUME/CAPACITY (V/C) RATIO:				0.982			0.976
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.882			0.876
LEVEL OF SERVICE (LOS):				D			D



Level of Service Worksheet (Circular 212 Method)



I/S #:
14

PROJECT TITLE: SPW, POC Addendum
North-South Street: Pacific Ave
Scenario: Future No Project
Count Date: 1/0/1900

East-West Street: 7th St

Analyst: <Fehr & Peers> **Date:** <date>

		AM			PM		
		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
No. of Phases				2			2
Opposed Ø'ing: N/S-1, E/W-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		NB-- 0	SB-- 0	0	NB-- 0	SB-- 0	0
ATSAC-1 or ATSAC+ATCS-2?		EB-- 0	WB-- 0	0	EB-- 0	WB-- 0	0
Override Capacity				2			2
				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	↵ Left	28	1	28	73	1	73
	↵↔ Left-Through		0			0	
	→ Through	1252	1	1252	863	1	863
	↘ Through-Right		0			0	
	↘ Right	47	1	28	28	1	0
	↘↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
SOUTHBOUND	↵ Left	16	1	16	20	1	20
	↵↔ Left-Through		0			0	
	→ Through	740	1	740	1015	1	1015
	↘ Through-Right		0			0	
	↘ Right	51	1	26	51	1	34
	↘↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
EASTBOUND	↵ Left	51	1	51	35	1	35
	↵↔ Left-Through		0			0	
	→ Through	97	0	129	164	0	214
	↘ Through-Right		1			1	
	↘ Right	32	0	0	50	0	0
	↘↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
WESTBOUND	↵ Left	38	1	38	114	1	114
	↵↔ Left-Through		0			0	
	→ Through	99	0	120	178	0	225
	↘ Through-Right		1			1	
	↘ Right	21	0	0	47	0	0
	↘↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
CRITICAL VOLUMES				<i>North-South:</i> 1268			<i>North-South:</i> 1088
				<i>East-West:</i> 171			<i>East-West:</i> 328
				SUM: 1439			SUM: 1416
VOLUME/CAPACITY (V/C) RATIO:				0.959			0.944
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.859			0.844
LEVEL OF SERVICE (LOS):				D			D



Level of Service Worksheet (Circular 212 Method)



I/S #:
15

PROJECT TITLE: SPW, POC Addendum
North-South Street: Pacific Ave
Scenario: Future No Project
Count Date: 1/0/1900

East-West Street: 6th St

Analyst: <Fehr & Peers> **Date:** <date>

		AM			PM		
		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
No. of Phases				4			4
Opposed Ø'ing: N/S-1, E/W-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		NB-- 0	SB-- 0	0	NB-- 0	SB-- 0	0
ATSAC-1 or ATSAC+ATCS-2?		EB-- 0	WB-- 0	0	EB-- 0	WB-- 0	0
Override Capacity				2			2
Override Capacity				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	↵ Left	32	1	32	38	1	38
	↵↔ Left-Through		0			0	
	→ Through	1236	1	1236	849	1	849
	↘ Through-Right		0			0	
	↘ Right	52	1	52	75	1	75
	↘↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
SOUTHBOUND	↵ Left	30	1	30	36	1	36
	↵↔ Left-Through		0			0	
	→ Through	722	1	722	999	1	999
	↘ Through-Right		0			0	
	↘ Right	28	1	28	46	1	46
	↘↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
EASTBOUND	↵ Left	25	0	25	25	0	25
	↵↔ Left-Through		0			0	
	→ Through	76	0	128	80	0	150
	↘ Through-Right		0			0	
	↘ Right	27	0	0	45	0	0
	↘↔ Left-Through-Right		1			1	
	↘↔ Left-Right		0			0	
WESTBOUND	↵ Left	40	0	40	62	0	62
	↵↔ Left-Through		0			0	
	→ Through	22	0	98	77	0	175
	↘ Through-Right		0			0	
	↘ Right	36	0	0	36	0	0
	↘↔ Left-Through-Right		1			1	
	↘↔ Left-Right		0			0	
CRITICAL VOLUMES				<i>North-South:</i> 1266			<i>North-South:</i> 1037
				<i>East-West:</i> 168			<i>East-West:</i> 212
				SUM: 1434			SUM: 1249
VOLUME/CAPACITY (V/C) RATIO:				1.043			0.908
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.943			0.808
LEVEL OF SERVICE (LOS):				E			D



Level of Service Worksheet (Circular 212 Method)



I/S #:
16

PROJECT TITLE: SPW, POC Addendum
North-South Street: Pacific Ave
Scenario: Future No Project
Count Date: 1/0/1900

East-West Street: 5th St

Analyst: <Fehr & Peers> **Date:** <date>

		AM			PM		
		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
No. of Phases				2			2
Opposed Ø'ing: N/S-1, E/W-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		NB-- 0	SB-- 0	0	NB-- 0	SB-- 0	0
ATSAC-1 or ATSAC+ATCS-2?		EB-- 0	WB-- 0	0	EB-- 0	WB-- 0	0
Override Capacity				2			2
				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	↵ Left	36	1	36	40	1	40
	↵↔ Left-Through		0			0	
	→ Through	1196	1	1196	854	1	854
	↘ Through-Right		0			0	
	↘ Right	68	1	22	66	1	0
	↘↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
SOUTHBOUND	↵ Left	50	1	50	50	1	50
	↵↔ Left-Through		0			0	
	→ Through	668	1	668	851	1	851
	↘ Through-Right		0			0	
	↘ Right	38	1	19	32	1	5
	↘↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
EASTBOUND	↵ Left	38	1	38	55	1	55
	↵↔ Left-Through		0			0	
	→ Through	211	0	250	130	0	178
	↘ Through-Right		1			1	
	↘ Right	39	0	0	48	0	0
	↘↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
WESTBOUND	↵ Left	93	1	93	186	1	186
	↵↔ Left-Through		0			0	
	→ Through	173	0	225	176	0	235
	↘ Through-Right		1			1	
	↘ Right	52	0	0	59	0	0
	↘↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
CRITICAL VOLUMES				<i>North-South:</i> 1246			<i>North-South:</i> 904
				<i>East-West:</i> 343			<i>East-West:</i> 364
				<i>SUM:</i> 1589			<i>SUM:</i> 1268
VOLUME/CAPACITY (V/C) RATIO:				1.059			0.845
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.959			0.745
LEVEL OF SERVICE (LOS):				E			C



Level of Service Worksheet (Circular 212 Method)



I/S #:
17

PROJECT TITLE: SPW, POC Addendum
North-South Street: Pacific Ave
Scenario: Future No Project
Count Date: 1/0/1900

East-West Street: 1st St

Analyst: <Fehr & Peers> **Date:** <date>

		AM			PM		
				2			2
No. of Phases				0			0
Opposed Ø'ing: N/S-1, E/W-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		<i>NB--</i> 0	<i>SB--</i> 0	0	<i>NB--</i> 0	<i>SB--</i> 0	0
ATSAC-1 or ATSAC+ATCS-2?		<i>EB--</i> 0	<i>WB--</i> 0	0	<i>EB--</i> 0	<i>WB--</i> 0	0
Override Capacity				2			2
				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	Left	217	1	217	153	1	153
	Left-Through		0			0	
	Through	1070	1	1070	762	1	762
	Through-Right		0			0	
	Right	46	1	46	33	1	33
	Left-Through-Right		0			0	
	Left-Right		0			0	
SOUTHBOUND	Left	35	1	35	29	1	29
	Left-Through		0			0	
	Through	610	1	610	825	1	825
	Through-Right		0			0	
	Right	45	1	45	59	1	59
	Left-Through-Right		0			0	
	Left-Right		0			0	
EASTBOUND	Left	52	0	52	62	0	62
	Left-Through		1			1	
	Through	116	0	168	142	0	204
	Through-Right		0			0	
	Right	64	1	0	93	1	17
	Left-Through-Right		0			0	
	Left-Right		0			0	
WESTBOUND	Left	112	0	112	58	0	58
	Left-Through		1			1	
	Through	138	0	250	119	0	177
	Through-Right		0			0	
	Right	58	1	41	22	1	8
	Left-Through-Right		0			0	
	Left-Right		0			0	
CRITICAL VOLUMES				<i>North-South:</i> 1105			<i>North-South:</i> 978
				<i>East-West:</i> 302			<i>East-West:</i> 262
				SUM: 1407			SUM: 1240
VOLUME/CAPACITY (V/C) RATIO:				0.938			0.827
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.838			0.727
LEVEL OF SERVICE (LOS):				D			C



Level of Service Worksheet (Circular 212 Method)



I/S #:
20

PROJECT TITLE: SPW, POC Addendum
North-South Street: Miner St
Scenario: Future No Project
Count Date: 1/0/1900

East-West Street: 22nd St

Analyst: <Fehr & Peers> **Date:** <date>

		AM			PM		
		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
No. of Phases				4			4
Opposed Ø'ing: N/S-1, E/W-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		NB-- 0	SB-- 0	0	NB-- 0	SB-- 0	0
ATSAC-1 or ATSAC+ATCS-2?		EB-- 0	WB-- 0	0	EB-- 0	WB-- 0	0
Override Capacity				2			2
Override Capacity				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	↵ Left	30	1	30	43	1	43
	↵↔ Left-Through		0			0	
	→ Through	73	1	46	136	1	83
	↘ Through-Right		1			1	
	↘ Right	18	0	18	30	0	30
	↘↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
SOUTHBOUND	↵ Left	59	1	59	34	1	34
	↵↔ Left-Through		0			0	
	→ Through	104	1	104	142	1	142
	↘ Through-Right		1			1	
	↘ Right	168	0	0	483	0	354
	↘↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
EASTBOUND	↵ Left	528	1	528	258	1	258
	↵↔ Left-Through		0			0	
	→ Through	71	1	53	56	1	49
	↘ Through-Right		1			1	
	↘ Right	34	0	34	42	0	42
	↘↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
WESTBOUND	↵ Left	19	1	19	36	1	36
	↵↔ Left-Through		0			0	
	→ Through	27	1	27	51	1	47
	↘ Through-Right		1			1	
	↘ Right	34	0	5	42	0	42
	↘↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
CRITICAL VOLUMES			<i>North-South:</i>	134		<i>North-South:</i>	397
			<i>East-West:</i>	555		<i>East-West:</i>	305
			<i>SUM:</i>	689		<i>SUM:</i>	702
VOLUME/CAPACITY (V/C) RATIO:				0.501			0.511
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.401			0.411
LEVEL OF SERVICE (LOS):				A			A



Level of Service Worksheet (Circular 212 Method)



I/S #:
21

PROJECT TITLE: SPW, POC Addendum
North-South Street: Harbor Bl / Miner St
Scenario: Future No Project
Count Date: 1/0/1900

East-West Street: Crescent Av

Analyst: <Fehr & Peers> **Date:** <date>

		AM			PM		
		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
No. of Phases Opposed Ø'ing: N/S-1, E/W-2 or Both-3? Right Turns: FREE-1, NRTOR-2 or OLA-3? ATSAC-1 or ATSAC+ATCS-2? Override Capacity				0			0
				0			0
		NB-- 0		SB-- 0	NB-- 0		SB-- 0
		EB-- 0		WB-- 0	EB-- 0		WB-- 0
				2			2
				1200			1200
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	↵ Left	2	1	2	10	1	10
	↵↵ Left-Through		0			0	
	→ Through	682	2	341	430	2	215
	↵↵ Through-Right		0			0	
	→ Right	0	0	0	0	0	0
	↵↵ Left-Through-Right		0			0	
	↵↵ Left-Right		0			0	
SOUTHBOUND	↵ Left	0	0	0	0	0	0
	↵↵ Left-Through		0			0	
	→ Through	310	1	218	660	1	523
	↵↵ Through-Right		1			1	
	→ Right	125	0	125	386	0	386
	↵↵ Left-Through-Right		0			0	
	↵↵ Left-Right		0			0	
EASTBOUND	↵ Left	299	0	299	103	0	103
	↵↵ Left-Through		0			0	
	→ Through	0	0	0	0	0	0
	↵↵ Through-Right		0			0	
	→ Right	8	0	307	6	0	109
	↵↵ Left-Through-Right		0			0	
	↵↵ Left-Right		1			1	
WESTBOUND	↵ Left	0	0	0	0	0	0
	↵↵ Left-Through		0			0	
	→ Through	0	0	0	0	0	0
	↵↵ Through-Right		0			0	
	→ Right	0	0	0	0	0	0
	↵↵ Left-Through-Right		0			0	
	↵↵ Left-Right		0			0	
CRITICAL VOLUMES				North-South: 341			North-South: 533
				East-West: 307			East-West: 109
				SUM: 648			SUM: 642
VOLUME/CAPACITY (V/C) RATIO:				0.540			0.535
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.440			0.435
LEVEL OF SERVICE (LOS):				A			A



Level of Service Worksheet (Circular 212 Method)



I/S #:
22

PROJECT TITLE: SPW, POC Addendum
North-South Street: Harbor Blvd
Scenario: Future No Project
Count Date: 1/0/1900

East-West Street: 7th St

Analyst: <Fehr & Peers> **Date:** <date>

		AM			PM		
		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
No. of Phases				3			3
Opposed Ø'ing: N/S-1, E/W-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		NB-- 0	SB-- 0	0	NB-- 0	SB-- 0	0
ATSAC-1 or ATSAC+ATCS-2?		EB-- 0	WB-- 0	0	EB-- 0	WB-- 0	0
Override Capacity				2			2
Override Capacity				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	↶ Left	16	1	16	21	1	21
	↶↷ Left-Through		0			0	
	→ Through	1016	2	508	598	2	299
	↷ Through-Right		0			0	
	→ Right	0	0	0	0	0	0
	↷↶ Left-Through-Right		0			0	
	↷ Left-Right		0			0	
SOUTHBOUND	↷ Left	0	0	0	0	0	0
	↷↶ Left-Through		0			0	
	→ Through	464	2	232	1125	2	563
	↷ Through-Right		0			0	
	→ Right	244	1	162	372	1	289
	↷↶ Left-Through-Right		0			0	
	↷ Left-Right		0			0	
EASTBOUND	↶ Left	299	2	164	303	2	167
	↶↷ Left-Through		0			0	
	→ Through	0	0	0	0	0	0
	↷ Through-Right		0			0	
	→ Right	7	1	0	28	1	18
	↷↶ Left-Through-Right		0			0	
	↷ Left-Right		0			0	
WESTBOUND	↶ Left	0	0	0	0	0	0
	↶↷ Left-Through		0			0	
	→ Through	0	0	0	0	0	0
	↷ Through-Right		0			0	
	→ Right	0	0	0	0	0	0
	↷↶ Left-Through-Right		0			0	
	↷ Left-Right		0			0	
CRITICAL VOLUMES				<i>North-South:</i> 508			<i>North-South:</i> 584
				<i>East-West:</i> 164			<i>East-West:</i> 167
				SUM: 672			SUM: 751
VOLUME/CAPACITY (V/C) RATIO:				0.472			0.527
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.372			0.427
LEVEL OF SERVICE (LOS):				A			A



Level of Service Worksheet (Circular 212 Method)



I/S #:
23

PROJECT TITLE: SPW, POC Addendum
North-South Street: Harbor Blvd
Scenario: Future No Project
Count Date: 1/0/1900

East-West Street: 6th St

Analyst: <Fehr & Peers> **Date:** <date>

		AM			PM		
		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
No. of Phases				3			3
Opposed Ø'ing: N/S-1, E/W-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		NB-- 0	SB-- 0	0	NB-- 0	SB-- 0	0
ATSAC-1 or ATSAC+ATCS-2?		EB-- 0	WB-- 0	0	EB-- 0	WB-- 0	0
Override Capacity				2			2
Override Capacity				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	↶ Left	18	1	18	23	1	23
	↶↷ Left-Through		0			0	
	→ Through	1331	1	673	841	1	443
	↷ Through-Right		1			1	
	↷ Right	15	0	15	44	0	44
	↷↶ Left-Through-Right		0			0	
	↷↶ Left-Right		0			0	
SOUTHBOUND	↷ Left	72	1	72	146	1	146
	↷↶ Left-Through		0			0	
	→ Through	735	1	424	1378	1	728
	↷ Through-Right		1			1	
	↷ Right	113	0	113	78	0	78
	↷↶ Left-Through-Right		0			0	
	↷↶ Left-Right		0			0	
EASTBOUND	↶ Left	42	1	42	50	1	50
	↶↷ Left-Through		0			0	
	→ Through	8	0	29	39	0	58
	↷ Through-Right		1			1	
	↷ Right	21	0	0	19	0	0
	↷↶ Left-Through-Right		0			0	
	↷↶ Left-Right		0			0	
WESTBOUND	↶ Left	7	1	7	28	1	28
	↶↷ Left-Through		0			0	
	→ Through	15	1	15	33	1	33
	↷ Through-Right		0			0	
	↷ Right	24	1	0	124	1	51
	↷↶ Left-Through-Right		0			0	
	↷↶ Left-Right		0			0	
CRITICAL VOLUMES				<i>North-South:</i> 745			<i>North-South:</i> 751
				<i>East-West:</i> 57			<i>East-West:</i> 101
				SUM: 802			SUM: 852
VOLUME/CAPACITY (V/C) RATIO:				0.563			0.598
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.463			0.498
LEVEL OF SERVICE (LOS):				A			A



Level of Service Worksheet (Circular 212 Method)



I/S #:
24

PROJECT TITLE: SPW, POC Addendum
North-South Street: Harbor Blvd
Scenario: Future No Project
Count Date: 1/0/1900

East-West Street: 5th St

Analyst: <Fehr & Peers> **Date:** <date>

		AM			PM		
		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
No. of Phases				3			3
Opposed Ø'ing: N/S-1, E/W-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		NB-- 0	SB-- 0	0	NB-- 0	SB-- 0	0
ATSAC-1 or ATSAC+ATCS-2?		EB-- 0	WB-- 0	0	EB-- 0	WB-- 0	0
Override Capacity				2			2
Override Capacity				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	↵ Left	34	1	34	17	1	17
	↵↵ Left-Through		0			0	
	→ Through	1230	1	617	894	1	447
	↵↵↵ Through-Right		1			1	
	↵ Right	4	0	4	0	0	0
	↵↵↵ Left-Through-Right		0			0	
	↵↵↵ Left-Right		0			0	
SOUTHBOUND	↵ Left	0	1	0	0	1	0
	↵↵ Left-Through		0			0	
	→ Through	912	1	654	1616	1	879
	↵↵↵ Through-Right		1			1	
	↵ Right	396	0	396	141	0	141
	↵↵↵ Left-Through-Right		0			0	
	↵↵↵ Left-Right		0			0	
EASTBOUND	↵ Left	184	1	184	368	1	368
	↵↵ Left-Through		0			0	
	→ Through	8	0	23	4	0	37
	↵↵↵ Through-Right		1			1	
	↵ Right	15	0	0	33	0	0
	↵↵↵ Left-Through-Right		0			0	
	↵↵↵ Left-Right		0			0	
WESTBOUND	↵ Left	4	1	4	1	1	1
	↵↵ Left-Through		0			0	
	→ Through	6	1	6	5	1	5
	↵↵↵ Through-Right		0			0	
	↵ Right	29	1	29	28	1	28
	↵↵↵ Left-Through-Right		0			0	
	↵↵↵ Left-Right		0			0	
CRITICAL VOLUMES		<i>North-South:</i>		688	<i>North-South:</i>		896
		<i>East-West:</i>		213	<i>East-West:</i>		396
		SUM:		901	SUM:		1292
VOLUME/CAPACITY (V/C) RATIO:				0.632			0.907
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.532			0.807
LEVEL OF SERVICE (LOS):				A			D



Level of Service Worksheet (Circular 212 Method)



I/S #:
25

PROJECT TITLE: SPW, POC Addendum
North-South Street: Harbor Blvd
Scenario: Future No Project
Count Date: 1/0/1900

East-West Street: 1st St

Analyst: <Fehr & Peers> **Date:** <date>

		AM			PM		
		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
No. of Phases				4			4
Opposed Ø'ing: N/S-1, E/W-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		NB-- 0	SB-- 0	0	NB-- 0	SB-- 0	0
ATSAC-1 or ATSAC+ATCS-2?		EB-- 0	WB-- 0	0	EB-- 0	WB-- 0	0
Override Capacity				2			2
Override Capacity				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	↵ Left	7	1	7	16	1	16
	↵↔ Left-Through		0			0	
	→ Through	1608	1	806	1394	1	699
	↘ Through-Right		1			1	
	↘ Right	4	0	4	3	0	3
	↘↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
SOUTHBOUND	↵ Left	303	1	303	28	1	28
	↵↔ Left-Through		0			0	
	→ Through	1282	1	687	1700	1	884
	↘ Through-Right		1			1	
	↘ Right	92	0	92	68	0	68
	↘↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
EASTBOUND	↵ Left	125	1	125	100	1	100
	↵↔ Left-Through		0			0	
	→ Through	0	0	13	3	0	18
	↘ Through-Right		1			1	
	↘ Right	13	0	0	15	0	0
	↘↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
WESTBOUND	↵ Left	2	0	2	5	0	5
	↵↔ Left-Through		1			1	
	→ Through	0	0	2	13	0	18
	↘ Through-Right		0			0	
	↘ Right	10	1	0	68	1	54
	↘↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
CRITICAL VOLUMES			<i>North-South:</i>	1109		<i>North-South:</i>	900
			<i>East-West:</i>	127		<i>East-West:</i>	154
			SUM:	1236		SUM:	1054
VOLUME/CAPACITY (V/C) RATIO:				0.899			0.767
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.799			0.667
LEVEL OF SERVICE (LOS):				C			B

Level of Service Worksheet (Circular 212 Method)



I/S #:
26

PROJECT TITLE: SPW, POC Addendum
North-South Street: Harbor Blvd
Scenario: Future No Project
Count Date: 1/0/1900

East-West Street: SR 47 EB Off-Ramp / Swinford St
Analyst: <Fehr & Peers> **Date:** <date>

		AM			PM		
				4			4
No. of Phases				0			0
Opposed Ø'ing: N/S-1, E/W-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		0	0	0	0	0	0
ATSAC-1 or ATSAC+ATCS-2?		3	3	3	3	3	3
Override Capacity				2			2
Override Capacity				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	↶ Left	535	2	294	360	2	198
	↶↷ Left-Through		0			0	
	↷ Through	639	1	336	804	1	408
	↷↶ Through-Right		1			1	
	↷ Right	32	0	32	12	0	12
	↷↷ Left-Through-Right		0			0	
	↷↷ Left-Right		0			0	
SOUTHBOUND	↷ Left	246	2	135	157	2	86
	↷↷ Left-Through		0			0	
	↷ Through	547	2	205	1464	2	521
	↷↶ Through-Right		1			1	
	↷ Right	69	0	69	99	0	99
	↷↷ Left-Through-Right		0			0	
	↷↷ Left-Right		0			0	
EASTBOUND	↶ Left	38	1	38	45	1	45
	↶↷ Left-Through		0			0	
	↷ Through	311	1	235	64	1	64
	↷↶ Through-Right		1			1	
	↷ Right	395	1	0	265	1	0
	↷↷ Left-Through-Right		0			0	
	↷↷ Left-Right		0			0	
WESTBOUND	↷ Left	0	1	0	1	1	1
	↷↷ Left-Through		0			0	
	↷ Through	129	1	129	69	1	69
	↷↶ Through-Right		0			0	
	↷ Right	308	1	173	114	1	28
	↷↷ Left-Through-Right		0			0	
	↷↷ Left-Right		0			0	
CRITICAL VOLUMES				<i>North-South:</i> 499			<i>North-South:</i> 719
				<i>East-West:</i> 235			<i>East-West:</i> 114
				<i>SUM:</i> 734			<i>SUM:</i> 833
VOLUME/CAPACITY (V/C) RATIO:				0.534			0.606
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.434			0.506
LEVEL OF SERVICE (LOS):				A			A



Level of Service Worksheet (Circular 212 Method)



I/S #:
27

PROJECT TITLE: SPW, POC Addendum
North-South Street: Harbor Blvd
Scenario: Future No Project
Count Date: 1/0/1900

East-West Street: SR-47 WB On-Ramp
Analyst: <Fehr & Peers> **Date:** <date>

		AM			PM		
No. of Phases				4			4
Opposed Ø'ing: N/S-1, E/W-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		NB-- 3	SB-- 3	3	NB-- 3	SB-- 3	3
ATSAC-1 or ATSAC+ATCS-2?		EB-- 1	WB-- 0	0	EB-- 1	WB-- 0	0
Override Capacity				2			2
Override Capacity				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	↵ Left	1020	2	561	743	2	409
	↵↵ Left-Through		0			0	
	→ Through	334	0	376	248	0	285
	↵↵↵ Through-Right		1			1	
	↵ Right	42	0	0	37	0	0
	↵↵↵ Left-Through-Right		0			0	
	↵↵↵ Left-Right		0			0	
SOUTHBOUND	↵↵ Left	4	1	4	34	1	34
	↵↵ Left-Through		0			0	
	→ Through	311	2	156	438	2	219
	↵↵ Through-Right		0			0	
	↵ Right	29	1	0	0	1	0
	↵↵↵ Left-Through-Right		0			0	
	↵↵↵ Left-Right		0			0	
EASTBOUND	↵ Left	43	1	43	100	1	100
	↵↵ Left-Through		0			0	
	→ Through	234	1	234	60	1	60
	↵↵ Through-Right		0			0	
	↵ Right	486	1	0	954	1	0
	↵↵↵ Left-Through-Right		0			0	
	↵↵↵ Left-Right		0			0	
WESTBOUND	↵ Left	45	2	25	141	2	78
	↵↵ Left-Through		0			0	
	→ Through	138	2	69	95	2	48
	↵↵ Through-Right		0			0	
	↵ Right	11	1	9	27	1	10
	↵↵↵ Left-Through-Right		0			0	
	↵↵↵ Left-Right		0			0	
CRITICAL VOLUMES				<i>North-South:</i> 717			<i>North-South:</i> 628
				<i>East-West:</i> 259			<i>East-West:</i> 148
				SUM: 976			SUM: 776
VOLUME/CAPACITY (V/C) RATIO:				0.710			0.564
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.610			0.464
LEVEL OF SERVICE (LOS):				B			A



Level of Service Worksheet (Circular 212 Method)



I/S #:
29

PROJECT TITLE: SPW, POC Addendum
North-South Street: Harbor
Scenario: Future No Project
Count Date: 1/0/1900

East-West Street: O'Farrell

Analyst: <Fehr & Peers> **Date:** <date>

		AM			PM		
		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
No. of Phases				2			2
Opposed Ø'ing: N/S-1, E/W-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		NB-- 0	SB-- 0	0	NB-- 0	SB-- 0	0
ATSAC-1 or ATSAC+ATCS-2?		EB-- 0	WB-- 0	0	EB-- 0	WB-- 0	0
Override Capacity				2			2
Override Capacity				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	↵ Left	11	1	11	14	1	14
	↵↔ Left-Through		0			0	
	→ Through	1786	2	893	1693	2	847
	↘ Through-Right		0			0	
	↘ Right	0	0	0	0	0	0
	↘↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
SOUTHBOUND	↵ Left	0	0	0	0	0	0
	↵↔ Left-Through		0			0	
	→ Through	1859	1	938	2679	1	1357
	↘ Through-Right		1			1	
	↘ Right	16	0	16	35	0	35
	↘↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
EASTBOUND	↵ Left	128	1	128	133	1	133
	↵↔ Left-Through		0			0	
	→ Through	0	0	0	0	0	0
	↘ Through-Right		0			0	
	↘ Right	11	1	6	14	1	7
	↘↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
WESTBOUND	↵ Left	0	0	0	0	0	0
	↵↔ Left-Through		0			0	
	→ Through	0	0	0	0	0	0
	↘ Through-Right		0			0	
	↘ Right	0	0	0	0	0	0
	↘↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
CRITICAL VOLUMES			<i>North-South:</i>	949		<i>North-South:</i>	1371
			<i>East-West:</i>	128		<i>East-West:</i>	133
			<i>SUM:</i>	1077		<i>SUM:</i>	1504
VOLUME/CAPACITY (V/C) RATIO:				0.718			1.003
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.618			0.903
LEVEL OF SERVICE (LOS):				B			E



Level of Service Worksheet (Circular 212 Method)



I/S #:
30

PROJECT TITLE: SPW, POC Addendum
North-South Street: Harbor
Scenario: Future No Project
Count Date: 1/0/1900

East-West Street: 3rd

Analyst: <Fehr & Peers> **Date:** <date>

		AM			PM		
		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
No. of Phases Opposed Ø'ing: N/S-1, E/W-2 or Both-3? Right Turns: FREE-1, NRTOR-2 or OLA-3? ATSAC-1 or ATSAC+ATCS-2? Override Capacity				0			0
				0			0
		NB-- 0	SB-- 0	0	NB-- 0	SB-- 0	0
		EB-- 0	WB-- 0	0	EB-- 0	WB-- 0	0
				2			2
				1200			1200
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	↵ Left	18	1	18	18	1	18
	↵↵ Left-Through		0			0	
	→ Through	1373	2	687	1313	2	657
	↵↵↵ Through-Right		0			0	
	↵↵↵ Right	0	0	0	0	0	0
	↵↵↵↵ Left-Through-Right		0			0	
↵↵↵↵ Left-Right		0			0		
SOUTHBOUND	↵↵ Left	0	0	0	0	0	0
	↵↵ Left-Through		0			0	
	→ Through	1096	1	645	1597	1	839
	↵↵ Through-Right		1			1	
	↵↵↵ Right	194	0	194	80	0	80
	↵↵↵↵ Left-Through-Right		0			0	
↵↵↵↵ Left-Right		0			0		
EASTBOUND	↵ Left	130	1	130	72	1	72
	↵↵ Left-Through		0			0	
	→ Through	0	0	0	0	0	0
	↵↵ Through-Right		0			0	
	↵↵↵ Right	17	1	8	19	1	10
	↵↵↵↵ Left-Through-Right		0			0	
↵↵↵↵ Left-Right		0			0		
WESTBOUND	↵ Left	0	0	0	0	0	0
	↵↵ Left-Through		0			0	
	→ Through	0	0	0	0	0	0
	↵↵ Through-Right		0			0	
	↵↵↵ Right	0	0	0	0	0	0
	↵↵↵↵ Left-Through-Right		0			0	
↵↵↵↵ Left-Right		0			0		
CRITICAL VOLUMES				<i>North-South:</i> 687			<i>North-South:</i> 857
				<i>East-West:</i> 130			<i>East-West:</i> 72
				SUM: 817			SUM: 929
VOLUME/CAPACITY (V/C) RATIO:				0.681			0.774
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.581			0.674
LEVEL OF SERVICE (LOS):				A			B



Level of Service Worksheet (Circular 212 Method)



I/S #:
31

PROJECT TITLE: SPW, POC Addendum
North-South Street: Pacific Ave
Scenario: Future No Project
Count Date: 1/0/1900

East-West Street: 13th

Analyst: <Fehr & Peers> **Date:** <date>

		AM			PM		
		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
No. of Phases				2			2
Opposed Ø'ing: N/S-1, E/W-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		NB-- 0	SB-- 0	0	NB-- 0	SB-- 0	0
ATSAC-1 or ATSAC+ATCS-2?		EB-- 0	WB-- 0	0	EB-- 0	WB-- 0	0
Override Capacity				2			2
Override Capacity				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	↵ Left	53	1	53	49	1	49
	↵↔ Left-Through		0			0	
	→ Through	1001	1	1001	667	1	667
	↘ Through-Right		0			0	
	↘ Right	22	1	22	19	1	19
	↘↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
SOUTHBOUND	↵ Left	11	1	11	34	1	34
	↵↔ Left-Through		0			0	
	→ Through	353	1	353	833	1	833
	↘ Through-Right		0			0	
	↘ Right	121	1	121	114	1	114
	↘↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
EASTBOUND	↵ Left	121	0	121	78	0	78
	↵↔ Left-Through		0			0	
	→ Through	68	0	231	94	0	235
	↘ Through-Right		0			0	
	↘ Right	42	0	0	63	0	0
	↘↔ Left-Through-Right		1			1	
	↘↔ Left-Right		0			0	
WESTBOUND	↵ Left	10	0	10	16	0	16
	↵↔ Left-Through		0			0	
	→ Through	116	0	181	95	0	139
	↘ Through-Right		0			0	
	↘ Right	55	0	0	28	0	0
	↘↔ Left-Through-Right		1			1	
	↘↔ Left-Right		0			0	
CRITICAL VOLUMES				<i>North-South:</i> 1012			<i>North-South:</i> 882
				<i>East-West:</i> 302			<i>East-West:</i> 251
				SUM: 1314			SUM: 1133
VOLUME/CAPACITY (V/C) RATIO:				0.876			0.755
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.776			0.655
LEVEL OF SERVICE (LOS):				C			B



Level of Service Worksheet (Circular 212 Method)



I/S #:
32

PROJECT TITLE: SPW, POC Addendum
North-South Street: Pacific Ave
Scenario: Future No Project
Count Date: 1/0/1900

East-West Street: 17th

Analyst: <Fehr & Peers> **Date:** <date>

		AM			PM		
		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
No. of Phases				2			2
Opposed Ø'ing: N/S-1, E/W-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		NB-- 0	SB-- 0	0	NB-- 0	SB-- 0	0
ATSAC-1 or ATSAC+ATCS-2?		EB-- 0	WB-- 0	0	EB-- 0	WB-- 0	0
Override Capacity				2			2
				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	↵ Left	57	1	57	19	1	19
	↵↔ Left-Through		0			0	
	→ Through	662	1	662	560	1	560
	↘ Through-Right		0			0	
	↘ Right	4	1	4	8	1	8
	↘↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
SOUTHBOUND	↵ Left	21	1	21	17	1	17
	↵↔ Left-Through		0			0	
	→ Through	300	1	300	735	1	735
	↘ Through-Right		0			0	
	↘ Right	83	1	83	78	1	78
	↘↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
EASTBOUND	↵ Left	192	0	192	49	0	49
	↵↔ Left-Through		0			0	
	→ Through	141	0	375	53	0	130
	↘ Through-Right		0			0	
	↘ Right	42	0	0	28	0	0
	↘↔ Left-Through-Right		1			1	
	↘↔ Left-Right		0			0	
WESTBOUND	↵ Left	6	0	6	33	0	33
	↵↔ Left-Through		0			0	
	→ Through	123	0	165	106	0	169
	↘ Through-Right		0			0	
	↘ Right	36	0	0	30	0	0
	↘↔ Left-Through-Right		1			1	
	↘↔ Left-Right		0			0	
CRITICAL VOLUMES				<i>North-South:</i> 683			<i>North-South:</i> 754
				<i>East-West:</i> 381			<i>East-West:</i> 218
				SUM: 1064			SUM: 972
VOLUME/CAPACITY (V/C) RATIO:				0.709			0.648
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.609			0.548
LEVEL OF SERVICE (LOS):				B			A



Level of Service Worksheet (Circular 212 Method)



I/S #:
33

PROJECT TITLE: SPW, POC Addendum
North-South Street: 19th St
Scenario: Future No Project
Count Date: 1/0/1900

East-West Street: Pacific

Analyst: <Fehr & Peers> **Date:** <date>

		AM			PM		
		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
No. of Phases				2			2
Opposed Ø'ing: N/S-1, E/W-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		NB-- 0	SB-- 0	0	NB-- 0	SB-- 0	0
ATSAC-1 or ATSAC+ATCS-2?		EB-- 0	WB-- 0	0	EB-- 0	WB-- 0	0
Override Capacity				2			2
Override Capacity				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	↶ Left	17	1	17	29	1	29
	↶↷ Left-Through		0			0	
	→ Through	535	1	535	456	1	456
	↷ Through-Right		0			0	
	↷ Right	17	1	17	16	1	16
	↷↶ Left-Through-Right		0			0	
	↷↶ Left-Right		0			0	
SOUTHBOUND	↷ Left	15	1	15	27	1	27
	↷↶ Left-Through		0			0	
	→ Through	247	1	247	675	1	675
	↷ Through-Right		0			0	
	↷ Right	27	1	27	42	1	42
	↷↶ Left-Through-Right		0			0	
	↷↶ Left-Right		0			0	
EASTBOUND	↶ Left	36	0	36	45	0	45
	↶↷ Left-Through		0			0	
	→ Through	108	0	183	43	0	120
	↷ Through-Right		0			0	
	↷ Right	39	0	0	32	0	0
	↷↶ Left-Through-Right		1			1	
	↷↶ Left-Right		0			0	
WESTBOUND	↶ Left	10	0	10	42	0	42
	↶↷ Left-Through		0			0	
	→ Through	53	0	73	111	0	174
	↷ Through-Right		0			0	
	↷ Right	10	0	0	21	0	0
	↷↶ Left-Through-Right		1			1	
	↷↶ Left-Right		0			0	
CRITICAL VOLUMES				<i>North-South:</i> 550			<i>North-South:</i> 704
				<i>East-West:</i> 193			<i>East-West:</i> 219
				SUM: 743			SUM: 923
VOLUME/CAPACITY (V/C) RATIO:				0.495			0.615
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.395			0.515
LEVEL OF SERVICE (LOS):				A			A



Level of Service Worksheet (Circular 212 Method)



I/S #:
34

PROJECT TITLE: SPW, POC Addendum
North-South Street: Gaffey St
Scenario: Future No Project
Count Date: 1/0/1900

East-West Street: 13th St.

Analyst: <Fehr & Peers> **Date:** <date>

		AM			PM		
				2			2
No. of Phases				0			0
Opposed Ø'ing: N/S-1, E/W-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		<i>NB--</i> 0	<i>SB--</i> 0	0	<i>NB--</i> 0	<i>SB--</i> 0	0
		<i>EB--</i> 0	<i>WB--</i> 0	0	<i>EB--</i> 0	<i>WB--</i> 0	0
ATSAC-1 or ATSAC+ATCS-2?				2			2
Override Capacity				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	Left	38	1	38	71	1	71
	Left-Through		0			0	
	Through	1460	1	766	1028	1	538
	Through-Right		1			1	
	Right	71	0	71	48	0	48
	Left-Through-Right		0			0	
	Left-Right		0			0	
SOUTHBOUND	Left	34	1	34	95	1	95
	Left-Through		0			0	
	Through	819	1	484	1224	1	656
	Through-Right		1			1	
	Right	149	0	149	87	0	87
	Left-Through-Right		0			0	
	Left-Right		0			0	
EASTBOUND	Left	215	0	215	195	0	195
	Left-Through		0			0	
	Through	307	0	579	159	0	446
	Through-Right		0			0	
	Right	57	0	0	92	0	0
	Left-Through-Right		1			1	
	Left-Right		0			0	
WESTBOUND	Left	60	0	60	33	0	33
	Left-Through		0			0	
	Through	346	0	597	200	0	310
	Through-Right		0			0	
	Right	191	0	0	77	0	0
	Left-Through-Right		1			1	
	Left-Right		0			0	
CRITICAL VOLUMES				<i>North-South:</i> 800			<i>North-South:</i> 727
				<i>East-West:</i> 812			<i>East-West:</i> 505
				SUM: 1612			SUM: 1232
VOLUME/CAPACITY (V/C) RATIO:				1.075			0.821
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.975			0.721
LEVEL OF SERVICE (LOS):				E			C



Level of Service Worksheet (Circular 212 Method)



I/S #:
5

PROJECT TITLE: SPW, POC Addendum
North-South Street: Gaffey St
Scenario: Future No Project
Count Date: 1/0/1900

East-West Street: 9th St

Analyst: <Fehr & Peers> **Date:** <date>

		SAT					
No. of Phases				2			2
Opposed Ø'ing: N/S-1, EW-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		NB-- 0	SB-- 0	0	NB-- 0	SB-- 0	0
ATSAC-1 or ATSAC+ATCS-2?		EB-- 0	WB-- 0	0	EB-- 0	WB-- 0	0
Override Capacity				2			2
				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	↵ Left	76	1	76	0	1	0
	↵↔ Left-Through		0			0	
	→ Through	1264	2	632	0	2	0
	↵↔ Through-Right		0			0	
	↵ Right	53	1	12	0	1	0
	↵↔ Left-Through-Right		0			0	
	↵↔ Left-Right		0			0	
SOUTHBOUND	↵↔ Left	139	1	139	0	1	0
	↵↔ Left-Through		0			0	
	→ Through	1372	1	734	0	1	0
	↵↔ Through-Right		1			1	
	↵ Right	95	0	95	0	0	0
	↵↔ Left-Through-Right		0			0	
	↵↔ Left-Right		0			0	
EASTBOUND	↵ Left	202	1	202	0	1	0
	↵↔ Left-Through		0			0	
	→ Through	237	1	237	0	1	0
	↵↔ Through-Right		0			0	
	↵ Right	64	1	26	0	1	0
	↵↔ Left-Through-Right		0			0	
	↵↔ Left-Right		0			0	
WESTBOUND	↵ Left	83	1	83	0	1	0
	↵↔ Left-Through		0			0	
	→ Through	211	0	344	0	0	0
	↵↔ Through-Right		1			1	
	↵ Right	133	0	0	0	0	0
	↵↔ Left-Through-Right		0			0	
	↵↔ Left-Right		0			0	
CRITICAL VOLUMES				<i>North-South:</i> 810			<i>North-South:</i> 0
				<i>East-West:</i> 546			<i>East-West:</i> 0
				<i>SUM:</i> 1356			<i>SUM:</i> 0
VOLUME/CAPACITY (V/C) RATIO:				0.904			0.000
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.804			0.000
LEVEL OF SERVICE (LOS):				D			A



Level of Service Worksheet (Circular 212 Method)



I/S #:
6

PROJECT TITLE: SPW, POC Addendum
North-South Street: Gaffey St
Scenario: Future No Project
Count Date: 1/0/1900

East-West Street: 7th St

Analyst: <Fehr & Peers> **Date:** <date>

		SAT					
No. of Phases				2			2
Opposed Ø'ing: N/S-1, E/W-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		NB-- 0	SB-- 0	0	NB-- 0	SB-- 0	0
ATSAC-1 or ATSAC+ATCS-2?		EB-- 0	WB-- 0	0	EB-- 0	WB-- 0	0
Override Capacity				2			2
				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	↶ Left	29	1	29	0	1	0
	↷ Left-Through		0		0	0	0
	→ Through	1614	2	807	0	2	0
	↷ Through-Right		0		0	0	0
	↘ Right	49	1	13	0	1	0
	↷ Left-Through-Right		0		0	0	0
	↷ Left-Right		0		0	0	
SOUTHBOUND	↷ Left	162	1	162	0	1	0
	↶ Left-Through		0		0	0	0
	→ Through	1406	1	763	0	1	0
	↷ Through-Right		1		0	1	0
	↘ Right	119	0	119	0	0	0
	↷ Left-Through-Right		0		0	0	0
	↷ Left-Right		0		0	0	
EASTBOUND	↶ Left	116	1	116	0	1	0
	↷ Left-Through		0		0	0	0
	→ Through	123	0	176	0	0	0
	↷ Through-Right		1		0	1	0
	↘ Right	53	0	0	0	0	0
	↷ Left-Through-Right		0		0	0	0
	↷ Left-Right		0		0	0	
WESTBOUND	↶ Left	73	1	73	0	1	0
	↷ Left-Through		0		0	0	0
	→ Through	125	0	232	0	0	0
	↷ Through-Right		1		0	1	0
	↘ Right	107	0	0	0	0	0
	↷ Left-Through-Right		0		0	0	0
	↷ Left-Right		0		0	0	
CRITICAL VOLUMES				<i>North-South:</i> 969			<i>North-South:</i> 0
				<i>East-West:</i> 348			<i>East-West:</i> 0
				<i>SUM:</i> 1317			<i>SUM:</i> 0
VOLUME/CAPACITY (V/C) RATIO:				0.878			0.000
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.778			0.000
LEVEL OF SERVICE (LOS):				C			A



Level of Service Worksheet (Circular 212 Method)



I/S #:
7

PROJECT TITLE: SPW, POC Addendum
North-South Street: Gaffey St
Scenario: Future No Project
Count Date: 1/0/1900

East-West Street: 6th St

Analyst: <Fehr & Peers> **Date:** <date>

		SAT					
No. of Phases				0			0
Opposed Ø'ing: N/S-1, EW-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		<i>NB--</i> 0	<i>SB--</i> 0	0	<i>NB--</i> 0	<i>SB--</i> 0	0
ATSAC-1 or ATSAC+ATCS-2?		<i>EB--</i> 0	<i>WB--</i> 0	0	<i>EB--</i> 0	<i>WB--</i> 0	0
Override Capacity				2			2
				1200			1200
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	Left	73	1	73	0	1	0
	Left-Through		0		0	0	
	Through	1698	1	873	0	1	0
	Through-Right		1		0	1	
	Right	47	0	47	0	0	0
	Left-Through-Right		0		0	0	
	Left-Right		0		0	0	
SOUTHBOUND	Left	101	1	101	0	1	0
	Left-Through		0		0	0	
	Through	1642	1	841	0	1	0
	Through-Right		1		0	1	
	Right	39	0	39	0	0	0
	Left-Through-Right		0		0	0	
	Left-Right		0		0	0	
EASTBOUND	Left	11	0	11	0	0	0
	Left-Through		1		0	1	
	Through	14	0	25	0	0	0
	Through-Right		0		0	0	
	Right	64	1	28	0	1	0
	Left-Through-Right		0		0	0	
	Left-Right		0		0	0	
WESTBOUND	Left	10	0	10	0	0	0
	Left-Through		1		0	1	
	Through	15	0	25	0	0	0
	Through-Right		0		0	0	
	Right	103	1	53	0	1	0
	Left-Through-Right		0		0	0	
	Left-Right		0		0	0	
CRITICAL VOLUMES			<i>North-South:</i>	974	<i>North-South:</i>		0
			<i>East-West:</i>	64	<i>East-West:</i>		0
			<i>SUM:</i>	1038	<i>SUM:</i>		0
VOLUME/CAPACITY (V/C) RATIO:				0.865			0.000
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.765			0.000
LEVEL OF SERVICE (LOS):				C			A



Level of Service Worksheet (Circular 212 Method)



I/S #:
8

PROJECT TITLE: SPW, POC Addendum
North-South Street: Gaffey St
Scenario: Future No Project
Count Date: 1/0/1900

East-West Street: 5th St

Analyst: <Fehr & Peers> **Date:** <date>

		SAT					
				3			3
No. of Phases				3			3
Opposed Ø'ing: N/S-1, E/W-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		<i>NB--</i> 0	<i>SB--</i> 0	0	<i>NB--</i> 0	<i>SB--</i> 0	0
		<i>EB--</i> 0	<i>WB--</i> 0	0	<i>EB--</i> 0	<i>WB--</i> 0	0
ATSAC-1 or ATSAC+ATCS-2?				2			2
Override Capacity				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	Left	50	1	50	0	1	0
	Left-Through		0		0	0	
	Through	1679	2	840	0	2	0
	Through-Right		0		0	0	
	Right	32	1	10	0	1	0
	Left-Through-Right		0		0	0	
	Left-Right		0		0		0
SOUTHBOUND	Left	125	1	125	0	1	0
	Left-Through		0		0	0	
	Through	1769	2	885	0	2	0
	Through-Right		0		0	0	
	Right	90	1	31	0	1	0
	Left-Through-Right		0		0	0	
	Left-Right		0		0		0
EASTBOUND	Left	118	1	118	0	1	0
	Left-Through		0		0	0	
	Through	91	0	120	0	0	0
	Through-Right		1		0	1	
	Right	29	0	0	0	0	0
	Left-Through-Right		0		0	0	
	Left-Right		0		0		0
WESTBOUND	Left	44	1	44	0	1	0
	Left-Through		0		0	0	
	Through	107	0	228	0	0	0
	Through-Right		1		0	1	
	Right	121	0	0	0	0	0
	Left-Through-Right		0		0	0	
	Left-Right		0		0		0
CRITICAL VOLUMES			<i>North-South:</i>	965		<i>North-South:</i>	0
			<i>East-West:</i>	346		<i>East-West:</i>	0
			<i>SUM:</i>	1311		<i>SUM:</i>	0
VOLUME/CAPACITY (V/C) RATIO:				0.920			0.000
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.820			0.000
LEVEL OF SERVICE (LOS):				D			A



Level of Service Worksheet (Circular 212 Method)



I/S #:
9

PROJECT TITLE: SPW, POC Addendum
North-South Street: Gaffey St
Scenario: Future No Project
Count Date: 1/0/1900

East-West Street: 1st St

Analyst: <Fehr & Peers> **Date:** <date>

		SAT					
				4			4
		No. of Phases		2			2
		Opposed Ø'ing: N/S-1, EW-2 or Both-3?		0			0
		Right Turns: FREE-1, NRTOR-2 or OLA-3?		0			0
		ATSAC-1 or ATSAC+ATCS-2?		2			2
		Override Capacity		0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	↶	49	1	49	0	1	0
	↷		0		0	0	
	→	1682	2	569	0	2	0
	↷		1		0	1	
	→	25	0	25	0	0	0
	↶		0		0	0	
SOUTHBOUND	↷	198	1	198	0	1	0
	↶		0		0	0	
	→	2288	2	938	0	2	0
	↶		1		0	1	
	→	527	0	527	0	0	0
	↷		0		0	0	
EASTBOUND	↶	763	2	420	0	2	0
	↷		0		0	0	
	→	178	0	287	0	0	0
	↷		1		0	1	
	→	109	0	0	0	0	0
	↶		0		0	0	
WESTBOUND	↶	64	1	64	0	1	0
	↷		0		0	0	
	→	205	1	205	0	1	0
	↷		0		0	0	
	→	216	1	117	0	1	0
	↶		0		0	0	
CRITICAL VOLUMES		<i>North-South:</i>		987	<i>North-South:</i>		0
		<i>East-West:</i>		625	<i>East-West:</i>		0
		<i>SUM:</i>		1612	<i>SUM:</i>		0
VOLUME/CAPACITY (V/C) RATIO:				1.172			0.000
V/C LESS ATSAC/ATCS ADJUSTMENT:				1.072			0.000
LEVEL OF SERVICE (LOS):				F			A



Level of Service Worksheet (Circular 212 Method)



I/S #:
11

PROJECT TITLE: SPW, POC Addendum
North-South Street: Summerland Ave
Scenario: Future No Project
Count Date: 1/0/1900

East-West Street: Gaffey St
Analyst: <Fehr & Peers> **Date:** <date>

		SAT					
				3			3
No. of Phases				3			3
Opposed Ø'ing: N/S-1, E/W-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		NB-- 0	SB-- 0	0	NB-- 0	SB-- 0	0
ATSAC-1 or ATSAC+ATCS-2?		EB-- 0	WB-- 0	0	EB-- 0	WB-- 0	0
Override Capacity				2			2
				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	Left	200	1	200	0	1	0
	Left-Through		0		0	0	
	Through	625	1	332	0	1	0
	Through-Right		1		0	1	
	Right	38	0	38	0	0	0
	Left-Through-Right		0		0	0	
	Left-Right		0		0	0	
SOUTHBOUND	Left	18	1	18	0	1	0
	Left-Through		0		0	0	
	Through	694	2	347	0	2	0
	Through-Right		0		0	0	
	Right	216	1	112	0	1	0
	Left-Through-Right		0		0	0	
	Left-Right		0		0	0	
EASTBOUND	Left	209	1	209	0	1	0
	Left-Through		0		0	0	
	Through	6	0	98	0	0	0
	Through-Right		1		0	1	
	Right	92	0	0	0	0	0
	Left-Through-Right		0		0	0	
	Left-Right		0		0	0	
WESTBOUND	Left	432	2	238	0	2	0
	Left-Through		0		0	0	
	Through	153	0	318	0	0	0
	Through-Right		1		0	1	
	Right	165	0	0	0	0	0
	Left-Through-Right		0		0	0	
	Left-Right		0		0	0	
CRITICAL VOLUMES				<i>North-South:</i> 547			<i>North-South:</i> 0
				<i>East-West:</i> 527			<i>East-West:</i> 0
				<i>SUM:</i> 1074			<i>SUM:</i> 0
VOLUME/CAPACITY (V/C) RATIO:				0.754			0.000
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.654			0.000
LEVEL OF SERVICE (LOS):				B			A



Level of Service Worksheet (Circular 212 Method)



I/S #:
12

PROJECT TITLE: SPW, POC Addendum
North-South Street: Pacific Ave
Scenario: Future No Project
Count Date: 1/0/1900

East-West Street: 22nd St

Analyst: <Fehr & Peers> **Date:** <date>

		SAT					
No. of Phases				2			2
Opposed Ø'ing: N/S-1, EW-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		NB-- 0	SB-- 0	0	NB-- 0	SB-- 0	0
ATSAC-1 or ATSAC+ATCS-2?		EB-- 0	WB-- 0	0	EB-- 0	WB-- 0	0
Override Capacity				2			2
				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	↶ Left	33	1	33	0	1	0
	↷ Left-Through		0			0	
	→ Through	343	1	343	0	1	0
	↷ Through-Right		0			0	
	↷ Right	113	1	113	0	1	0
	↷ Left-Through-Right		0			0	
	↷ Left-Right		0			0	
SOUTHBOUND	↷ Left	58	1	58	0	1	0
	↶ Left-Through		0			0	
	→ Through	351	1	351	0	1	0
	↶ Through-Right		0			0	
	↶ Right	64	1	64	0	1	0
	↶ Left-Through-Right		0			0	
	↶ Left-Right		0			0	
EASTBOUND	↶ Left	22	0	22	0	0	0
	↷ Left-Through		0			0	
	→ Through	178	0	241	0	0	0
	↷ Through-Right		0			0	
	↷ Right	41	0	0	0	0	0
	↷ Left-Through-Right		1			1	
	↷ Left-Right		0			0	
WESTBOUND	↷ Left	180	0	180	0	0	0
	↶ Left-Through		0			0	
	→ Through	159	0	390	0	0	0
	↶ Through-Right		0			0	
	↶ Right	51	0	0	0	0	0
	↶ Left-Through-Right		1			1	
	↶ Left-Right		0			0	
CRITICAL VOLUMES			<i>North-South:</i>	401		<i>North-South:</i>	0
			<i>East-West:</i>	421		<i>East-West:</i>	0
			SUM:	822		SUM:	0
VOLUME/CAPACITY (V/C) RATIO:				0.548			0.000
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.448			0.000
LEVEL OF SERVICE (LOS):				A			A



Level of Service Worksheet (Circular 212 Method)



I/S #:
13

PROJECT TITLE: SPW, POC Addendum
North-South Street: Pacific Ave
Scenario: Future No Project
Count Date: 1/0/1900

East-West Street: 9th St

Analyst: <Fehr & Peers> **Date:** <date>

		SAT					
No. of Phases				2			2
Opposed Ø'ing: N/S-1, EW-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		<i>NB--</i> 0	<i>SB--</i> 0	0	<i>NB--</i> 0	<i>SB--</i> 0	0
ATSAC-1 or ATSAC+ATCS-2?		<i>EB--</i> 0	<i>WB--</i> 0	0	<i>EB--</i> 0	<i>WB--</i> 0	0
Override Capacity				2			2
				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	Left	66	1	66	0	1	0
	Left-Through		0			0	
	Through	721	1	721	0	1	0
	Through-Right		0			0	
	Right	34	1	8	0	1	0
	Left-Through-Right		0			0	
	Left-Right		0			0	
SOUTHBOUND	Left	102	1	102	0	1	0
	Left-Through		0			0	
	Through	738	1	738	0	1	0
	Through-Right		0			0	
	Right	49	1	3	0	1	0
	Left-Through-Right		0			0	
	Left-Right		0			0	
EASTBOUND	Left	93	1	93	0	1	0
	Left-Through		0			0	
	Through	179	0	277	0	0	0
	Through-Right		1			1	
	Right	98	0	0	0	0	0
	Left-Through-Right		0			0	
	Left-Right		0			0	
WESTBOUND	Left	52	1	52	0	1	0
	Left-Through		0			0	
	Through	139	0	204	0	0	0
	Through-Right		1			1	
	Right	65	0	0	0	0	0
	Left-Through-Right		0			0	
	Left-Right		0			0	
CRITICAL VOLUMES			<i>North-South:</i>	823	<i>North-South:</i>		0
			<i>East-West:</i>	329	<i>East-West:</i>		0
			<i>SUM:</i>	1152	<i>SUM:</i>		0
VOLUME/CAPACITY (V/C) RATIO:				0.768			0.000
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.668			0.000
LEVEL OF SERVICE (LOS):				B			A



Level of Service Worksheet (Circular 212 Method)



I/S #:
14

PROJECT TITLE: SPW, POC Addendum
North-South Street: Pacific Ave
Scenario: Future No Project
Count Date: 1/0/1900

East-West Street: 7th St

Analyst: <Fehr & Peers> **Date:** <date>

		SAT					
No. of Phases				2			2
Opposed Ø'ing: N/S-1, EW-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		<i>NB--</i> 0	<i>SB--</i> 0	0	<i>NB--</i> 0	<i>SB--</i> 0	0
ATSAC-1 or ATSAC+ATCS-2?		<i>EB--</i> 0	<i>WB--</i> 0	0	<i>EB--</i> 0	<i>WB--</i> 0	0
Override Capacity				2			2
				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	Left	75	1	75	0	1	0
	Left-Through		0			0	
	Through	779	1	779	0	1	0
	Through-Right		0			0	
	Right	42	1	9	0	1	0
	Left-Through-Right		0			0	
	Left-Right		0			0	
SOUTHBOUND	Left	25	1	25	0	1	0
	Left-Through		0			0	
	Through	758	1	758	0	1	0
	Through-Right		0			0	
	Right	55	1	27	0	1	0
	Left-Through-Right		0			0	
	Left-Right		0			0	
EASTBOUND	Left	56	1	56	0	1	0
	Left-Through		0			0	
	Through	186	0	267	0	0	0
	Through-Right		1			1	
	Right	81	0	0	0	0	0
	Left-Through-Right		0			0	
	Left-Right		0			0	
WESTBOUND	Left	66	1	66	0	1	0
	Left-Through		0			0	
	Through	129	0	172	0	0	0
	Through-Right		1			1	
	Right	43	0	0	0	0	0
	Left-Through-Right		0			0	
	Left-Right		0			0	
CRITICAL VOLUMES		<i>North-South:</i>		833	<i>North-South:</i>		0
		<i>East-West:</i>		333	<i>East-West:</i>		0
		<i>SUM:</i>		1166	<i>SUM:</i>		0
VOLUME/CAPACITY (V/C) RATIO:				0.777			0.000
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.677			0.000
LEVEL OF SERVICE (LOS):				B			A



Level of Service Worksheet (Circular 212 Method)



I/S #:
15

PROJECT TITLE: SPW, POC Addendum
North-South Street: Pacific Ave
Scenario: Future No Project
Count Date: 1/0/1900

East-West Street: 6th St

Analyst: <Fehr & Peers> **Date:** <date>

		SAT					
No. of Phases				4			4
Opposed Ø'ing: N/S-1, E/W-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		NB-- 0	SB-- 0	0	NB-- 0	SB-- 0	0
ATSAC-1 or ATSAC+ATCS-2?		EB-- 0	WB-- 0	0	EB-- 0	WB-- 0	0
Override Capacity				2			2
				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	↵ Left	42	1	42	0	1	0
	↵↔ Left-Through		0			0	
	→ Through	742	1	742	0	1	0
	↗ Through-Right		0			0	
	↘ Right	87	1	87	0	1	0
	↗↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
SOUTHBOUND	↵ Left	65	1	65	0	1	0
	↵↔ Left-Through		0			0	
	→ Through	789	1	789	0	1	0
	↗ Through-Right		0			0	
	↘ Right	38	1	38	0	1	0
	↗↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
EASTBOUND	↵ Left	33	0	33	0	0	0
	↵↔ Left-Through		0			0	
	→ Through	146	0	213	0	0	0
	↗ Through-Right		0			0	
	↘ Right	34	0	0	0	0	0
	↗↔ Left-Through-Right		1			1	
	↘↔ Left-Right		0			0	
WESTBOUND	↵ Left	66	0	66	0	0	0
	↵↔ Left-Through		0			0	
	→ Through	106	0	230	0	0	0
	↗ Through-Right		0			0	
	↘ Right	58	0	0	0	0	0
	↗↔ Left-Through-Right		1			1	
	↘↔ Left-Right		0			0	
CRITICAL VOLUMES		<i>North-South:</i>		831	<i>North-South:</i>		0
		<i>East-West:</i>		279	<i>East-West:</i>		0
		<i>SUM:</i>		1110	<i>SUM:</i>		0
VOLUME/CAPACITY (V/C) RATIO:				0.807			0.000
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.707			0.000
LEVEL OF SERVICE (LOS):				C			A



Level of Service Worksheet (Circular 212 Method)



I/S #:
16

PROJECT TITLE: SPW, POC Addendum
North-South Street: Pacific Ave
Scenario: Future No Project
Count Date: 1/0/1900

East-West Street: 5th St

Analyst: <Fehr & Peers> **Date:** <date>

		SAT					
No. of Phases				2			2
Opposed Ø'ing: N/S-1, E/W-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		NB-- 0	SB-- 0	0	NB-- 0	SB-- 0	0
ATSAC-1 or ATSAC+ATCS-2?		EB-- 0	WB-- 0	0	EB-- 0	WB-- 0	0
Override Capacity				2			2
				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	Left	34	1	34	0	1	0
	Left-Through		0		0	0	
	Through	750	1	750	0	1	0
	Through-Right		0		0	0	
	Right	86	1	41	0	1	0
	Left-Through-Right		0		0	0	
	Left-Right		0		0		0
SOUTHBOUND	Left	83	1	83	0	1	0
	Left-Through		0		0	0	
	Through	717	1	717	0	1	0
	Through-Right		0		0	0	
	Right	46	1	28	0	1	0
	Left-Through-Right		0		0	0	
	Left-Right		0		0		0
EASTBOUND	Left	36	1	36	0	1	0
	Left-Through		0		0	0	
	Through	114	0	175	0	0	0
	Through-Right		1		0	1	
	Right	61	0	0	0	0	0
	Left-Through-Right		0		0	0	
	Left-Right		0		0		0
WESTBOUND	Left	91	1	91	0	1	0
	Left-Through		0		0	0	
	Through	135	0	236	0	0	0
	Through-Right		1		0	1	
	Right	101	0	0	0	0	0
	Left-Through-Right		0		0	0	
	Left-Right		0		0		0
CRITICAL VOLUMES			<i>North-South:</i>	833		<i>North-South:</i>	0
			<i>East-West:</i>	272		<i>East-West:</i>	0
			<i>SUM:</i>	1105		<i>SUM:</i>	0
VOLUME/CAPACITY (V/C) RATIO:				0.737			0.000
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.637			0.000
LEVEL OF SERVICE (LOS):				B			A



Level of Service Worksheet (Circular 212 Method)



I/S #:
17

PROJECT TITLE: SPW, POC Addendum
North-South Street: Pacific Ave
Scenario: Future No Project
Count Date: 1/0/1900

East-West Street: 1st St

Analyst: <Fehr & Peers> **Date:** <date>

		SAT					
No. of Phases				2			2
Opposed Ø'ing: N/S-1, EW-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		NB-- 0	SB-- 0	0	NB-- 0	SB-- 0	0
ATSAC-1 or ATSAC+ATCS-2?		EB-- 0	WB-- 0	0	EB-- 0	WB-- 0	0
Override Capacity				2			2
				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	Left	136	1	136	0	1	0
	Left-Through		0			0	
	Through	662	1	662	0	1	0
	Through-Right		0			0	
	Right	43	1	43	0	1	0
	Left-Through-Right		0			0	
	Left-Right		0			0	
SOUTHBOUND	Left	26	1	26	0	1	0
	Left-Through		0			0	
	Through	664	1	664	0	1	0
	Through-Right		0			0	
	Right	41	1	41	0	1	0
	Left-Through-Right		0			0	
	Left-Right		0			0	
EASTBOUND	Left	41	0	41	0	0	0
	Left-Through		1			1	
	Through	164	0	205	0	0	0
	Through-Right		0			0	
	Right	101	1	33	0	1	0
	Left-Through-Right		0			0	
	Left-Right		0			0	
WESTBOUND	Left	70	0	70	0	0	0
	Left-Through		1			1	
	Through	152	0	222	0	0	0
	Through-Right		0			0	
	Right	33	1	20	0	1	0
	Left-Through-Right		0			0	
	Left-Right		0			0	
CRITICAL VOLUMES			<i>North-South:</i>	800		<i>North-South:</i>	0
			<i>East-West:</i>	275		<i>East-West:</i>	0
			SUM:	1075		SUM:	0
VOLUME/CAPACITY (V/C) RATIO:				0.717			0.000
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.617			0.000
LEVEL OF SERVICE (LOS):				B			A



Level of Service Worksheet (Circular 212 Method)



I/S #:
20

PROJECT TITLE: SPW, POC Addendum
North-South Street: Miner St
Scenario: Future No Project
Count Date: 1/0/1900

East-West Street: 22nd St

Analyst: <Fehr & Peers> **Date:** <date>

		SAT					
				4			4
No. of Phases				4			4
Opposed Ø'ing: N/S-1, E/W-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		<i>NB--</i> 0	<i>SB--</i> 0	0	<i>NB--</i> 0	<i>SB--</i> 0	0
		<i>EB--</i> 0	<i>WB--</i> 0	0	<i>EB--</i> 0	<i>WB--</i> 0	0
ATSAC-1 or ATSAC+ATCS-2?				2			2
Override Capacity				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	Left	64	1	64	0	1	0
	Left-Through		0			0	
	Through	222	1	140	0	1	0
	Through-Right		1			1	
	Right	58	0	58	0	0	0
	Left-Through-Right		0			0	
	Left-Right		0			0	
SOUTHBOUND	Left	25	1	25	0	1	0
	Left-Through		0			0	
	Through	225	1	225	0	1	0
	Through-Right		1			1	
	Right	254	0	142	0	0	0
	Left-Through-Right		0			0	
	Left-Right		0			0	
EASTBOUND	Left	225	1	225	0	1	0
	Left-Through		0			0	
	Through	73	1	67	0	1	0
	Through-Right		1			1	
	Right	60	0	60	0	0	0
	Left-Through-Right		0			0	
	Left-Right		0			0	
WESTBOUND	Left	56	1	56	0	1	0
	Left-Through		0			0	
	Through	66	1	55	0	1	0
	Through-Right		1			1	
	Right	44	0	44	0	0	0
	Left-Through-Right		0			0	
	Left-Right		0			0	
CRITICAL VOLUMES				<i>North-South:</i> 289			<i>North-South:</i> 0
				<i>East-West:</i> 280			<i>East-West:</i> 0
				<i>SUM:</i> 569			<i>SUM:</i> 0
VOLUME/CAPACITY (V/C) RATIO:				0.414			0.000
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.314			0.000
LEVEL OF SERVICE (LOS):				A			A



Level of Service Worksheet (Circular 212 Method)



I/S #:
21

PROJECT TITLE: SPW, POC Addendum
North-South Street: Harbor Bl / Miner St
Scenario: Future No Project
Count Date: 1/0/1900

East-West Street: Crescent Av

Analyst: <Fehr & Peers> **Date:** <date>

		SAT					
No. of Phases				0			0
Opposed Ø'ing: N/S-1, E/W-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		<i>NB--</i> 0	<i>SB--</i> 0	0	<i>NB--</i> 0	<i>SB--</i> 0	0
		<i>EB--</i> 0	<i>WB--</i> 0	0	<i>EB--</i> 0	<i>WB--</i> 0	0
ATSAC-1 or ATSAC+ATCS-2?				2			2
Override Capacity				1200			1200
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	Left	4	1	4	0	1	0
	Left-Through		0		0	0	
	Through	476	2	238	0	2	0
	Through-Right		0		0	0	
	Right	0	0	0	0	0	0
	Left-Through-Right		0		0	0	
	Left-Right		0		0		0
SOUTHBOUND	Left	0	0	0	0	0	0
	Left-Through		0		0	0	
	Through	478	1	326	0	1	0
	Through-Right		1		0	1	
	Right	174	0	174	0	0	0
	Left-Through-Right		0		0	0	
	Left-Right		0		0		0
EASTBOUND	Left	102	0	102	0	0	0
	Left-Through		0		0	0	
	Through	0	0	0	0	0	0
	Through-Right		0		0	0	
	Right	2	0	104	0	0	0
	Left-Through-Right		0		0	0	
	Left-Right		1		1		0
WESTBOUND	Left	0	0	0	0	0	0
	Left-Through		0		0	0	
	Through	0	0	0	0	0	0
	Through-Right		0		0	0	
	Right	0	0	0	0	0	0
	Left-Through-Right		0		0	0	
	Left-Right		0		0		0
CRITICAL VOLUMES			<i>North-South:</i>	330	<i>North-South:</i>		0
			<i>East-West:</i>	104	<i>East-West:</i>		0
			<i>SUM:</i>	434	<i>SUM:</i>		0
VOLUME/CAPACITY (V/C) RATIO:				0.362			0.000
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.262			0.000
LEVEL OF SERVICE (LOS):				A			A



Level of Service Worksheet (Circular 212 Method)



I/S #:
22

PROJECT TITLE: SPW, POC Addendum
North-South Street: Harbor Blvd
Scenario: Future No Project
Count Date: 1/0/1900

East-West Street: 7th St

Analyst: <Fehr & Peers> **Date:** <date>

		SAT					
				3			3
		No. of Phases					
		Opposed Ø'ing: N/S-1, EW-2 or Both-3?					
		Right Turns: FREE-1, NRTOR-2 or OLA-3?		NB-- 0	SB-- 0	NB-- 0	SB-- 0
		ATSAC-1 or ATSAC+ATCS-2?		EB-- 0	WB-- 0	EB-- 0	WB-- 0
		Override Capacity					
				2		2	
				0		0	
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	Left	11	1	11	0	1	0
	Left-Through		0			0	
	Through	612	2	306	0	2	0
	Through-Right		0			0	
	Right	0	0	0	0	0	0
	Left-Through-Right		0			0	
SOUTHBOUND	Left	0	0	0	0	0	0
	Left-Through		0			0	
	Through	732	2	366	0	2	0
	Through-Right		0			0	
	Right	186	1	117	0	1	0
	Left-Through-Right		0			0	
EASTBOUND	Left	252	2	139	0	2	0
	Left-Through		0			0	
	Through	0	0	0	0	0	0
	Through-Right		0			0	
	Right	27	1	22	0	1	0
	Left-Through-Right		0			0	
WESTBOUND	Left	0	0	0	0	0	0
	Left-Through		0			0	
	Through	0	0	0	0	0	0
	Through-Right		0			0	
	Right	0	0	0	0	0	0
	Left-Through-Right		0			0	
CRITICAL VOLUMES		<i>North-South:</i>		377	<i>North-South:</i>		0
		<i>East-West:</i>		139	<i>East-West:</i>		0
		<i>SUM:</i>		516	<i>SUM:</i>		0
VOLUME/CAPACITY (V/C) RATIO:				0.362			0.000
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.262			0.000
LEVEL OF SERVICE (LOS):				A			A



Level of Service Worksheet (Circular 212 Method)



I/S #:
23

PROJECT TITLE: SPW, POC Addendum
North-South Street: Harbor Blvd
Scenario: Future No Project
Count Date: 1/0/1900

East-West Street: 6th St

Analyst: <Fehr & Peers> **Date:** <date>

		SAT					
				3			3
No. of Phases				3			3
Opposed Ø'ing: N/S-1, E/W-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		<i>NB--</i> 0	<i>SB--</i> 0	0	<i>NB--</i> 0	<i>SB--</i> 0	0
		<i>EB--</i> 0	<i>WB--</i> 0	0	<i>EB--</i> 0	<i>WB--</i> 0	0
ATSAC-1 or ATSAC+ATCS-2?				2			2
Override Capacity				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	Left	14	1	14	0	1	0
	Left-Through		0		0	0	
	Through	751	1	447	0	1	0
	Through-Right		1		0	1	
	Right	143	0	143	0	0	0
	Left-Through-Right		0		0	0	
	Left-Right		0		0	0	
SOUTHBOUND	Left	422	1	422	0	1	0
	Left-Through		0		0	0	
	Through	825	1	441	0	1	0
	Through-Right		1		0	1	
	Right	56	0	56	0	0	0
	Left-Through-Right		0		0	0	
	Left-Right		0		0	0	
EASTBOUND	Left	49	1	49	0	1	0
	Left-Through		0		0	0	
	Through	138	0	154	0	0	0
	Through-Right		1		0	1	
	Right	16	0	0	0	0	0
	Left-Through-Right		0		0	0	
	Left-Right		0		0	0	
WESTBOUND	Left	41	1	41	0	1	0
	Left-Through		0		0	0	
	Through	146	1	146	0	1	0
	Through-Right		0		0	0	
	Right	536	1	325	0	1	0
	Left-Through-Right		0		0	0	
	Left-Right		0		0	0	
CRITICAL VOLUMES			<i>North-South:</i>	869		<i>North-South:</i>	0
			<i>East-West:</i>	374		<i>East-West:</i>	0
			<i>SUM:</i>	1243		<i>SUM:</i>	0
VOLUME/CAPACITY (V/C) RATIO:				0.872			0.000
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.772			0.000
LEVEL OF SERVICE (LOS):				C			A



Level of Service Worksheet (Circular 212 Method)



I/S #:
24

PROJECT TITLE: SPW, POC Addendum
North-South Street: Harbor Blvd
Scenario: Future No Project
Count Date: 1/0/1900

East-West Street: 5th St

Analyst: <Fehr & Peers> **Date:** <date>

		SAT					
				3			3
No. of Phases				3			3
Opposed Ø'ing: N/S-1, EW-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		<i>NB--</i> 0	<i>SB--</i> 0	0	<i>NB--</i> 0	<i>SB--</i> 0	0
		<i>EB--</i> 0	<i>WB--</i> 0	0	<i>EB--</i> 0	<i>WB--</i> 0	0
ATSAC-1 or ATSAC+ATCS-2?				2			2
Override Capacity				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	Left	25	1	25	0	1	0
	Left-Through		0			0	
	Through	1225	1	615	0	1	0
	Through-Right		1			1	
	Right	4	0	4	0	0	0
	Left-Through-Right		0			0	
	Left-Right		0			0	
SOUTHBOUND	Left	0	1	0	0	1	0
	Left-Through		0			0	
	Through	1232	1	650	0	1	0
	Through-Right		1			1	
	Right	68	0	68	0	0	0
	Left-Through-Right		0			0	
	Left-Right		0			0	
EASTBOUND	Left	92	1	92	0	1	0
	Left-Through		0			0	
	Through	159	0	200	0	0	0
	Through-Right		1			1	
	Right	41	0	0	0	0	0
	Left-Through-Right		0			0	
	Left-Right		0			0	
WESTBOUND	Left	1	1	1	0	1	0
	Left-Through		0			0	
	Through	50	1	50	0	1	0
	Through-Right		0			0	
	Right	33	1	33	0	1	0
	Left-Through-Right		0			0	
	Left-Right		0			0	
CRITICAL VOLUMES			<i>North-South:</i>	675		<i>North-South:</i>	0
			<i>East-West:</i>	201		<i>East-West:</i>	0
			<i>SUM:</i>	876		<i>SUM:</i>	0
VOLUME/CAPACITY (V/C) RATIO:				0.615			0.000
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.515			0.000
LEVEL OF SERVICE (LOS):				A			A



Level of Service Worksheet (Circular 212 Method)



I/S #:
25

PROJECT TITLE: SPW, POC Addendum
North-South Street: Harbor Blvd
Scenario: Future No Project
Count Date: 1/0/1900

East-West Street: 1st St

Analyst: <Fehr & Peers> **Date:** <date>

		SAT					
No. of Phases				4			4
Opposed Ø'ing: N/S-1, E/W-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		NB-- 0	SB-- 0	0	NB-- 0	SB-- 0	0
ATSAC-1 or ATSAC+ATCS-2?		EB-- 0	WB-- 0	0	EB-- 0	WB-- 0	0
Override Capacity				2			2
				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	↵ Left	35	1	35	0	1	0
	↵↔ Left-Through		0			0	
	→ Through	1399	1	702	0	1	0
	↘ Through-Right		1			1	
	↘ Right	5	0	5	0	0	0
	↘↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
SOUTHBOUND	↵ Left	124	1	124	0	1	0
	↵↔ Left-Through		0			0	
	→ Through	1337	1	712	0	1	0
	↘ Through-Right		1			1	
	↘ Right	87	0	87	0	0	0
	↘↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
EASTBOUND	↵ Left	83	1	83	0	1	0
	↵↔ Left-Through		0			0	
	→ Through	18	0	53	0	0	0
	↘ Through-Right		1			1	
	↘ Right	35	0	0	0	0	0
	↘↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
WESTBOUND	↵ Left	4	0	4	0	0	0
	↵↔ Left-Through		1			1	
	→ Through	17	0	21	0	0	0
	↘ Through-Right		0			0	
	↘ Right	89	1	27	0	1	0
	↘↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
CRITICAL VOLUMES			<i>North-South:</i>	826		<i>North-South:</i>	0
			<i>East-West:</i>	110		<i>East-West:</i>	0
			<i>SUM:</i>	936		<i>SUM:</i>	0
VOLUME/CAPACITY (V/C) RATIO:				0.681			0.000
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.581			0.000
LEVEL OF SERVICE (LOS):				A			A

Level of Service Worksheet (Circular 212 Method)



I/S #:
26

PROJECT TITLE: SPW, POC Addendum
North-South Street: Harbor Blvd
Scenario: Future No Project
Count Date: 1/0/1900

East-West Street: SR 47 EB Off-Ramp / Swinford St
Analyst: <Fehr & Peers> **Date:** <date>

		SAT					
				4			4
No. of Phases				0			0
Opposed Ø'ing: N/S-1, E/W-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		NB-- 0	SB-- 0	0	NB-- 0	SB-- 0	0
ATSAC-1 or ATSAC+ATCS-2?		EB-- 3	WB-- 3	3	EB-- 3	WB-- 3	3
Override Capacity				2			2
Override Capacity				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	↶ Left	384	2	211		2	0
	↶↷ Left-Through		0			0	
	↷ Through	670	1	368		1	0
	↷↶ Through-Right		1			1	
	↷ Right	66	0	66		0	0
	↷↷ Left-Through-Right		0			0	
	↷↷ Left-Right		0			0	
SOUTHBOUND	↷ Left	56	2	31		2	0
	↷↷ Left-Through		0			0	
	↷ Through	255	2	122		2	0
	↷↶ Through-Right		1			1	
	↷ Right	110	0	110		0	0
	↷↷ Left-Through-Right		0			0	
	↷↷ Left-Right		0			0	
EASTBOUND	↶ Left	273	1	273		1	0
	↶↷ Left-Through		0			0	
	↷ Through	140	1	140		1	0
	↷↶ Through-Right		1			1	
	↷ Right	765	1	210		1	0
	↷↷ Left-Through-Right		0			0	
	↷↷ Left-Right		0			0	
WESTBOUND	↶ Left	54	1	54		1	0
	↶↷ Left-Through		0			0	
	↷ Through	91	1	91		1	0
	↷↶ Through-Right		0			0	
	↷ Right	88	1	57		1	0
	↷↷ Left-Through-Right		0			0	
	↷↷ Left-Right		0			0	
CRITICAL VOLUMES				<i>North-South:</i> 399			<i>North-South:</i> 0
				<i>East-West:</i> 364			<i>East-West:</i> 0
				<i>SUM:</i> 763			<i>SUM:</i> 0
VOLUME/CAPACITY (V/C) RATIO:				0.555			0.000
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.455			0.000
LEVEL OF SERVICE (LOS):				A			A



Level of Service Worksheet (Circular 212 Method)



I/S #:
27

PROJECT TITLE: SPW, POC Addendum
North-South Street: Harbor Blvd
Scenario: Future No Project
Count Date: 1/0/1900

East-West Street: SR-47 WB On-Ramp
Analyst: <Fehr & Peers> **Date:** <date>

		SAT					
		No. of Phases					
Opposed Ø'ing: N/S-1, E/W-2 or Both-3?				4			4
Right Turns: FREE-1, NRTOR-2 or OLA-3?		NB-- 3	SB-- 3	3	NB-- 3	SB-- 3	3
ATSAC-1 or ATSAC+ATCS-2?		EB-- 1	WB-- 0	0	EB-- 1	WB-- 0	0
Override Capacity				2			2
				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	Left	798	2	439	0	2	0
	Left-Through		0		0	0	0
	Through	206	0	233	0	0	0
	Through-Right		1		1	1	0
	Right	27	0	0	0	0	0
	Left-Through-Right		0		0	0	0
	Left-Right		0		0	0	0
SOUTHBOUND	Left	25	1	25	0	1	0
	Left-Through		0		0	0	0
	Through	232	2	116	0	2	0
	Through-Right		0		0	0	0
	Right	0	1	0	0	1	0
	Left-Through-Right		0		0	0	0
	Left-Right		0		0	0	0
EASTBOUND	Left	4	1	4	0	1	0
	Left-Through		0		0	0	0
	Through	44	1	44	0	1	0
	Through-Right		0		0	0	0
	Right	136	1	0	0	1	0
	Left-Through-Right		0		0	0	0
	Left-Right		0		0	0	0
WESTBOUND	Left	53	2	29	0	2	0
	Left-Through		0		0	0	0
	Through	35	2	18	0	2	0
	Through-Right		0		0	0	0
	Right	10	1	0	0	1	0
	Left-Through-Right		0		0	0	0
	Left-Right		0		0	0	0
CRITICAL VOLUMES		<i>North-South:</i>		555	<i>North-South:</i>		0
		<i>East-West:</i>		73	<i>East-West:</i>		0
		<i>SUM:</i>		628	<i>SUM:</i>		0
VOLUME/CAPACITY (V/C) RATIO:				0.457			0.000
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.357			0.000
LEVEL OF SERVICE (LOS):				A			A



Level of Service Worksheet (Circular 212 Method)



I/S #:
29

PROJECT TITLE: SPW, POC Addendum
North-South Street: Harbor
Scenario: Future No Project
Count Date: 1/0/1900

East-West Street: O'Farrell

Analyst: <Fehr & Peers> **Date:** <date>

		SAT					
No. of Phases				2			2
Opposed Ø'ing: N/S-1, EW-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		NB-- 0	SB-- 0	0	NB-- 0	SB-- 0	0
ATSAC-1 or ATSAC+ATCS-2?		EB-- 0	WB-- 0	0	EB-- 0	WB-- 0	0
Override Capacity				2			2
				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	↵ Left	9	1	9	0	1	0
	↵↔ Left-Through		0		0	0	
	→ Through	1498	2	749	0	2	0
	↘ Through-Right		0		0	0	
	↘ Right	0	0	0	0	0	0
	↘↔ Left-Through-Right		0		0	0	
	↘↔ Left-Right		0		0		0
SOUTHBOUND	↵ Left	0	0	0	0	0	0
	↵↔ Left-Through		0		0	0	
	→ Through	1946	1	989	0	1	0
	↘ Through-Right		1		0	1	0
	↘ Right	32	0	32	0	0	0
	↘↔ Left-Through-Right		0		0	0	
	↘↔ Left-Right		0		0		0
EASTBOUND	↵ Left	107	1	107	0	1	0
	↵↔ Left-Through		0		0	0	
	→ Through	0	0	0	0	0	0
	↘ Through-Right		0		0	0	
	↘ Right	31	1	27	0	1	0
	↘↔ Left-Through-Right		0		0	0	
	↘↔ Left-Right		0		0		0
WESTBOUND	↵ Left	0	0	0	0	0	0
	↵↔ Left-Through		0		0	0	
	→ Through	0	0	0	0	0	0
	↘ Through-Right		0		0	0	
	↘ Right	0	0	0	0	0	0
	↘↔ Left-Through-Right		0		0	0	
	↘↔ Left-Right		0		0		0
CRITICAL VOLUMES		<i>North-South:</i>		998	<i>North-South:</i>		0
		<i>East-West:</i>		107	<i>East-West:</i>		0
		<i>SUM:</i>		1105	<i>SUM:</i>		0
VOLUME/CAPACITY (V/C) RATIO:				0.737			0.000
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.637			0.000
LEVEL OF SERVICE (LOS):				B			A



Level of Service Worksheet (Circular 212 Method)



I/S #:
30

PROJECT TITLE: SPW, POC Addendum
North-South Street: Harbor
Scenario: Future No Project
Count Date: 1/0/1900

East-West Street: 3rd

Analyst: <Fehr & Peers> **Date:** <date>

		SAT					
		No. of Phases		0		0	
Opposed Ø'ing: N/S-1, E/W-2 or Both-3?				0		0	
Right Turns: FREE-1, NRTOR-2 or OLA-3?		<i>NB--</i> 0	<i>SB--</i> 0	<i>NB--</i> 0	<i>SB--</i> 0	0	
ATSAC-1 or ATSAC+ATCS-2?		<i>EB--</i> 0	<i>WB--</i> 0	<i>EB--</i> 0	<i>WB--</i> 0	0	
Override Capacity		2		2		2	
		1200		1200		1200	
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	Left	31	1	31	0	1	0
	Left-Through		0		0	0	0
	Through	1375	2	688	0	2	0
	Through-Right		0		0	0	0
	Right	0	0	0	0	0	0
	Left-Through-Right		0	0		0	0
	Left-Right		0		0	0	0
SOUTHBOUND	Left	0	0	0	0	0	0
	Left-Through		0		0	0	0
	Through	1334	1	692	0	1	0
	Through-Right		1		0	1	0
	Right	49	0	49	0	0	0
	Left-Through-Right		0		0	0	0
	Left-Right		0		0	0	0
EASTBOUND	Left	71	1	71	0	1	0
	Left-Through		0		0	0	0
	Through	0	0	0	0	0	0
	Through-Right		0		0	0	0
	Right	26	1	11	0	1	0
	Left-Through-Right		0		0	0	0
	Left-Right		0		0	0	0
WESTBOUND	Left	0	0	0	0	0	0
	Left-Through		0		0	0	0
	Through	0	0	0	0	0	0
	Through-Right		0		0	0	0
	Right	0	0	0	0	0	0
	Left-Through-Right		0		0	0	0
	Left-Right		0		0	0	0
CRITICAL VOLUMES		<i>North-South:</i>		723	<i>North-South:</i>		0
		<i>East-West:</i>		71	<i>East-West:</i>		0
		<i>SUM:</i>		794	<i>SUM:</i>		0
VOLUME/CAPACITY (V/C) RATIO:				0.662			0.000
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.562			0.000
LEVEL OF SERVICE (LOS):				A			A



Level of Service Worksheet (Circular 212 Method)



I/S #:
31

PROJECT TITLE: SPW, POC Addendum
North-South Street: Pacific Ave
Scenario: Future No Project
Count Date: 1/0/1900

East-West Street: 13th

Analyst: <Fehr & Peers> **Date:** <date>

		SAT					
No. of Phases				2			2
Opposed Ø'ing: N/S-1, E/W-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		NB-- 0	SB-- 0	0	NB-- 0	SB-- 0	0
ATSAC-1 or ATSAC+ATCS-2?		EB-- 0	WB-- 0	0	EB-- 0	WB-- 0	0
Override Capacity				2			2
				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	↶ Left	47	1	47	0	1	0
	↷ Left-Through		0			0	
	→ Through	745	1	745	0	1	0
	↷ Through-Right		0			0	
	↷ Right	18	1	18	0	1	0
	↷ Left-Through-Right		0			0	
	↷ Left-Right		0			0	
SOUTHBOUND	↷ Left	36	1	36	0	1	0
	↶ Left-Through		0			0	
	→ Through	692	1	692	0	1	0
	↶ Through-Right		0			0	
	↶ Right	84	1	84	0	1	0
	↶ Left-Through-Right		0			0	
	↶ Left-Right		0			0	
EASTBOUND	↶ Left	75	0	75	0	0	0
	↷ Left-Through		0			0	
	→ Through	80	0	195	0	0	0
	↷ Through-Right		0			0	
	↷ Right	40	0	0	0	0	0
	↷ Left-Through-Right		1			1	
	↷ Left-Right		0			0	
WESTBOUND	↶ Left	8	0	8	0	0	0
	↷ Left-Through		0			0	
	→ Through	66	0	109	0	0	0
	↷ Through-Right		0			0	
	↷ Right	35	0	0	0	0	0
	↷ Left-Through-Right		1			1	
	↷ Left-Right		0			0	
CRITICAL VOLUMES			<i>North-South:</i>	781		<i>North-South:</i>	0
			<i>East-West:</i>	203		<i>East-West:</i>	0
			<i>SUM:</i>	984		<i>SUM:</i>	0
VOLUME/CAPACITY (V/C) RATIO:				0.656			0.000
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.556			0.000
LEVEL OF SERVICE (LOS):				A			A



Level of Service Worksheet (Circular 212 Method)



I/S #:
32

PROJECT TITLE: SPW, POC Addendum
North-South Street: Pacific Ave
Scenario: Future No Project
Count Date: 1/0/1900

East-West Street: 17th

Analyst: <Fehr & Peers> **Date:** <date>

		SAT					
No. of Phases				2			2
Opposed Ø'ing: N/S-1, E/W-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		<i>NB--</i> 0	<i>SB--</i> 0	0	<i>NB--</i> 0	<i>SB--</i> 0	0
		<i>EB--</i> 0	<i>WB--</i> 0	0	<i>EB--</i> 0	<i>WB--</i> 0	0
ATSAC-1 or ATSAC+ATCS-2?				2			2
Override Capacity				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	Left	17	1	17	0	1	0
	Left-Through		0			0	
	Through	629	1	629	0	1	0
	Through-Right		0			0	
	Right	13	1	13	0	1	0
	Left-Through-Right		0			0	
	Left-Right		0			0	
SOUTHBOUND	Left	23	1	23	0	1	0
	Left-Through		0			0	
	Through	618	1	618	0	1	0
	Through-Right		0			0	
	Right	69	1	69	0	1	0
	Left-Through-Right		0			0	
	Left-Right		0			0	
EASTBOUND	Left	42	0	42	0	0	0
	Left-Through		0			0	
	Through	50	0	125	0	0	0
	Through-Right		0			0	
	Right	33	0	0	0	0	0
	Left-Through-Right		1			1	
	Left-Right		0			0	
WESTBOUND	Left	17	0	17	0	0	0
	Left-Through		0			0	
	Through	89	0	129	0	0	0
	Through-Right		0			0	
	Right	23	0	0	0	0	0
	Left-Through-Right		1			1	
	Left-Right		0			0	
CRITICAL VOLUMES			<i>North-South:</i>	652	<i>North-South:</i>		0
			<i>East-West:</i>	171	<i>East-West:</i>		0
			<i>SUM:</i>	823	<i>SUM:</i>		0
VOLUME/CAPACITY (V/C) RATIO:				0.549			0.000
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.449			0.000
LEVEL OF SERVICE (LOS):				A			A



Level of Service Worksheet (Circular 212 Method)



I/S #:
33

PROJECT TITLE: SPW, POC Addendum
North-South Street: 19th St
Scenario: Future No Project
Count Date: 1/0/1900

East-West Street: Pacific

Analyst: <Fehr & Peers> **Date:** <date>

		SAT					
No. of Phases				2			2
Opposed Ø'ing: N/S-1, EW-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		NB-- 0	SB-- 0	0	NB-- 0	SB-- 0	0
ATSAC-1 or ATSAC+ATCS-2?		EB-- 0	WB-- 0	0	EB-- 0	WB-- 0	0
Override Capacity				2			2
				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	↶ Left	21	1	21	0	1	0
	↷ Left-Through		0			0	
	→ Through	556	1	556	0	1	0
	↷ Through-Right		0			0	
	↷ Right	18	1	18	0	1	0
	↷ Left-Through-Right		0			0	
	↷ Left-Right		0			0	
SOUTHBOUND	↷ Left	13	1	13	0	1	0
	↶ Left-Through		0			0	
	→ Through	550	1	550	0	1	0
	↶ Through-Right		0			0	
	↶ Right	50	1	50	0	1	0
	↶ Left-Through-Right		0			0	
	↶ Left-Right		0			0	
EASTBOUND	↶ Left	48	0	48	0	0	0
	↷ Left-Through		0			0	
	→ Through	35	0	115	0	0	0
	↷ Through-Right		0			0	
	↷ Right	32	0	0	0	0	0
	↷ Left-Through-Right		1			1	
	↷ Left-Right		0			0	
WESTBOUND	↶ Left	12	0	12	0	0	0
	↷ Left-Through		0			0	
	→ Through	56	0	90	0	0	0
	↷ Through-Right		0			0	
	↷ Right	22	0	0	0	0	0
	↷ Left-Through-Right		1			1	
	↷ Left-Right		0			0	
CRITICAL VOLUMES			<i>North-South:</i>	571		<i>North-South:</i>	0
			<i>East-West:</i>	138		<i>East-West:</i>	0
			<i>SUM:</i>	709		<i>SUM:</i>	0
VOLUME/CAPACITY (V/C) RATIO:				0.473			0.000
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.373			0.000
LEVEL OF SERVICE (LOS):				A			A



Level of Service Worksheet (Circular 212 Method)



I/S #:
34

PROJECT TITLE: SPW, POC Addendum
North-South Street: Gaffey St
Scenario: Future No Project
Count Date: 1/0/1900

East-West Street: 13th St.

Analyst: <Fehr & Peers> **Date:** <date>

		SAT					
No. of Phases				2			2
Opposed Ø'ing: N/S-1, E/W-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		<i>NB--</i> 0	<i>SB--</i> 0	0	<i>NB--</i> 0	<i>SB--</i> 0	0
		<i>EB--</i> 0	<i>WB--</i> 0	0	<i>EB--</i> 0	<i>WB--</i> 0	0
ATSAC-1 or ATSAC+ATCS-2?				2			2
Override Capacity				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	Left	67	1	67	0	1	0
	Left-Through		0			0	
	Through	1127	1	587	0	1	0
	Through-Right		1			1	
	Right	46	0	46	0	0	0
	Left-Through-Right		0			0	
	Left-Right		0			0	
SOUTHBOUND	Left	75	1	75	0	1	0
	Left-Through		0			0	
	Through	1139	1	604	0	1	0
	Through-Right		1			1	
	Right	68	0	68	0	0	0
	Left-Through-Right		0			0	
	Left-Right		0			0	
EASTBOUND	Left	190	0	190	0	0	0
	Left-Through		0			0	
	Through	118	0	370	0	0	0
	Through-Right		0			0	
	Right	62	0	0	0	0	0
	Left-Through-Right		1			1	
	Left-Right		0			0	
WESTBOUND	Left	60	0	60	0	0	0
	Left-Through		0			0	
	Through	143	0	273	0	0	0
	Through-Right		0			0	
	Right	70	0	0	0	0	0
	Left-Through-Right		1			1	
	Left-Right		0			0	
CRITICAL VOLUMES		<i>North-South:</i>		671	<i>North-South:</i>		0
		<i>East-West:</i>		463	<i>East-West:</i>		0
		<i>SUM:</i>		1134	<i>SUM:</i>		0
VOLUME/CAPACITY (V/C) RATIO:				0.756			0.000
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.656			0.000
LEVEL OF SERVICE (LOS):				B			A



Level of Service Worksheet (Circular 212 Method)



I/S #:
5

PROJECT TITLE: SPW, POC Addendum
North-South Street: Gaffey St
Scenario: Future With Project
Count Date: 1/0/1900

East-West Street: 9th St

Analyst: <Fehr & Peers> **Date:** <date>

		AM			PM		
		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
No. of Phases				2			2
Opposed Ø'ing: N/S-1, E/W-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		NB-- 0	SB-- 0	0	NB-- 0	SB-- 0	0
ATSAC-1 or ATSAC+ATCS-2?		EB-- 0	WB-- 0	0	EB-- 0	WB-- 0	0
Override Capacity				2			2
Override Capacity				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	↵ Left	77	1	77	63	1	63
	↵↔ Left-Through		0			0	
	→ Through	1527	2	764	1153	2	577
	↘ Through-Right		0			0	
	↘ Right	28	1	0	42	1	0
	↘↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
SOUTHBOUND	↵ Left	46	1	46	151	1	151
	↵↔ Left-Through		0			0	
	→ Through	1136	1	628	1629	1	888
	↘ Through-Right		1			1	
	↘ Right	119	0	119	146	0	146
	↘↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
EASTBOUND	↵ Left	289	1	289	201	1	201
	↵↔ Left-Through		0			0	
	→ Through	506	1	506	278	1	278
	↘ Through-Right		0			0	
	↘ Right	68	1	30	50	1	19
	↘↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
WESTBOUND	↵ Left	77	1	77	98	1	98
	↵↔ Left-Through		0			0	
	→ Through	325	0	404	287	0	408
	↘ Through-Right		1			1	
	↘ Right	79	0	0	121	0	0
	↘↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
CRITICAL VOLUMES				<i>North-South:</i> 810			<i>North-South:</i> 951
				<i>East-West:</i> 693			<i>East-West:</i> 609
				SUM: 1503			SUM: 1560
VOLUME/CAPACITY (V/C) RATIO:				1.002			1.040
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.902			0.940
LEVEL OF SERVICE (LOS):				E			E



Level of Service Worksheet (Circular 212 Method)



I/S #:
6

PROJECT TITLE: SPW, POC Addendum
North-South Street: Gaffey St
Scenario: Future With Project
Count Date: 1/0/1900

East-West Street: 7th St

Analyst: <Fehr & Peers> **Date:** <date>

		AM			PM		
		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
No. of Phases				2			2
Opposed Ø'ing: N/S-1, E/W-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		NB-- 0	SB-- 0	0	NB-- 0	SB-- 0	0
ATSAC-1 or ATSAC+ATCS-2?		EB-- 0	WB-- 0	0	EB-- 0	WB-- 0	0
Override Capacity				2			2
0				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	↵ Left	22	1	22	53	1	53
	↵↵ Left-Through		0			0	
	→ Through	1821	2	911	1365	2	683
	↵↵↵ Through-Right		0			0	
	↵ Right	55	1	0	49	1	0
	↵↵↵ Left-Through-Right		0			0	
	↵↵ Left-Right		0			0	
SOUTHBOUND	↵↵ Left	72	1	72	108	1	108
	↵↵ Left-Through		0			0	
	→ Through	1230	1	700	1748	1	923
	↵↵ Through-Right		1			1	
	↵ Right	170	0	170	97	0	97
	↵↵↵ Left-Through-Right		0			0	
	↵↵ Left-Right		0			0	
EASTBOUND	↵ Left	302	1	302	163	1	163
	↵↵ Left-Through		0			0	
	→ Through	186	0	221	184	0	237
	↵↵ Through-Right		1			1	
	↵ Right	35	0	0	53	0	0
	↵↵↵ Left-Through-Right		0			0	
	↵↵ Left-Right		0			0	
WESTBOUND	↵ Left	115	1	115	111	1	111
	↵↵ Left-Through		0			0	
	→ Through	113	0	192	200	0	312
	↵↵ Through-Right		1			1	
	↵ Right	79	0	0	112	0	0
	↵↵↵ Left-Through-Right		0			0	
	↵↵ Left-Right		0			0	
CRITICAL VOLUMES				<i>North-South:</i> 983			<i>North-South:</i> 976
				<i>East-West:</i> 494			<i>East-West:</i> 475
				SUM: 1477			SUM: 1451
VOLUME/CAPACITY (V/C) RATIO:				0.985			0.967
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.885			0.867
LEVEL OF SERVICE (LOS):				D			D



Level of Service Worksheet (Circular 212 Method)



I/S #:
7

PROJECT TITLE: SPW, POC Addendum
North-South Street: Gaffey St
Scenario: Future With Project
Count Date: 1/0/1900

East-West Street: 6th St

Analyst: <Fehr & Peers> **Date:** <date>

		AM			PM		
		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
No. of Phases				0			0
Opposed Ø'ing: N/S-1, E/W-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		<i>NB--</i> 0	<i>SB--</i> 0	0	<i>NB--</i> 0	<i>SB--</i> 0	0
		<i>EB--</i> 0	<i>WB--</i> 0	0	<i>EB--</i> 0	<i>WB--</i> 0	0
ATSAC-1 or ATSAC+ATCS-2?				2			2
Override Capacity				1200			1200
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	Left	61	1	61	64	1	64
	Left-Through		0			0	
	Through	2045	1	1055	1557	1	808
	Through-Right		1			1	
	Right	64	0	64	58	0	58
	Left-Through-Right		0			0	
	Left-Right		0			0	
SOUTHBOUND	Left	114	1	114	71	1	71
	Left-Through		0			0	
	Through	1515	1	808	1817	1	961
	Through-Right		1			1	
	Right	101	0	101	104	0	104
	Left-Through-Right		0			0	
	Left-Right		0			0	
EASTBOUND	Left	13	0	13	15	0	15
	Left-Through		1			1	
	Through	12	0	25	12	0	27
	Through-Right		0			0	
	Right	38	1	8	93	1	61
	Left-Through-Right		0			0	
	Left-Right		0			0	
WESTBOUND	Left	2	0	2	10	0	10
	Left-Through		1			1	
	Through	31	0	33	13	0	23
	Through-Right		0			0	
	Right	44	1	0	103	1	68
	Left-Through-Right		0			0	
	Left-Right		0			0	
CRITICAL VOLUMES				<i>North-South:</i> 1169 <i>East-West:</i> 46 <i>SUM:</i> 1215			<i>North-South:</i> 1025 <i>East-West:</i> 83 <i>SUM:</i> 1108
VOLUME/CAPACITY (V/C) RATIO:				1.013			0.923
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.913			0.823
LEVEL OF SERVICE (LOS):				E			D



Level of Service Worksheet (Circular 212 Method)



I/S #:
8

PROJECT TITLE: SPW, POC Addendum
North-South Street: Gaffey St
Scenario: Future With Project
Count Date: 1/0/1900

East-West Street: 5th St

Analyst: <Fehr & Peers> **Date:** <date>

		AM			PM		
		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
No. of Phases				3			3
Opposed Ø'ing: N/S-1, E/W-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		NB-- 0	SB-- 0	0	NB-- 0	SB-- 0	0
ATSAC-1 or ATSAC+ATCS-2?		EB-- 0	WB-- 0	0	EB-- 0	WB-- 0	0
Override Capacity				2			2
Override Capacity				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	↵ Left	17	1	17	46	1	46
	↵↔ Left-Through		0			0	
	→ Through	2037	2	1019	1639	2	820
	↘ Through-Right		0			0	
	↘ Right	28	1	0	34	1	0
	↵↔ Left-Through-Right		0			0	
	↘ Left-Right		0			0	
SOUTHBOUND	↵ Left	126	1	126	133	1	133
	↵↔ Left-Through		0			0	
	→ Through	1553	2	777	1892	2	946
	↘ Through-Right		0			0	
	↘ Right	141	1	0	137	1	69
	↵↔ Left-Through-Right		0			0	
	↘ Left-Right		0			0	
EASTBOUND	↵ Left	299	1	299	137	1	137
	↵↔ Left-Through		0			0	
	→ Through	184	0	217	93	0	117
	↘ Through-Right		1			1	
	↘ Right	33	0	0	24	0	0
	↵↔ Left-Through-Right		0			0	
	↘ Left-Right		0			0	
WESTBOUND	↵ Left	102	1	102	103	1	103
	↵↔ Left-Through		0			0	
	→ Through	116	0	254	339	0	474
	↘ Through-Right		1			1	
	↘ Right	138	0	0	135	0	0
	↵↔ Left-Through-Right		0			0	
	↘ Left-Right		0			0	
CRITICAL VOLUMES				<i>North-South:</i> 1145			<i>North-South:</i> 992
				<i>East-West:</i> 553			<i>East-West:</i> 611
				SUM: 1698			SUM: 1603
VOLUME/CAPACITY (V/C) RATIO:				1.192			1.125
V/C LESS ATSAC/ATCS ADJUSTMENT:				1.092			1.025
LEVEL OF SERVICE (LOS):				F			F



Level of Service Worksheet (Circular 212 Method)



I/S #:
9

PROJECT TITLE: SPW, POC Addendum
North-South Street: Gaffey St
Scenario: Future With Project
Count Date: 1/0/1900

East-West Street: 1st St

Analyst: <Fehr & Peers> **Date:** <date>

		AM			PM		
		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
No. of Phases				4			4
Opposed Ø'ing: N/S-1, E/W-2 or Both-3?				2			2
Right Turns: FREE-1, NRTOR-2 or OLA-3?		NB-- 0	SB-- 0	0	NB-- 0	SB-- 0	0
ATSAC-1 or ATSAC+ATCS-2?		EB-- 0	WB-- 0	0	EB-- 0	WB-- 0	0
Override Capacity				2			2
Override Capacity				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	↵ Left	19	1	19	38	1	38
	↵↔ Left-Through		0			0	
	→ Through	2585	2	865	1899	2	638
	↘ Through-Right		1			1	
	↘ Right	11	0	11	16	0	16
	↘↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
SOUTHBOUND	↵ Left	128	1	128	141	1	141
	↵↔ Left-Through		0			0	
	→ Through	1876	2	739	2196	2	905
	↘ Through-Right		1			1	
	↘ Right	341	0	341	519	0	519
	↘↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
EASTBOUND	↵ Left	1302	2	716	945	2	520
	↵↔ Left-Through		0			0	
	→ Through	80	0	98	149	0	208
	↘ Through-Right		1			1	
	↘ Right	18	0	0	59	0	0
	↘↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
WESTBOUND	↵ Left	55	1	55	88	1	88
	↵↔ Left-Through		0			0	
	→ Through	203	1	203	185	1	185
	↘ Through-Right		0			0	
	↘ Right	281	1	217	211	1	141
	↘↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
CRITICAL VOLUMES				<i>North-South:</i> 993			<i>North-South:</i> 943
				<i>East-West:</i> 933			<i>East-West:</i> 705
				SUM: 1926			SUM: 1648
VOLUME/CAPACITY (V/C) RATIO:				1.401			1.199
V/C LESS ATSAC/ATCS ADJUSTMENT:				1.301			1.099
LEVEL OF SERVICE (LOS):				F			F



Level of Service Worksheet (Circular 212 Method)



I/S #:
11

PROJECT TITLE: SPW, POC Addendum
North-South Street: Summerland Ave
Scenario: Future With Project
Count Date: 1/0/1900

East-West Street: Gaffey St
Analyst: <Fehr & Peers> **Date:** <date>

		AM			PM		
		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
No. of Phases				3			3
Opposed Ø'ing: N/S-1, E/W-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		NB-- 0	SB-- 0	0	NB-- 0	SB-- 0	0
ATSAC-1 or ATSAC+ATCS-2?		EB-- 0	WB-- 0	0	EB-- 0	WB-- 0	0
Override Capacity				2			2
Override Capacity				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	↵ Left	146	1	146	183	1	183
	↵↔ Left-Through		0			0	
	→ Through	594	1	310	580	1	317
	↘ Through-Right		1			1	
	↘ Right	25	0	25	53	0	53
	↘↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
SOUTHBOUND	↵ Left	13	1	13	23	1	23
	↵↔ Left-Through		0			0	
	→ Through	562	2	281	815	2	408
	↘ Through-Right		0			0	
	↘ Right	210	1	0	381	1	262
	↘↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
EASTBOUND	↵ Left	570	1	570	238	1	238
	↵↔ Left-Through		0			0	
	→ Through	5	0	74	4	0	73
	↘ Through-Right		1			1	
	↘ Right	69	0	0	69	0	0
	↘↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
WESTBOUND	↵ Left	399	2	219	676	2	372
	↵↔ Left-Through		0			0	
	→ Through	171	0	478	362	0	750
	↘ Through-Right		1			1	
	↘ Right	307	0	0	388	0	0
	↘↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
CRITICAL VOLUMES				<i>North-South:</i> 427			<i>North-South:</i> 591
				<i>East-West:</i> 1048			<i>East-West:</i> 988
				SUM: 1475			SUM: 1579
VOLUME/CAPACITY (V/C) RATIO:				1.035			1.108
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.935			1.008
LEVEL OF SERVICE (LOS):				E			F



Level of Service Worksheet (Circular 212 Method)



I/S #:
12

PROJECT TITLE: SPW, POC Addendum
North-South Street: Pacific Ave
Scenario: Future With Project
Count Date: 1/0/1900

East-West Street: 22nd St

Analyst: <Fehr & Peers> **Date:** <date>

		AM			PM		
		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
No. of Phases				2			2
Opposed Ø'ing: N/S-1, E/W-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		NB-- 0	SB-- 0	0	NB-- 0	SB-- 0	0
ATSAC-1 or ATSAC+ATCS-2?		EB-- 0	WB-- 0	0	EB-- 0	WB-- 0	0
Override Capacity				2			2
				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	↵ Left	24	1	24	34	1	34
	↵↵ Left-Through		0			0	
	→ Through	561	1	561	440	1	440
	↵↵↵ Through-Right		0			0	
	↵ Right	352	1	352	128	1	128
	↵↵↵ Left-Through-Right		0			0	
	↵↵ Left-Right		0			0	
SOUTHBOUND	↵↵ Left	47	1	47	32	1	32
	↵↵ Left-Through		0			0	
	→ Through	194	1	194	388	1	388
	↵↵↵ Through-Right		0			0	
	↵ Right	34	1	34	87	1	87
	↵↵↵ Left-Through-Right		0			0	
	↵↵ Left-Right		0			0	
EASTBOUND	↵ Left	47	0	47	34	0	34
	↵↵ Left-Through		0			0	
	→ Through	386	0	469	165	0	254
	↵↵↵ Through-Right		0			0	
	↵ Right	36	0	0	55	0	0
	↵↵↵ Left-Through-Right		1			1	
	↵↵ Left-Right		0			0	
WESTBOUND	↵ Left	72	0	72	219	0	219
	↵↵ Left-Through		0			0	
	→ Through	151	0	248	234	0	499
	↵↵↵ Through-Right		0			0	
	↵ Right	25	0	0	46	0	0
	↵↵↵ Left-Through-Right		1			1	
	↵↵ Left-Right		0			0	
CRITICAL VOLUMES		<i>North-South:</i>		608	<i>North-South:</i>		472
		<i>East-West:</i>		541	<i>East-West:</i>		533
		SUM:		1149	SUM:		1005
VOLUME/CAPACITY (V/C) RATIO:				0.766			0.670
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.666			0.570
LEVEL OF SERVICE (LOS):				B			A



Level of Service Worksheet (Circular 212 Method)



I/S #:
13

PROJECT TITLE: SPW, POC Addendum
North-South Street: Pacific Ave
Scenario: Future With Project
Count Date: 1/0/1900

East-West Street: 9th St

Analyst: <Fehr & Peers> **Date:** <date>

		AM			PM		
		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
No. of Phases				2			2
Opposed Ø'ing: N/S-1, E/W-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		NB-- 0	SB-- 0	0	NB-- 0	SB-- 0	0
ATSAC-1 or ATSAC+ATCS-2?		EB-- 0	WB-- 0	0	EB-- 0	WB-- 0	0
Override Capacity				2			2
Override Capacity				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	↵ Left	97	1	97	64	1	64
	↵↵ Left-Through		0			0	
	→ Through	1054	1	1054	765	1	765
	↵↵↵ Through-Right		0			0	
	↵ Right	38	1	33	41	1	16
	↵↵↵ Left-Through-Right		0			0	
	↵↵ Left-Right		0			0	
SOUTHBOUND	↵↵ Left	16	1	16	41	1	41
	↵↵ Left-Through		0			0	
	→ Through	592	1	592	1011	1	1011
	↵↵↵ Through-Right		0			0	
	↵ Right	132	1	49	130	1	67
	↵↵↵ Left-Through-Right		0			0	
	↵↵ Left-Right		0			0	
EASTBOUND	↵ Left	166	1	166	127	1	127
	↵↵ Left-Through		0			0	
	→ Through	164	0	216	193	0	300
	↵↵↵ Through-Right		1			1	
	↵ Right	52	0	0	107	0	0
	↵↵↵ Left-Through-Right		0			0	
	↵↵ Left-Right		0			0	
WESTBOUND	↵ Left	11	1	11	50	1	50
	↵↵ Left-Through		0			0	
	→ Through	186	0	238	203	0	266
	↵↵↵ Through-Right		1			1	
	↵ Right	52	0	0	63	0	0
	↵↵↵ Left-Through-Right		0			0	
	↵↵ Left-Right		0			0	
CRITICAL VOLUMES				<i>North-South:</i> 1070			<i>North-South:</i> 1075
				<i>East-West:</i> 404			<i>East-West:</i> 393
				<i>SUM:</i> 1474			<i>SUM:</i> 1468
VOLUME/CAPACITY (V/C) RATIO:				0.983			0.979
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.883			0.879
LEVEL OF SERVICE (LOS):				D			D



Level of Service Worksheet (Circular 212 Method)



I/S #:
14

PROJECT TITLE: SPW, POC Addendum
North-South Street: Pacific Ave
Scenario: Future With Project
Count Date: 1/0/1900

East-West Street: 7th St

Analyst: <Fehr & Peers> **Date:** <date>

		AM			PM		
No. of Phases				2			2
Opposed Ø'ing: N/S-1, E/W-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		NB-- 0	SB-- 0	0	NB-- 0	SB-- 0	0
ATSAC-1 or ATSAC+ATCS-2?		EB-- 0	WB-- 0	0	EB-- 0	WB-- 0	0
Override Capacity				2			2
Override Capacity				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	↵ Left	28	1	28	73	1	73
	↵↔ Left-Through		0			0	
	→ Through	1253	1	1253	863	1	863
	↘ Through-Right		0			0	
	↘ Right	47	1	28	28	1	0
	↘↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
SOUTHBOUND	↵ Left	16	1	16	20	1	20
	↵↔ Left-Through		0			0	
	→ Through	741	1	741	1016	1	1016
	↘ Through-Right		0			0	
	↘ Right	51	1	26	51	1	34
	↘↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
EASTBOUND	↵ Left	51	1	51	35	1	35
	↵↔ Left-Through		0			0	
	→ Through	101	0	133	176	0	226
	↘ Through-Right		1			1	
	↘ Right	32	0	0	50	0	0
	↘↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
WESTBOUND	↵ Left	38	1	38	114	1	114
	↵↔ Left-Through		0			0	
	→ Through	101	0	122	187	0	234
	↘ Through-Right		1			1	
	↘ Right	21	0	0	47	0	0
	↘↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
CRITICAL VOLUMES				<i>North-South:</i> 1269			<i>North-South:</i> 1089
				<i>East-West:</i> 173			<i>East-West:</i> 340
				SUM: 1442			SUM: 1429
VOLUME/CAPACITY (V/C) RATIO:				0.961			0.953
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.861			0.853
LEVEL OF SERVICE (LOS):				D			D



Level of Service Worksheet (Circular 212 Method)



I/S #:
15

PROJECT TITLE: SPW, POC Addendum
North-South Street: Pacific Ave
Scenario: Future With Project
Count Date: 1/0/1900

East-West Street: 6th St

Analyst: <Fehr & Peers> **Date:** <date>

		AM			PM		
		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
No. of Phases				4			4
Opposed Ø'ing: N/S-1, E/W-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		NB-- 0	SB-- 0	0	NB-- 0	SB-- 0	0
ATSAC-1 or ATSAC+ATCS-2?		EB-- 0	WB-- 0	0	EB-- 0	WB-- 0	0
Override Capacity				2			2
Override Capacity				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	↵ Left	32	1	32	38	1	38
	↵↔ Left-Through		0			0	
	→ Through	1236	1	1236	849	1	849
	↘ Through-Right		0			0	
	↘ Right	53	1	53	76	1	76
	↘↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
SOUTHBOUND	↵ Left	30	1	30	36	1	36
	↵↔ Left-Through		0			0	
	→ Through	722	1	722	999	1	999
	↘ Through-Right		0			0	
	↘ Right	28	1	28	46	1	46
	↘↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
EASTBOUND	↵ Left	25	0	25	25	0	25
	↵↔ Left-Through		0			0	
	→ Through	78	0	130	83	0	153
	↘ Through-Right		0			0	
	↘ Right	27	0	0	45	0	0
	↘↔ Left-Through-Right		1			1	
	↘↔ Left-Right		0			0	
WESTBOUND	↵ Left	41	0	41	63	0	63
	↵↔ Left-Through		0			0	
	→ Through	24	0	101	80	0	179
	↘ Through-Right		0			0	
	↘ Right	36	0	0	36	0	0
	↘↔ Left-Through-Right		1			1	
	↘↔ Left-Right		0			0	
CRITICAL VOLUMES				<i>North-South:</i> 1266			<i>North-South:</i> 1037
				<i>East-West:</i> 171			<i>East-West:</i> 216
				SUM: 1437			SUM: 1253
VOLUME/CAPACITY (V/C) RATIO:				1.045			0.911
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.945			0.811
LEVEL OF SERVICE (LOS):				E			D



Level of Service Worksheet (Circular 212 Method)



I/S #:
16

PROJECT TITLE: SPW, POC Addendum
North-South Street: Pacific Ave
Scenario: Future With Project
Count Date: 1/0/1900

East-West Street: 5th St

Analyst: <Fehr & Peers> **Date:** <date>

		AM			PM		
		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
No. of Phases				2			2
Opposed Ø'ing: N/S-1, E/W-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		NB-- 0	SB-- 0	0	NB-- 0	SB-- 0	0
ATSAC-1 or ATSAC+ATCS-2?		EB-- 0	WB-- 0	0	EB-- 0	WB-- 0	0
Override Capacity				2			2
Override Capacity				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	↵ Left	36	1	36	40	1	40
	↵↔ Left-Through		0			0	
	→ Through	1196	1	1196	854	1	854
	↘ Through-Right		0			0	
	↘ Right	68	1	22	66	1	0
	↘↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
SOUTHBOUND	↵ Left	50	1	50	50	1	50
	↵↔ Left-Through		0			0	
	→ Through	668	1	668	851	1	851
	↘ Through-Right		0			0	
	↘ Right	38	1	19	32	1	5
	↘↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
EASTBOUND	↵ Left	38	1	38	55	1	55
	↵↔ Left-Through		0			0	
	→ Through	212	0	251	132	0	180
	↘ Through-Right		1			1	
	↘ Right	39	0	0	48	0	0
	↘↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
WESTBOUND	↵ Left	93	1	93	186	1	186
	↵↔ Left-Through		0			0	
	→ Through	174	0	226	178	0	237
	↘ Through-Right		1			1	
	↘ Right	52	0	0	59	0	0
	↘↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
CRITICAL VOLUMES				<i>North-South:</i> 1246			<i>North-South:</i> 904
				<i>East-West:</i> 344			<i>East-West:</i> 366
				<i>SUM:</i> 1590			<i>SUM:</i> 1270
VOLUME/CAPACITY (V/C) RATIO:				1.060			0.847
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.960			0.747
LEVEL OF SERVICE (LOS):				E			C



Level of Service Worksheet (Circular 212 Method)



I/S #:
17

PROJECT TITLE: SPW, POC Addendum
North-South Street: Pacific Ave
Scenario: Future With Project
Count Date: 1/0/1900

East-West Street: 1st St

Analyst: <Fehr & Peers> **Date:** <date>

		AM			PM		
		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
No. of Phases				2			2
Opposed Ø'ing: N/S-1, E/W-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		NB-- 0	SB-- 0	0	NB-- 0	SB-- 0	0
ATSAC-1 or ATSAC+ATCS-2?		EB-- 0	WB-- 0	0	EB-- 0	WB-- 0	0
Override Capacity				2			2
				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	↵ Left	217	1	217	153	1	153
	↵↔ Left-Through		0			0	
	→ Through	1070	1	1070	762	1	762
	↘ Through-Right		0			0	
	↘ Right	46	1	46	33	1	33
	↘↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
SOUTHBOUND	↵ Left	35	1	35	29	1	29
	↵↔ Left-Through		0			0	
	→ Through	610	1	610	825	1	825
	↘ Through-Right		0			0	
	↘ Right	45	1	45	59	1	59
	↘↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
EASTBOUND	↵ Left	52	0	52	62	0	62
	↵↔ Left-Through		1			1	
	→ Through	119	0	171	150	0	212
	↘ Through-Right		0			0	
	↘ Right	64	1	0	93	1	17
	↘↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
WESTBOUND	↵ Left	112	0	112	58	0	58
	↵↔ Left-Through		1			1	
	→ Through	140	0	252	125	0	183
	↘ Through-Right		0			0	
	↘ Right	58	1	41	22	1	8
	↘↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
CRITICAL VOLUMES				<i>North-South:</i> 1105			<i>North-South:</i> 978
				<i>East-West:</i> 304			<i>East-West:</i> 270
				SUM: 1409			SUM: 1248
VOLUME/CAPACITY (V/C) RATIO:				0.939			0.832
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.839			0.732
LEVEL OF SERVICE (LOS):				D			C



Level of Service Worksheet (Circular 212 Method)



I/S #:
20

PROJECT TITLE: SPW, POC Addendum
North-South Street: Miner St
Scenario: Future With Project
Count Date: 1/0/1900

East-West Street: 22nd St

Analyst: <Fehr & Peers> **Date:** <date>

		AM			PM		
		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
No. of Phases				4			4
Opposed Ø'ing: N/S-1, E/W-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		NB-- 0	SB-- 0	0	NB-- 0	SB-- 0	0
ATSAC-1 or ATSAC+ATCS-2?		EB-- 0	WB-- 0	0	EB-- 0	WB-- 0	0
Override Capacity				2			2
Override Capacity				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	↵ Left	63	1	63	51	1	51
	↵↔ Left-Through		0			0	
	→ Through	544	1	308	241	1	142
	↘ Through-Right		1			1	
	↘ Right	71	0	71	43	0	43
	↘↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
SOUTHBOUND	↵ Left	212	1	212	63	1	63
	↵↔ Left-Through		0			0	
	→ Through	392	1	280	245	1	245
	↘ Through-Right		1			1	
	↘ Right	168	0	168	483	0	354
	↘↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
EASTBOUND	↵ Left	528	1	528	258	1	258
	↵↔ Left-Through		0			0	
	→ Through	131	1	92	87	1	69
	↘ Through-Right		1			1	
	↘ Right	52	0	52	50	0	50
	↘↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
WESTBOUND	↵ Left	48	1	48	47	1	47
	↵↔ Left-Through		0			0	
	→ Through	42	1	42	117	1	117
	↘ Through-Right		1			1	
	↘ Right	66	0	0	179	0	148
	↘↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
CRITICAL VOLUMES				<i>North-South:</i> 520			<i>North-South:</i> 405
				<i>East-West:</i> 570			<i>East-West:</i> 406
				SUM: 1090			SUM: 811
VOLUME/CAPACITY (V/C) RATIO:				0.793			0.590
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.693			0.490
LEVEL OF SERVICE (LOS):				B			A



Level of Service Worksheet (Circular 212 Method)



I/S #:
21

PROJECT TITLE: SPW, POC Addendum
North-South Street: Harbor Bl / Miner St
Scenario: Future With Project
Count Date: 1/0/1900

East-West Street: Crescent Av

Analyst: <Fehr & Peers> **Date:** <date>

		AM			PM		
		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
No. of Phases Opposed Ø'ing: N/S-1, E/W-2 or Both-3? Right Turns: FREE-1, NRTOR-2 or OLA-3? ATSAC-1 or ATSAC+ATCS-2? Override Capacity				0			0
				0			0
		NB-- 0		SB-- 0	NB-- 0		SB-- 0
		EB-- 0		WB-- 0	EB-- 0		WB-- 0
				2			2
				1200			1200
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	↵ Left	3	1	3	18	1	18
	↵↔ Left-Through		0			0	
	→ Through	1183	2	592	715	2	358
	↵↔ Through-Right		0			0	
	↵ Right	0	0	0	0	0	0
	↵↔ Left-Through-Right		0			0	
	↵↔ Left-Right		0			0	
SOUTHBOUND	↵ Left	0	0	0	0	0	0
	↵↔ Left-Through		0			0	
	→ Through	777	1	452	833	1	614
	↵↔ Through-Right		1			1	
	↵ Right	127	0	127	394	0	394
	↵↔ Left-Through-Right		0			0	
	↵↔ Left-Right		0			0	
EASTBOUND	↵ Left	303	0	303	113	0	113
	↵↔ Left-Through		0			0	
	→ Through	0	0	0	0	0	0
	↵↔ Through-Right		0			0	
	↵ Right	14	0	317	9	0	122
	↵↔ Left-Through-Right		0			0	
	↵↔ Left-Right		1			1	
WESTBOUND	↵ Left	0	0	0	0	0	0
	↵↔ Left-Through		0			0	
	→ Through	0	0	0	0	0	0
	↵↔ Through-Right		0			0	
	↵ Right	0	0	0	0	0	0
	↵↔ Left-Through-Right		0			0	
	↵↔ Left-Right		0			0	
CRITICAL VOLUMES				<i>North-South:</i> 592			<i>North-South:</i> 632
				<i>East-West:</i> 317			<i>East-West:</i> 122
				SUM: 909			SUM: 754
VOLUME/CAPACITY (V/C) RATIO:				0.758			0.628
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.658			0.528
LEVEL OF SERVICE (LOS):				B			A



Level of Service Worksheet (Circular 212 Method)



I/S #:
22

PROJECT TITLE: SPW, POC Addendum
North-South Street: Harbor Blvd
Scenario: Future With Project
Count Date: 1/0/1900

East-West Street: 7th St

Analyst: <Fehr & Peers> **Date:** <date>

		AM			PM		
		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
No. of Phases				3			3
Opposed Ø'ing: N/S-1, E/W-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		NB-- 0	SB-- 0	0	NB-- 0	SB-- 0	0
ATSAC-1 or ATSAC+ATCS-2?		EB-- 0	WB-- 0	0	EB-- 0	WB-- 0	0
Override Capacity				2			2
Override Capacity				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	↵ Left	33	1	33	80	1	80
	↵↔ Left-Through		0			0	
	→ Through	1648	2	824	1304	2	652
	↘ Through-Right		0			0	
	↘ Right	0	0	0	0	0	0
	↘↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
SOUTHBOUND	↵ Left	0	0	0	0	0	0
	↵↔ Left-Through		0			0	
	→ Through	1179	2	590	1750	2	875
	↘ Through-Right		0			0	
	↘ Right	246	1	163	374	1	291
	↘↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
EASTBOUND	↵ Left	301	2	166	304	2	167
	↵↔ Left-Through		0			0	
	→ Through	0	0	0	0	0	0
	↘ Through-Right		0			0	
	↘ Right	51	1	35	75	1	35
	↘↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
WESTBOUND	↵ Left	0	0	0	0	0	0
	↵↔ Left-Through		0			0	
	→ Through	0	0	0	0	0	0
	↘ Through-Right		0			0	
	↘ Right	0	0	0	0	0	0
	↘↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
CRITICAL VOLUMES				<i>North-South:</i> 824			<i>North-South:</i> 955
				<i>East-West:</i> 166			<i>East-West:</i> 167
				<i>SUM:</i> 990			<i>SUM:</i> 1122
VOLUME/CAPACITY (V/C) RATIO:				0.695			0.787
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.595			0.687
LEVEL OF SERVICE (LOS):				A			B



Level of Service Worksheet (Circular 212 Method)



I/S #:
23

PROJECT TITLE: SPW, POC Addendum
North-South Street: Harbor Blvd
Scenario: Future With Project
Count Date: 1/0/1900

East-West Street: 6th St

Analyst: <Fehr & Peers> **Date:** <date>

		AM			PM		
		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
No. of Phases				3			3
Opposed Ø'ing: N/S-1, E/W-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		NB-- 0	SB-- 0	0	NB-- 0	SB-- 0	0
ATSAC-1 or ATSAC+ATCS-2?		EB-- 0	WB-- 0	0	EB-- 0	WB-- 0	0
Override Capacity				2			2
Override Capacity				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	↵ Left	10	1	10	10	1	10
	↵↔ Left-Through		0			0	
	→ Through	1970	1	986	1560	1	781
	↘ Through-Right		1			1	
	↘ Right	1	0	1	1	0	1
	↘↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
SOUTHBOUND	↵ Left	14	1	14	10	1	10
	↵↔ Left-Through		0			0	
	→ Through	1454	1	784	2003	1	1041
	↘ Through-Right		1			1	
	↘ Right	113	0	113	78	0	78
	↘↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
EASTBOUND	↵ Left	43	1	43	51	1	51
	↵↔ Left-Through		0			0	
	→ Through	-1	0	15	0	0	49
	↘ Through-Right		1			1	
	↘ Right	16	0	0	49	0	0
	↘↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
WESTBOUND	↵ Left	2	1	2	1	1	1
	↵↔ Left-Through		0			0	
	→ Through	4	1	4	2	1	2
	↘ Through-Right		0			0	
	↘ Right	14	1	7	10	1	5
	↘↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
CRITICAL VOLUMES			<i>North-South:</i>	1000		<i>North-South:</i>	1051
			<i>East-West:</i>	50		<i>East-West:</i>	56
			SUM:	1050		SUM:	1107
VOLUME/CAPACITY (V/C) RATIO:				0.737			0.777
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.637			0.677
LEVEL OF SERVICE (LOS):				B			B



Level of Service Worksheet (Circular 212 Method)



I/S #:
24

PROJECT TITLE: SPW, POC Addendum
North-South Street: Harbor Blvd
Scenario: Future With Project
Count Date: 1/0/1900

East-West Street: 5th St

Analyst: <Fehr & Peers> **Date:** <date>

		AM			PM		
		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
No. of Phases				3			3
Opposed Ø'ing: N/S-1, E/W-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		NB-- 0	SB-- 0	0	NB-- 0	SB-- 0	0
ATSAC-1 or ATSAC+ATCS-2?		EB-- 0	WB-- 0	0	EB-- 0	WB-- 0	0
Override Capacity				2			2
Override Capacity				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	↵ Left	34	1	34	17	1	17
	↵↵ Left-Through		0			0	
	→ Through	1886	1	943	1509	1	755
	↵↵↵ Through-Right		1			1	
	↵↵↵ Right	0	0	0	0	0	0
	↵↵↵↵ Left-Through-Right		0			0	
	↵↵↵↵ Left-Right		0			0	
SOUTHBOUND	↵↵ Left	1	1	1	1	1	1
	↵↵ Left-Through		0			0	
	→ Through	1573	1	982	2105	1	1123
	↵↵↵ Through-Right		1			1	
	↵↵↵ Right	391	0	391	141	0	141
	↵↵↵↵ Left-Through-Right		0			0	
	↵↵↵↵ Left-Right		0			0	
EASTBOUND	↵ Left	186	1	186	370	1	370
	↵↵ Left-Through		0			0	
	→ Through	0	0	15	0	0	33
	↵↵↵ Through-Right		1			1	
	↵↵↵ Right	15	0	0	33	0	0
	↵↵↵↵ Left-Through-Right		0			0	
	↵↵↵↵ Left-Right		0			0	
WESTBOUND	↵ Left	0	1	0	0	1	0
	↵↵ Left-Through		0			0	
	→ Through	2	1	2	0	1	0
	↵↵↵ Through-Right		0			0	
	↵↵↵ Right	1	1	1	12	1	12
	↵↵↵↵ Left-Through-Right		0			0	
	↵↵↵↵ Left-Right		0			0	
CRITICAL VOLUMES				<i>North-South:</i> 1016			<i>North-South:</i> 1140
				<i>East-West:</i> 188			<i>East-West:</i> 382
				<i>SUM:</i> 1204			<i>SUM:</i> 1522
VOLUME/CAPACITY (V/C) RATIO:				0.845			1.068
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.745			0.968
LEVEL OF SERVICE (LOS):				C			E



Level of Service Worksheet (Circular 212 Method)



I/S #:
25

PROJECT TITLE: SPW, POC Addendum
North-South Street: Harbor Blvd
Scenario: Future With Project
Count Date: 1/0/1900

East-West Street: 1st St

Analyst: <Fehr & Peers> **Date:** <date>

		AM			PM		
		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
No. of Phases				4			4
Opposed Ø'ing: N/S-1, E/W-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		NB-- 0	SB-- 0	0	NB-- 0	SB-- 0	0
ATSAC-1 or ATSAC+ATCS-2?		EB-- 0	WB-- 0	0	EB-- 0	WB-- 0	0
Override Capacity				2			2
Override Capacity				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	↵ Left	8	1	8	22	1	22
	↵↔ Left-Through		0			0	
	→ Through	2174	1	1119	1969	1	991
	↵↔ Through-Right		1			1	
	↵ Right	63	0	63	12	0	12
	↵↔ Left-Through-Right		0			0	
	↵↔ Left-Right		0			0	
SOUTHBOUND	↵ Left	323	1	323	32	1	32
	↵↔ Left-Through		0			0	
	→ Through	1934	1	1013	2163	1	1116
	↵↔ Through-Right		1			1	
	↵ Right	92	0	92	68	0	68
	↵↔ Left-Through-Right		0			0	
	↵↔ Left-Right		0			0	
EASTBOUND	↵ Left	125	1	125	101	1	101
	↵↔ Left-Through		0			0	
	→ Through	2	0	17	3	0	26
	↵↔ Through-Right		1			1	
	↵ Right	15	0	0	23	0	0
	↵↔ Left-Through-Right		0			0	
	↵↔ Left-Right		0			0	
WESTBOUND	↵ Left	2	0	2	6	0	6
	↵↔ Left-Through		1			1	
	→ Through	0	0	2	15	0	21
	↵↔ Through-Right		0			0	
	↵ Right	12	1	0	77	1	61
	↵↔ Left-Through-Right		0			0	
	↵↔ Left-Right		0			0	
CRITICAL VOLUMES		<i>North-South:</i>		1442	<i>North-South:</i>		1138
		<i>East-West:</i>		127	<i>East-West:</i>		162
		SUM:		1569	SUM:		1300
VOLUME/CAPACITY (V/C) RATIO:				1.141			0.945
V/C LESS ATSAC/ATCS ADJUSTMENT:				1.041			0.845
LEVEL OF SERVICE (LOS):				F			D

Level of Service Worksheet (Circular 212 Method)



I/S #:
26

PROJECT TITLE: SPW, POC Addendum
North-South Street: Harbor Blvd
Scenario: Future With Project
Count Date: 1/0/1900

East-West Street: SR 47 EB Off-Ramp / Swinford St
Analyst: <Fehr & Peers> **Date:** <date>

		AM			PM		
		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
No. of Phases				4			4
Opposed Ø'ing: N/S-1, E/W-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		NB-- 0	SB-- 0	0	NB-- 0	SB-- 0	0
		EB-- 3	WB-- 3	3	EB-- 3	WB-- 3	3
ATSAC-1 or ATSAC+ATCS-2?				2			2
Override Capacity				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	↶ Left	652	2	359	573	2	315
	↶↷ Left-Through		0			0	
	→ Through	1098	1	565	1168	1	590
	↷ Through-Right		1			1	
	↷ Right	32	0	32	12	0	12
	↷↶ Left-Through-Right		0			0	
	↷↶ Left-Right		0			0	
SOUTHBOUND	↷ Left	250	2	138	158	2	87
	↷↶ Left-Through		0			0	
	→ Through	687	2	252	1569	2	556
	↷ Through-Right		1			1	
	↷ Right	69	0	69	99	0	99
	↷↶ Left-Through-Right		0			0	
	↷↶ Left-Right		0			0	
EASTBOUND	↶ Left	38	1	38	45	1	45
	↶↷ Left-Through		0			0	
	→ Through	323	1	323	69	1	69
	↷ Through-Right		1			1	
	↷ Right	853	1	110	606	1	18
	↷↶ Left-Through-Right		0			0	
	↷↶ Left-Right		0			0	
WESTBOUND	↶ Left	17	1	17	12	1	12
	↶↷ Left-Through		0			0	
	→ Through	133	1	133	70	1	70
	↷ Through-Right		0			0	
	↷ Right	347	1	209	122	1	35
	↷↶ Left-Through-Right		0			0	
	↷↶ Left-Right		0			0	
CRITICAL VOLUMES				<i>North-South:</i> 703			<i>North-South:</i> 871
				<i>East-West:</i> 340			<i>East-West:</i> 115
				<i>SUM:</i> 1043			<i>SUM:</i> 986
VOLUME/CAPACITY (V/C) RATIO:				0.759			0.717
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.659			0.617
LEVEL OF SERVICE (LOS):				B			B



Level of Service Worksheet (Circular 212 Method)



I/S #:
27

PROJECT TITLE: SPW, POC Addendum
North-South Street: Harbor Blvd
Scenario: Future With Project
Count Date: 1/0/1900

East-West Street: SR-47 WB On-Ramp
Analyst: <Fehr & Peers> **Date:** <date>

		AM			PM		
No. of Phases				4			4
Opposed Ø'ing: N/S-1, E/W-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		NB-- 3	SB-- 3	3	NB-- 3	SB-- 3	3
ATSAC-1 or ATSAC+ATCS-2?		EB-- 1	WB-- 0	0	EB-- 1	WB-- 0	0
Override Capacity				2			2
Override Capacity				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	↵ Left	1462	2	804	1083	2	596
	↵↵ Left-Through		0			0	
	→ Through	390	0	432	280	0	317
	↵↵↵ Through-Right		1			1	
	↵ Right	42	0	0	37	0	0
	↵↵↵ Left-Through-Right		0			0	
↵↵↵ Left-Right		0			0		
SOUTHBOUND	↵↵ Left	4	1	4	34	1	34
	↵↵ Left-Through		0			0	
	→ Through	340	2	170	459	2	230
	↵↵ Through-Right		0			0	
	↵ Right	29	1	0	0	1	0
	↵↵↵ Left-Through-Right		0			0	
↵↵↵ Left-Right		0			0		
EASTBOUND	↵ Left	43	1	43	100	1	100
	↵↵ Left-Through		0			0	
	→ Through	234	1	234	60	1	60
	↵↵ Through-Right		0			0	
	↵ Right	601	1	0	1039	1	0
	↵↵↵ Left-Through-Right		0			0	
↵↵↵ Left-Right		0			0		
WESTBOUND	↵ Left	45	2	25	141	2	78
	↵↵ Left-Through		0			0	
	→ Through	138	2	69	95	2	48
	↵↵ Through-Right		0			0	
	↵ Right	11	1	9	27	1	10
	↵↵↵ Left-Through-Right		0			0	
↵↵↵ Left-Right		0			0		
CRITICAL VOLUMES				<i>North-South:</i> 974			<i>North-South:</i> 826
				<i>East-West:</i> 259			<i>East-West:</i> 148
				SUM: 1233			SUM: 974
VOLUME/CAPACITY (V/C) RATIO:				0.897			0.708
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.797			0.608
LEVEL OF SERVICE (LOS):				C			B



Level of Service Worksheet (Circular 212 Method)



I/S #:
29

PROJECT TITLE: SPW, POC Addendum
North-South Street: Harbor
Scenario: Future With Project
Count Date: 1/0/1900

East-West Street: O'Farrell

Analyst: <Fehr & Peers> **Date:** <date>

		AM			PM		
		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
No. of Phases				2			2
Opposed Ø'ing: N/S-1, E/W-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		NB-- 0	SB-- 0	0	NB-- 0	SB-- 0	0
ATSAC-1 or ATSAC+ATCS-2?		EB-- 0	WB-- 0	0	EB-- 0	WB-- 0	0
Override Capacity				2			2
Override Capacity				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	↶ Left	11	1	11	17	1	17
	↷ Left-Through		0			0	
	→ Through	2362	2	1181	2270	2	1135
	↷ Through-Right		0			0	
	→ Right	0	0	0	0	0	0
	↷ Left-Through-Right		0			0	
	↶ Left-Right		0			0	
SOUTHBOUND	↷ Left	0	0	0	0	0	0
	↶ Left-Through		0			0	
	→ Through	2528	1	1272	3137	1	1586
	↶ Through-Right		1			1	
	→ Right	16	0	16	35	0	35
	↶ Left-Through-Right		0			0	
	↷ Left-Right		0			0	
EASTBOUND	↶ Left	128	1	128	133	1	133
	↷ Left-Through		0			0	
	→ Through	0	0	0	0	0	0
	↷ Through-Right		0			0	
	→ Right	13	1	8	17	1	9
	↷ Left-Through-Right		0			0	
	↶ Left-Right		0			0	
WESTBOUND	↷ Left	0	0	0	0	0	0
	↶ Left-Through		0			0	
	→ Through	0	0	0	0	0	0
	↷ Through-Right		0			0	
	→ Right	0	0	0	0	0	0
	↷ Left-Through-Right		0			0	
	↶ Left-Right		0			0	
CRITICAL VOLUMES				<i>North-South:</i> 1283			<i>North-South:</i> 1603
				<i>East-West:</i> 128			<i>East-West:</i> 133
				<i>SUM:</i> 1411			<i>SUM:</i> 1736
VOLUME/CAPACITY (V/C) RATIO:				0.941			1.157
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.841			1.057
LEVEL OF SERVICE (LOS):				D			F



Level of Service Worksheet (Circular 212 Method)



I/S #:
30

PROJECT TITLE: SPW, POC Addendum
North-South Street: Harbor
Scenario: Future With Project
Count Date: 1/0/1900

East-West Street: 3rd

Analyst: <Fehr & Peers> **Date:** <date>

		AM			PM		
		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
No. of Phases Opposed Ø'ing: N/S-1, E/W-2 or Both-3? Right Turns: FREE-1, NRTOR-2 or OLA-3? ATSAC-1 or ATSAC+ATCS-2? Override Capacity				0			0
				0			0
		<i>NB--</i> 0		<i>SB--</i> 0	<i>NB--</i> 0		<i>SB--</i> 0
		<i>EB--</i> 0		<i>WB--</i> 0	<i>EB--</i> 0		<i>WB--</i> 0
				2			2
				1200			1200
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	↵ Left	22	1	22	33	1	33
	↵↵ Left-Through		0			0	
	→ Through	1999	2	1000	1898	2	949
	↵↵↵ Through-Right		0			0	
	↵ Right	1	0	0	0	0	0
	↵↵↵ Left-Through-Right		0			0	
	↵↵ Left-Right		0			0	
SOUTHBOUND	↵↵ Left	3	0	0	2	0	0
	↵↵ Left-Through		0			0	
	→ Through	1748	1	971	2066	1	1073
	↵↵ Through-Right		1			1	
	↵ Right	194	0	194	80	0	80
	↵↵↵ Left-Through-Right		0			0	
	↵↵ Left-Right		0			0	
EASTBOUND	↵ Left	130	1	130	72	1	72
	↵↵ Left-Through		0			0	
	→ Through	0	0	0	0	0	0
	↵↵ Through-Right		0			0	
	↵ Right	24	1	13	36	1	20
	↵↵↵ Left-Through-Right		0			0	
	↵↵ Left-Right		0			0	
WESTBOUND	↵ Left	0	0	0	1	0	0
	↵↵ Left-Through		0			0	
	→ Through	0	0	0	0	0	0
	↵↵ Through-Right		0			0	
	↵ Right	1	0	0	5	0	0
	↵↵↵ Left-Through-Right		0			0	
	↵↵ Left-Right		0			0	
CRITICAL VOLUMES				<i>North-South:</i> 1000 <i>East-West:</i> 130 <i>SUM:</i> 1130			<i>North-South:</i> 1106 <i>East-West:</i> 72 <i>SUM:</i> 1178
VOLUME/CAPACITY (V/C) RATIO:				0.942			0.982
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.842			0.882
LEVEL OF SERVICE (LOS):				D			D



Level of Service Worksheet (Circular 212 Method)



I/S #:
31

PROJECT TITLE: SPW, POC Addendum
North-South Street: Pacific Ave
Scenario: Future With Project
Count Date: 1/0/1900

East-West Street: 13th

Analyst: <Fehr & Peers> **Date:** <date>

		AM			PM		
		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
No. of Phases				2			2
Opposed Ø'ing: N/S-1, E/W-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		NB-- 0	SB-- 0	0	NB-- 0	SB-- 0	0
ATSAC-1 or ATSAC+ATCS-2?		EB-- 0	WB-- 0	0	EB-- 0	WB-- 0	0
Override Capacity				2			2
Override Capacity				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	↵ Left	53	1	53	49	1	49
	↵↔ Left-Through		0			0	
	→ Through	1002	1	1002	670	1	670
	↘ Through-Right		0			0	
	↘ Right	24	1	24	29	1	29
	↘↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
SOUTHBOUND	↵ Left	11	1	11	34	1	34
	↵↔ Left-Through		0			0	
	→ Through	355	1	355	836	1	836
	↘ Through-Right		0			0	
	↘ Right	121	1	121	114	1	114
	↘↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
EASTBOUND	↵ Left	121	0	121	78	0	78
	↵↔ Left-Through		0			0	
	→ Through	76	0	239	101	0	242
	↘ Through-Right		0			0	
	↘ Right	42	0	0	63	0	0
	↘↔ Left-Through-Right		1			1	
	↘↔ Left-Right		0			0	
WESTBOUND	↵ Left	18	0	18	24	0	24
	↵↔ Left-Through		0			0	
	→ Through	127	0	200	100	0	152
	↘ Through-Right		0			0	
	↘ Right	55	0	0	28	0	0
	↘↔ Left-Through-Right		1			1	
	↘↔ Left-Right		0			0	
CRITICAL VOLUMES				<i>North-South:</i> 1013			<i>North-South:</i> 885
				<i>East-West:</i> 321			<i>East-West:</i> 266
				<i>SUM:</i> 1334			<i>SUM:</i> 1151
VOLUME/CAPACITY (V/C) RATIO:				0.889			0.767
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.789			0.667
LEVEL OF SERVICE (LOS):				C			B



Level of Service Worksheet (Circular 212 Method)



I/S #:
32

PROJECT TITLE: SPW, POC Addendum
North-South Street: Pacific Ave
Scenario: Future With Project
Count Date: 1/0/1900

East-West Street: 17th

Analyst: <Fehr & Peers> **Date:** <date>

		AM			PM		
		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
No. of Phases				2			2
Opposed Ø'ing: N/S-1, E/W-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		NB-- 0	SB-- 0	0	NB-- 0	SB-- 0	0
ATSAC-1 or ATSAC+ATCS-2?		EB-- 0	WB-- 0	0	EB-- 0	WB-- 0	0
Override Capacity				2			2
Override Capacity				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	↵ Left	57	1	57	19	1	19
	↵↔ Left-Through		0			0	
	→ Through	665	1	665	573	1	573
	↘ Through-Right		0			0	
	↘ Right	4	1	4	9	1	9
	↘↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
SOUTHBOUND	↵ Left	21	1	21	17	1	17
	↵↔ Left-Through		0			0	
	→ Through	309	1	309	745	1	745
	↘ Through-Right		0			0	
	↘ Right	83	1	83	78	1	78
	↘↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
EASTBOUND	↵ Left	192	0	192	49	0	49
	↵↔ Left-Through		0			0	
	→ Through	145	0	379	56	0	133
	↘ Through-Right		0			0	
	↘ Right	42	0	0	28	0	0
	↘↔ Left-Through-Right		1			1	
	↘↔ Left-Right		0			0	
WESTBOUND	↵ Left	6	0	6	34	0	34
	↵↔ Left-Through		0			0	
	→ Through	124	0	166	111	0	176
	↘ Through-Right		0			0	
	↘ Right	36	0	0	31	0	0
	↘↔ Left-Through-Right		1			1	
	↘↔ Left-Right		0			0	
CRITICAL VOLUMES				<i>North-South:</i> 686			<i>North-South:</i> 764
				<i>East-West:</i> 385			<i>East-West:</i> 225
				SUM: 1071			SUM: 989
VOLUME/CAPACITY (V/C) RATIO:				0.714			0.659
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.614			0.559
LEVEL OF SERVICE (LOS):				B			A



Level of Service Worksheet (Circular 212 Method)



I/S #:
33

PROJECT TITLE: SPW, POC Addendum
North-South Street: 19th St
Scenario: Future With Project
Count Date: 1/0/1900

East-West Street: Pacific
Analyst: <Fehr & Peers> **Date:** <date>

		AM			PM		
		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
No. of Phases				2			2
Opposed Ø'ing: N/S-1, E/W-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		NB-- 0	SB-- 0	0	NB-- 0	SB-- 0	0
ATSAC-1 or ATSAC+ATCS-2?		EB-- 0	WB-- 0	0	EB-- 0	WB-- 0	0
Override Capacity				2			2
				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	↶ Left	17	1	17	29	1	29
	↷ Left-Through		0			0	
	→ Through	538	1	538	469	1	469
	↷ Through-Right		0			0	
	↷ Right	17	1	17	16	1	16
	↷ Left-Through-Right		0			0	
	↷ Left-Right		0			0	
SOUTHBOUND	↷ Left	15	1	15	27	1	27
	↶ Left-Through		0			0	
	→ Through	256	1	256	685	1	685
	↶ Through-Right		0			0	
	↶ Right	28	1	28	43	1	43
	↶ Left-Through-Right		0			0	
	↶ Left-Right		0			0	
EASTBOUND	↶ Left	37	0	37	46	0	46
	↷ Left-Through		0			0	
	→ Through	111	0	187	43	0	121
	↷ Through-Right		0			0	
	↷ Right	39	0	0	32	0	0
	↷ Left-Through-Right		1			1	
	↷ Left-Right		0			0	
WESTBOUND	↶ Left	10	0	10	42	0	42
	↷ Left-Through		0			0	
	→ Through	54	0	74	114	0	177
	↷ Through-Right		0			0	
	↷ Right	10	0	0	21	0	0
	↷ Left-Through-Right		1			1	
	↷ Left-Right		0			0	
CRITICAL VOLUMES				<i>North-South:</i> 553			<i>North-South:</i> 714
				<i>East-West:</i> 197			<i>East-West:</i> 223
				<i>SUM:</i> 750			<i>SUM:</i> 937
VOLUME/CAPACITY (V/C) RATIO:				0.500			0.625
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.400			0.525
LEVEL OF SERVICE (LOS):				A			A



Level of Service Worksheet (Circular 212 Method)



I/S #:
34

PROJECT TITLE: SPW, POC Addendum
North-South Street: Gaffey St
Scenario: Future With Project
Count Date: 1/0/1900

East-West Street: 13th

Analyst: <Fehr & Peers> **Date:** <date>

		AM			PM		
		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
No. of Phases				2			2
Opposed Ø'ing: N/S-1, E/W-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		NB-- 0	SB-- 0	0	NB-- 0	SB-- 0	0
ATSAC-1 or ATSAC+ATCS-2?		EB-- 0	WB-- 0	0	EB-- 0	WB-- 0	0
Override Capacity				2			2
Override Capacity				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	↵ Left	38	1	38	71	1	71
	↵↵ Left-Through		0			0	
	↵↵ Through	1486	1	779	1050	1	550
	↵↵ Through-Right		1			1	
	↵↵ Right	71	0	71	50	0	50
	↵↵↵ Left-Through-Right		0			0	
	↵↵↵ Left-Right		0			0	
SOUTHBOUND	↵↵ Left	37	1	37	97	1	97
	↵↵ Left-Through		0			0	
	↵↵ Through	848	1	499	1234	1	661
	↵↵ Through-Right		1			1	
	↵↵ Right	149	0	149	87	0	87
	↵↵↵ Left-Through-Right		0			0	
	↵↵↵ Left-Right		0			0	
EASTBOUND	↵↵ Left	215	0	215	195	0	195
	↵↵ Left-Through		0			0	
	↵↵ Through	307	0	579	159	0	446
	↵↵ Through-Right		0			0	
	↵↵ Right	57	0	0	92	0	0
	↵↵↵ Left-Through-Right		1			1	
	↵↵↵ Left-Right		0			0	
WESTBOUND	↵↵ Left	60	0	60	34	0	34
	↵↵ Left-Through		0			0	
	↵↵ Through	346	0	598	200	0	315
	↵↵ Through-Right		0			0	
	↵↵ Right	192	0	0	81	0	0
	↵↵↵ Left-Through-Right		1			1	
	↵↵↵ Left-Right		0			0	
CRITICAL VOLUMES				<i>North-South:</i> 816			<i>North-South:</i> 732
				<i>East-West:</i> 813			<i>East-West:</i> 510
				SUM: 1629			SUM: 1242
VOLUME/CAPACITY (V/C) RATIO:				1.086			0.828
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.986			0.728
LEVEL OF SERVICE (LOS):				E			C



Level of Service Worksheet (Circular 212 Method)



I/S #:
5

PROJECT TITLE: SPW, POC Addendum
North-South Street: Gaffey St
Scenario: Future With Project
Count Date: 1/0/1900

East-West Street: 9th St

Analyst: <Fehr & Peers> **Date:** <date>

		SAT					
No. of Phases				2			2
Opposed Ø'ing: N/S-1, E/W-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		<i>NB--</i> 0	<i>SB--</i> 0	0	<i>NB--</i> 0	<i>SB--</i> 0	0
ATSAC-1 or ATSAC+ATCS-2?		<i>EB--</i> 0	<i>WB--</i> 0	0	<i>EB--</i> 0	<i>WB--</i> 0	0
Override Capacity				2			2
				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	Left	81	1	81	0	1	0
	Left-Through		0			0	
	Through	1283	2	642	0	2	0
	Through-Right		0			0	
	Right	53	1	12	0	1	0
	Left-Through-Right		0			0	
	Left-Right		0			0	
SOUTHBOUND	Left	159	1	159	0	1	0
	Left-Through		0			0	
	Through	1402	1	753	0	1	0
	Through-Right		1			1	
	Right	103	0	103	0	0	0
	Left-Through-Right		0			0	
	Left-Right		0			0	
EASTBOUND	Left	212	1	212	0	1	0
	Left-Through		0			0	
	Through	244	1	244	0	1	0
	Through-Right		0			0	
	Right	73	1	33	0	1	0
	Left-Through-Right		0			0	
	Left-Right		0			0	
WESTBOUND	Left	83	1	83	0	1	0
	Left-Through		0			0	
	Through	216	0	366	0	0	0
	Through-Right		1			1	
	Right	150	0	0	0	0	0
	Left-Through-Right		0			0	
	Left-Right		0			0	
CRITICAL VOLUMES		<i>North-South:</i>		834	<i>North-South:</i>		0
		<i>East-West:</i>		578	<i>East-West:</i>		0
		<i>SUM:</i>		1412	<i>SUM:</i>		0
VOLUME/CAPACITY (V/C) RATIO:				0.941			0.000
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.841			0.000
LEVEL OF SERVICE (LOS):				D			A



Level of Service Worksheet (Circular 212 Method)



I/S #:
6

PROJECT TITLE: SPW, POC Addendum
North-South Street: Gaffey St
Scenario: Future With Project
Count Date: 1/0/1900

East-West Street: 7th St

Analyst: <Fehr & Peers> **Date:** <date>

		SAT					
No. of Phases				2			2
Opposed Ø'ing: N/S-1, E/W-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		NB-- 0	SB-- 0	0	NB-- 0	SB-- 0	0
ATSAC-1 or ATSAC+ATCS-2?		EB-- 0	WB-- 0	0	EB-- 0	WB-- 0	0
Override Capacity				2			2
				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	↶ Left	29	1	29	0	1	0
	↶↷ Left-Through		0		0	0	0
	→ Through	1652	2	826	0	2	0
	↷ Through-Right		0		0	0	0
	→ Right	60	1	20	0	1	0
	↷↶ Left-Through-Right		0		0	0	0
	↷ Left-Right		0		0	0	
SOUTHBOUND	↷ Left	164	1	164	0	1	0
	↷↶ Left-Through		0		0	0	0
	→ Through	1456	1	788	0	1	0
	↶ Through-Right		1		0	1	0
	→ Right	119	0	119	0	0	0
	↶↷ Left-Through-Right		0		0	0	0
	↷ Left-Right		0		0	0	
EASTBOUND	↶ Left	116	1	116	0	1	0
	↶↷ Left-Through		0		0	0	0
	→ Through	127	0	180	0	0	0
	↷ Through-Right		1		0	1	0
	→ Right	53	0	0	0	0	0
	↷↶ Left-Through-Right		0		0	0	0
	↷ Left-Right		0		0	0	
WESTBOUND	↶ Left	81	1	81	0	1	0
	↶↷ Left-Through		0		0	0	0
	→ Through	128	0	237	0	0	0
	↷ Through-Right		1		0	1	0
	→ Right	109	0	0	0	0	0
	↷↶ Left-Through-Right		0		0	0	0
	↷ Left-Right		0		0	0	
CRITICAL VOLUMES		<i>North-South:</i>		990	<i>North-South:</i>		0
		<i>East-West:</i>		353	<i>East-West:</i>		0
		SUM:		1343	SUM:		0
VOLUME/CAPACITY (V/C) RATIO:				0.895			0.000
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.795			0.000
LEVEL OF SERVICE (LOS):				C			A



Level of Service Worksheet (Circular 212 Method)



I/S #:
7

PROJECT TITLE: SPW, POC Addendum
North-South Street: Gaffey St
Scenario: Future With Project
Count Date: 1/0/1900

East-West Street: 6th St

Analyst: <Fehr & Peers> **Date:** <date>

		SAT					
No. of Phases				0			0
Opposed Ø'ing: N/S-1, E/W-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		<i>NB--</i> 0	<i>SB--</i> 0	0	<i>NB--</i> 0	<i>SB--</i> 0	0
ATSAC-1 or ATSAC+ATCS-2?		<i>EB--</i> 0	<i>WB--</i> 0	0	<i>EB--</i> 0	<i>WB--</i> 0	0
Override Capacity				2			2
				1200			1200
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	Left	73	1	73	0	1	0
	Left-Through		0		0	0	0
	Through	1738	1	893	0	1	0
	Through-Right		1		0	1	0
	Right	47	0	47	0	0	0
	Left-Through-Right		0		0	0	0
	Left-Right		0		0	0	0
SOUTHBOUND	Left	102	1	102	0	1	0
	Left-Through		0		0	0	0
	Through	1695	1	867	0	1	0
	Through-Right		1		0	1	0
	Right	39	0	39	0	0	0
	Left-Through-Right		0		0	0	0
	Left-Right		0		0	0	0
EASTBOUND	Left	11	0	11	0	0	0
	Left-Through		1		0	1	0
	Through	18	0	29	0	0	0
	Through-Right		0		0	0	0
	Right	64	1	28	0	1	0
	Left-Through-Right		0		0	0	0
	Left-Right		0		0	0	0
WESTBOUND	Left	10	0	10	0	0	0
	Left-Through		1		0	1	0
	Through	19	0	29	0	0	0
	Through-Right		0		0	0	0
	Right	104	1	53	0	1	0
	Left-Through-Right		0		0	0	0
	Left-Right		0		0	0	0
CRITICAL VOLUMES		<i>North-South:</i>		995	<i>North-South:</i>		0
		<i>East-West:</i>		64	<i>East-West:</i>		0
		<i>SUM:</i>		1059	<i>SUM:</i>		0
VOLUME/CAPACITY (V/C) RATIO:				0.883			0.000
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.783			0.000
LEVEL OF SERVICE (LOS):				C			A



Level of Service Worksheet (Circular 212 Method)



I/S #:
8

PROJECT TITLE: SPW, POC Addendum
North-South Street: Gaffey St
Scenario: Future With Project
Count Date: 1/0/1900

East-West Street: 5th St

Analyst: <Fehr & Peers> **Date:** <date>

		SAT					
				3			3
No. of Phases				3			3
Opposed Ø'ing: N/S-1, E/W-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		<i>NB--</i> 0	<i>SB--</i> 0	0	<i>NB--</i> 0	<i>SB--</i> 0	0
ATSAC-1 or ATSAC+ATCS-2?		<i>EB--</i> 0	<i>WB--</i> 0	0	<i>EB--</i> 0	<i>WB--</i> 0	0
Override Capacity				2			2
				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	Left	50	1	50	0	1	0
	Left-Through		0		0	0	0
	Through	1719	2	860	0	2	0
	Through-Right		0		0	0	0
	Right	32	1	10	0	1	0
	Left-Through-Right		0		0	0	0
SOUTHBOUND	Left	132	1	132	0	1	0
	Left-Through		0		0	0	0
	Through	1823	2	912	0	2	0
	Through-Right		0		0	0	0
	Right	90	1	31	0	1	0
	Left-Through-Right		0		0	0	0
EASTBOUND	Left	118	1	118	0	1	0
	Left-Through		0		0	0	0
	Through	91	0	120	0	0	0
	Through-Right		1		0	1	0
	Right	29	0	0	0	0	0
	Left-Through-Right		0		0	0	0
WESTBOUND	Left	44	1	44	0	1	0
	Left-Through		0		0	0	0
	Through	107	0	230	0	0	0
	Through-Right		1		0	1	0
	Right	123	0	0	0	0	0
	Left-Through-Right		0		0	0	0
CRITICAL VOLUMES				<i>North-South:</i> 992		<i>North-South:</i> 0	
				<i>East-West:</i> 348		<i>East-West:</i> 0	
				<i>SUM:</i> 1340		<i>SUM:</i> 0	
VOLUME/CAPACITY (V/C) RATIO:				0.940		0.000	
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.840		0.000	
LEVEL OF SERVICE (LOS):				D		A	



Level of Service Worksheet (Circular 212 Method)



I/S #:
9

PROJECT TITLE: SPW, POC Addendum
North-South Street: Gaffey St
Scenario: Future With Project
Count Date: 1/0/1900

East-West Street: 1st St

Analyst: <Fehr & Peers> **Date:** <date>

		SAT					
No. of Phases				4			4
Opposed Ø'ing: N/S-1, E/W-2 or Both-3?				2			2
Right Turns: FREE-1, NRTOR-2 or OLA-3?		NB-- 0	SB-- 0	0	NB-- 0	SB-- 0	0
		EB-- 0	WB-- 0	0	EB-- 0	WB-- 0	0
ATSAC-1 or ATSAC+ATCS-2?				2			2
Override Capacity				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	↶ Left	49	1	49	0	1	0
	↷ Left-Through		0		0	0	0
	→ Through	1725	2	583	0	2	0
	↷ Through-Right		1		0	1	0
	↘ Right	25	0	25	0	0	0
	↷ Left-Through-Right		0		0	0	0
	↶ Left-Right		0		0	0	
SOUTHBOUND	↷ Left	200	1	200	0	1	0
	↶ Left-Through		0		0	0	0
	→ Through	2348	2	958	0	2	0
	↶ Through-Right		1		0	1	0
	↘ Right	527	0	527	0	0	0
	↷ Left-Through-Right		0		0	0	0
	↷ Left-Right		0		0	0	
EASTBOUND	↶ Left	763	2	420	0	2	0
	↷ Left-Through		0		0	0	0
	→ Through	188	0	297	0	0	0
	↷ Through-Right		1		0	1	0
	↘ Right	109	0	0	0	0	0
	↷ Left-Through-Right		0		0	0	0
	↷ Left-Right		0		0	0	
WESTBOUND	↶ Left	64	1	64	0	1	0
	↷ Left-Through		0		0	0	0
	→ Through	212	1	212	0	1	0
	↷ Through-Right		0		0	0	0
	↘ Right	218	1	118	0	1	0
	↷ Left-Through-Right		0		0	0	0
	↷ Left-Right		0		0	0	
CRITICAL VOLUMES		<i>North-South:</i>		1007	<i>North-South:</i>		0
		<i>East-West:</i>		632	<i>East-West:</i>		0
		SUM:		1639	SUM:		0
VOLUME/CAPACITY (V/C) RATIO:				1.192			0.000
V/C LESS ATSAC/ATCS ADJUSTMENT:				1.092			0.000
LEVEL OF SERVICE (LOS):				F			A



Level of Service Worksheet (Circular 212 Method)



I/S #:
11

PROJECT TITLE: SPW, POC Addendum
North-South Street: Summerland Ave
Scenario: Future With Project
Count Date: 1/0/1900

East-West Street: Gaffey St
Analyst: <Fehr & Peers> **Date:** <date>

		SAT					
				3			3
No. of Phases				3			3
Opposed Ø'ing: N/S-1, E/W-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		<i>NB--</i> 0	<i>SB--</i> 0	0	<i>NB--</i> 0	<i>SB--</i> 0	0
ATSAC-1 or ATSAC+ATCS-2?		<i>EB--</i> 0	<i>WB--</i> 0	0	<i>EB--</i> 0	<i>WB--</i> 0	0
Override Capacity				2			2
				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	Left	200	1	200	0	1	0
	Left-Through		0			0	
	Through	654	1	346	0	1	0
	Through-Right		1			1	
	Right	38	0	38	0	0	0
	Left-Through-Right		0			0	
	Left-Right		0			0	
SOUTHBOUND	Left	18	1	18	0	1	0
	Left-Through		0			0	
	Through	731	2	366	0	2	0
	Through-Right		0			0	
	Right	216	1	112	0	1	0
	Left-Through-Right		0			0	
	Left-Right		0			0	
EASTBOUND	Left	209	1	209	0	1	0
	Left-Through		0			0	
	Through	6	0	99	0	0	0
	Through-Right		1			1	
	Right	93	0	0	0	0	0
	Left-Through-Right		0			0	
	Left-Right		0			0	
WESTBOUND	Left	435	2	239	0	2	0
	Left-Through		0			0	
	Through	153	0	318	0	0	0
	Through-Right		1			1	
	Right	165	0	0	0	0	0
	Left-Through-Right		0			0	
	Left-Right		0			0	
CRITICAL VOLUMES				<i>North-South:</i> 566			<i>North-South:</i> 0
				<i>East-West:</i> 527			<i>East-West:</i> 0
				<i>SUM:</i> 1093			<i>SUM:</i> 0
VOLUME/CAPACITY (V/C) RATIO:				0.767			0.000
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.667			0.000
LEVEL OF SERVICE (LOS):				B			A



Level of Service Worksheet (Circular 212 Method)



I/S #:
12

PROJECT TITLE: SPW, POC Addendum
North-South Street: Pacific Ave
Scenario: Future With Project
Count Date: 1/0/1900

East-West Street: 22nd St

Analyst: <Fehr & Peers> **Date:** <date>

		SAT					
				2			2
No. of Phases				2			2
Opposed Ø'ing: N/S-1, E/W-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		NB-- 0	SB-- 0	0	NB-- 0	SB-- 0	0
		EB-- 0	WB-- 0	0	EB-- 0	WB-- 0	0
ATSAC-1 or ATSAC+ATCS-2?				2			2
Override Capacity				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	Left	33	1	33	0	1	0
	Left-Through		0			0	
	Through	345	1	345	0	1	0
	Through-Right		0			0	
	Right	115	1	115	0	1	0
	Left-Through-Right		0			0	
SOUTHBOUND	Left	69	1	69	0	1	0
	Left-Through		0			0	
	Through	352	1	352	0	1	0
	Through-Right		0			0	
	Right	64	1	64	0	1	0
	Left-Through-Right		0			0	
EASTBOUND	Left	22	0	22	0	0	0
	Left-Through		0			0	
	Through	251	0	314	0	0	0
	Through-Right		0			0	
	Right	41	0	0	0	0	0
	Left-Through-Right		1			1	
WESTBOUND	Left	182	0	182	0	0	0
	Left-Through		0			0	
	Through	205	0	446	0	0	0
	Through-Right		0			0	
	Right	59	0	0	0	0	0
	Left-Through-Right		1			1	
CRITICAL VOLUMES				<i>North-South:</i> 414			<i>North-South:</i> 0
				<i>East-West:</i> 496			<i>East-West:</i> 0
				<i>SUM:</i> 910			<i>SUM:</i> 0
VOLUME/CAPACITY (V/C) RATIO:				0.607			0.000
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.507			0.000
LEVEL OF SERVICE (LOS):				A			A



Level of Service Worksheet (Circular 212 Method)



I/S #:
13

PROJECT TITLE: SPW, POC Addendum
North-South Street: Pacific Ave
Scenario: Future With Project
Count Date: 1/0/1900

East-West Street: 9th St

Analyst: <Fehr & Peers> **Date:** <date>

		SAT					
No. of Phases				2			2
Opposed Ø'ing: N/S-1, E/W-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		NB-- 0	SB-- 0	0	NB-- 0	SB-- 0	0
ATSAC-1 or ATSAC+ATCS-2?		EB-- 0	WB-- 0	0	EB-- 0	WB-- 0	0
Override Capacity				2			2
				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	Left	68	1	68	0	1	0
	Left-Through		0			0	
	Through	722	1	722	0	1	0
	Through-Right		0			0	
	Right	34	1	8	0	1	0
	Left-Through-Right		0			0	
	Left-Right		0			0	
SOUTHBOUND	Left	102	1	102	0	1	0
	Left-Through		0			0	
	Through	740	1	740	0	1	0
	Through-Right		0			0	
	Right	49	1	3	0	1	0
	Left-Through-Right		0			0	
	Left-Right		0			0	
EASTBOUND	Left	93	1	93	0	1	0
	Left-Through		0			0	
	Through	203	0	302	0	0	0
	Through-Right		1			1	
	Right	99	0	0	0	0	0
	Left-Through-Right		0			0	
	Left-Right		0			0	
WESTBOUND	Left	52	1	52	0	1	0
	Left-Through		0			0	
	Through	159	0	224	0	0	0
	Through-Right		1			1	
	Right	65	0	0	0	0	0
	Left-Through-Right		0			0	
	Left-Right		0			0	
CRITICAL VOLUMES				<i>North-South:</i> 824			<i>North-South:</i> 0
				<i>East-West:</i> 354			<i>East-West:</i> 0
				<i>SUM:</i> 1178			<i>SUM:</i> 0
VOLUME/CAPACITY (V/C) RATIO:				0.785			0.000
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.685			0.000
LEVEL OF SERVICE (LOS):				B			A



Level of Service Worksheet (Circular 212 Method)



I/S #:
14

PROJECT TITLE: SPW, POC Addendum
North-South Street: Pacific Ave
Scenario: Future With Project
Count Date: 1/0/1900

East-West Street: 7th St

Analyst: <Fehr & Peers> **Date:** <date>

		SAT					
No. of Phases				2			2
Opposed Ø'ing: N/S-1, E/W-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		<i>NB--</i> 0	<i>SB--</i> 0	0	<i>NB--</i> 0	<i>SB--</i> 0	0
ATSAC-1 or ATSAC+ATCS-2?		<i>EB--</i> 0	<i>WB--</i> 0	0	<i>EB--</i> 0	<i>WB--</i> 0	0
Override Capacity				2			2
				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	Left	75	1	75	0	1	0
	Left-Through		0			0	
	Through	782	1	782	0	1	0
	Through-Right		0			0	
	Right	42	1	9	0	1	0
	Left-Through-Right		0			0	
SOUTHBOUND	Left	25	1	25	0	1	0
	Left-Through		0			0	
	Through	764	1	764	0	1	0
	Through-Right		0			0	
	Right	55	1	27	0	1	0
	Left-Through-Right		0			0	
EASTBOUND	Left	56	1	56	0	1	0
	Left-Through		0			0	
	Through	205	0	286	0	0	0
	Through-Right		1			1	
	Right	81	0	0	0	0	0
	Left-Through-Right		0			0	
WESTBOUND	Left	66	1	66	0	1	0
	Left-Through		0			0	
	Through	143	0	186	0	0	0
	Through-Right		1			1	
	Right	43	0	0	0	0	0
	Left-Through-Right		0			0	
CRITICAL VOLUMES		<i>North-South:</i>		839	<i>North-South:</i>		0
		<i>East-West:</i>		352	<i>East-West:</i>		0
		<i>SUM:</i>		1191	<i>SUM:</i>		0
VOLUME/CAPACITY (V/C) RATIO:				0.794			0.000
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.694			0.000
LEVEL OF SERVICE (LOS):				B			A



Level of Service Worksheet (Circular 212 Method)



I/S #:	PROJECT TITLE: SPW, POC Addendum	East-West Street: 6th St
15	North-South Street: Pacific Ave	
	Scenario: Future With Project	
	Count Date: 1/0/1900	Analyst: <Fehr & Peers> Date: <date>

		SAT					
				4			4
No. of Phases				0			0
Opposed Ø'ing: N/S-1, E/W-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		<i>NB--</i> 0	<i>SB--</i> 0	0	<i>NB--</i> 0	<i>SB--</i> 0	0
ATSAC-1 or ATSAC+ATCS-2?		<i>EB--</i> 0	<i>WB--</i> 0	0	<i>EB--</i> 0	<i>WB--</i> 0	0
Override Capacity				2			2
				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	Left	42	1	42	0	1	0
	Left-Through		0			0	
	Through	744	1	744	0	1	0
	Through-Right		0			0	
	Right	88	1	88	0	1	0
	Left-Through-Right		0			0	
	Left-Right		0			0	
SOUTHBOUND	Left	65	1	65	0	1	0
	Left-Through		0			0	
	Through	794	1	794	0	1	0
	Through-Right		0			0	
	Right	38	1	38	0	1	0
	Left-Through-Right		0			0	
	Left-Right		0			0	
EASTBOUND	Left	33	0	33	0	0	0
	Left-Through		0			0	
	Through	152	0	219	0	0	0
	Through-Right		0			0	
	Right	34	0	0	0	0	0
	Left-Through-Right		1			1	
	Left-Right		0			0	
WESTBOUND	Left	67	0	67	0	0	0
	Left-Through		0			0	
	Through	110	0	235	0	0	0
	Through-Right		0			0	
	Right	58	0	0	0	0	0
	Left-Through-Right		1			1	
	Left-Right		0			0	
CRITICAL VOLUMES		<i>North-South:</i>		836	<i>North-South:</i>		0
		<i>East-West:</i>		286	<i>East-West:</i>		0
		<i>SUM:</i>		1122	<i>SUM:</i>		0
VOLUME/CAPACITY (V/C) RATIO:				0.816			0.000
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.716			0.000
LEVEL OF SERVICE (LOS):				C			A



Level of Service Worksheet (Circular 212 Method)



I/S #:
16

PROJECT TITLE: SPW, POC Addendum
North-South Street: Pacific Ave
Scenario: Future With Project
Count Date: 1/0/1900

East-West Street: 5th St

Analyst: <Fehr & Peers> **Date:** <date>

		SAT					
No. of Phases				2			2
Opposed Ø'ing: N/S-1, E/W-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		<i>NB--</i> 0	<i>SB--</i> 0	0	<i>NB--</i> 0	<i>SB--</i> 0	0
ATSAC-1 or ATSAC+ATCS-2?		<i>EB--</i> 0	<i>WB--</i> 0	0	<i>EB--</i> 0	<i>WB--</i> 0	0
Override Capacity				2			2
				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	Left	34	1	34	0	1	0
	Left-Through		0			0	
	Through	751	1	751	0	1	0
	Through-Right		0			0	
	Right	86	1	41	0	1	0
	Left-Through-Right		0			0	
	Left-Right		0			0	
SOUTHBOUND	Left	83	1	83	0	1	0
	Left-Through		0			0	
	Through	718	1	718	0	1	0
	Through-Right		0			0	
	Right	46	1	28	0	1	0
	Left-Through-Right		0			0	
	Left-Right		0			0	
EASTBOUND	Left	36	1	36	0	1	0
	Left-Through		0			0	
	Through	117	0	181	0	0	0
	Through-Right		1			1	
	Right	64	0	0	0	0	0
	Left-Through-Right		0			0	
	Left-Right		0			0	
WESTBOUND	Left	91	1	91	0	1	0
	Left-Through		0			0	
	Through	138	0	239	0	0	0
	Through-Right		1			1	
	Right	101	0	0	0	0	0
	Left-Through-Right		0			0	
	Left-Right		0			0	
CRITICAL VOLUMES		<i>North-South:</i>		834	<i>North-South:</i>		0
		<i>East-West:</i>		275	<i>East-West:</i>		0
		<i>SUM:</i>		1109	<i>SUM:</i>		0
VOLUME/CAPACITY (V/C) RATIO:				0.739			0.000
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.639			0.000
LEVEL OF SERVICE (LOS):				B			A



Level of Service Worksheet (Circular 212 Method)



I/S #:
17

PROJECT TITLE: SPW, POC Addendum
North-South Street: Pacific Ave
Scenario: Future With Project
Count Date: 1/0/1900

East-West Street: 1st St

Analyst: <Fehr & Peers> **Date:** <date>

		SAT					
				2			2
No. of Phases				2			2
Opposed Ø'ing: N/S-1, E/W-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		<i>NB--</i> 0	<i>SB--</i> 0	0	<i>NB--</i> 0	<i>SB--</i> 0	0
ATSAC-1 or ATSAC+ATCS-2?		<i>EB--</i> 0	<i>WB--</i> 0	0	<i>EB--</i> 0	<i>WB--</i> 0	0
Override Capacity				2			2
				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	Left	136	1	136	0	1	0
	Left-Through		0		0	0	
	Through	663	1	663	0	1	0
	Through-Right		0		0	0	
	Right	43	1	43	0	1	0
	Left-Through-Right		0		0	0	
SOUTHBOUND	Left	26	1	26	0	1	0
	Left-Through		0		0	0	
	Through	666	1	666	0	1	0
	Through-Right		0		0	0	
	Right	41	1	41	0	1	0
	Left-Through-Right		0		0	0	
EASTBOUND	Left	41	0	41	0	0	0
	Left-Through		1		1	0	
	Through	176	0	217	0	0	0
	Through-Right		0		0	0	
	Right	101	1	33	0	1	0
	Left-Through-Right		0		0	0	
WESTBOUND	Left	70	0	70	0	0	0
	Left-Through		1		1	0	
	Through	161	0	231	0	0	0
	Through-Right		0		0	0	
	Right	33	1	20	0	1	0
	Left-Through-Right		0		0	0	
CRITICAL VOLUMES				<i>North-South:</i> 802			<i>North-South:</i> 0
				<i>East-West:</i> 287			<i>East-West:</i> 0
				<i>SUM:</i> 1089			<i>SUM:</i> 0
VOLUME/CAPACITY (V/C) RATIO:				0.726			0.000
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.626			0.000
LEVEL OF SERVICE (LOS):				B			A



Level of Service Worksheet (Circular 212 Method)



I/S #:
20

PROJECT TITLE: SPW, POC Addendum
North-South Street: Miner St
Scenario: Future With Project
Count Date: 1/0/1900

East-West Street: 22nd St

Analyst: <Fehr & Peers> **Date:** <date>

		SAT					
				4			4
No. of Phases				4			4
Opposed Ø'ing: N/S-1, E/W-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		<i>NB--</i> 0	<i>SB--</i> 0	0	<i>NB--</i> 0	<i>SB--</i> 0	0
ATSAC-1 or ATSAC+ATCS-2?		<i>EB--</i> 0	<i>WB--</i> 0	0	<i>EB--</i> 0	<i>WB--</i> 0	0
Override Capacity				2			2
				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	Left	87	1	87	0	1	0
	Left-Through		0		0	0	
	Through	538	1	316	0	1	0
	Through-Right		1		0	1	
	Right	94	0	94	0	0	0
	Left-Through-Right		0		0	0	
	Left-Right		0		0	0	
SOUTHBOUND	Left	63	1	63	0	1	0
	Left-Through		0		0	0	
	Through	726	1	490	0	1	0
	Through-Right		1		0	1	
	Right	254	0	254	0	0	0
	Left-Through-Right		0		0	0	
	Left-Right		0		0	0	
EASTBOUND	Left	225	1	225	0	1	0
	Left-Through		0		0	0	
	Through	117	1	107	0	1	0
	Through-Right		1		0	1	
	Right	97	0	97	0	0	0
	Left-Through-Right		0		0	0	
	Left-Right		0		0	0	
WESTBOUND	Left	116	1	116	0	1	0
	Left-Through		0		0	0	
	Through	97	1	80	0	1	0
	Through-Right		1		0	1	
	Right	62	0	62	0	0	0
	Left-Through-Right		0		0	0	
	Left-Right		0		0	0	
CRITICAL VOLUMES		<i>North-South:</i>		577	<i>North-South:</i>		0
		<i>East-West:</i>		305	<i>East-West:</i>		0
		SUM:		882	SUM:		0
VOLUME/CAPACITY (V/C) RATIO:				0.641			0.000
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.541			0.000
LEVEL OF SERVICE (LOS):				A			A



Level of Service Worksheet (Circular 212 Method)



I/S #:
21

PROJECT TITLE: SPW, POC Addendum
North-South Street: Harbor Bl / Miner St
Scenario: Future With Project
Count Date: 1/0/1900

East-West Street: Crescent Av

Analyst: <Fehr & Peers> **Date:** <date>

		SAT					
No. of Phases				0			0
Opposed Ø'ing: N/S-1, E/W-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		<i>NB--</i> 0	<i>SB--</i> 0	0	<i>NB--</i> 0	<i>SB--</i> 0	0
ATSAC-1 or ATSAC+ATCS-2?		<i>EB--</i> 0	<i>WB--</i> 0	0	<i>EB--</i> 0	<i>WB--</i> 0	0
Override Capacity				2			2
				1200			1200
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	Left	7	1	7	0	1	0
	Left-Through		0		0	0	
	Through	856	2	428	0	2	0
	Through-Right		0		0	0	
	Right	0	0	0	0	0	0
	Left-Through-Right		0		0	0	
SOUTHBOUND	Left	0	0	0	0	0	0
	Left-Through		0		0	0	
	Through	1078	1	632	0	1	0
	Through-Right		1		0	1	
	Right	185	0	185	0	0	0
	Left-Through-Right		0		0	0	
EASTBOUND	Left	117	0	117	0	0	0
	Left-Through		0		0	0	
	Through	0	0	0	0	0	0
	Through-Right		0		0	0	
	Right	5	0	122	0	0	0
	Left-Through-Right		0		0	0	
WESTBOUND	Left	0	0	0	0	0	0
	Left-Through		0		0	0	
	Through	0	0	0	0	0	0
	Through-Right		0		0	0	
	Right	0	0	0	0	0	0
	Left-Through-Right		0		0	0	
CRITICAL VOLUMES				<i>North-South:</i> 639			<i>North-South:</i> 0
				<i>East-West:</i> 122			<i>East-West:</i> 0
				<i>SUM:</i> 761			<i>SUM:</i> 0
VOLUME/CAPACITY (V/C) RATIO:				0.634			0.000
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.534			0.000
LEVEL OF SERVICE (LOS):				A			A



Level of Service Worksheet (Circular 212 Method)



I/S #:
22

PROJECT TITLE: SPW, POC Addendum
North-South Street: Harbor Blvd
Scenario: Future With Project
Count Date: 1/0/1900

East-West Street: 7th St

Analyst: <Fehr & Peers> **Date:** <date>

		SAT					
				3			3
No. of Phases				3			3
Opposed Ø'ing: N/S-1, E/W-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		<i>NB--</i> 0	<i>SB--</i> 0	0	<i>NB--</i> 0	<i>SB--</i> 0	0
ATSAC-1 or ATSAC+ATCS-2?		<i>EB--</i> 0	<i>WB--</i> 0	0	<i>EB--</i> 0	<i>WB--</i> 0	0
Override Capacity				2			2
				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	Left	66	1	66	0	1	0
	Left-Through		0			0	
	Through	1894	2	947	0	2	0
	Through-Right		0			0	
	Right	0	0	0	0	0	0
	Left-Through-Right		0			0	
SOUTHBOUND	Left	0	0	0	0	0	0
	Left-Through		0			0	
	Through	2387	2	1194	0	2	0
	Through-Right		0			0	
	Right	188	1	119	0	1	0
	Left-Through-Right		0			0	
EASTBOUND	Left	253	2	139	0	2	0
	Left-Through		0			0	
	Through	0	0	0	0	0	0
	Through-Right		0			0	
	Right	97	1	64	0	1	0
	Left-Through-Right		0			0	
WESTBOUND	Left	0	0	0	0	0	0
	Left-Through		0			0	
	Through	0	0	0	0	0	0
	Through-Right		0			0	
	Right	0	0	0	0	0	0
	Left-Through-Right		0			0	
CRITICAL VOLUMES				<i>North-South:</i> 1260			<i>North-South:</i> 0
				<i>East-West:</i> 139			<i>East-West:</i> 0
				<i>SUM:</i> 1399			<i>SUM:</i> 0
VOLUME/CAPACITY (V/C) RATIO:				0.982			0.000
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.882			0.000
LEVEL OF SERVICE (LOS):				D			A



Level of Service Worksheet (Circular 212 Method)



I/S #:
23

PROJECT TITLE: SPW, POC Addendum
North-South Street: Harbor Blvd
Scenario: Future With Project
Count Date: 1/0/1900

East-West Street: 6th St

Analyst: <Fehr & Peers> **Date:** <date>

		SAT					
				3			3
No. of Phases				3			3
Opposed Ø'ing: N/S-1, E/W-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		<i>NB--</i> 0	<i>SB--</i> 0	0	<i>NB--</i> 0	<i>SB--</i> 0	0
ATSAC-1 or ATSAC+ATCS-2?		<i>EB--</i> 0	<i>WB--</i> 0	0	<i>EB--</i> 0	<i>WB--</i> 0	0
Override Capacity				2			2
				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	Left	4	1	4	0	1	0
	Left-Through		0			0	
	Through	2043	1	1023	0	1	0
	Through-Right		1			1	
	Right	2	0	2	0	0	0
	Left-Through-Right		0			0	
	Left-Right		0			0	
SOUTHBOUND	Left	14	1	14	0	1	0
	Left-Through		0			0	
	Through	2353	1	1205	0	1	0
	Through-Right		1			1	
	Right	56	0	56	0	0	0
	Left-Through-Right		0			0	
	Left-Right		0			0	
EASTBOUND	Left	49	1	49	0	1	0
	Left-Through		0			0	
	Through	2	0	4	0	0	0
	Through-Right		1			1	
	Right	2	0	0	0	0	0
	Left-Through-Right		0			0	
	Left-Right		0			0	
WESTBOUND	Left	4	1	4	0	1	0
	Left-Through		0			0	
	Through	14	1	14	0	1	0
	Through-Right		0			0	
	Right	334	1	327	0	1	0
	Left-Through-Right		0			0	
	Left-Right		0			0	
CRITICAL VOLUMES			<i>North-South:</i>	1209	<i>North-South:</i>		0
			<i>East-West:</i>	376	<i>East-West:</i>		0
			<i>SUM:</i>	1585	<i>SUM:</i>		0
VOLUME/CAPACITY (V/C) RATIO:				1.112			0.000
V/C LESS ATSAC/ATCS ADJUSTMENT:				1.012			0.000
LEVEL OF SERVICE (LOS):				F			A



Level of Service Worksheet (Circular 212 Method)



I/S #:
24

PROJECT TITLE: SPW, POC Addendum
North-South Street: Harbor Blvd
Scenario: Future With Project
Count Date: 1/0/1900

East-West Street: 5th St

Analyst: <Fehr & Peers> **Date:** <date>

		SAT					
				3			3
No. of Phases				3			3
Opposed Ø'ing: N/S-1, E/W-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		<i>NB--</i> 0	<i>SB--</i> 0	0	<i>NB--</i> 0	<i>SB--</i> 0	0
ATSAC-1 or ATSAC+ATCS-2?		<i>EB--</i> 0	<i>WB--</i> 0	0	<i>EB--</i> 0	<i>WB--</i> 0	0
Override Capacity				2			2
				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	Left	25	1	25	0	1	0
	Left-Through		0			0	
	Through	2013	1	1008	0	1	0
	Through-Right		1			1	
	Right	2	0	2	0	0	0
	Left-Through-Right		0			0	
	Left-Right		0			0	
SOUTHBOUND	Left	1	1	1	0	1	0
	Left-Through		0			0	
	Through	2352	1	1212	0	1	0
	Through-Right		1			1	
	Right	72	0	72	0	0	0
	Left-Through-Right		0			0	
	Left-Right		0			0	
EASTBOUND	Left	93	1	93	0	1	0
	Left-Through		0			0	
	Through	5	0	46	0	0	0
	Through-Right		1			1	
	Right	41	0	0	0	0	0
	Left-Through-Right		0			0	
	Left-Right		0			0	
WESTBOUND	Left	0	1	0	0	1	0
	Left-Through		0			0	
	Through	2	1	2	0	1	0
	Through-Right		0			0	
	Right	14	1	14	0	1	0
	Left-Through-Right		0			0	
	Left-Right		0			0	
CRITICAL VOLUMES			<i>North-South:</i>	1237	<i>North-South:</i>		0
			<i>East-West:</i>	107	<i>East-West:</i>		0
			<i>SUM:</i>	1344	<i>SUM:</i>		0
VOLUME/CAPACITY (V/C) RATIO:				0.943			0.000
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.843			0.000
LEVEL OF SERVICE (LOS):				D			A



Level of Service Worksheet (Circular 212 Method)



I/S #:
25

PROJECT TITLE: SPW, POC Addendum
North-South Street: Harbor Blvd
Scenario: Future With Project
Count Date: 1/0/1900

East-West Street: 1st St

Analyst: <Fehr & Peers> **Date:** <date>

		SAT					
				4			4
No. of Phases				4			4
Opposed Ø'ing: N/S-1, E/W-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		<i>NB--</i> 0	<i>SB--</i> 0	0	<i>NB--</i> 0	<i>SB--</i> 0	0
ATSAC-1 or ATSAC+ATCS-2?		<i>EB--</i> 0	<i>WB--</i> 0	0	<i>EB--</i> 0	<i>WB--</i> 0	0
Override Capacity				2			2
				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	Left	44	1	44	0	1	0
	Left-Through		0			0	
	Through	2108	1	1073	0	1	0
	Through-Right		1			1	
	Right	38	0	38	0	0	0
	Left-Through-Right		0			0	
	Left-Right		0			0	
SOUTHBOUND	Left	131	1	131	0	1	0
	Left-Through		0			0	
	Through	2420	1	1254	0	1	0
	Through-Right		1			1	
	Right	87	0	87	0	0	0
	Left-Through-Right		0			0	
	Left-Right		0			0	
EASTBOUND	Left	83	1	83	0	1	0
	Left-Through		0			0	
	Through	18	0	65	0	0	0
	Through-Right		1			1	
	Right	47	0	0	0	0	0
	Left-Through-Right		0			0	
	Left-Right		0			0	
WESTBOUND	Left	4	0	4	0	0	0
	Left-Through		1			1	
	Through	17	0	21	0	0	0
	Through-Right		0			0	
	Right	89	1	24	0	1	0
	Left-Through-Right		0			0	
	Left-Right		0			0	
CRITICAL VOLUMES		<i>North-South:</i>		1298	<i>North-South:</i>		0
		<i>East-West:</i>		107	<i>East-West:</i>		0
		<i>SUM:</i>		1405	<i>SUM:</i>		0
VOLUME/CAPACITY (V/C) RATIO:				1.022			0.000
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.922			0.000
LEVEL OF SERVICE (LOS):				E			A

Level of Service Worksheet (Circular 212 Method)



I/S #:
26

PROJECT TITLE: SPW, POC Addendum
North-South Street: Harbor Blvd
Scenario: Future With Project
Count Date: 1/0/1900

East-West Street: SR 47 EB Off-Ramp / Swinford St
Analyst: <Fehr & Peers> **Date:** <date>

MOVEMENT		SAT			SAT		
		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
No. of Phases Opposed Ø'ing: N/S-1, E/W-2 or Both-3? Right Turns: FREE-1, NRTOR-2 or OLA-3? ATSAC-1 or ATSAC+ATCS-2? Override Capacity							
		4			4		
		0			0		
		0			0		
		3			3		
		2			2		
		0			0		
NORTHBOUND	↔ Left	657	2	361		2	0
	↔ Left-Through		0			0	
	↔ Through	1100	1	584		1	0
	↔ Through-Right		1			1	
	↔ Right	68	0	68		0	0
	↔ Left-Through-Right		0			0	0
	↔ Left-Right		0			0	0
SOUTHBOUND	↔ Left	62	2	34		2	0
	↔ Left-Through		0			0	
	↔ Through	497	2	202		2	0
	↔ Through-Right		1			1	
	↔ Right	110	0	110		0	0
	↔ Left-Through-Right		0			0	0
	↔ Left-Right		0			0	0
EASTBOUND	↔ Left	273	1	273		1	0
	↔ Left-Through		0			0	
	↔ Through	166	1	166		1	0
	↔ Through-Right		1			1	
	↔ Right	1551	1	492		1	0
	↔ Left-Through-Right		0			0	0
	↔ Left-Right		0			0	0
WESTBOUND	↔ Left	93	1	92		0	0
	↔ Left-Through		0			1	
	↔ Through	94	1	94		0	0
	↔ Through-Right		0			1	
	↔ Right	114	1	80		0	0
	↔ Left-Through-Right		0			0	0
	↔ Left-Right		0			0	0
Version: 1i Beta; 8/4/2011		SAT			0		
		EB Critical Move			EB Critical Move		
		RT	LT		RT	LT	
		N-S	618	618	N-S	0	0
		EB	360	273	EB	0	0
		WB	94	94	WB	0	0
		Sum	1072	985	Sum	0	0
		V/C	0.780	0.716	V/C	0.000	0.000
		Less A	0.680	0.616	Less A	-0.100	-0.100
		LOS	B	B	LOS	A	A
		Int V/C	0.680		Int V/C	-0.100	
			B			A	



Level of Service Worksheet (Circular 212 Method)



I/S #:
27

PROJECT TITLE: SPW, POC Addendum
North-South Street: Harbor Blvd
Scenario: Future With Project
Count Date: 1/0/1900

East-West Street: SR-47 WB On-Ramp
Analyst: <Fehr & Peers> **Date:** <date>

		SAT					
		No. of Phases					
		Opposed Ø'ing: N/S-1, E/W-2 or Both-3?					
		Right Turns: FREE-1, NRTOR-2 or OLA-3?					
		ATSAC-1 or ATSAC+ATCS-2?					
		Override Capacity					
		NB--	SB--	WB--	NB--	SB--	WB--
		3	3	0	3	3	0
		1	0	0	1	0	0
				2			2
				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	↵ Left	1204	2	662		2	0
	↵↵ Left-Through		0			0	
	→ Through	256	0	283		0	0
	↵↵ Through-Right		1			1	
	↵ Right	27	0	0		0	0
	↵↵ Left-Through-Right		0			0	
	↵↵ Left-Right		0			0	
SOUTHBOUND	↵ Left	25	1	25		1	0
	↵↵ Left-Through		0			0	
	→ Through	283	2	142		2	0
	↵↵ Through-Right		0			0	
	↵ Right	0	1	0		1	0
	↵↵ Left-Through-Right		0			0	
	↵↵ Left-Right		0			0	
EASTBOUND	↵ Left	4	1	4		1	0
	↵↵ Left-Through		0			0	
	→ Through	44	1	44		1	0
	↵↵ Through-Right		0			0	
	↵ Right	333	1	0		1	0
	↵↵ Left-Through-Right		0			0	
	↵↵ Left-Right		0			0	
WESTBOUND	↵ Left	53	2	29		2	0
	↵↵ Left-Through		0			0	
	→ Through	35	2	18		2	0
	↵↵ Through-Right		0			0	
	↵ Right	10	1	0		1	0
	↵↵ Left-Through-Right		0			0	
	↵↵ Left-Right		0			0	
CRITICAL VOLUMES		<i>North-South:</i>		804	<i>North-South:</i>		0
		<i>East-West:</i>		73	<i>East-West:</i>		0
		<i>SUM:</i>		877	<i>SUM:</i>		0
VOLUME/CAPACITY (V/C) RATIO:				0.638			0.000
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.538			0.000
LEVEL OF SERVICE (LOS):				A			A



Level of Service Worksheet (Circular 212 Method)



I/S #:
29

PROJECT TITLE: SPW, POC Addendum
North-South Street: Harbor
Scenario: Future With Project
Count Date: 1/0/1900

East-West Street: O'Farrell

Analyst: <Fehr & Peers> **Date:** <date>

		SAT					
No. of Phases				2			2
Opposed Ø'ing: N/S-1, E/W-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		NB-- 0	SB-- 0	0	NB-- 0	SB-- 0	0
ATSAC-1 or ATSAC+ATCS-2?		EB-- 0	WB-- 0	0	EB-- 0	WB-- 0	0
Override Capacity				2			2
				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	↵ Left	13	1	13	0	1	0
	↵↔ Left-Through		0			0	
	→ Through	2202	2	1101	0	2	0
	↵↔ Through-Right		0			0	
	→ Right	0	0	0	0	0	0
	↵↔ Left-Through-Right		0			0	
	↵↔ Left-Right		0			0	
SOUTHBOUND	↵ Left	0	0	0	0	0	0
	↵↔ Left-Through		0			0	
	→ Through	3020	1	1526	0	1	0
	↵↔ Through-Right		1			1	
	→ Right	32	0	32	0	0	0
	↵↔ Left-Through-Right		0			0	
	↵↔ Left-Right		0			0	
EASTBOUND	↵ Left	107	1	107	0	1	0
	↵↔ Left-Through		0			0	
	→ Through	0	0	0	0	0	0
	↵↔ Through-Right		0			0	
	→ Right	36	1	30	0	1	0
	↵↔ Left-Through-Right		0			0	
	↵↔ Left-Right		0			0	
WESTBOUND	↵ Left	0	0	0	0	0	0
	↵↔ Left-Through		0			0	
	→ Through	0	0	0	0	0	0
	↵↔ Through-Right		0			0	
	→ Right	0	0	0	0	0	0
	↵↔ Left-Through-Right		0			0	
	↵↔ Left-Right		0			0	
CRITICAL VOLUMES				<i>North-South:</i> 1539			<i>North-South:</i> 0
				<i>East-West:</i> 107			<i>East-West:</i> 0
				<i>SUM:</i> 1646			<i>SUM:</i> 0
VOLUME/CAPACITY (V/C) RATIO:				1.097			0.000
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.997			0.000
LEVEL OF SERVICE (LOS):				E			A



Level of Service Worksheet (Circular 212 Method)



I/S #:
30

PROJECT TITLE: SPW, POC Addendum
North-South Street: Harbor
Scenario: Future With Project
Count Date: 1/0/1900

East-West Street: 3rd

Analyst: <Fehr & Peers> **Date:** <date>

		SAT					
No. of Phases				0			0
Opposed Ø'ing: N/S-1, E/W-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		<i>NB--</i> 0	<i>SB--</i> 0	0	<i>NB--</i> 0	<i>SB--</i> 0	0
ATSAC-1 or ATSAC+ATCS-2?		<i>EB--</i> 0	<i>WB--</i> 0	0	<i>EB--</i> 0	<i>WB--</i> 0	0
Override Capacity				2			2
				1200			1200
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	Left	52	1	52	0	1	0
	Left-Through		0		0	0	0
	Through	2124	2	1062	0	2	0
	Through-Right		0		0	0	0
	Right	1	0	0	0	0	0
	Left-Through-Right		0		0	0	0
	Left-Right		0		0	0	0
SOUTHBOUND	Left	2	0	0	0	0	0
	Left-Through		0		0	0	0
	Through	2426	1	1238	0	1	0
	Through-Right		1		0	1	0
	Right	49	0	49	0	0	0
	Left-Through-Right		0		0	0	0
	Left-Right		0		0	0	0
EASTBOUND	Left	71	1	71	0	1	0
	Left-Through		0		0	0	0
	Through	0	0	0	0	0	0
	Through-Right		0		0	0	0
	Right	53	1	27	0	1	0
	Left-Through-Right		0		0	0	0
	Left-Right		0		0	0	0
WESTBOUND	Left	0	0	0	0	0	0
	Left-Through		0		0	0	0
	Through	0	0	0	0	0	0
	Through-Right		0		0	0	0
	Right	2	0	0	0	0	0
	Left-Through-Right		0		0	0	0
	Left-Right		0		0	0	0
CRITICAL VOLUMES		<i>North-South:</i>		1290	<i>North-South:</i>		0
		<i>East-West:</i>		71	<i>East-West:</i>		0
		<i>SUM:</i>		1361	<i>SUM:</i>		0
VOLUME/CAPACITY (V/C) RATIO:				1.134			0.000
V/C LESS ATSAC/ATCS ADJUSTMENT:				1.034			0.000
LEVEL OF SERVICE (LOS):				F			A



Level of Service Worksheet (Circular 212 Method)



I/S #:
31

PROJECT TITLE: SPW, POC Addendum
North-South Street: Pacific Ave
Scenario: Future With Project
Count Date: 1/0/1900

East-West Street: 13th

Analyst: <Fehr & Peers> **Date:** <date>

		SAT					
No. of Phases				2			2
Opposed Ø'ing: N/S-1, E/W-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		NB-- 0	SB-- 0	0	NB-- 0	SB-- 0	0
ATSAC-1 or ATSAC+ATCS-2?		EB-- 0	WB-- 0	0	EB-- 0	WB-- 0	0
Override Capacity				2			2
				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	Left	47	1	47	0	1	0
	Left-Through		0			0	
	Through	748	1	748	0	1	0
	Through-Right		0			0	
	Right	27	1	27	0	1	0
	Left-Through-Right		0			0	
	Left-Right		0			0	
SOUTHBOUND	Left	36	1	36	0	1	0
	Left-Through		0			0	
	Through	696	1	696	0	1	0
	Through-Right		0			0	
	Right	84	1	84	0	1	0
	Left-Through-Right		0			0	
	Left-Right		0			0	
EASTBOUND	Left	75	0	75	0	0	0
	Left-Through		0			0	
	Through	87	0	202	0	0	0
	Through-Right		0			0	
	Right	40	0	0	0	0	0
	Left-Through-Right		1			1	
	Left-Right		0			0	
WESTBOUND	Left	20	0	20	0	0	0
	Left-Through		0			0	
	Through	71	0	126	0	0	0
	Through-Right		0			0	
	Right	35	0	0	0	0	0
	Left-Through-Right		1			1	
	Left-Right		0			0	
CRITICAL VOLUMES				<i>North-South:</i> 784		<i>North-South:</i> 0	
				<i>East-West:</i> 222		<i>East-West:</i> 0	
				<i>SUM:</i> 1006		<i>SUM:</i> 0	
VOLUME/CAPACITY (V/C) RATIO:				0.671		0.000	
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.571		0.000	
LEVEL OF SERVICE (LOS):				A		A	



Level of Service Worksheet (Circular 212 Method)



I/S #:
32

PROJECT TITLE: SPW, POC Addendum
North-South Street: Pacific Ave
Scenario: Future With Project
Count Date: 1/0/1900

East-West Street: 17th

Analyst: <Fehr & Peers> **Date:** <date>

		SAT					
No. of Phases				2			2
Opposed Ø'ing: N/S-1, E/W-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		NB-- 0	SB-- 0	0	NB-- 0	SB-- 0	0
ATSAC-1 or ATSAC+ATCS-2?		EB-- 0	WB-- 0	0	EB-- 0	WB-- 0	0
Override Capacity				2			2
				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	↶ Left	17	1	17	0	1	0
	↷ Left-Through		0			0	
	→ Through	640	1	640	0	1	0
	↷ Through-Right		0			0	
	→ Right	15	1	15	0	1	0
	↷ Left-Through-Right		0			0	
	↷ Left-Right		0			0	
SOUTHBOUND	↷ Left	23	1	23	0	1	0
	↶ Left-Through		0			0	
	→ Through	633	1	633	0	1	0
	↶ Through-Right		0			0	
	→ Right	69	1	69	0	1	0
	↶ Left-Through-Right		0			0	
	↶ Left-Right		0			0	
EASTBOUND	↶ Left	42	0	42	0	0	0
	↷ Left-Through		0			0	
	→ Through	55	0	130	0	0	0
	↷ Through-Right		0			0	
	→ Right	33	0	0	0	0	0
	↷ Left-Through-Right		1			1	
	↷ Left-Right		0			0	
WESTBOUND	↶ Left	18	0	18	0	0	0
	↷ Left-Through		0			0	
	→ Through	93	0	135	0	0	0
	↷ Through-Right		0			0	
	→ Right	24	0	0	0	0	0
	↷ Left-Through-Right		1			1	
	↷ Left-Right		0			0	
CRITICAL VOLUMES				<i>North-South:</i> 663			<i>North-South:</i> 0
				<i>East-West:</i> 177			<i>East-West:</i> 0
				<i>SUM:</i> 840			<i>SUM:</i> 0
VOLUME/CAPACITY (V/C) RATIO:				0.560			0.000
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.460			0.000
LEVEL OF SERVICE (LOS):				A			A



Level of Service Worksheet (Circular 212 Method)



I/S #:
33

PROJECT TITLE: SPW, POC Addendum
North-South Street: 19th St
Scenario: Future With Project
Count Date: 1/0/1900

East-West Street: Pacific

Analyst: <Fehr & Peers> **Date:** <date>

		SAT					
				2			2
No. of Phases				2			2
Opposed Ø'ing: N/S-1, E/W-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		<i>NB--</i> 0	<i>SB--</i> 0	0	<i>NB--</i> 0	<i>SB--</i> 0	0
ATSAC-1 or ATSAC+ATCS-2?		<i>EB--</i> 0	<i>WB--</i> 0	0	<i>EB--</i> 0	<i>WB--</i> 0	0
Override Capacity				2			2
				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	Left	21	1	21	0	1	0
	Left-Through		0			0	
	Through	568	1	568	0	1	0
	Through-Right		0			0	
	Right	18	1	18	0	1	0
	Left-Through-Right		0			0	
	Left-Right		0			0	
SOUTHBOUND	Left	13	1	13	0	1	0
	Left-Through		0			0	
	Through	564	1	564	0	1	0
	Through-Right		0			0	
	Right	51	1	51	0	1	0
	Left-Through-Right		0			0	
	Left-Right		0			0	
EASTBOUND	Left	50	0	50	0	0	0
	Left-Through		0			0	
	Through	36	0	118	0	0	0
	Through-Right		0			0	
	Right	32	0	0	0	0	0
	Left-Through-Right		1			1	
	Left-Right		0			0	
WESTBOUND	Left	12	0	12	0	0	0
	Left-Through		0			0	
	Through	57	0	91	0	0	0
	Through-Right		0			0	
	Right	22	0	0	0	0	0
	Left-Through-Right		1			1	
	Left-Right		0			0	
CRITICAL VOLUMES		<i>North-South:</i>		585	<i>North-South:</i>		0
		<i>East-West:</i>		141	<i>East-West:</i>		0
		<i>SUM:</i>		726	<i>SUM:</i>		0
VOLUME/CAPACITY (V/C) RATIO:				0.484			0.000
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.384			0.000
LEVEL OF SERVICE (LOS):				A			A



Level of Service Worksheet (Circular 212 Method)



I/S #:
34

PROJECT TITLE: SPW, POC Addendum
North-South Street: Gaffey St
Scenario: Future With Project
Count Date: 1/0/1900

East-West Street: 13th

Analyst: <Fehr & Peers> **Date:** <date>

		SAT					
No. of Phases				2			2
Opposed Ø'ing: N/S-1, E/W-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		NB-- 0	SB-- 0	0	NB-- 0	SB-- 0	0
ATSAC-1 or ATSAC+ATCS-2?		EB-- 0	WB-- 0	0	EB-- 0	WB-- 0	0
Override Capacity				2			2
				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	↶ Left	67	1	67	0	1	0
	↷ Left-Through		0			0	
	→ Through	1147	1	598	0	1	0
	↷ Through-Right		1			1	
	→ Right	49	0	49	0	0	0
	↷ Left-Through-Right		0			0	
	↶ Left-Right		0			0	
SOUTHBOUND	↷ Left	77	1	77	0	1	0
	↶ Left-Through		0			0	
	→ Through	1171	1	620	0	1	0
	↶ Through-Right		1			1	
	→ Right	68	0	68	0	0	0
	↶ Left-Through-Right		0			0	
	↷ Left-Right		0			0	
EASTBOUND	↶ Left	190	0	190	0	0	0
	↷ Left-Through		0			0	
	→ Through	118	0	370	0	0	0
	↷ Through-Right		0			0	
	→ Right	62	0	0	0	0	0
	↷ Left-Through-Right		1			1	
	↶ Left-Right		0			0	
WESTBOUND	↶ Left	62	0	62	0	0	0
	↷ Left-Through		0			0	
	→ Through	143	0	277	0	0	0
	↷ Through-Right		0			0	
	→ Right	72	0	0	0	0	0
	↷ Left-Through-Right		1			1	
	↶ Left-Right		0			0	
CRITICAL VOLUMES		<i>North-South:</i>		687	<i>North-South:</i>		0
		<i>East-West:</i>		467	<i>East-West:</i>		0
		SUM:		1154	SUM:		0
VOLUME/CAPACITY (V/C) RATIO:				0.769			0.000
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.669			0.000
LEVEL OF SERVICE (LOS):				B			A



Level of Service Worksheet (Circular 212 Method)



I/S #:
5

PROJECT TITLE: SPW, POC Addendum

North-South Street: Gaffey St

East-West Street: 9th St

Scenario: Future With Project With Mitigation

Count Date: 1/0/1900

Analyst: <Fehr & Peers>

Date: <date>

		AM			PM		
		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
No. of Phases				2			2
Opposed Ø'ing: N/S-1, E/W-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		NB-- 0	SB-- 0	0	NB-- 0	SB-- 0	0
ATSAC-1 or ATSAC+ATCS-2?		EB-- 0	WB-- 0	0	EB-- 0	WB-- 0	0
Override Capacity				2			2
				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	↵ Left	77	1	77	63	1	63
	↵↔ Left-Through		0			0	
	→ Through	1527	2	764	1153	2	577
	↘ Through-Right		0			0	
	↘ Right	28	1	0	42	1	0
	↘↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
SOUTHBOUND	↵ Left	46	1	46	151	1	151
	↵↔ Left-Through		0			0	
	→ Through	1136	2	568	1629	2	815
	↘ Through-Right		0			0	
	↘ Right	119	1	0	146	1	46
	↘↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
EASTBOUND	↵ Left	289	1	289	201	1	201
	↵↔ Left-Through		0			0	
	→ Through	506	1	506	278	1	278
	↘ Through-Right		0			0	
	↘ Right	68	1	30	50	1	19
	↘↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
WESTBOUND	↵ Left	77	1	77	98	1	98
	↵↔ Left-Through		0			0	
	→ Through	325	0	404	287	0	408
	↘ Through-Right		1			1	
	↘ Right	79	0	0	121	0	0
	↘↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
CRITICAL VOLUMES		<i>North-South:</i>		810	<i>North-South:</i>		878
		<i>East-West:</i>		693	<i>East-West:</i>		609
		SUM:		1503	SUM:		1487
VOLUME/CAPACITY (V/C) RATIO:				1.002			0.991
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.902			0.891
LEVEL OF SERVICE (LOS):				E			D



Level of Service Worksheet (Circular 212 Method)



I/S #:
6

PROJECT TITLE: SPW, POC Addendum

North-South Street: Gaffey St

East-West Street: 7th St

Scenario: Future With Project With Mitigation

Count Date: 1/0/1900

Analyst: <Fehr & Peers>

Date: <date>

		AM			PM		
		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
No. of Phases				2			2
Opposed Ø'ing: N/S-1, E/W-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		NB-- 0	SB-- 0	0	NB-- 0	SB-- 0	0
ATSAC-1 or ATSAC+ATCS-2?		EB-- 0	WB-- 0	0	EB-- 0	WB-- 0	0
Override Capacity				2			2
				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	↵ Left	22	1	22	53	1	53
	↵↔ Left-Through		0			0	
	→ Through	1821	2	625	1365	2	471
	↘ Through-Right		1			1	
	↘ Right	55	0	55	49	0	49
	↘↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
SOUTHBOUND	↵ Left	72	1	72	108	1	108
	↵↔ Left-Through		0			0	
	→ Through	1230	2	467	1748	2	615
	↘ Through-Right		1			1	
	↘ Right	170	0	170	97	0	97
	↘↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
EASTBOUND	↵ Left	302	1	302	163	1	163
	↵↔ Left-Through		0			0	
	→ Through	186	0	221	184	0	237
	↘ Through-Right		1			1	
	↘ Right	35	0	0	53	0	0
	↘↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
WESTBOUND	↵ Left	115	1	115	111	1	111
	↵↔ Left-Through		0			0	
	→ Through	113	0	192	200	0	312
	↘ Through-Right		1			1	
	↘ Right	79	0	0	112	0	0
	↘↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
CRITICAL VOLUMES		<i>North-South:</i>		697	<i>North-South:</i>		668
		<i>East-West:</i>		494	<i>East-West:</i>		475
		SUM:		1191	SUM:		1143
VOLUME/CAPACITY (V/C) RATIO:				0.794			0.762
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.694			0.662
LEVEL OF SERVICE (LOS):				B			B



Level of Service Worksheet (Circular 212 Method)



I/S #:
7

PROJECT TITLE: SPW, POC Addendum

North-South Street: Gaffey St

East-West Street: 6th St

Scenario: Future With Project With Mitigation

Count Date: 1/0/1900

Analyst: <Fehr & Peers>

Date: <date>

		AM			PM		
No. of Phases				2			2
Opposed Ø'ing: N/S-1, EW-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		NB-- 0	SB-- 0	0	NB-- 0	SB-- 0	0
ATSAC-1 or ATSAC+ATCS-2?		EB-- 0	WB-- 0	0	EB-- 0	WB-- 0	0
Override Capacity				2			2
Override Capacity				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	↶ Left	61	1	61	64	1	64
	↷ Left-Through		0			0	
	→ Through	2045	2	703	1557	2	538
	↷ Through-Right		1			1	
	→ Right	64	0	64	58	0	58
	↷ Left-Through-Right		0			0	
	↷ Left-Right		0			0	
SOUTHBOUND	↷ Left	114	1	114	71	1	71
	↶ Left-Through		0			0	
	→ Through	1515	2	539	1817	2	640
	↶ Through-Right		1			1	
	→ Right	101	0	101	104	0	104
	↶ Left-Through-Right		0			0	
	↶ Left-Right		0			0	
EASTBOUND	↶ Left	13	0	13	15	0	15
	↷ Left-Through		1			1	
	→ Through	12	0	25	12	0	27
	↷ Through-Right		0			0	
	→ Right	38	1	8	93	1	61
	↷ Left-Through-Right		0			0	
	↷ Left-Right		0			0	
WESTBOUND	↶ Left	2	0	2	10	0	10
	↷ Left-Through		1			1	
	→ Through	31	0	33	13	0	23
	↷ Through-Right		0			0	
	→ Right	44	1	0	103	1	68
	↷ Left-Through-Right		0			0	
	↷ Left-Right		0			0	
CRITICAL VOLUMES				<i>North-South:</i> 817			<i>North-South:</i> 704
				<i>East-West:</i> 46			<i>East-West:</i> 83
				SUM: 863			SUM: 787
VOLUME/CAPACITY (V/C) RATIO:				0.575			0.525
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.475			0.425
LEVEL OF SERVICE (LOS):				A			A



Level of Service Worksheet (Circular 212 Method)



I/S #:
8

PROJECT TITLE: SPW, POC Addendum

North-South Street: Gaffey St

East-West Street: 5th St

Scenario: Future With Project With Mitigation

Count Date: 1/0/1900

Analyst: <Fehr & Peers>

Date: <date>

		AM			PM		
		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
No. of Phases				3			3
Opposed Ø'ing: N/S-1, E/W-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		NB-- 0	SB-- 0	0	NB-- 0	SB-- 0	0
ATSAC-1 or ATSAC+ATCS-2?		EB-- 0	WB-- 0	0	EB-- 0	WB-- 0	0
Override Capacity				2			2
Override Capacity				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	↵ Left	17	1	17	46	1	46
	↵↔ Left-Through		0			0	
	→ Through	2037	2	688	1639	2	558
	↗ Through-Right		1			1	
	↘ Right	28	0	28	34	0	34
	↗↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
SOUTHBOUND	↵ Left	126	1	126	133	1	133
	↵↔ Left-Through		0			0	
	→ Through	1553	2	565	1892	2	676
	↗ Through-Right		1			1	
	↘ Right	141	0	141	137	0	137
	↗↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
EASTBOUND	↵ Left	299	1	299	137	1	137
	↵↔ Left-Through		0			0	
	→ Through	184	0	217	93	0	117
	↗ Through-Right		1			1	
	↘ Right	33	0	0	24	0	0
	↗↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
WESTBOUND	↵ Left	102	1	102	103	1	103
	↵↔ Left-Through		0			0	
	→ Through	116	0	254	339	0	474
	↗ Through-Right		1			1	
	↘ Right	138	0	0	135	0	0
	↗↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
CRITICAL VOLUMES				<i>North-South:</i> 814			<i>North-South:</i> 722
				<i>East-West:</i> 553			<i>East-West:</i> 611
				SUM: 1367			SUM: 1333
VOLUME/CAPACITY (V/C) RATIO:				0.959			0.935
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.859			0.835
LEVEL OF SERVICE (LOS):				D			D



Level of Service Worksheet (Circular 212 Method)



I/S #:
22

PROJECT TITLE: SPW, POC Addendum

North-South Street: Harbor Blvd

East-West Street: 7th St

Scenario: Future With Project With Mitigation

Count Date: 1/0/1900

Analyst: <Fehr & Peers>

Date: <date>

		AM			PM		
		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
No. of Phases				3			3
Opposed Ø'ing: N/S-1, E/W-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		NB-- 0	SB-- 0	0	NB-- 0	SB-- 0	0
ATSAC-1 or ATSAC+ATCS-2?		EB-- 0	WB-- 0	0	EB-- 0	WB-- 0	0
Override Capacity				2			2
Override Capacity				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	↵ Left	33	1	33	80	1	80
	↵↔ Left-Through		0			0	
	→ Through	1648	3	549	1304	3	435
	↘ Through-Right		0			0	
	↘ Right	0	0	0	0	0	0
	↘↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
SOUTHBOUND	↵ Left	0	0	0	0	0	0
	↵↔ Left-Through		0			0	
	→ Through	1179	2	590	1750	2	875
	↘ Through-Right		0			0	
	↘ Right	246	1	163	374	1	291
	↘↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
EASTBOUND	↵ Left	301	2	166	304	2	167
	↵↔ Left-Through		0			0	
	→ Through	0	0	0	0	0	0
	↘ Through-Right		0			0	
	↘ Right	51	1	35	75	1	35
	↘↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
WESTBOUND	↵ Left	0	0	0	0	0	0
	↵↔ Left-Through		0			0	
	→ Through	0	0	0	0	0	0
	↘ Through-Right		0			0	
	↘ Right	0	0	0	0	0	0
	↘↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
CRITICAL VOLUMES		<i>North-South:</i>		623	<i>North-South:</i>		955
		<i>East-West:</i>		166	<i>East-West:</i>		167
		SUM:		789	SUM:		1122
VOLUME/CAPACITY (V/C) RATIO:				0.554			0.787
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.454			0.687
LEVEL OF SERVICE (LOS):				A			B



Level of Service Worksheet (Circular 212 Method)



I/S #:
23

PROJECT TITLE: SPW, POC Addendum

North-South Street: Harbor Blvd

East-West Street: 6th St

Scenario: Future With Project With Mitigation

Count Date: 1/0/1900

Analyst: <Fehr & Peers>

Date: <date>

		AM			PM		
		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
No. of Phases				3			3
Opposed Ø'ing: N/S-1, E/W-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		NB-- 0	SB-- 0	0	NB-- 0	SB-- 0	0
ATSAC-1 or ATSAC+ATCS-2?		EB-- 0	WB-- 0	0	EB-- 0	WB-- 0	0
Override Capacity				2			2
Override Capacity				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	↵ Left	10	1	10	10	1	10
	↵↔ Left-Through		0			0	
	→ Through	1970	2	657	1560	2	520
	↵↔ Through-Right		1			1	
	↵ Right	1	0	1	1	0	1
	↵↔ Left-Through-Right		0			0	
	↵↔ Left-Right		0			0	
SOUTHBOUND	↵ Left	14	1	14	10	1	10
	↵↔ Left-Through		0			0	
	→ Through	1454	2	522	2003	2	694
	↵↔ Through-Right		1			1	
	↵ Right	113	0	113	78	0	78
	↵↔ Left-Through-Right		0			0	
	↵↔ Left-Right		0			0	
EASTBOUND	↵ Left	43	1	43	51	1	51
	↵↔ Left-Through		0			0	
	→ Through	-1	0	15	0	0	49
	↵↔ Through-Right		1			1	
	↵ Right	16	0	0	49	0	0
	↵↔ Left-Through-Right		0			0	
	↵↔ Left-Right		0			0	
WESTBOUND	↵ Left	2	1	2	1	1	1
	↵↔ Left-Through		0			0	
	→ Through	4	1	4	2	1	2
	↵↔ Through-Right		0			0	
	↵ Right	14	1	7	10	1	5
	↵↔ Left-Through-Right		0			0	
	↵↔ Left-Right		0			0	
CRITICAL VOLUMES		<i>North-South:</i>		671	<i>North-South:</i>		704
		<i>East-West:</i>		50	<i>East-West:</i>		56
		SUM:		721	SUM:		760
VOLUME/CAPACITY (V/C) RATIO:				0.506			0.533
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.406			0.433
LEVEL OF SERVICE (LOS):				A			A



Level of Service Worksheet (Circular 212 Method)



I/S #:
24

PROJECT TITLE: SPW, POC Addendum

North-South Street: Harbor Blvd

East-West Street: 5th St

Scenario: Future With Project With Mitigation

Count Date: 1/0/1900

Analyst: <Fehr & Peers>

Date: <date>

		AM			PM		
		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
No. of Phases				3			3
Opposed Ø'ing: N/S-1, E/W-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		NB-- 0	SB-- 0	0	NB-- 0	SB-- 0	0
ATSAC-1 or ATSAC+ATCS-2?		EB-- 0	WB-- 0	0	EB-- 0	WB-- 0	0
Override Capacity				2			2
Override Capacity				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	↵ Left	34	1	34	17	1	17
	↵↔ Left-Through		0			0	
	→ Through	1886	2	629	1509	2	503
	↗ Through-Right		1			1	
	↘ Right	0	0	0	0	0	0
	↗↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
SOUTHBOUND	↵ Left	1	1	1	1	1	1
	↵↔ Left-Through		0			0	
	→ Through	1573	2	655	2105	2	749
	↗ Through-Right		1			1	
	↘ Right	391	0	391	141	0	141
	↗↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
EASTBOUND	↵ Left	186	1	186	370	1	370
	↵↔ Left-Through		0			0	
	→ Through	0	0	15	0	0	33
	↗ Through-Right		1			1	
	↘ Right	15	0	0	33	0	0
	↗↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
WESTBOUND	↵ Left	0	1	0	0	1	0
	↵↔ Left-Through		0			0	
	→ Through	2	1	2	0	1	0
	↗ Through-Right		0			0	
	↘ Right	1	1	1	12	1	12
	↗↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
CRITICAL VOLUMES				<i>North-South:</i> 689			<i>North-South:</i> 766
				<i>East-West:</i> 188			<i>East-West:</i> 382
				<i>SUM:</i> 877			<i>SUM:</i> 1148
VOLUME/CAPACITY (V/C) RATIO:				0.615			0.806
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.515			0.706
LEVEL OF SERVICE (LOS):				A			C



Level of Service Worksheet (Circular 212 Method)



I/S #:
25

PROJECT TITLE: SPW, POC Addendum

North-South Street: Harbor Blvd

East-West Street: 1st St

Scenario: Future With Project With Mitigation

Count Date: 1/0/1900

Analyst: <Fehr & Peers>

Date: <date>

		AM			PM		
		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
No. of Phases				4			4
Opposed Ø'ing: N/S-1, E/W-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		NB-- 0	SB-- 0	0	NB-- 0	SB-- 0	0
ATSAC-1 or ATSAC+ATCS-2?		EB-- 0	WB-- 0	0	EB-- 0	WB-- 0	0
Override Capacity				2			2
Override Capacity				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	↵ Left	8	1	8	22	1	22
	↵↔ Left-Through		0			0	
	→ Through	2174	2	746	1969	2	660
	↗ Through-Right		1			1	
	↘ Right	63	0	63	12	0	12
	↗↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
SOUTHBOUND	↵ Left	323	1	323	32	1	32
	↵↔ Left-Through		0			0	
	→ Through	1934	2	675	2163	2	744
	↗ Through-Right		1			1	
	↘ Right	92	0	92	68	0	68
	↗↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
EASTBOUND	↵ Left	125	1	125	101	1	101
	↵↔ Left-Through		0			0	
	→ Through	2	0	17	3	0	26
	↗ Through-Right		1			1	
	↘ Right	15	0	0	23	0	0
	↗↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
WESTBOUND	↵ Left	2	0	2	6	0	6
	↵↔ Left-Through		1			1	
	→ Through	0	0	2	15	0	21
	↗ Through-Right		0			0	
	↘ Right	12	1	0	77	1	61
	↗↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
CRITICAL VOLUMES				<i>North-South:</i> 1069			<i>North-South:</i> 766
				<i>East-West:</i> 127			<i>East-West:</i> 162
				<i>SUM:</i> 1196			<i>SUM:</i> 928
VOLUME/CAPACITY (V/C) RATIO:				0.870			0.675
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.770			0.575
LEVEL OF SERVICE (LOS):				C			A

Level of Service Worksheet (Circular 212 Method)



I/S #:
26

PROJECT TITLE: SPW, POC Addendum

North-South Street: Harbor Blvd

East-West Street: SR 47 EB Off-Ramp / Swinford St

Scenario: Future With Project With Mitigation

Count Date: 1/0/1900

Analyst: <Fehr & Peers>

Date: <date>

		AM			PM		
				4			4
No. of Phases				0			0
Opposed Ø'ing: N/S-1, E/W-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		0	0	0	0	0	0
ATSAC-1 or ATSAC+ATCS-2?		3	3	3	3	3	3
Override Capacity				2			2
Override Capacity				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	↶ Left	652	2	359	573	2	315
	↶↷ Left-Through		0			0	
	→ Through	1098	1	565	1168	1	590
	↷ Through-Right		1			1	
	↷ Right	32	0	32	12	0	12
	↷↶ Left-Through-Right		0			0	
	↷↶ Left-Right		0			0	
SOUTHBOUND	↷ Left	250	2	138	158	1	158
	↷↶ Left-Through		0			0	
	→ Through	687	2	252	1569	2	556
	↷ Through-Right		1			1	
	↷ Right	69	0	69	99	0	99
	↷↶ Left-Through-Right		0			0	
	↷↶ Left-Right		0			0	
EASTBOUND	↶ Left	38	1	38	45	1	45
	↶↷ Left-Through		0			0	
	→ Through	323	1	323	69	1	69
	↷ Through-Right		1			1	
	↷ Right	853	1	110	606	1	18
	↷↶ Left-Through-Right		0			0	
	↷↶ Left-Right		0			0	
WESTBOUND	↶ Left	17	1	17	12	1	12
	↶↷ Left-Through		0			0	
	→ Through	133	1	133	70	1	70
	↷ Through-Right		0			0	
	↷ Right	347	1	209	122	1	0
	↷↶ Left-Through-Right		0			0	
	↷↶ Left-Right		0			0	
CRITICAL VOLUMES				<i>North-South:</i> 703			<i>North-South:</i> 871
				<i>East-West:</i> 340			<i>East-West:</i> 115
				<i>SUM:</i> 1043			<i>SUM:</i> 986
VOLUME/CAPACITY (V/C) RATIO:				0.759			0.717
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.659			0.617
LEVEL OF SERVICE (LOS):				B			B



Level of Service Worksheet (Circular 212 Method)



I/S #:
27

PROJECT TITLE: SPW, POC Addendum

North-South Street: Harbor Blvd

East-West Street: SR-47 WB On-Ramp

Scenario: Future With Project With Mitigation

Count Date: 1/0/1900

Analyst: <Fehr & Peers>

Date: <date>

		AM			PM		
				4			4
No. of Phases				0			0
Opposed Ø'ing: N/S-1, E/W-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		NB-- 3	SB-- 3	3	NB-- 3	SB-- 3	3
		EB-- 1	WB-- 0	0	EB-- 1	WB-- 0	0
ATSAC-1 or ATSAC+ATCS-2?				2			2
Override Capacity				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	Left	1462	2	804	1083	2	596
	Left-Through		0			0	
	Through	390	0	432	280	0	317
	Through-Right		1			1	
	Right	42	0	0	37	0	0
	Left-Through-Right		0			0	
	Left-Right		0			0	
SOUTHBOUND	Left	4	1	4	34	1	34
	Left-Through		0			0	
	Through	340	2	170	459	2	230
	Through-Right		0			0	
	Right	29	1	0	0	1	0
	Left-Through-Right		0			0	
	Left-Right		0			0	
EASTBOUND	Left	43	1	43	100	1	100
	Left-Through		0			0	
	Through	234	1	234	60	1	60
	Through-Right		0			0	
	Right	601	1	0	1039	1	0
	Left-Through-Right		0			0	
	Left-Right		0			0	
WESTBOUND	Left	45	2	25	141	2	78
	Left-Through		0			0	
	Through	138	2	69	95	2	48
	Through-Right		0			0	
	Right	11	1	9	27	1	10
	Left-Through-Right		0			0	
	Left-Right		0			0	
CRITICAL VOLUMES				974			826
				259			148
				1233			974
VOLUME/CAPACITY (V/C) RATIO:				0.897			0.708
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.797			0.608
LEVEL OF SERVICE (LOS):				C			B



Level of Service Worksheet (Circular 212 Method)



I/S #:
29

PROJECT TITLE: SPW, POC Addendum

North-South Street: Harbor

East-West Street: O'Farrell

Scenario: Future With Project With Mitigation

Count Date: 1/0/1900

Analyst: <Fehr & Peers>

Date: <date>

		AM			PM		
		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
No. of Phases				2			2
Opposed Ø'ing: N/S-1, E/W-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		NB-- 0	SB-- 0	0	NB-- 0	SB-- 0	0
ATSAC-1 or ATSAC+ATCS-2?		EB-- 0	WB-- 0	0	EB-- 0	WB-- 0	0
Override Capacity				2			2
Override Capacity				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	↵ Left	11	1	11	17	1	17
	↵↔ Left-Through		0			0	
	→ Through	2362	3	787	2270	3	757
	↗ Through-Right		0			0	
	↘ Right	0	0	0	0	0	0
	↗↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
SOUTHBOUND	↵ Left	0	0	0	0	0	0
	↵↔ Left-Through		0			0	
	→ Through	2528	2	848	3137	2	1057
	↗ Through-Right		1			1	
	↘ Right	16	0	16	35	0	35
	↗↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
EASTBOUND	↵ Left	128	1	128	133	1	133
	↵↔ Left-Through		0			0	
	→ Through	0	0	0	0	0	0
	↗ Through-Right		0			0	
	↘ Right	13	1	8	17	1	9
	↗↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
WESTBOUND	↵ Left	0	0	0	0	0	0
	↵↔ Left-Through		0			0	
	→ Through	0	0	0	0	0	0
	↗ Through-Right		0			0	
	↘ Right	0	0	0	0	0	0
	↗↔ Left-Through-Right		0			0	
	↘↔ Left-Right		0			0	
CRITICAL VOLUMES				<i>North-South:</i> 859			<i>North-South:</i> 1074
				<i>East-West:</i> 128			<i>East-West:</i> 133
				<i>SUM:</i> 987			<i>SUM:</i> 1207
VOLUME/CAPACITY (V/C) RATIO:				0.658			0.805
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.558			0.705
LEVEL OF SERVICE (LOS):				A			C



Level of Service Worksheet (Circular 212 Method)



I/S #:
30

PROJECT TITLE: SPW, POC Addendum

North-South Street: Harbor

East-West Street: 3rd

Scenario: Future With Project With Mitigation

Count Date: 1/0/1900

Analyst: <Fehr & Peers>

Date: <date>

		AM			PM		
				0			0
No. of Phases				0			0
Opposed Ø'ing: N/S-1, E/W-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		<i>NB--</i> 0	<i>SB--</i> 0	0	<i>NB--</i> 0	<i>SB--</i> 0	0
		<i>EB--</i> 0	<i>WB--</i> 0	0	<i>EB--</i> 0	<i>WB--</i> 0	0
ATSAC-1 or ATSAC+ATCS-2?				2			2
Override Capacity				1200			1200
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	Left	22	1	22	33	1	33
	Left-Through		0			0	
	Through	1999	3	666	1898	3	633
	Through-Right		0			0	
	Right	1	0	0	0	0	0
	Left-Through-Right		0			0	
	Left-Right		0			0	
SOUTHBOUND	Left	3	0	0	2	0	0
	Left-Through		0			0	
	Through	1748	2	647	2066	2	715
	Through-Right		1			1	
	Right	194	0	194	80	0	80
	Left-Through-Right		0			0	
	Left-Right		0			0	
EASTBOUND	Left	130	1	130	72	1	72
	Left-Through		0			0	
	Through	0	0	0	0	0	0
	Through-Right		0			0	
	Right	24	1	13	36	1	20
	Left-Through-Right		0			0	
	Left-Right		0			0	
WESTBOUND	Left	0	0	0	1	0	0
	Left-Through		0			0	
	Through	0	0	0	0	0	0
	Through-Right		0			0	
	Right	1	0	0	5	0	0
	Left-Through-Right		0			0	
	Left-Right		0			0	
CRITICAL VOLUMES			<i>North-South:</i>	669	<i>North-South:</i>		748
			<i>East-West:</i>	130	<i>East-West:</i>		72
			<i>SUM:</i>	799	<i>SUM:</i>		820
VOLUME/CAPACITY (V/C) RATIO:				0.666			0.683
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.566			0.583
LEVEL OF SERVICE (LOS):				A			A



Level of Service Worksheet (Circular 212 Method)



I/S #:
34

PROJECT TITLE: SPW, POC Addendum

North-South Street: Gaffey St.

East-West Street: 13th

Scenario: Future With Project With Mitigation

Count Date: 1/0/1900

Analyst: <Fehr & Peers>

Date: <date>

		AM			PM		
		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
No. of Phases				2			2
Opposed Ø'ing: N/S-1, E/W-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		NB-- 0	SB-- 0	0	NB-- 0	SB-- 0	0
ATSAC-1 or ATSAC+ATCS-2?		EB-- 0	WB-- 0	0	EB-- 0	WB-- 0	0
Override Capacity				2			2
Override Capacity				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	↵ Left	38	1	38	71	1	71
	↵↔ Left-Through		0			0	
	→ Through	1486	1	779	1050	1	550
	↵↔ Through-Right		1			1	
	↵ Right	71	0	71	50	0	50
	↵↔ Left-Through-Right		0			0	
	↵↔ Left-Right		0			0	
SOUTHBOUND	↵ Left	37	1	37	97	1	97
	↵↔ Left-Through		0			0	
	→ Through	848	1	499	1234	1	661
	↵↔ Through-Right		1			1	
	↵ Right	149	0	149	87	0	87
	↵↔ Left-Through-Right		0			0	
	↵↔ Left-Right		0			0	
EASTBOUND	↵ Left	215	1	215	195	1	195
	↵↔ Left-Through		0			0	
	→ Through	307	0	364	159	0	251
	↵↔ Through-Right		1			1	
	↵ Right	57	0	0	92	0	0
	↵↔ Left-Through-Right		0			0	
	↵↔ Left-Right		0			0	
WESTBOUND	↵ Left	60	1	60	34	1	34
	↵↔ Left-Through		0			0	
	→ Through	346	0	538	200	0	281
	↵↔ Through-Right		1			1	
	↵ Right	192	0	0	81	0	0
	↵↔ Left-Through-Right		0			0	
	↵↔ Left-Right		0			0	
CRITICAL VOLUMES				<i>North-South:</i> 816			<i>North-South:</i> 732
				<i>East-West:</i> 753			<i>East-West:</i> 476
				SUM: 1569			SUM: 1208
VOLUME/CAPACITY (V/C) RATIO:				1.046			0.805
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.946			0.705
LEVEL OF SERVICE (LOS):				E			C



Level of Service Worksheet (Circular 212 Method)



I/S #:
5

PROJECT TITLE: SPW, POC Addendum

North-South Street: Gaffey St

East-West Street: 9th St

Scenario: Future With Project With Mitigation

Count Date: 1/0/1900

Analyst: <Fehr & Peers>

Date: <date>

		SAT					
No. of Phases				2			2
Opposed Ø'ing: N/S-1, EW-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		NB-- 0	SB-- 0	0	NB-- 0	SB-- 0	0
ATSAC-1 or ATSAC+ATCS-2?		EB-- 0	WB-- 0	0	EB-- 0	WB-- 0	0
Override Capacity				2			2
				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	Left	81	1	81	0	1	0
	Left-Through		0			0	
	Through	1283	2	642	0	2	0
	Through-Right		0			0	
	Right	53	1	12	0	1	0
	Left-Through-Right		0			0	
	Left-Right		0			0	
SOUTHBOUND	Left	159	1	159	0	1	0
	Left-Through		0			0	
	Through	1402	1	753	0	1	0
	Through-Right		1			1	
	Right	103	0	103	0	0	0
	Left-Through-Right		0			0	
	Left-Right		0			0	
EASTBOUND	Left	212	1	212	0	1	0
	Left-Through		0			0	
	Through	244	1	244	0	1	0
	Through-Right		0			0	
	Right	73	1	33	0	1	0
	Left-Through-Right		0			0	
	Left-Right		0			0	
WESTBOUND	Left	83	1	83	0	1	0
	Left-Through		0			0	
	Through	216	0	366	0	0	0
	Through-Right		1			1	
	Right	150	0	0	0	0	0
	Left-Through-Right		0			0	
	Left-Right		0			0	
CRITICAL VOLUMES			<i>North-South:</i>	834		<i>North-South:</i>	0
			<i>East-West:</i>	578		<i>East-West:</i>	0
			<i>SUM:</i>	1412		<i>SUM:</i>	0
VOLUME/CAPACITY (V/C) RATIO:				0.941			0.000
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.841			0.000
LEVEL OF SERVICE (LOS):				D			A



Level of Service Worksheet (Circular 212 Method)



I/S #:
6

PROJECT TITLE: SPW, POC Addendum

North-South Street: Gaffey St

East-West Street: 7th St

Scenario: Future With Project With Mitigation

Count Date: 1/0/1900

Analyst: <Fehr & Peers>

Date: <date>

		SAT					
				2			2
		No. of Phases					
		Opposed Ø'ing: N/S-1, EW-2 or Both-3?					
		Right Turns: FREE-1, NRTOR-2 or OLA-3?					
		ATSAC-1 or ATSAC+ATCS-2?					
		Override Capacity					
		NB-- 0 SB-- 0 EB-- 0 WB-- 0		NB-- 0 SB-- 0 EB-- 0 WB-- 0			
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	↵	29	1	29	0	1	0
	↵↵		0			0	
	↵↵↵	1652	2	826	0	2	0
	↵↵↵↵		0			0	
	↵↵↵↵↵	60	1	20	0	1	0
	↵↵↵↵↵↵		0			0	
SOUTHBOUND	↵↵	164	1	164	0	1	0
	↵↵↵		0			0	
	↵↵↵↵	1456	1	788	0	1	0
	↵↵↵↵↵		1			1	
	↵↵↵↵↵↵	119	0	119	0	0	0
	↵↵↵↵↵↵↵		0			0	
EASTBOUND	↵↵	116	1	116	0	1	0
	↵↵↵		0			0	
	↵↵↵↵	127	0	180	0	0	0
	↵↵↵↵↵		1			1	
	↵↵↵↵↵↵	53	0	0	0	0	0
	↵↵↵↵↵↵↵		0			0	
WESTBOUND	↵↵	81	1	81	0	1	0
	↵↵↵		0			0	
	↵↵↵↵	128	0	237	0	0	0
	↵↵↵↵↵		1			1	
	↵↵↵↵↵↵	109	0	0	0	0	0
	↵↵↵↵↵↵↵		0			0	
CRITICAL VOLUMES		<i>North-South:</i>		990	<i>North-South:</i>		0
		<i>East-West:</i>		353	<i>East-West:</i>		0
		<i>SUM:</i>		1343	<i>SUM:</i>		0
VOLUME/CAPACITY (V/C) RATIO:				0.895			0.000
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.795			0.000
LEVEL OF SERVICE (LOS):				C			A



Level of Service Worksheet (Circular 212 Method)



I/S #:
7

PROJECT TITLE: SPW, POC Addendum

North-South Street: Gaffey St

East-West Street: 6th St

Scenario: Future With Project With Mitigation

Count Date: 1/0/1900

Analyst: <Fehr & Peers>

Date: <date>

		SAT					
		No. of Phases		2			2
		Opposed Ø'ing: N/S-1, EW-2 or Both-3?		0			0
		Right Turns: FREE-1, NRTOR-2 or OLA-3?	<i>NB--</i> 0 <i>SB--</i> 0	0	<i>NB--</i> 0 <i>SB--</i> 0		0
		ATSAC-1 or ATSAC+ATCS-2?	<i>EB--</i> 0 <i>WB--</i> 0	0	<i>EB--</i> 0 <i>WB--</i> 0		0
		Override Capacity		2			2
				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	Left	73	1	73	0	1	0
	Left-Through		0		0	0	
	Through	1738	1	893	0	1	0
	Through-Right		1		0	1	
	Right	47	0	47	0	0	0
	Left-Through-Right		0		0	0	
	Left-Right		0		0	0	
SOUTHBOUND	Left	102	1	102	0	1	0
	Left-Through		0		0	0	
	Through	1695	1	867	0	1	0
	Through-Right		1		0	1	
	Right	39	0	39	0	0	0
	Left-Through-Right		0		0	0	
	Left-Right		0		0	0	
EASTBOUND	Left	11	0	11	0	0	0
	Left-Through		1		0	1	
	Through	18	0	29	0	0	0
	Through-Right		0		0	0	
	Right	64	1	28	0	1	0
	Left-Through-Right		0		0	0	
	Left-Right		0		0	0	
WESTBOUND	Left	10	0	10	0	0	0
	Left-Through		1		0	1	
	Through	19	0	29	0	0	0
	Through-Right		0		0	0	
	Right	104	1	53	0	1	0
	Left-Through-Right		0		0	0	
	Left-Right		0		0	0	
CRITICAL VOLUMES			<i>North-South:</i>	995	<i>North-South:</i>		0
			<i>East-West:</i>	64	<i>East-West:</i>		0
			<i>SUM:</i>	1059	<i>SUM:</i>		0
VOLUME/CAPACITY (V/C) RATIO:				0.706			0.000
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.606			0.000
LEVEL OF SERVICE (LOS):				B			A



Level of Service Worksheet (Circular 212 Method)



I/S #:
8

PROJECT TITLE: SPW, POC Addendum

North-South Street: Gaffey St

East-West Street: 5th St

Scenario: Future With Project With Mitigation

Count Date: 1/0/1900

Analyst: <Fehr & Peers>

Date: <date>

		SAT					
				3			3
No. of Phases				3			3
Opposed Ø'ing: N/S-1, E/W-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		<i>NB--</i> 0	<i>SB--</i> 0	0	<i>NB--</i> 0	<i>SB--</i> 0	0
		<i>EB--</i> 0	<i>WB--</i> 0	0	<i>EB--</i> 0	<i>WB--</i> 0	0
ATSAC-1 or ATSAC+ATCS-2?				2			2
Override Capacity				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	Left	50	1	50	0	1	0
	Left-Through		0		0	0	
	Through	1719	2	860	0	2	0
	Through-Right		0		0	0	
	Right	32	1	10	0	1	0
	Left-Through-Right		0		0	0	
	Left-Right		0		0		0
SOUTHBOUND	Left	132	1	132	0	1	0
	Left-Through		0		0	0	
	Through	1823	2	912	0	2	0
	Through-Right		0		0	0	
	Right	90	1	31	0	1	0
	Left-Through-Right		0		0	0	
	Left-Right		0		0		0
EASTBOUND	Left	118	1	118	0	1	0
	Left-Through		0		0	0	
	Through	91	0	120	0	0	0
	Through-Right		1		0	1	
	Right	29	0	0	0	0	0
	Left-Through-Right		0		0	0	
	Left-Right		0		0		0
WESTBOUND	Left	44	1	44	0	1	0
	Left-Through		0		0	0	
	Through	107	0	230	0	0	0
	Through-Right		1		0	1	
	Right	123	0	0	0	0	0
	Left-Through-Right		0		0	0	
	Left-Right		0		0		0
CRITICAL VOLUMES		<i>North-South:</i>		992	<i>North-South:</i>		0
		<i>East-West:</i>		348	<i>East-West:</i>		0
		<i>SUM:</i>		1340	<i>SUM:</i>		0
VOLUME/CAPACITY (V/C) RATIO:				0.940			0.000
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.840			0.000
LEVEL OF SERVICE (LOS):				D			A



Level of Service Worksheet (Circular 212 Method)



I/S #:
22

PROJECT TITLE: SPW, POC Addendum

North-South Street: Harbor Blvd

East-West Street: 7th St

Scenario: Future With Project With Mitigation

Count Date: 1/0/1900

Analyst: <Fehr & Peers>

Date: <date>

		SAT					
				3			3
No. of Phases				3			3
Opposed Ø'ing: N/S-1, E/W-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		<i>NB--</i> 0	<i>SB--</i> 0	0	<i>NB--</i> 0	<i>SB--</i> 0	0
		<i>EB--</i> 0	<i>WB--</i> 0	0	<i>EB--</i> 0	<i>WB--</i> 0	0
ATSAC-1 or ATSAC+ATCS-2?				2			2
Override Capacity				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	Left	66	1	66	0	1	0
	Left-Through		0		0	0	
	Through	1894	3	631	0	3	0
	Through-Right		0		0	0	
	Right	0	0	0	0	0	0
	Left-Through-Right		0			0	
	Left-Right		0			0	
SOUTHBOUND	Left	0	0	0	0	0	0
	Left-Through		0		0	0	
	Through	2387	2	1194	0	2	0
	Through-Right		0		0	0	
	Right	188	1	119	0	1	0
	Left-Through-Right		0		0	0	
	Left-Right		0			0	
EASTBOUND	Left	253	2	139	0	2	0
	Left-Through		0		0	0	
	Through	0	0	0	0	0	0
	Through-Right		0		0	0	
	Right	97	1	64	0	1	0
	Left-Through-Right		0		0	0	
	Left-Right		0			0	
WESTBOUND	Left	0	0	0	0	0	0
	Left-Through		0		0	0	
	Through	0	0	0	0	0	0
	Through-Right		0		0	0	
	Right	0	0	0	0	0	0
	Left-Through-Right		0		0	0	
	Left-Right		0			0	
CRITICAL VOLUMES			<i>North-South:</i>	1260	<i>North-South:</i>		0
			<i>East-West:</i>	139	<i>East-West:</i>		0
			<i>SUM:</i>	1399	<i>SUM:</i>		0
VOLUME/CAPACITY (V/C) RATIO:				0.982			0.000
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.882			0.000
LEVEL OF SERVICE (LOS):				D			A



Level of Service Worksheet (Circular 212 Method)



I/S #:
23

PROJECT TITLE: SPW, POC Addendum

North-South Street: Harbor Blvd

East-West Street: 6th St

Scenario: Future With Project With Mitigation

Count Date: 1/0/1900

Analyst: <Fehr & Peers>

Date: <date>

		SAT					
				3			3
No. of Phases				3			3
Opposed Ø'ing: N/S-1, E/W-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		<i>NB--</i> 0	<i>SB--</i> 0	0	<i>NB--</i> 0	<i>SB--</i> 0	0
		<i>EB--</i> 0	<i>WB--</i> 0	0	<i>EB--</i> 0	<i>WB--</i> 0	0
ATSAC-1 or ATSAC+ATCS-2?				2			2
Override Capacity				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	Left	4	1	4	0	1	0
	Left-Through		0			0	
	Through	2043	2	682	0	2	0
	Through-Right		1			1	
	Right	2	0	2	0	0	0
	Left-Through-Right		0			0	
	Left-Right		0			0	
SOUTHBOUND	Left	14	1	14	0	1	0
	Left-Through		0			0	
	Through	2353	2	803	0	2	0
	Through-Right		1			1	
	Right	56	0	56	0	0	0
	Left-Through-Right		0			0	
	Left-Right		0			0	
EASTBOUND	Left	49	1	49	0	1	0
	Left-Through		0			0	
	Through	2	0	4	0	0	0
	Through-Right		1			1	
	Right	2	0	0	0	0	0
	Left-Through-Right		0			0	
	Left-Right		0			0	
WESTBOUND	Left	4	1	4	0	1	0
	Left-Through		0			0	
	Through	14	1	14	0	1	0
	Through-Right		0			0	
	Right	334	1	327	0	1	0
	Left-Through-Right		0			0	
	Left-Right		0			0	
CRITICAL VOLUMES		<i>North-South:</i>		807	<i>North-South:</i>		0
		<i>East-West:</i>		376	<i>East-West:</i>		0
		<i>SUM:</i>		1183	<i>SUM:</i>		0
VOLUME/CAPACITY (V/C) RATIO:				0.830			0.000
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.730			0.000
LEVEL OF SERVICE (LOS):				C			A



Level of Service Worksheet (Circular 212 Method)



I/S #:
24

PROJECT TITLE: SPW, POC Addendum

North-South Street: Harbor Blvd

East-West Street: 5th St

Scenario: Future With Project With Mitigation

Count Date: 1/0/1900

Analyst: <Fehr & Peers>

Date: <date>

		SAT					
				3			3
No. of Phases				0			0
Opposed Ø'ing: N/S-1, E/W-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		<i>NB--</i> 0	<i>SB--</i> 0	0	<i>NB--</i> 0	<i>SB--</i> 0	0
		<i>EB--</i> 0	<i>WB--</i> 0	0	<i>EB--</i> 0	<i>WB--</i> 0	0
ATSAC-1 or ATSAC+ATCS-2?				2			2
Override Capacity				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	Left	25	1	25	0	1	0
	Left-Through		0			0	
	Through	2013	2	672	0	2	0
	Through-Right		1			1	
	Right	2	0	2	0	0	0
	Left-Through-Right		0			0	
	Left-Right		0			0	
SOUTHBOUND	Left	1	1	1	0	1	0
	Left-Through		0			0	
	Through	2352	2	808	0	2	0
	Through-Right		1			1	
	Right	72	0	72	0	0	0
	Left-Through-Right		0			0	
	Left-Right		0			0	
EASTBOUND	Left	93	1	93	0	1	0
	Left-Through		0			0	
	Through	5	0	46	0	0	0
	Through-Right		1			1	
	Right	41	0	0	0	0	0
	Left-Through-Right		0			0	
	Left-Right		0			0	
WESTBOUND	Left	0	1	0	0	1	0
	Left-Through		0			0	
	Through	2	1	2	0	1	0
	Through-Right		0			0	
	Right	14	1	14	0	1	0
	Left-Through-Right		0			0	
	Left-Right		0			0	
CRITICAL VOLUMES			<i>North-South:</i>	833		<i>North-South:</i>	0
			<i>East-West:</i>	107		<i>East-West:</i>	0
			<i>SUM:</i>	940		<i>SUM:</i>	0
VOLUME/CAPACITY (V/C) RATIO:				0.660			0.000
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.560			0.000
LEVEL OF SERVICE (LOS):				A			A



Level of Service Worksheet (Circular 212 Method)



I/S #:
25

PROJECT TITLE: SPW, POC Addendum

North-South Street: Harbor Blvd

East-West Street: 1st St

Scenario: Future With Project With Mitigation

Count Date: 1/0/1900

Analyst: <Fehr & Peers>

Date: <date>

		SAT					
No. of Phases				4			4
Opposed Ø'ing: N/S-1, EW-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		<i>NB--</i> 0	<i>SB--</i> 0	0	<i>NB--</i> 0	<i>SB--</i> 0	0
		<i>EB--</i> 0	<i>WB--</i> 0	0	<i>EB--</i> 0	<i>WB--</i> 0	0
ATSAC-1 or ATSAC+ATCS-2?				2			2
Override Capacity				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	Left	44	1	44	0	1	0
	Left-Through		0		0	0	
	Through	2108	2	715	0	2	0
	Through-Right		1		0	1	
	Right	38	0	38	0	0	0
	Left-Through-Right		0		0	0	
	Left-Right		0		0	0	
SOUTHBOUND	Left	131	1	131	0	1	0
	Left-Through		0		0	0	
	Through	2420	2	836	0	2	0
	Through-Right		1		0	1	
	Right	87	0	87	0	0	0
	Left-Through-Right		0		0	0	
	Left-Right		0		0	0	
EASTBOUND	Left	83	1	83	0	1	0
	Left-Through		0		0	0	
	Through	18	0	65	0	0	0
	Through-Right		1		0	1	
	Right	47	0	0	0	0	0
	Left-Through-Right		0		0	0	
	Left-Right		0		0	0	
WESTBOUND	Left	4	0	4	0	0	0
	Left-Through		1		0	1	
	Through	17	0	21	0	0	0
	Through-Right		0		0	0	
	Right	89	1	24	0	1	0
	Left-Through-Right		0		0	0	
	Left-Right		0		0	0	
CRITICAL VOLUMES			<i>North-South:</i>	880	<i>North-South:</i>		0
			<i>East-West:</i>	107	<i>East-West:</i>		0
			<i>SUM:</i>	987	<i>SUM:</i>		0
VOLUME/CAPACITY (V/C) RATIO:				0.718			0.000
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.618			0.000
LEVEL OF SERVICE (LOS):				B			A



Level of Service Worksheet (Circular 212 Method)



I/S #:
27

PROJECT TITLE: SPW, POC Addendum

North-South Street: Harbor Blvd

East-West Street: SR-47 WB On-Ramp

Scenario: Future With Project With Mitigation

Count Date: 1/0/1900

Analyst: <Fehr & Peers>

Date: <date>

		SAT					
No. of Phases				4			4
Opposed Ø'ing: N/S-1, E/W-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		NB-- 3	SB-- 3	3	NB-- 3	SB-- 3	3
		EB-- 1	WB-- 0	0	EB-- 1	WB-- 0	0
ATSAC-1 or ATSAC+ATCS-2?				2			2
Override Capacity				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	↵ Left	1204	2	662	0	2	0
	↵↔ Left-Through		0		0	0	0
	→ Through	256	0	283	0	0	0
	↘ Through-Right		1		0	1	0
	↘ Right	27	0	0	0	0	0
	↘↔ Left-Through-Right		0		0	0	0
	↘↔ Left-Right		0		0	0	
SOUTHBOUND	↵ Left	25	1	25	0	1	0
	↵↔ Left-Through		0		0	0	0
	→ Through	283	2	142	0	2	0
	↘ Through-Right		0		0	0	0
	↘ Right	0	1	0	0	1	0
	↘↔ Left-Through-Right		0		0	0	0
	↘↔ Left-Right		0		0	0	
EASTBOUND	↵ Left	4	1	4	0	1	0
	↵↔ Left-Through		0		0	0	0
	→ Through	44	1	44	0	1	0
	↘ Through-Right		0		0	0	0
	↘ Right	333	1	0	0	1	0
	↘↔ Left-Through-Right		0		0	0	0
	↘↔ Left-Right		0		0	0	
WESTBOUND	↵ Left	53	2	29	0	2	0
	↵↔ Left-Through		0		0	0	0
	→ Through	35	2	18	0	2	0
	↘ Through-Right		0		0	0	0
	↘ Right	10	1	0	0	1	0
	↘↔ Left-Through-Right		0		0	0	0
	↘↔ Left-Right		0		0	0	
CRITICAL VOLUMES				<i>North-South:</i> 804			<i>North-South:</i> 0
				<i>East-West:</i> 73			<i>East-West:</i> 0
				<i>SUM:</i> 877			<i>SUM:</i> 0
VOLUME/CAPACITY (V/C) RATIO:				0.638			0.000
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.538			0.000
LEVEL OF SERVICE (LOS):				A			A



Level of Service Worksheet (Circular 212 Method)



I/S #:
29

PROJECT TITLE: SPW, POC Addendum

North-South Street: Harbor

East-West Street: O'Farrell

Scenario: Future With Project With Mitigation

Count Date: 1/0/1900

Analyst: <Fehr & Peers>

Date: <date>

		SAT					
				2			2
		No. of Phases		2			2
		Opposed Ø'ing: N/S-1, E/W-2 or Both-3?		0			0
		Right Turns: FREE-1, NRTOR-2 or OLA-3?	<i>NB--</i> 0	0	<i>NB--</i> 0	<i>SB--</i> 0	0
			<i>EB--</i> 0	0	<i>EB--</i> 0	<i>WB--</i> 0	0
		ATSAC-1 or ATSAC+ATCS-2?		2			2
		Override Capacity		0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	↵	13	1	13	0	1	0
	↵↵		0			0	
	↵↵↵	2202	3	734	0	3	0
	↵↵↵↵		0			0	
	↵↵↵↵↵	0	0	0	0	0	0
	↵↵↵↵↵↵		0			0	
SOUTHBOUND	↵	0	0	0	0	0	0
	↵↵		0			0	
	↵↵↵	3020	2	1017	0	2	0
	↵↵↵↵		1			1	
	↵↵↵↵↵	32	0	32	0	0	0
	↵↵↵↵↵↵		0			0	
EASTBOUND	↵	107	1	107	0	1	0
	↵↵		0			0	
	↵↵↵	0	0	0	0	0	0
	↵↵↵↵		0			0	
	↵↵↵↵↵	36	1	30	0	1	0
	↵↵↵↵↵↵		0			0	
WESTBOUND	↵	0	0	0	0	0	0
	↵↵		0			0	
	↵↵↵	0	0	0	0	0	0
	↵↵↵↵		0			0	
	↵↵↵↵↵	0	0	0	0	0	0
	↵↵↵↵↵↵		0			0	
CRITICAL VOLUMES			<i>North-South:</i>	1030	<i>North-South:</i>		0
			<i>East-West:</i>	107	<i>East-West:</i>		0
			<i>SUM:</i>	1137	<i>SUM:</i>		0
VOLUME/CAPACITY (V/C) RATIO:				0.758			0.000
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.658			0.000
LEVEL OF SERVICE (LOS):				B			A



Level of Service Worksheet (Circular 212 Method)



I/S #:
30

PROJECT TITLE: SPW, POC Addendum

North-South Street: Harbor

East-West Street: 3rd

Scenario: Future With Project With Mitigation

Count Date: 1/0/1900

Analyst: <Fehr & Peers>

Date: <date>

		SAT					
No. of Phases				0			0
Opposed Ø'ing: N/S-1, E/W-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		<i>NB--</i> 0	<i>SB--</i> 0	0	<i>NB--</i> 0	<i>SB--</i> 0	0
		<i>EB--</i> 0	<i>WB--</i> 0	0	<i>EB--</i> 0	<i>WB--</i> 0	0
ATSAC-1 or ATSAC+ATCS-2?				2			2
Override Capacity				1200			1200
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	Left	52	1	52	0	1	0
	Left-Through		0		0	0	0
	Through	2124	3	708	0	3	0
	Through-Right		0		0	0	0
	Right	1	0	0	0	0	0
	Left-Through-Right		0		0	0	0
	Left-Right		0		0	0	0
SOUTHBOUND	Left	2	0	0	0	0	0
	Left-Through		0		0	0	0
	Through	2426	2	825	0	2	0
	Through-Right		1		0	1	0
	Right	49	0	49	0	0	0
	Left-Through-Right		0		0	0	0
	Left-Right		0		0	0	0
EASTBOUND	Left	71	1	71	0	1	0
	Left-Through		0		0	0	0
	Through	0	0	0	0	0	0
	Through-Right		0		0	0	0
	Right	53	1	27	0	1	0
	Left-Through-Right		0		0	0	0
	Left-Right		0		0	0	0
WESTBOUND	Left	0	0	0	0	0	0
	Left-Through		0		0	0	0
	Through	0	0	0	0	0	0
	Through-Right		0		0	0	0
	Right	2	0	0	0	0	0
	Left-Through-Right		0		0	0	0
	Left-Right		0		0	0	0
CRITICAL VOLUMES		<i>North-South:</i>		877	<i>North-South:</i>		0
		<i>East-West:</i>		71	<i>East-West:</i>		0
		<i>SUM:</i>		948	<i>SUM:</i>		0
VOLUME/CAPACITY (V/C) RATIO:				0.790			0.000
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.690			0.000
LEVEL OF SERVICE (LOS):				B			A



Level of Service Worksheet (Circular 212 Method)



I/S #:
34

PROJECT TITLE: SPW, POC Addendum

North-South Street: Gaffey St.

East-West Street: 13th

Scenario: Future With Project With Mitigation

Count Date: 1/0/1900

Analyst: <Fehr & Peers>

Date: <date>

		SAT					
				2			2
No. of Phases				2			2
Opposed Ø'ing: N/S-1, EW-2 or Both-3?				0			0
Right Turns: FREE-1, NRTOR-2 or OLA-3?		<i>NB--</i> 0	<i>SB--</i> 0	0	<i>NB--</i> 0	<i>SB--</i> 0	0
		<i>EB--</i> 0	<i>WB--</i> 0	0	<i>EB--</i> 0	<i>WB--</i> 0	0
ATSAC-1 or ATSAC+ATCS-2?				2			2
Override Capacity				0			0
MOVEMENT		Volume	No. of Lanes	Lane Volume	Volume	No. of Lanes	Lane Volume
NORTHBOUND	Left	67	1	67	0	1	0
	Left-Through		0			0	
	Through	1147	1	598	0	1	0
	Through-Right		1			1	
	Right	49	0	49	0	0	0
	Left-Through-Right		0			0	
	Left-Right		0			0	
SOUTHBOUND	Left	77	1	77	0	1	0
	Left-Through		0			0	
	Through	1171	1	620	0	1	0
	Through-Right		1			1	
	Right	68	0	68	0	0	0
	Left-Through-Right		0			0	
	Left-Right		0			0	
EASTBOUND	Left	190	1	190	0	1	0
	Left-Through		0			0	
	Through	118	0	180	0	0	0
	Through-Right		1			1	
	Right	62	0	0	0	0	0
	Left-Through-Right		0			0	
	Left-Right		0			0	
WESTBOUND	Left	62	1	62	0	1	0
	Left-Through		0			0	
	Through	143	0	215	0	0	0
	Through-Right		1			1	
	Right	72	0	0	0	0	0
	Left-Through-Right		0			0	
	Left-Right		0			0	
CRITICAL VOLUMES			<i>North-South:</i>	687		<i>North-South:</i>	0
			<i>East-West:</i>	405		<i>East-West:</i>	0
			<i>SUM:</i>	1092		<i>SUM:</i>	0
VOLUME/CAPACITY (V/C) RATIO:				0.728			0.000
V/C LESS ATSAC/ATCS ADJUSTMENT:				0.628			0.000
LEVEL OF SERVICE (LOS):				B			A

Appendix B
Summary of Mitigation Measures for San Pedro
Waterfront Addendum—
San Pedro Public Market Project

This is a summary of the mitigation measures contained in the San Pedro Waterfront Mitigation Monitoring and Reporting Program (MMRP) that apply specifically to the San Pedro Public Market (SPPM) Project and is not a replacement for the Final MMRP which was approved by the Board. However, this summary table includes certain modifications compared to Table 2-1 in the approved MMRP in order to tailor all applicable mitigation measure requirements to the SPPM Project. Such modifications include: 1) removing language for construction equipment engine requirements which have sunsetted 2) adding language to the “Methods” and “Implementation” sections to specifically indicate the requirements of the SPPM Developer (Developer) and 3) requiring that the Developer follow the Paleontological Monitoring and Mitigation Plan San Pedro Waterfront Project which the Harbor Department developed as a requirement of Mitigation Measure CR-4.

Mitigation Monitoring and Reporting Program Summary for the San Pedro Waterfront Addendum – San Pedro Public Market Project

<i>Mitigation Measure</i>	<i>Timing and Methods</i>	<i>Responsible Parties</i>
Air Quality and Meteorology: Construction		
<p>MM AQ-1. Harbor Craft Engine Standards. All harbor craft used during the construction phase of the proposed Project shall, at a minimum, be repowered to meet the cleanest existing marine engine emission standards or EPA Tier 2. Additionally, where available, harbor craft shall meet the proposed EPA Tier 3 (which are proposed to be phased-in beginning 2009) or cleaner marine engine emission standards.</p> <p>The above harbor craft measure shall be met unless one of the following circumstances exists and the contractor is able to provide proof that any of these circumstances exists:</p> <ul style="list-style-type: none"> ▪ A piece of specialized equipment is unavailable in a controlled form within the state of California, including through a leasing agreement; ▪ A contractor has applied for necessary incentive funds to put controls on a piece of uncontrolled equipment planned for use on the proposed Project, but the application process is not yet approved, or the application has been approved, but funds are not yet available; or ▪ A contractor has ordered a control device for a piece of equipment planned for use on the proposed Project, or the contractor has ordered a new piece of controlled equipment to replace the uncontrolled equipment, but that order has not been completed by the manufacturer or dealer. In addition, for this exemption to apply, the contractor must attempt to lease controlled equipment to avoid using uncontrolled equipment, but no dealer within 200 miles of the proposed Project has the controlled equipment available for lease. 	<p>Timing: During specified construction phases.</p> <p>Methods: This measure shall be incorporated into the LAHD and Developer contract specifications for all construction work to reduce the impact of construction diesel emissions. The contractor(s) shall submit an Environmental Compliance Plan for review and approval by LAHD prior to beginning of any construction activity. The contractor shall adhere to these specifications and Compliance Plan throughout construction phases. Enforcement shall include oversight by the LAHD project/construction manager or designated building inspectors to ensure compliance with contract specifications.</p>	<p>Implementation: LAHD and Developer through Construction Contractor</p> <p>Monitoring and Reporting: Environmental Management Division, Construction Management Division</p>
<p>MM AQ-3. Fleet Modernization for Onroad Trucks.</p> <ol style="list-style-type: none"> 1. Trucks hauling materials such as debris or fill shall be fully covered while operating off Port property. 2. Idling shall be restricted to a maximum of 5 minutes when not in use. 3. Tier Specifications: <p>All onroad heavy-duty diesel trucks with a GVWR of 19,500 pounds or greater used on site or to transport materials to and from the site shall comply with</p>	<p>Timing: Throughout all construction phases.</p> <p>Methods: This measure shall be incorporated into the LAHD and Developer contract specifications for all construction work to reduce the impact of construction diesel emissions. The contractor(s) shall submit an Environmental Compliance Plan for review and approval by</p>	<p>Implementation: LAHD and Developer through Construction Contractor</p> <p>Monitoring and Reporting: Environmental Management Division, Construction</p>

<i>Mitigation Measure</i>	<i>Timing and Methods</i>	<i>Responsible Parties</i>
<p>2010 emission standards, where available.</p> <p>A copy of each unit’s certified EPA rating, BACT documentation, and CARB or SCAQMD operating permit shall be provided at the time of mobilization of each applicable unit of equipment.</p> <p>The above standards/specifications shall be met unless one of the following circumstances exists and the contractor is able to provide proof that any of these circumstances exists:</p> <p>A piece of specialized equipment is unavailable in a controlled form within the state of California, including through a leasing agreement;</p> <p>A contractor has applied for necessary incentive funds to put controls on a piece of uncontrolled equipment planned for use on the proposed Project, but the application process is not yet approved, or the application has been approved, but funds are not yet available; or</p> <p>A contractor has ordered a control device for a piece of equipment planned for use on the proposed Project, or the contractor has ordered a new piece of controlled equipment to replace the uncontrolled equipment, but that order has not been completed by the manufacturer or dealer. In addition, for this exemption to apply, the contractor must attempt to lease controlled equipment to avoid using uncontrolled equipment, but no dealer within 200 miles of the proposed Project has the controlled equipment available for lease.</p>	<p>LAHD prior to beginning of any construction activity. The contractor shall adhere to these specifications and Compliance Plan throughout construction phases. Enforcement shall include oversight by the LAHD project/construction manager or designated building inspectors to ensure compliance with contract specifications.</p> <p>The construction equipment measures shall be met, unless one of the following circumstances exist and the contractor is able to provide proof that any of these circumstances exists:</p> <ol style="list-style-type: none"> 1. A piece of specialized equipment is unavailable in a controlled form within the state of California, including through a leasing agreement. 2. A contractor has applied for necessary incentive funds to put controls on a piece of uncontrolled equipment planned for use on the project, but the application process is not yet approved, or the application has been approved, but funds are not yet available. 3. A contractor has ordered a control device for a piece of equipment planned for use on the project, or the contractor has ordered a new piece of controlled equipment to replace the uncontrolled equipment, but that order has not been completed by the manufacturer or dealer. In addition, for this exemption to apply, the contractor must attempt to lease controlled equipment to avoid using uncontrolled equipment, but no dealer within 200 miles of the project has the controlled equipment available for lease. 	<p>Management Division</p>
<p>MM AQ-4. Fleet Modernization for Construction Equipment.</p> <ol style="list-style-type: none"> 1. Construction equipment shall incorporate, where feasible, emissions savings technology such as hybrid drives and specific fuel economy 	<p>Timing: Throughout all construction phases. Methods: This measure shall be incorporated into the LAHD and Developer contract</p>	<p>Implementation: LAHD and Developer through Construction Contractor</p>

<i>Mitigation Measure</i>	<i>Timing and Methods</i>	<i>Responsible Parties</i>
<p>standards.</p> <p>2. Idling shall be restricted to a maximum of 5 minutes when not in use.</p> <p>3. Tier Specifications: All offroad diesel-powered construction equipment greater than 50 hp shall meet the Tier 4 emission standards, where available. In addition, all construction equipment shall be outfitted with BACT devices certified by CARB. Any emissions control device used by the contractor shall achieve emissions reductions that are no less than what could be achieved by a Level 3 diesel emissions control strategy for a similarly sized engine as defined by CARB regulations.</p> <p>A copy of each unit's certified tier specification, BACT documentation, and CARB or SCAQMD operating permit shall be provided at the time of mobilization of each applicable unit of equipment.</p> <p>The construction equipment measures shall be met, unless one of the following circumstances exist and the contractor is able to provide proof that any of these circumstances exists:</p> <ul style="list-style-type: none"> ▪ A piece of specialized equipment is unavailable in a controlled form within the state of California, including through a leasing agreement. ▪ A contractor has applied for necessary incentive funds to put controls on a piece of uncontrolled equipment planned for use on the project, but the application process is not yet approved, or the application has been approved, but funds are not yet available. <p>A contractor has ordered a control device for a piece of equipment planned for use on the project, or the contractor has ordered a new piece of controlled equipment to replace the uncontrolled equipment, but that order has not been completed by the manufacturer or dealer. In addition, for this exemption to apply, the contractor must attempt to lease controlled equipment to avoid using uncontrolled equipment, but no dealer within 200 miles of the project has the controlled equipment available for lease.</p>	<p>specifications for all construction work to reduce the impact of construction diesel emissions. The contractor(s) shall submit an Environmental Compliance Plan for review and approval by LAHD prior to beginning of any construction activity. The contractor shall adhere to these specifications and Compliance Plan throughout construction phases. Enforcement shall include oversight by the LAHD project/construction manager or designated building inspectors to ensure compliance with contract specifications.</p>	<p>Monitoring and Reporting: Environmental Management Division, Construction Management Division</p>
<p>MM AQ-5. Additional Fugitive Dust Controls. The calculation of fugitive dust (PM10) from unmitigated proposed project earth-moving activities assumes a 75% reduction from uncontrolled levels to simulate rigorous watering of the site and use of other measures (listed below) to ensure proposed project compliance with SCAQMD Rule 403.</p>	<p>Timing: Throughout all construction phases. Methods: This measure shall be incorporated into the LAHD and Developer contract specifications for all construction work to reduce the impact of fugitive</p>	<p>Implementation: LAHD and Developer through Construction Contractor</p> <p>Monitoring and Reporting:</p>

<i>Mitigation Measure</i>	<i>Timing and Methods</i>	<i>Responsible Parties</i>
<p>The construction contractor shall apply for a SCAQMD Rule 403 Dust Control Permit.</p> <p>The construction contractor shall further reduce fugitive dust emissions to 90% from uncontrolled levels. The construction contractor shall designate personnel to monitor the dust control program and to order increased watering or other dust control measures, as necessary, to ensure a 90% control level. Their duties shall include holiday and weekend periods when work may not be in progress.</p> <p>The following measures, at minimum, must be part of the contractor Rule 403 dust control plan:</p> <ul style="list-style-type: none"> ▪ Active grading sites shall be watered one additional time per day beyond that required by Rule 403; ▪ Contractors shall apply approved nontoxic chemical soil stabilizers to all inactive construction areas or replace groundcover in disturbed areas; ▪ Construction contractors shall provide temporary wind fencing around sites being graded or cleared; ▪ Trucks hauling dirt, sand, or gravel shall be covered or shall maintain at least 2 feet of freeboard in accordance with Section 23114 of the California Vehicle Code; ▪ Construction contractors shall install wheel washers where vehicles enter and exit unpaved roads onto paved roads or wash off tires of vehicles and any equipment leaving the construction site; ▪ The grading contractor shall suspend all soil disturbance activities when winds exceed 25 mph or when visible dust plumes emanate from a site; disturbed areas shall be stabilized if construction is delayed; and ▪ Trucks hauling materials such as debris or fill shall be fully covered while operating off LAHD property. ▪ A construction relations officer shall be appointed to act as a community liaison concerning onsite construction activity including resolution of issues related to PM10 generation; ▪ All streets shall be swept at least once a day using South Coast Air Quality Management District (SCAQMD) Rule 1186, 1186.1 certified street sweepers or roadway washing trucks if visible soil materials are carried to 	<p>dust (PM10) emissions. The contractor(s) shall submit an Environmental Compliance Plan for review and approval by LAHD prior to beginning of any construction activity. The contractor shall adhere to these specifications and Compliance Plan throughout construction phases. Enforcement shall include oversight by the LAHD project/construction manager or designated building inspectors to ensure compliance with contract specifications.</p>	<p>Environmental Management Division, Construction Management Division</p>

<i>Mitigation Measure</i>	<i>Timing and Methods</i>	<i>Responsible Parties</i>
<p>adjacent streets;</p> <ul style="list-style-type: none"> ▪ Water or non-toxic soil stabilizer shall be applied three times daily to all unpaved parking or staging areas or unpaved road surfaces; ▪ Roads and shoulders shall be paved; and ▪ Water shall be applied three times daily or as needed to areas where soil is disturbed. 		
<p>MM AQ-6. Best Management Practices. The following types of measures are required on construction equipment (including on-road trucks):</p> <ol style="list-style-type: none"> 1. Use diesel oxidation catalysts and catalyzed diesel particulate traps. 2. Maintain equipment according to manufacturers' specifications 3. Restrict idling of construction equipment to a maximum of 5 minutes when not in use 4. Install high-pressure fuel injectors on construction equipment vehicles <p>LAHD shall implement a process by which to select additional BMPs to further reduce air emissions during construction. The LAHD shall determine the BMPs once the contractor identifies and secures a final equipment list.</p>	<p>Timing: Throughout all construction phases. Methods: This measure shall be incorporated into the LAHD and Developer contract specifications for all construction work to reduce the impact of construction diesel emissions. The contractor(s) shall submit an Environmental Compliance Plan for review and approval by LAHD prior to beginning of any construction activity. The contractor shall adhere to these specifications and Compliance Plan throughout construction phases. Enforcement shall include oversight by the LAHD project/construction manager or designated building inspectors to ensure compliance with contract specifications.</p>	<p>Implementation: LAHD and Developer through Construction Contractor</p> <p>Monitoring and Reporting: Environmental Management Division, Construction Management Division</p>
<p>MM AQ-7. General Mitigation Measure.</p> <p>For any of the above mitigation measures (MM AQ-1 through AQ-6), if a CARB-certified technology becomes available and is shown to be as good as or better in terms of emissions performance than the existing measure, the technology could replace the existing measure pending approval by the LAHD.</p>	<p>Timing: Throughout all construction phases. Methods: This measure shall be incorporated into the LAHD and Developer contract specifications. The contractor(s) shall submit an Environmental Compliance Plan for review and approval by LAHD prior to beginning of any construction activity, which would include any proposed new technology.</p>	<p>Implementation: LAHD and Developer through Construction Contractor</p> <p>Monitoring and Reporting: Environmental Management Division, Construction Management Division</p>

<i>Mitigation Measure</i>	<i>Timing and Methods</i>	<i>Responsible Parties</i>
<p>MM AQ-8. Special Precautions near Sensitive Sites. When construction activities are planned within 1,000 feet of sensitive receptors (defined as schools, playgrounds, day care centers, and hospitals), the construction contractor shall notify each of these sites in writing at least 30 days before construction activities begin.</p>	<p>Timing: Throughout all construction phases. Methods: This measure shall be incorporated into the LAHD and Developer contract specifications for all construction work. The contractor(s) shall submit an Environmental Compliance Plan for review and approval by LAHD prior to beginning of any construction activity which shall include a plan to notify sensitive receptors and shall be approved by the LAHD.</p>	<p>Implementation: LAHD and Developer through Construction Contractor</p> <p>Monitoring and Reporting: Environmental Management Division, Construction Management Division</p>
Biological Resources: Construction		
<p>MM BIO-2. Conduct nesting bird surveys. This measure applies if construction is to occur between February 15 and September 1. Prior to ground-disturbing activities, a qualified biologist will conduct surveys for the presence of black crowned night herons, blue herons, and other nesting birds within Berth 78–Ports O’Call or other appropriate and known locations within the study area that contain potential nesting bird habitat. Surveys will be conducted 24 hours prior to the clearing, removal, or grubbing of any vegetation or ground disturbance. If active nests of species protected under the MBTA and/or similar provisions of the California Fish and Game Code (i.e., native birds including but not limited to the black-crowned night heron) are located, then a barrier installed at a 50–100 foot radius from the nest(s) will be established and the tree/location containing the nest will be marked and will remain in place and undisturbed until a qualified biologist performs a survey to determine that the young have fledged or the nest is no longer active.</p>	<p>Timing: During any construction between February 15 and September 1 of every year. Methods: This measure shall be incorporated into LAHD and Developer contract specifications for all construction work. The construction contractor shall instruct construction personnel as part of normal construction procedures. LAHD shall arrange for the presence of the qualified biologist to monitor during construction activity.</p>	<p>Implementation: LAHD and Developer through Construction Contractor</p> <p>Monitoring and Reporting: Environmental Management Division, Construction Management Division</p>
<p>MM BIO-3. Avoid marine mammals. The contractor will be required to use sound abatement techniques to reduce both noise and vibrations from pile driving activities. Sound abatement techniques will include, but are not limited to, vibration or hydraulic insertion techniques, drilled or augured holes for cast-in-place piles, bubble curtain technology, and sound aprons where feasible. At the initiation of each pile driving event, and after breaks of more than 15 minutes, the pile driving will also employ a “soft-start” in which the hammer is</p>	<p>Timing: During all in-water construction activities requiring pile driving. Methods: This measure shall be incorporated into LAHD and Developer contract specifications for all construction work. The construction contractor shall instruct construction personnel as part of normal</p>	<p>Implementation: LAHD and Developer through Construction Contractor</p> <p>Monitoring and Reporting: Environmental Management Division, Construction</p>

<i>Mitigation Measure</i>	<i>Timing and Methods</i>	<i>Responsible Parties</i>
<p>operated at less than full capacity (i.e., approximately 40–60% energy levels) with no less than a 1-minute interval between each strike for a 5-minute period. Pile driving activities occurring within the Outer Harbor will include establishment of a safety zone, and the area surrounding the operations will be monitored by a qualified marine biologist for pinnipeds. As the disturbance threshold level sound is expected to extend at least 1,000 feet from the steel pile driving operations, a safety zone will be established around the steel pile driving site and monitored for pinnipeds within a 1,200-foot-radius safety zone around the pile. As the steel pile driving site will move with each new pile, the 1,200 foot safety zone will move accordingly. Observers on shore or by boat will survey the safety zone to ensure that no marine mammals are seen within the zone before pile driving of a steel pile segment begins. If marine mammals are found within the safety zone, pile driving of the segment will be delayed until they move out of the area. If a marine mammal is seen above water and then dives below, the biologist will instruct the contractor to wait at least 15 minutes, and if no marine mammals are seen by the biologist in that time, it may be assumed that the animal has moved beyond the safety zone. This 15-minute criterion is based on a study indicating that pinnipeds dive for a mean time of 0.50 minutes to 3.33 minutes; the 15-minute delay will allow a more than sufficient period of observation to be reasonably sure the animal has left the project vicinity.</p> <p>If pinnipeds enter the safety zone after pile driving of a segment has begun, pile driving will continue. The biologist will monitor and record the species and number of individuals observed, and make note of their behavior patterns. If the animal appears distressed and, if it is operationally safe to do so, pile driving will cease until the animal leaves the area. Pile driving cannot be terminated safely and without severe operational difficulties until reaching a designated depth. Therefore, if it is deemed operationally unsafe by the project engineer to discontinue pile driving activities, and a pinniped is observed in the safety zone, pile driving activities will continue until the critical depth is reached (at which time pile driving will cease) or until the pinniped leaves the safety zone. Prior to the initiation of each new pile driving episode, the area will again be thoroughly surveyed by the biologist</p>	<p>construction procedures. LAHD shall arrange for the presence of a qualified biologist to monitor during construction activity.</p>	<p>Management Division</p>
Cultural Resources: Construction		
MM CR-3: Stop Work If Unanticipated Cultural Resources Are Identified	Timing: During initial ground disturbance	Implementation: LAHD,

<i>Mitigation Measure</i>	<i>Timing and Methods</i>	<i>Responsible Parties</i>
<p>During Ground Disturbing Activities. In the event that any artifact or an unusual amount of bone, shell, or non-native stone is encountered during construction, work will be immediately stopped and relocated from that area. The contractor will stop construction within 100 feet of the exposure of these finds until a qualified archaeologist, retained by LAHD in advance of construction, can be contacted to evaluate the find (see 36 CFR 800.11.1 and pertinent CEQA regulations). Examples of such cultural materials might include concentrations of ground stone tools such as mortars, bowls, pestles, and manos; chipped stone tools such as projectile points or choppers; flakes of stone not consistent with the immediate geology such as obsidian or fused shale; trash pits containing bottles and/or ceramics; or structural remains. If the resources are found to be significant, they will be avoided or will be mitigated consistent with SHPO guidelines as appropriate. All construction equipment operators will attend a pre-construction meeting presented by a professional archaeologist retained by LAHD to review types of cultural resources and artifacts that would be considered potentially significant to ensure operator recognition of these materials during construction.</p> <p>If human remains are encountered, there will be no further excavation or disturbance of the site or any nearby area reasonably suspected to overlie adjacent human remains. The Los Angeles County Coroner will be contacted to determine the age and cause of death. If the remains are not of Native American heritage, construction in the area may recommence. If the remains are of Native American origin, the most likely descendants of the deceased will be identified by the NAHC. LAHD and the USACE will consult with the Native American most likely descendant(s) to identify a mutually acceptable strategy for treating and disposing of, with appropriate dignity, the human remains and any associated grave goods as provided in PRC Section 5097.98. If the NAHC is unable to identify a most likely descendant; if the descendant fails to make a recommendation within 24 hours of being notified by the NAHC, LAHD, or the USACE; and if the descendant is not capable of reaching a mutually acceptable strategy through mediation by the NAHC, the Native American human remains and associated grave goods will be reburied with appropriate dignity on the proposed project site in a location not subject to further subsurface disturbance.</p>	<p>during construction</p> <p>Methods: To avoid or reduce this potential impact, the Environmental Management Division (EMD) shall retain a qualified archaeologist. The Construction Manager/Contractor shall instruct construction personnel as part of normal construction procedures to halt/redirect construction activities if any materials are uncovered that are suspect of being associated with historical or prehistoric occupation. If materials are found, the construction contractor shall contact the Construction Manager, EMD, and archeologist</p>	<p>archaeological consultants (ICF Jones & Stokes), Developer through construction contractor</p> <p>Monitoring and Reporting: Environmental Management Division, Construction Management Division</p>
Geology: Construction and Operation		

<i>Mitigation Measure</i>	<i>Timing and Methods</i>	<i>Responsible Parties</i>
<p>MM GEO-1. Emergency response planning. The tenants within the proposed project area will work with Port engineers and LAHD police to develop tsunami response training and procedures to assure that construction and operations personnel will be prepared to act in the event of a large seismic event. Such procedures will include immediate evacuation requirements in the event that a large seismic event is felt at the proposed project site, as part of overall emergency response planning for this proposed Project.</p> <p>Such procedures will be included in any bid specifications for construction or operations personnel, with a copy of such bid specifications to be provided to LAHD, including a completed copy of its operations emergency response plan prior to commencement of construction activities and/or operations.</p>	<p>Timing: At beginning of Construction and within first year of Operation (with annual updates)</p> <p>Method: Construction: LAHD Engineering Division shall provide procedures for inclusion in bid specifications. Such procedures will be included in any bid specifications for construction or operations personnel, with a copy of such bid specifications to be provided to LAHD, including a completed copy of its operations emergency response plan prior to commencement of construction activities and/or operations. The contractor(s) shall submit an Environmental Compliance Plan for review and approval by LAHD prior to beginning of any construction activity. The contractor shall adhere to these specifications and Compliance Plan throughout construction phases. Enforcement shall include oversight by the LAHD project/construction manager or designated building inspectors to ensure compliance with contract specifications</p> <p>Method: Operations: General requirements of this measure shall be incorporated into the lease. All tenants and LAHD shall prepare an emergency response plan for submittal to the LAHD within first year of operation. Enforcement shall include oversight by the Real Estate Division. Annual staff reports shall be made available to the Board at a regularly scheduled public Board Meeting.</p>	<p>Implementation: LAHD and Developer through Construction Contractor; tenant for operations.</p> <p>Monitoring and Reporting: Environmental Management Division, Port Operations, Construction Management Division, Real Estate Division.</p>
Groundwater and Soils: Construction		
<p>MM GW-1. Complete site remediation. Unless otherwise authorized by the lead regulatory agency for any given site, the LAHD will remediate all</p>	<p>Timing: Prior to or during grading activities</p> <p>Method: Soil and groundwater remediation</p>	<p>Implementation: LAHD through Construction</p>

<i>Mitigation Measure</i>	<i>Timing and Methods</i>	<i>Responsible Parties</i>
<p>contaminated soils within proposed project boundaries prior to or during demolition and grading activities. Remediation will occur in compliance with local, state, and federal regulations and as directed by the LACFD, DTSC, and/or RWQCB.</p> <p>Soil remediation will be completed such that contamination levels are below health screening levels established by OEHHA and/or applicable action levels established by the lead regulatory agency with jurisdiction over the site. Use of localized soil capping/paving, combined with agency-approved deed restrictions, may be an acceptable remediation measure in upland areas and/or risk-based soil assessments, but would be subject to the discretion of the lead regulatory agency.</p> <p>Existing groundwater contamination throughout the proposed project boundary will continue to be monitored and remediated, simultaneous and/or subsequent to site redevelopment, in accordance with direction provided by the RWQCB.</p> <p>Unless otherwise authorized by the lead regulatory agency for any given site, areas of soil contamination that will be remediated prior to or in conjunction with project demolition, grading, and construction would include, but not be limited to, the properties within and adjacent to the proposed Project.</p>	<p>shall be completed such that contamination levels are below health screening levels established by OEHHA and/or applicable action levels established by the lead regulatory agency with jurisdiction over the site. Soil contamination waivers may be acceptable as a result of encapsulation (i.e., paving) and/or risk-based soil assessments, but would be subject to the discretion of the lead regulatory agency.</p>	<p>Contractor.</p> <p>Monitoring and Reporting: Environmental Management Division, Construction Management Division, Engineering Division, Real Estate Division. Environmental Management Division will conduct independent soil sampling as appropriate.</p>
<p>MM GW-2. LAHD will prepare a contamination contingency plan for non-specific facilities. The project site has a long history of industrial activity, so it is possible that future construction activity could encounter historical soil or groundwater contamination that had not been previously reported to regulatory agencies. The following contingency plan will be implemented to address previously unknown contamination during demolition, grading, and construction:</p> <p>a) All trench excavation and fill operations will be observed for the presence of chemicals of potential concern and petroleum products. Soils that are suspected to be impacted with chemicals of potential concern and/or petroleum products will be segregated from clean soil. Indications of contaminated/impacted soil may include but are not limited to: discolored soil, petroleum or organic odors, and/or visible sheen. In the event unexpected suspected chemically impacted material (soil or water) is encountered during construction, the contractor will notify LAHD’s Chief Harbor Engineer, Director of Environmental Management, and Risk Management’s Industrial Hygienist. LAHD will confirm the presence of</p>	<p>Timing: Prior to construction</p> <p>Method: LAHD will prepare a contamination contingency plan and the plan shall be included in bid specifications. Developer shall include the plan in any bid specifications. Such procedures will be included in any bid specifications for construction or operations personnel, with a copy of such bid specifications to be provided to LAHD, including a completed copy of its operations emergency response plan prior to commencement of construction activities and/or operations. The contractor(s) shall submit an Environmental Compliance Plan for review and approval by LAHD prior to beginning of any construction activity. The contractor shall adhere to these specifications and Compliance</p>	<p>Implementation: LAHD through Construction Contractor; Developer undertake soil disturbing construction activities.</p> <p>Monitoring and Reporting: Environmental Management Division, Construction Management Division, Engineering Division, Real Estate Division. Environmental Management Division will conduct independent soil sampling as appropriate.</p>

<i>Mitigation Measure</i>	<i>Timing and Methods</i>	<i>Responsible Parties</i>
<p>the suspect material; direct the contractor to remove, stockpile, or contain the material; and characterize the suspect material identified within the boundaries of the construction area. Continued work at a contaminated site will require the approval of the Chief Harbor Engineer.</p> <p>b) As warranted, appropriate air monitoring equipment (e.g., photoionization detector, combustible gas indicator, organic vapor analyzer, etc.) will be present during grading and/or excavation activities in soils that are suspected to be impacted with chemicals of concern and/or petroleum products.</p> <p>c) Excavation of VOC-impacted soil will require obtaining and complying with a South Coast Air Quality Management District Rule 1166 permit.</p> <p>d) The remedial option(s) selected will be dependent upon a number of criteria (including but not limited to types of chemical constituents, concentration of the chemicals, health and safety issues, time constraints, cost, etc.) and will be determined on a site-specific basis. Both off-site and on-site remedial options will be evaluated.</p> <p>e) The extent of removal actions will be determined on a site-specific basis. At a minimum, the chemically impacted area(s) within the boundaries of the construction area will be remediated to the satisfaction of the lead regulatory agency for the site. The LAHD Project Manager overseeing removal actions will inform the contractor when the removal action is complete.</p> <p>f) Copies of hazardous waste manifests or other documents indicating the amount, nature, and disposition of such materials will be submitted to the Chief Harbor Engineer within 30 days of project completion.</p> <p>g) In the event that suspected contaminated soil is encountered, all onsite personnel handling the suspected contaminated material must be trained in accordance with the federal Hazardous Waste Operations and Emergency Response (HAZWOPER) standard. This training provides precautions and protective measures for workers remediating contaminated sites. Workers not certified with HAZWOPER training will not be allowed to resume work in suspected contaminated areas until appropriate site characterization confirms that contaminated soil, groundwater, or soil vapor are not present.</p> <p>h) As warranted, real-time perimeter and ambient air monitoring stations will be established during all grading, excavation, trenching, and/or soil handling activities associated with contaminated soil.</p>	<p>Plan throughout construction phases.</p>	

<i>Mitigation Measure</i>	<i>Timing and Methods</i>	<i>Responsible Parties</i>
i) All excavations will be filled with structurally suitable fill material that is free from contamination.		
Transportation and Circulation (Ground): Construction		
<p>MM TC-1: Develop and implement a Traffic Control Plan throughout proposed project construction. In accordance with the City’s policy on street closures and traffic diversion for arterial and collector roadways, the construction contractor will prepare a traffic control plan (to be approved by the city and county engineers) before construction. The traffic control plan will include:</p> <ul style="list-style-type: none"> a street layout showing the location of construction activity and surrounding streets to be used as detour routes, including special signage; a tentative start date and construction duration period for each phase of construction; the name, address, and emergency contact number for those responsible for maintaining the traffic control devices during the course of construction; and written approval to implement traffic control from other agencies, as needed. <p>Additionally, the traffic control plan will include the following stipulations.</p> <ul style="list-style-type: none"> Provide access for emergency vehicles at all times. Avoid creating additional delay at intersections currently operating at congested conditions, either by choosing routes that avoid these locations, or constructing during nonpeak times of day. Maintain access for driveways and private roads, except for brief periods of construction, in which case property owners will be notified. Provide adequate off-street parking areas at designated staging areas for construction-related vehicles. Maintain pedestrian and bicycle access and circulation during proposed project construction where safe to do so. If construction encroaches on a sidewalk, a safe detour will be provided for pedestrians at the nearest crosswalk. If construction encroaches on a bike lane, warning signs will be posted that indicate bicycles and vehicles are sharing the roadway. 	<p>Timing: Prior to construction activities, to be implemented during construction.</p> <p>Methods: This measure shall be completed by the LAHD and Developer, with compliance reported to the Board of Harbor Commissioners.</p>	<p>Implementation: LAHD and Developer</p> <p>Monitoring and Reporting: LAHD Environmental Management and Engineering Divisions</p>

<i>Mitigation Measure</i>	<i>Timing and Methods</i>	<i>Responsible Parties</i>
<p>Traffic controls may include flag persons wearing Occupational Safety and Health Administration–approved vests and using a “Stop/Slow” paddle to warn motorists of construction activity.</p> <p>Maintain access to Metro, LADOT, MAX, PVPTA, and LAHD transit services and ensure that public transit vehicles are detoured.</p> <p>Post standard construction warning signs in advance of the construction area and at any intersection that provides access to the construction area.</p> <p>Construction warning signs will be posted, in accordance with local standards or those set forth in the Manual on Uniform Traffic Control Devices (Federal Highway Administration 2001) in advance of the construction area and at any intersection that provides access to the construction area.</p> <p>During lane closures, notify LAFD and LAPD, as well as the Los Angeles County Sheriff’s and Fire Departments, of construction locations to ensure that alternative evacuation and emergency routes are designed to maintain response times during construction periods, if necessary.</p> <p>Provide written notification to contractors regarding appropriate routes to and from construction sites, and weight and speed limits for local roads used to access construction sites. Submit a copy of all such written notifications to the City of Los Angeles Planning Department.</p> <p>Repair or restore the road right-of-way to its original condition or better upon completion of the work.</p>		
Noise: Construction		
<p>MM NOI-1. Construct temporary noise barriers, muffle and maintain construction equipment, prohibit idling, locate equipment, use quiet construction equipment, and notify residents. The following will reduce the impact of noise from construction activities:</p> <p>a) Temporary Noise Barriers. When construction is occurring within 500 feet of a residence or park, temporary noise barriers (solid fences or curtains) will be located between noise-generating construction activities and sensitive receivers.</p> <p>b) Construction Equipment. All construction equipment powered by internal</p>	<p>Timing: Throughout all construction phases.</p> <p>Methods: This measure shall be incorporated into contract specifications for all construction work to reduce noise the impacts. The contractor(s) shall submit an Environmental Compliance Plan for review and approval by LAHD prior to beginning of any construction activity. The contractor shall adhere to these specifications and Compliance Plan throughout construction phases. Enforcement shall include</p>	<p>Implementation: LAHD and Developer through Construction Contractor</p> <p>Monitoring and Reporting: Environmental Management Division, Construction Management Division</p>

<i>Mitigation Measure</i>	<i>Timing and Methods</i>	<i>Responsible Parties</i>
<p>combustion engines will be properly muffled and maintained.</p> <p>c) Idling Prohibitions. Unnecessary idling of internal combustion engines near noise sensitive areas will be prohibited.</p> <p>d) Equipment Location. All stationary noise-generating construction equipment, such as air compressors and portable power generators, will be located as far as practical from existing noise sensitive land uses.</p> <p>e) Quiet Equipment Selection. Select quiet construction equipment whenever possible. Comply where feasible with noise limits established in the City of Los Angeles Noise Ordinance.</p> <p>f) Notification. Notify residents within 500 feet to the proposed project site of the construction schedule in writing.</p>	<p>oversight by the LAHD project/construction manager or designated building inspectors to ensure compliance with contract specifications.</p>	
<p>MM NOI-2. Construction Hours. Construction activities for the proposed Project would not exceed the ambient noise level by 5 dBA at a noise sensitive use between the hours of 6:00 p.m. and 7:00 a.m. Monday through Friday, before 8:00 a.m. or after 6:00 p.m. on Saturday, or at any time on Sunday. If extended construction hours are needed during weekdays under special circumstances, LAHD and the contractor will provide at least 72 hours' notice to sensitive receptors within 0.5 miles of the construction area. Under no circumstances will construction hours exceed the range prescribed by the City of Los Angeles Municipal Code.</p>	<p>Timing: During construction.</p> <p>Methods: This measure shall be incorporated into contract specifications for all construction work to reduce noise the impacts. The contractor(s) shall submit an Environmental Compliance Plan for review and approval by LAHD prior to beginning of any construction activity. The contractor shall adhere to these specifications and Compliance Plan throughout construction phases. Enforcement shall include oversight by the LAHD project/construction manager or designated building inspectors to ensure compliance with contract specifications.</p>	<p>Implementation: LAHD and Developer through Construction Contractor</p> <p>Monitoring and Reporting: Environmental Management Division, Construction Management Division</p>
Utilities and Public Services: Construction		

<i>Mitigation Measure</i>	<i>Timing and Methods</i>	<i>Responsible Parties</i>
<p>MM PS-2: Recycle construction materials. Demolition and/or excess construction materials will be separated on site for reuse/recycling or proper disposal. During grading and construction, separate bins for recycling of construction materials will be provided on site.</p>	<p>Timing: Throughout construction. Methods: This measure shall be incorporated into contract specifications for all construction work to improve recycling efforts. The contractor(s) shall submit an Environmental Compliance Plan for review and approval by LAHD prior to beginning of any construction activity. The contractor shall adhere to these specifications and Compliance Plan throughout construction phases. Enforcement shall include oversight by the LAHD project/construction manager to ensure compliance with contract specifications.</p>	<p>Implementation: LAHD and Developer through Construction Contractor</p> <p>Monitoring and Reporting: Environmental Management Division, Construction Management Division</p>
<p>MM PS-3: Use materials with recycled content. Materials with recycled content, such as recycled steel from framing and recycled concrete and asphalt from roadway construction, will be used in project construction. Wood chippers registered through the California Air Resources Board’s Portable Equipment Registration Program will be operated on site during construction. Wood from tree removal, not from demolished structures, will be reused as landscape cover, further reducing the quantity of wood that would otherwise be disposed of at solid waste facilities.</p>	<p>Timing: Throughout construction. Methods: This measure shall be incorporated into contract specifications for all construction work to improve recycling efforts. The contractor(s) shall submit an Environmental Compliance Plan for review and approval by LAHD prior to beginning of any construction activity. The contractor shall adhere to these specifications and Compliance Plan throughout construction phases. Enforcement shall include oversight by the LAHD project/construction manager to ensure compliance with contract specifications.</p>	<p>Implementation: LAHD and Developer through Construction Contractor</p> <p>Monitoring and Reporting: Environmental Management Division, Construction Management Division</p>
<p>Utilities and Public Services: Operation</p>		

<i>Mitigation Measure</i>	<i>Timing and Methods</i>	<i>Responsible Parties</i>
<p>MM PS-4: Comply with AB 939. LAHD and Port tenants will implement a Solid Waste Management Program including the following measures to achieve a 50% reduction of current waste generation percentages by 2037 and ensure compliance with the California Solid Waste Management Act (AB 939).</p> <ol style="list-style-type: none"> Provide space and/or bins for storage of recyclable materials on the project site. All garbage and recycle bin storage space will be enclosed and plans will show equal area availability for both garbage and recycle bins in storage spaces. Establish a recyclable material pick-up area for commercial buildings. Participate in a curbside recycling program to serve the new development. Develop a plan for accessible collection of materials on a regular basis. Develop source reduction measures that indicate the method and amount of expected reduction. Implement a program to purchase materials that have recycled content for project construction and operation (e.g., lumber, plastic, office supplies). Provide a resident-tenant/employee education pamphlet to be used in conjunction with available Los Angeles County and federal source reduction educational materials. The pamphlet will be provided to all commercial tenants by the leasing/property management agency. Include lease language requiring tenant participation in recycling/waste reduction programs, including specification that janitorial contracts support recycling. 	<p>Timing: Throughout all operational years.</p> <p>Methods: This measure shall be incorporated into the Cruise Line, Cruise Terminal, Catalina Express, Tug Company and Ports O’Call Developer leases. If the tenant proposes replacing any mitigation measure, the tenant must first make a formal request to the Port’s Executive Director. The Executive Director will then consider the proposal. Annual staff reports shall be made available to the Board at a regularly scheduled public Board Meeting.</p>	<p>Implementation: Cruise Line, Cruise Terminal, Catalina Express, Tug Company and Ports O’Call Developer leases and LAHD</p> <p>Monitoring and Reporting: LAHD Environmental Management and Real Estate Divisions</p>
<p>MM PS-5: Water Conservation and Wastewater Reduction. LAHD and Port tenants will implement the following water conservation and wastewater reduction measures to further reduce impacts on water demand and wastewater flows.</p> <ol style="list-style-type: none"> The landscape irrigation system will be designed, installed, and tested to provide uniform irrigation coverage for each zone. Sprinkler head patterns will be adjusted to minimize overspray onto walkways and streets. Each zone (sprinkler valve) will water plants having similar watering needs (i.e., shrubs, flowers, and turf will not be in the same watering zone). Automatic irrigation timers will be set to water landscaping during early morning or late evening hours to reduce water losses from evaporation. Irrigation run times will be adjusted for all zones seasonally, reducing length and 	<p>Timing: Throughout all operational years.</p> <p>Methods: This measure shall be incorporated into the Cruise Line, Cruise Terminal, Catalina Express, Tug Company and Ports O’Call Developer leases. If the tenant proposes replacing any mitigation measure, the tenant must first make a formal request to the Port’s Executive Director. The Executive Director will then consider the proposal. Annual staff reports shall be made available to the Board at a regularly scheduled public Board Meeting.</p>	<p>Implementation: Cruise Line, Cruise Terminal, Catalina Express , Tug Company and Ports O’Call Developer leases and LAHD</p> <p>Monitoring and Reporting: LAHD Environmental Management and Real Estate Divisions</p>

<i>Mitigation Measure</i>	<i>Timing and Methods</i>	<i>Responsible Parties</i>
<p>frequency of waterings in the cooler months (i.e., fall, winter, spring). Adjust sprinkler timer run time to avoid water runoff, especially when irrigating sloped property. Sprinkler times will be reduced once drought-tolerant plants have been established.</p> <p>b. Drought-tolerant, low water consuming plant varieties will be used to reduce irrigation water consumption.</p> <p>c. Recycled water will be used for irrigation and toilet flushing (dual-flushing)</p> <p>d. Ultra-low-flush toilets, ultra-low-flush urinals, and water-saving showerheads must be installed in both new construction and when remodeling. Low flow faucet aerators will be installed on all sink faucets.</p> <p>e. Significant opportunities for water savings exist in air conditioning systems that utilize evaporative cooling (i.e., employ cooling towers). LADWP will be contacted for specific information of appropriate measures.</p> <p>f. Recirculating or point-of-use hot water systems will be installed to reduce water waste in long piping systems where water must be run for considerable period before heated water reaches the outlet.</p>		
<p>MM PS-6: Employ energy conservation measures. During the design process, LAHD will consult with LADWP’s Efficiency Solutions Business Group regarding possible energy efficiency measures. LAHD and its tenants will incorporate measures to meet or, if possible, exceed minimum efficiency standards for Title XXIV of the California Code of Regulations, such as:</p> <p>a. Built-in appliances, refrigerators, and space-conditioning equipment will exceed the minimum efficiency levels mandated in the California Code of Regulations.</p> <p>b. High-efficiency air conditioning will be installed that is controlled by a computerized energy-management system in office and retail spaces and provides the following:</p> <ul style="list-style-type: none"> a variable air-volume system that results in minimum energy consumption and avoids hot water energy consumption for terminal reheat, a 100% outdoor air-economizer cycle to obtain free cooling in appropriate climate zones during dry climatic periods, sequentially staged operation of air-conditioning equipment in accordance with building demands, 	<p>Timing: Throughout all operational years.</p> <p>Methods: This measure shall be incorporated into the Cruise Line, Cruise Terminal, Catalina Express, Tug Company and Ports O’Call Developer leases. If the tenant proposes replacing any mitigation measure, the tenant must first make a formal request to the Port’s Executive Director. The Executive Director will then consider the proposal. Annual staff reports shall be made available to the Board at a regularly scheduled public Board Meeting.</p>	<p>Implementation: Cruise Line, Cruise Terminal, Catalina Express, Tug Company and Ports O’Call Developer leases and LAHD</p> <p>Monitoring and Reporting: LAHD Environmental Management and Real Estate Divisions</p>

<i>Mitigation Measure</i>	<i>Timing and Methods</i>	<i>Responsible Parties</i>
<p>the isolation of air conditioning to any selected floor or floors, and considers the applicability of the use of thermal energy storage to handle cooling loads.</p> <p>c. Ventilation air will be cascaded from high-priority areas before being exhausted, thereby decreasing the volume of ventilation air required. For example, air could be cascaded from occupied space to corridors and then to mechanical spaces before being exhausted.</p> <p>d. Lighting system heat will be recycled for space heating during cool weather. While exhaust lighting-system heat will be recycled from the buildings, via ceiling plenums, to reduce cooling loads in warm weather.</p> <p>e. Low and medium static-pressure terminal units will be installed, as well as ductwork to reduce energy consumption by air-distribution systems.</p> <p>f. Buildings must be well sealed to prevent outside air from infiltrating and increasing interior space-conditioning loads. Where applicable, design building entrances with vestibules to restrict infiltration of unconditioned air and exhausting of conditioned air.</p> <p>g. A performance check of the installed space-conditioning system will be completed by the developer/installer prior to issuance of the certificate of occupancy to ensure that energy-efficiency measures incorporated into the proposed Project operate as designed.</p> <p>h. Exterior walls will be finished with light-colored materials and high-emissivity characteristics to reduce cooling loads. Interior walls will be finished with light-colored materials to reflect more light and, thus increase light efficiency.</p> <p>i. White reflective material will be used for roofing meeting California standards for reflectivity and emissivity to reject heat.</p> <p>j. Thermal insulation that exceeds requirements established by the California Code of Regulations will be installed in walls and ceilings.</p> <p>k. Window systems will be designed to reduce thermal gain and loss, thus reducing cooling loads during warm weather and heating loads during cool weather.</p> <p>l. Heat-rejecting window treatments will be installed, such as films, blinds, draperies, or others on appropriate exposures.</p> <p>m. Fluorescent and high-intensity discharge lamps that give the highest light output per watt of electricity consumed will be installed wherever possible,</p>		

<i>Mitigation Measure</i>	<i>Timing and Methods</i>	<i>Responsible Parties</i>
<p>including all street and parking lot lighting, to reduce electricity consumption. Reflectors will be used to direct maximum levels of light to work surfaces.</p> <p>n. Photosensitive controls and dimmable electronic ballasts will be installed to maximize the use of natural daylight available and reduce artificial lighting load.</p> <p>o. Occupant-controlled light switches and thermostats to permit individual adjustment of lighting, heating, and cooling will be installed to avoid unnecessary energy consumption.</p> <p>p. Time-controlled interior and exterior public area light will be installed, limited to that which is necessary for safety and security.</p> <p>q. Mechanical systems (HVAC and lighting) in the building will be controlled with timing systems to prevent accidental or inappropriate conditioning or lighting of unoccupied space.</p> <p>r. Windowless walls or passive solar inset of windows will be incorporated, where feasible, in building design.</p> <p>s. Project will focus pedestrian activity within sheltered outdoor areas.</p>		
Recreation: Construction		
<p>MM REC-1. Maintain pedestrian access during construction. The LAHD and construction contractors will follow standard safety procedures to protect pedestrian traffic from construction hazards, including providing brightly colored fencing and signage indicating closures and safely directing pedestrian traffic around construction areas. This will also require coordinated construction activities such that pedestrian access can be routed around construction with a minimum increase in distance.</p>	<p>Timing: During Construction</p> <p>Methods: This measure shall be incorporated into the LAHD and Developer design and contract specifications.</p> <p>The contractor shall adhere to these specifications and Compliance Plan throughout construction phases. Enforcement shall include oversight by the LAHD project/construction manager or designated building inspectors to ensure compliance with contract specifications.</p>	<p>Implementation: LAHD and Developer through Construction Contractor</p> <p>Monitoring and Reporting: Environmental Management Division, Construction Management Division</p>
<p>MM REC-2. Maintain bicycle access during construction. The LAHD and construction contractors will provide signage notifying users of bike lanes of closure as well as signage directing users to alternative bike routes. Alternative</p>	<p>Timing: During Construction</p> <p>Methods: This measure shall be incorporated into the LAHD and Developer design and</p>	<p>Implementation: LAHD and Developer through</p>

<i>Mitigation Measure</i>	<i>Timing and Methods</i>	<i>Responsible Parties</i>
<p>bike lanes in the proposed project vicinity include a north-south Class II bike path along the entire length of South Gaffey Street, and an east-west Class III bike path on 9th from North Harbor Boulevard west to State Route 213. LAHD will be required to inform the public prior to commencement of construction resulting in closures or possible disruptions to bike paths. Public sources to notify will, at minimum, include the City of Los Angeles Department of Transportation Bicycle Program, and Los Angeles area bicycling groups.</p>	<p>contract specifications. The contractor shall adhere to these specifications and Compliance Plan throughout construction phases. Enforcement shall include oversight by the LAHD project/construction manager or designated building inspectors to ensure compliance with contract specifications.</p>	<p>Construction Contractor Monitoring and Reporting: Environmental Management Division, Construction Management Division</p>
<p>MM REC-3. Maintain parking during construction. The LAHD and construction contractors will minimize parking obstructions during construction periods by placing construction areas out of roadways and parking lots, where possible. In areas where construction staging areas and construction activities must impede access to parking areas, detour signs and lane striping will direct traffic to additional off-site parking areas. LAHD will provide shuttle service to remote parking areas in the event that offsite parking areas are farther than 1 mile from existing waterfront areas and the Waterfront Red Car Line does not adequately service the offsite parking areas.</p>	<p>Timing: During Construction Methods: This measure shall be incorporated into the LAHD and Developer design and contract specifications. The contractor shall adhere to these specifications and Compliance Plan throughout construction phases. Enforcement shall include oversight by the LAHD project/construction manager or designated building inspectors to ensure compliance with contract specifications.</p>	<p>Implementation: LAHD and Developer through Construction Contractor Monitoring and Reporting: Environmental Management Division, Construction Management Division</p>
<p>MM REC-4. Maintain vehicle access during construction. The LAHD and construction contractors will minimize obstructions to vehicle access during construction periods by placing construction areas out of roadways and parking lots, where possible. In areas where construction staging areas and construction activities must impede access to roadways, detour signs and lane striping will safely direct traffic around construction areas.</p>	<p>Timing: During Construction Methods: This measure shall be incorporated into the LAHD and Developer design and contract specifications. The contractor shall adhere to these specifications and Compliance Plan throughout construction phases. Enforcement shall include oversight by the LAHD project/construction manager or designated building inspectors to ensure compliance with contract specifications.</p>	<p>Implementation: LAHD and Developer through Construction Contractor Monitoring and Reporting: Environmental Management Division, Construction Management Division</p>
<p>MM REC-6. Maintain access to open waters of the harbor during construction. The LAHD and construction contractors will minimize obstructions to open waters of the harbor during construction periods by placing</p>	<p>Timing: During Construction Methods: This measure shall be incorporated into the LAHD and Developer design and</p>	<p>Implementation: LAHD and Developer through Construction Contractor</p>

<i>Mitigation Measure</i>	<i>Timing and Methods</i>	<i>Responsible Parties</i>
<p>construction staging areas out of high-traffic waterways, parking lots leading to boat ramps, and boat docks, where possible. LAHD will embark on a public awareness campaign, providing information about construction periods, construction areas, closures, and suggestions of alternative boating areas. LAHD will inform the public prior to commencement of construction that will result in closures or possible disruptions to open waters of the harbor. Public notifications will, at minimum, include notifying local boating groups and posting flyers at boat ramps in the proposed project vicinity. LAHD will offer boater safety training for the public, specifically with respect to safe navigation around construction activities.</p>	<p>contract specifications. The contractor shall adhere to these specifications and Compliance Plan throughout construction phases. Enforcement shall include oversight by the LAHD project/construction manager or designated building inspectors to ensure compliance with contract specifications.</p>	<p>Monitoring and Reporting: Environmental Management Division, Construction Management Division</p>
<p>MM REC-7. Maintain docking space and dock access during construction. The LAHD and construction contractors will minimize obstructions to docking space and dock access during construction periods by placing construction staging areas away from boat docks where possible. LAHD will embark on a public awareness campaign, providing information about construction periods, construction areas, closures, and suggestions of alternative boating areas and docking locations. In cases where docking space will be closed or removed and existing tenants need alternative docking space, LAHD will provide temporary docking space in the near vicinity of the proposed Project. LAHD will provide notification and signage to direct users to these temporary alternative docking areas. LAHD will inform the public prior to commencement of construction that will result in closures or possible disruptions to dock access. Public notifications will, at minimum, include notifying local boating groups and posting flyers at boat ramps in the proposed project vicinity. LAHD will offer boater safety training for the public, specifically with respect to safe navigation around construction activities.</p>	<p>Timing: During Construction Methods: This measure shall be incorporated into the LAHD and Developer design and contract specifications. The contractor shall adhere to these specifications and Compliance Plan throughout construction phases. Enforcement shall include oversight by the LAHD project/construction manager or designated building inspectors to ensure compliance with contract specifications.</p>	<p>Implementation: LAHD and Developer through Construction Contractor Monitoring and Reporting: Environmental Management Division, Construction Management Division</p>
Other Requirements: Construction		
<p>Adherence to program to mitigate impacts on nonrenewable paleontologic resources developed by LAHD pursuant to MM CR-4</p>	<p>Timing: During construction of the parking structure Methods: The Paleontological Monitoring and Mitigation Plan San Pedro Waterfront Project shall be incorporated into the LAHD and Developer design and contract specifications. The contractor shall adhere to this Plan</p>	<p>Implementation: LAHD and Developer through Construction Contractor Monitoring and Reporting: Environmental Management Division, Construction</p>

<i>Mitigation Measure</i>	<i>Timing and Methods</i>	<i>Responsible Parties</i>
	throughout construction phases. Enforcement shall include oversight by the LAHD project/construction manager or designated building inspectors to ensure compliance with contract specifications.	Management Division